

Interpreting Solidity

Daniel Perez

Co-founder at Gyroscope & TLX



The Evolution of Solidity



Once upon a time, Solidity

- Solidity was designed/built to compile to EVM bytecode
- EVM bytecode was designed to execute smart-contracts

Source code

```
function withdraw(address account, uint amount) {  
    balances[account] -= amount;  
    payable(account).transfer(amount);  
}
```

Bytecode

Compile

```
SSTORE  
CALLER  
PUSH2 0x08fc  
CALL
```

On-chain contract

Deploy

0x303503.....8aC8602

Solidity “evolution”

Solidity has is evolving to fulfill more use-cases

- Frameworks such as Foundry use Solidity for
 - Testing
 - Scripting
 - Interactive environment (REPL)
- Solidity/EVM doesn't support many uses cases out of the box
 - Access external environment (e.g. filesystem, env vars)
 - Deploy/call a contract from an EOA

Solidity “devolution”

- In most cases, we start from a general purpose programming language and implement domain-specific languages on top of it
 - Testing frameworks in many languages
 - Rust to implement smart contracts
- Solidity is a domain-specific language trying (moderately hard) to become a general purpose programming language
- Slightly awkward situation that makes many things a bit quirky

Extending Solidity

To support more features, Solidity needs to do more than it was designed to. Some approaches include:

- Using a custom VM (anvil)
 - Can change the behaviour of calls (use cases: filesystem, env vars)
 - Can instrument execution (use cases: sending transactions from EOAs)
- Using a mini-language (chisel)
 - Can use a separate interpreter (e.g. `!fetch DAI 0x6B17...1d0F`)


Changing Solidity

- Some tasks require precise semantics (e.g. testing), some don't (e.g. scripting)
- Current approach indirectly changes Solidity semantics by changing the VM semantics
- If semantics don't matter, we can change the actual language
- Changing the language would make it easier to offer better UX for some use-cases
 - General-purpose scripting
 - REPL

(not) Compiling Solidity

Compiler 101

1. Parse the source code (code \rightarrow AST)
2. Transform/optimize the AST (AST \rightarrow IR)
3. Emit bytecode (IR \rightarrow bytecode)
4. Execute the bytecode



Semantics desiderata

We want to keep things similar to Solidity semantics but replace on-chain specific semantics

- Arithmetic and other basic operations should stay the same
 - $1 + 2 \rightarrow 3$
 - $[1, 2, 3][1] \rightarrow 2$
- Contract calls and other on-chain semantics should be replaced
 - `Contract("0x12...34").func()` \rightarrow RPC call

“Ideal” approach

The most flexible way would be:

- Replace the parser to allow flexibility on the syntax if desired
- Design a new bytecode to allow for general-purpose use-cases
- Implement the transformation and bytecode generation steps


This means re-implementing a language from scratch, which is a lot of work.

Mitigating the amount of effort


- Use existing Solidity parser
 - Almost no work to implement
 - No flexibility on the syntax
- Interpret the AST rather than interpreting bytecode
 - Easy to implement, no generation step
 - Much (much) slower

Interpreting the AST

$2 * (4 + 1)$



`ERC20(0x6b1...d0f).balanceOf(0xbEb...F1C7)`





Eclair, a Solidity Interpreter

<https://eclair.so>



Introducing Eclair

- Eclair is a Solidity REPL
- It executes the Solidity AST
- Its main goal is to allow easy interaction with smart contracts
- Built in Rust

```
>> repl.rpc("https://mainnet.optimism.io")
>> repl.loadLedger(5)
0x2Ed58a93c5Daf1f7D8a8b2eF3E9024CB6BFa9a77
>> usdc = ERC20(0x0b2C639c533813f4Aa9D7837CAf62653d097Ff85)
>> usdc.balanceOf(repl.account).format(usdc.decimals())
"5.00"
>> swapper = repl.fetchAbi("Swapper",
0x956f9d69Bae4dACad99fF5118b3BEDe0EED2abA2)
>> usdc.approve(swapper, 2e6)
Transaction(0xed2cfee9d712fcaeb0bf42f98e45d09d9b3626a0ee93dfc
730a3fb7a0cda8ff0)
>> target = 0xC013551A4c84BBcec4f75DBb8a45a444E2E9bbe7
>> trx = swapper.mint(usdc, target, 2e6, 0.5e18)
>> receipt = trx.getReceipt()
>> receipt.txHash
0xbdbaddb66c696afa584ef93d0d874fcba090e344aa104f199ecb6827170
09691
```

Main features

- Most common Solidity features
- Interaction with smart contracts using any RPC
- Loading ABIs from existing projects (Foundry, Hardhat, Brownie) and from Etherscan
- Loading accounts from raw private key, ledger, or encrypted keystore

```
>> for (uint256 i; i < 2; i++) {  
    console.log((i + 1) * 10); }  
  
0  
10  
  
>> repl.rpc("optimism")  
>> repl.rpc()  
"https://mainnet.optimism.io/"  
>> router = repl.fetchAbi("SwapRouter",  
0x68b3465833fb72A70ecDF485E0e4C7bD8665Fc45)  
>> repl.loadKeystore("account-name")  
Enter password:  
0x559822cf7213bC2DDa0aeCffA0b66Bd083C169CD  
>> router.swapTokensForExactTokens(...)
```


Differences to Solidity

- Dynamically typed

```
a = 1; a = "foo"; console.log(a.length);
```

- First-class functions and types

```
getBalance = token.balanceOf; getBalance(addr)
```

- More syntax sugar

- Concatenation: `[1, 2] + [3, 4] -> [1, 2, 3, 4]`

- Anonymous functions: `((a) >> a * 2)(3) -> 6`

- Functionalish programming

```
[1, 2, 3].filter((v) >> (v % 2 == 0)).map((v) >> v + 1)
```


State of the project

- Most desired features implemented
- Have been "tested in prod" for a few months
 - Used for most live debugging tasks
 - Used to generate/verify all kinds of transactions
 - Used to interact with wide range of contracts
- Only moderately tested
 - Few unit and integration tests but very (very) far from prod-level

Going forward

Short term

- Improve UX (completions, error messages, etc.)
- Add features
 - Execute files
 - Read/write files
 - JSON (de)serialization
- More testing

Longer term

- Move to a custom-built parser
 - Experiment with new syntaxes
 - More syntax sugar
- Move from interpreting the AST to interpreting bytecode
 - Much faster execution

Thank you!

Daniel Perez

Co-founder at Gyroscope & TLX

@danhper

<https://eclair.so>

