



WEBSERVICE DOCUMENTATION

Reviews

Version	Date	Author	Description
1.0	21-Sep-2020	Silvio Báez	Initial elaboration
1.1	05-Oct-2020	Silvio Báez	User registration method is added
1.2	13-Oct-2020	Silvio Báez	Login with social networks
1.3	16-Oct-2020	Silvio Báez	Login with social networks callback

Index

URL	6
Methods	7
login	7
Request.....	7
Response.....	7
register	8
Request.....	8
Response.....	9
refresh	10
Request.....	10
Response.....	10
logout	11
Request.....	11
Response.....	11
login/social-network	12
Return after logging in with social networks. Providers can be: google, facebook, etc.....	12
Request.....	12
Response.....	12
password/forgot	13
Request.....	13
Response.....	13
password/find/{token}	13
Request.....	14
Response.....	14
password/reset	14
Request.....	14
Response.....	15
countries.....	15
Request.....	15
Response.....	16

cities	16
Request.....	16
Response.....	17
roles	17
Request.....	17
Response.....	17
grades	18
Request.....	18
Response.....	18
academies	18
Request.....	19
Response.....	19
assistances/code	19
Request.....	19
Response.....	20
assistances/register	21
Request.....	21
Response.....	21
assistances/records	22
Request.....	22
Response.....	23
promotions/records	25
Request.....	25
Response.....	26
profile	28
Request.....	28
Response.....	28
profile/information	30
Request.....	31
Response.....	31
profile/social-networks	32
Request.....	32
Response.....	33
profile/photo	33

Request.....	33
Response.....	34
profile/photo	34
Request.....	35
Response.....	35
Glossary	37
Conventions	37
Status Codes.....	37

URL

Server	URL
Test	http://ikmf.upload.com.py/
Production	http://ikmf.upload.com.py/

Methods

login

User authentication with the system to obtain Authorization.

Request

Method	URL
POST	api/login

Type	Params	Values
HEAD	Accept	string
POST	email	string
POST	password	string

Authorization

`access_token` must be sent with all client requests. The `access_token` helps the server to validate the request source.

Accept

The value must always be `application/json`

Response

Status	Response
200	<pre>{ "access_token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpc3MiOiJodHRwOlwvXC8xOTIuMTY4LjAuMjUwXC9rcmF2bWFnYVwvYXBpXC9sb2dpbiIsIm1hdCI6MTYwMDczOTQwMSwiZXhwIjoxNjAwNzQzMdAxLCJuYmYiOiJE2MDA3Mzk0MDEsImp0aSI6InpjCEMyUUlVY09YZHAWSlMiLCJzdWIiOiIsInBydiI6IjIzYmQ1Yzg5NDlmNjAwYWRIImZl1NzAxYzQwMDg3MmRiN2E1OTc2ZjcifQ.nlg9yPQ08YK-ylgJ0yBewHyL2EzNh0sxKRZbYJ1s0Dw", "token_type": "bearer", "expires_in": 3600 }</pre>
400	<pre>{</pre>

	<pre>"message": "Token is expired" }</pre>
400	<pre>{ "message": "Token is invalid" }</pre>
400	<pre>{ "message": "Token absent" }</pre>
401	<pre>{ "message": "Unauthenticated." }</pre>
422	<pre>{ "message": "The given data was invalid.", "errors": [[["The email field is required."], ["The password field is required."]]] }</pre>

register

User register.

Request

Method	URL
POST	api/register

Type	Params	Values
HEAD	Accept	string

POST	email	string
POST	name	string
POST	last_name	string
POST	phone	string
POST	document_number	string
POST	birthday	date
POST	city_id	integer
POST	role_id	integer
POST	academy_id	integer

Response

Status	Response
200	<pre>{ "message": "The user is registered correctly." }</pre>
422	<pre>{ "message": "The given data was invalid.", "errors": [["El campo email es obligatorio."], ["El campo name es obligatorio."], ["El campo last name es obligatorio."], ["El campo password es obligatorio."], ["El campo phone es obligatorio."], ["El campo document number es obligatorio."], ["El campo birthday es obligatorio."]] }</pre>

	<pre> "El campo city id es obligatorio."], ["El campo role id es obligatorio."], ["El campo academy id es obligatorio."]]] }</pre>
--	---

refresh

It is used when the current token is about to expire, each token has a maximum validity time, by default it is an hour. When executing this action, the previous token is added to the blacklist.

Request

Method	URL
POST	api/refresh

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string

Authorization

The `access_token` that was given in response to `/api/login`

Response

Status	Response
200	<pre> { "access_token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpc3MiOiJodHRwOiJwXC8xOTIuMTY4LjAuMjUwXC9rcmF2bWFnYVwvYXBpXC9yZWZyZXNoIiwiaWF0IjoxNjAwNzQzOTIwLCJleHAiOiJlMjMDA3NDQwNjQsIm5iZiI6MTYwMDc0NDAwNCwianRpIjoiaXl0WVRoM0tNZEltVU" }</pre>

	<pre> syMiIsInN1YiI6MiwichJ2IjoiMjNiZDVjODk0OWY2MDBhZGIzOWU3MDFjNDAwODcyZGI3YTU5Nz ZmNyJ9.I8WGQmeUyMOGRGkM0mKZ8raAZAcZCVodgerb3KxwTa8", "token_type": "bearer", "expires_in": 3600 } </pre>
400	<pre> { "message": "Token is invalid" } </pre>
400	<pre> { "message": "Token absent" } </pre>

logout

You will add our token to a blacklist and that same token cannot be used, the user will have to authenticate to generate a new one.

Request

Method	URL
POST	api/logout

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string

Response

Status	Response
200	<pre> { "message": "Successfully logged out" } </pre>
401	<pre> { "message": "Unauthenticated." } </pre>

	}
--	---

login/social-network

Return after logging in with social networks. Providers can be: google, facebook, etc.

Request

Method	URL
POST	api/login/social-network

Type	Params	Values
HEAD	Accept	string
POST	provider	string [facebook google]
POST	id	string
POST	email	string
POST	name	string
POST	avatar	string

Response

Status	Response
200	<pre>{ "access_token": "eyJ0eXAiOiJKV1QiLCJhbGciOiJIUzI1NiJ9.eyJpc3MiOiJodHRwOiJwvXC8xOTIuMTY4LjAuMjUwXC9rcmF2bWFnYVwvYXBpXC9yZWZyZXNoIiwiaWF0IjoxNjAwNzQzOTIwLCJleHAiOiJlMDA3NDQwNjQsIm5iZiI6MTYwMDc0NDAwNCwianRpIjoiaXl0WVRoM0tNZEltVUyMiIsInN1YiI6MiwiCHJ2IjoiaWZDVjODk0OWY2MDBhZGIzOWU3MDFjNDAwODcyZGI3YTU5NzZmNyJ9.I8WQGmeUyMOGRGkM0mKZ8raAZAcZCvVodgerb3KxwTa8", "token_type": "bearer", "expires_in": 3600 }</pre>
403	<pre>{ "message": "Unauthorized action." }</pre>

password/forgot

.

Request

Method	URL
POST	api/password/forgot

Type	Params	Values
HEAD POST	Accept email	string string

Response

Status	Response
200	<pre>{ "message": "We have emailed your password reset link!" }</pre>
422	<pre>{ "message": "The given data was invalid.", "errors": { "email": ["The email field is required."] } }</pre>

password/find/{token}

.

Request

Method	URL
GET	api/password/find/{token}

Type	Params	Values
HEAD PATH GET	Accept token email	string string string

Response

Status	Response
200	<pre>{ "token": "217328dc06d67415a6b0b72f34e6fa133355599e34618aef20b1332c71e032cd", "email": "silviopy@outlook.com" }</pre>
401	<pre>{ "message": "We can't find a user with that email address." }</pre>
422	<pre>{ "message": "This password reset token is invalid." }</pre>

password/reset

.

Request

Method	URL
GET	api/password/reset

Type	Params	Values
HEAD	Accept	string
POST	token	string
POST	email	string
POST	password	string
POST	password_confirmation	string

Response

Status	Response
200	<pre>{ "message": "Your password has been reset!" }</pre>
422	<pre>{ "message": "The given data was invalid.", "errors": { "token": ["The token field is required."], "email": ["The email field is required."], "password": ["The password field is required."] } }</pre>

countries

.

Request

Method	URL
GET	api/countries

Type	Params	Values
HEAD	Accept	string

Response

Status	Response
200	<pre>[{ "id": 2, "name": "Argentina", "created_at": "2020-09-16T03:48:29.000000Z", "updated_at": "2020-09-16T03:48:42.000000Z" }, ...]</pre>

cities

.

Request

Method	URL
GET	api/cities

Type	Params	Values
HEAD GET	Accept country_id [optional]	string integer

country_id

The `country_id` that was given in response to `/api/countries`

Response

Status	Response
200	[{ "id": 1, "name": "Asunción", "country_id": 1, "created_at": "2020-09-11T18:09:08.000000Z", "updated_at": "2020-09-11T18:09:08.000000Z" }, ...]

roles

.

Request

Method	URL
GET	api/roles

Type	Params	Values
HEAD	Accept	string

Response

Status	Response
200	[{ "id": 1, "name": "Solo Alumno", "created_at": "2020-09-11T18:09:08.000000Z", "updated_at": "2020-09-11T18:09:08.000000Z" },]

	...
--	-----

grades

.

Request

Method	URL
GET	api/grades

Type	Params	Values
HEAD	Accept	string

Response

Status	Response
200	[{ "id": 12, "name": "E1", "created_at": "2020-09-11T18:09:08.000000Z", "updated_at": "2020-09-11T18:09:08.000000Z" }, ...]

academies

.

Request

Method	URL
GET	api/academies

Type	Params	Values
HEAD	Accept	string
GET	country_id [optional]	integer
GET	active [optional]	boolean

Response

Status	Response
200	<pre>[{ "id": 2, "name": "Kravgentina", "country_id": 2, "active": 1, "created_at": "2020-09-16T03:52:27.000000Z", "updated_at": "2020-09-16T03:52:42.000000Z" }, ...]</pre>

assistances/code

.

Request

Method	URL
POST	api/assistances/code

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string
POST	latitude	numeric
POST	longitude	numeric

Response

Status	Response
200	{ "code": "6R7P9UGKfh" }
400	{ "message": "Token is expired" }
400	{ "message": "Token is invalid" }
400	{ "message": "Token absent" }
401	{ "message": "Unauthenticated." }
422	{ "message": "The given data was invalid.", "errors": [[["The latitude field is required."], ["The longitude field is required."]] } }

assistances/register

Request

Method	URL
POST	api/assistances/register

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string
POST	code	string
POST	latitude	numeric
POST	longitude	numeric
POST	is_exam [optional]	boolean false

Response

Status	Response
200	<pre>{ "student_user_id": 2, "student_longitude": 1, "student_latitude": 1, "instructor_user_id": 2, "instructor_longitude": "1", "instructor_latitude": "1", "academy_id": 1, "is_exam": false, "updated_at": "2020-09-22T04:12:20.000000Z", "created_at": "2020-09-22T04:12:20.000000Z", "id": 6 }</pre>
400	<pre>{ "message": "Token is expired" }</pre>
400	<pre>{ "message": "Token is invalid" }</pre>

	}
400	{ "message": "Token absent" }
401	{ "message": "Unauthenticated." }
422	{ "message": "The given data was invalid.", "errors": [["The code field is required.", "The code is invalid or expired"], ["The latitude field is required."], ["The longitude field is required."]] }

assurances/records

.

Request

Method	URL
GET	api/assurances/records

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string

GET	pagination [optional]	integer 10
GET	search [optional]	string
GET	is_exam [optional]	boolean

Response

Status	Response
200	<pre>{ "current_page": 1, "data": [{ "id": 6, "student_user_id": 2, "instructor_user_id": 2, "student_latitude": 1, "student_longitude": 1, "instructor_latitude": 1, "instructor_longitude": 1, "academy_id": 1, "is_exam": 0, "created_at": "2020-09-22T04:12:20.000000Z", "updated_at": "2020-09-22T04:12:20.000000Z", "student_user": { "id": 2, "name": "Silvio Valentín", "email": "silviopy@outlook.com", "email_verified_at": null, "created_at": "2020-09-14T16:33:04.000000Z", "updated_at": "2020-09-22T03:32:49.000000Z", "last_name": "Báez", "phone": "595972801915", "city_id": 1, "document_number": "5169200", "birthday": "1991-04-11T00:00:00.000000Z", "academy_id": 1, "role_id": 1, "profile_photo": "http://192.168.0.250/kravmaga/storage/http://192.168.0.250/kravmaga/storage/users/profile_photo/9KCgvhy4r8lUxp5HdozwiCchpq3XnrQfkLEyiGCE.jpeg", "grade_id": 1, "active": 1 }, "instructor_user": { "id": 2,</pre>

```

        "name": "Silvio Valentín",
        "email": "silviopy@outlook.com",
        "email_verified_at": null,
        "created_at": "2020-09-14T16:33:04.000000Z",
        "updated_at": "2020-09-22T03:32:49.000000Z",
        "last_name": "Báez",
        "phone": "595972801915",
        "city_id": 1,
        "document_number": "5169200",
        "birthday": "1991-04-11T00:00:00.000000Z",
        "academy_id": 1,
        "role_id": 1,
        "profile_photo": "http://192.168.0.250/kravmaga/storage/http
://192.168.0.250/kravmaga/storage/users/profile_photo/9KCgvhy4r8lUxp5HdozwiC
chpq3XnrQfkLEyIGCE.jpeg",
        "grade_id": 1,
        "active": 1
    },
    "academy": {
        "id": 1,
        "name": "SIT",
        "country_id": 1,
        "active": 1,
        "created_at": "2020-09-11T18:09:08.000000Z",
        "updated_at": "2020-09-15T05:32:47.000000Z"
    }
}
...
],
"first_page_url": "http://192.168.0.250/kravmaga/api/assistances/records
?page=1",
"from": 1,
"last_page": 1,
"last_page_url": "http://192.168.0.250/kravmaga/api/assistances/records?
page=1",
"links": [
    {
        "url": null,
        "label": "Previous",
        "active": false
    },
    {
        "url": "http://192.168.0.250/kravmaga/api/assistances/records?pa
ge=1",
        "label": 1,
        "active": true
    },

```


	<pre> { "url": null, "label": "Next", "active": false }], "next_page_url": null, "path": "http://192.168.0.250/kravmaga/api/assistances/records", "per_page": 10, "prev_page_url": null, "to": 2, "total": 2 } </pre>
400	<pre> { "message": "Token is expired" } </pre>
400	<pre> { "message": "Token is invalid" } </pre>
400	<pre> { "message": "Token absent" } </pre>
401	<pre> { "message": "Unauthenticated." } </pre>

promotions/records

.

Request

Method	URL
GET	api/promotions/records

Type	Params	Values
------	--------	--------

HEAD	Authorization	string
HEAD	Accept	string
GET	pagination [optional]	integer 10

Response

Status	Response
200	<pre>{ "current_page": 1, "data": [{ "id": 2, "grade_id": 2, "student_user_id": 2, "instructor_user_id": 1, "created_at": "2020-09-17T02:56:05.000000Z", "updated_at": "2020-09-17T02:56:05.000000Z", "student_user": { "id": 2, "name": "Silvio Valentín", "email": "silviopy@outlook.com", "email_verified_at": null, "created_at": "2020-09-14T16:33:04.000000Z", "updated_at": "2020-09-22T03:32:49.000000Z", "last_name": "Báez", "phone": "595972801915", "city_id": 1, "document_number": "5169200", "birthday": "1991-04-11T00:00:00.000000Z", "academy_id": 1, "role_id": 1, "profile_photo": "users/profile_photo/9KCgvhy4r8lUxp5HdozwiCchpq3XnrQfkLEyiGCE.jpeg", "grade_id": 1, "active": 1 }, "instructor_user": { "id": 1, "name": "Super", "email": "admin@admin.com", "email_verified_at": null, "created_at": "2020-09-11T18:09:08.000000Z", "updated_at": "2020-09-11T18:09:08.000000Z", "last_name": "Admin", </pre>

```
        "phone": "+595 21 123 456",
        "city_id": 1,
        "document_number": "1234567",
        "birthday": "1969-01-01T00:00:00.000000Z",
        "academy_id": 1,
        "role_id": 2,
        "profile_photo": null,
        "grade_id": 1,
        "active": 1
    },
    "grade": {
        "id": 2,
        "name": "P1",
        "created_at": "2020-09-11T18:09:08.000000Z",
        "updated_at": "2020-09-11T18:09:08.000000Z"
    }
}
...
],
"first_page_url": "http://192.168.0.250/kravmaga/api/promotions/records?page=1",
"from": 1,
"last_page": 1,
"last_page_url": "http://192.168.0.250/kravmaga/api/promotions/records?page=1",
"links": [
    {
        "url": null,
        "label": "Previous",
        "active": false
    },
    {
        "url": "http://192.168.0.250/kravmaga/api/promotions/records?page=1",
        "label": 1,
        "active": true
    },
    {
        "url": null,
        "label": "Next",
        "active": false
    }
],
"next_page_url": null,
"path": "http://192.168.0.250/kravmaga/api/promotions/records",
"per_page": 10,
"prev_page_url": null,
```

	<pre> "to": 2, "total": 2 } </pre>
400	<pre> { "message": "Token is expired" } </pre>
400	<pre> { "message": "Token is invalid" } </pre>
400	<pre> { "message": "Token absent" } </pre>
401	<pre> { "message": "Unauthenticated." } </pre>

profile

Obtain authenticated user information.

Request

Method	URL
GET	api/profile

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string

Response

Status	Response
200	{

```
"id": 2,
"name": "Silvio Valentín",
"email": "silviopy@outlook.com",
"email_verified_at": null,
"created_at": "2020-09-14T16:33:04.000000Z",
"updated_at": "2020-09-21T23:13:15.000000Z",
"last_name": "Báez",
"phone": "595972801915",
"city_id": 1,
"document_number": "5169200",
"birthday": "1991-04-11T00:00:00.000000Z",
"academy_id": 1,
"role_id": 1,
"profile_photo": "http://192.168.0.250/kravmaga/storage/users/profile_ph
oto/9KCgvhy4r8lUxp5HdozwiCchpq3XnrQfkLEyiGCE.jpeg",
"grade_id": 1,
"active": 1,
"grade": {
  "id": 1,
  "name": "P0",
  "created_at": "2020-09-11T18:09:08.000000Z",
  "updated_at": "2020-09-11T18:09:08.000000Z"
},
"role": {
  "id": 1,
  "name": "Solo Alumno",
  "created_at": "2020-09-11T18:09:08.000000Z",
  "updated_at": "2020-09-11T18:09:08.000000Z"
},
"academy": {
  "id": 1,
  "name": "SIT",
  "country_id": 1,
  "active": 1,
  "created_at": "2020-09-11T18:09:08.000000Z",
  "updated_at": "2020-09-15T05:32:47.000000Z",
  "country": {
    "id": 1,
    "name": "Paraguay",
    "created_at": "2020-09-11T18:09:08.000000Z",
    "updated_at": "2020-09-11T18:09:08.000000Z"
  }
},
"city": {
  "id": 1,
  "name": "Asunción",
  "country_id": 1,
```

	<pre> "created_at": "2020-09-11T18:09:08.000000Z", "updated_at": "2020-09-11T18:09:08.000000Z", "country": { "id": 1, "name": "Paraguay", "created_at": "2020-09-11T18:09:08.000000Z", "updated_at": "2020-09-11T18:09:08.000000Z" }, }, "social_network": { "id": 1, "user_id": 2, "facebook": "https://www.facebook.com/silvio.baez.77/", "instagram": "@xilsh", "twitter": "@xilshpy", "pinterest": null, "youtube": null, "linkedin": null, "created_at": "2020-09-14T23:17:21.000000Z", "updated_at": "2020-09-21T16:24:58.000000Z" } } </pre>
400	<pre> { "message": "Token is expired" } </pre>
400	<pre> { "message": "Token is invalid" } </pre>
400	<pre> { "message": "Token absent" } </pre>
401	<pre> { "message": "Unauthenticated." } </pre>

profile/information

.

Request

Method	URL
POST PUT	api/profile/information

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string
POST PUT	name	string
POST PUT	last_name	string
POST PUT	phone	string
POST PUT	document_number	string
POST PUT	birthday	date
POST PUT	city_id	integer
POST PUT	academy_id	integer

Response

Status	Response
200	{ "message": "Profile information was updated correctly" }
400	{ "message": "Token is expired" }
400	{ "message": "Token is invalid" }
400	{ "message": "Token absent" }
401	{ "message": "Unauthenticated." }
422	{ "message": "The given data was invalid.", }

	<pre>"errors": [[["The name field is required."], ["The last name field is required."], ["The phone field is required."], ["The document number field is required."], ["The birthday field is required."], ["The city id field is required."], ["The academy id field is required."]]]</pre>
--	--

profile/social-networks

.

Request

Method	URL
POST PUT	api/profile/social-networks

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string

POST PUT	facebook [optional]	string
POST PUT	instagram [optional]	string
POST PUT	twitter [optional]	string
POST PUT	pinterest [optional]	string
POST PUT	youtube [optional]	string
POST PUT	linkedin [optional]	string

Response

Status	Response
200	{ "message": "Social networks were updated correctly" }
400	{ "message": "Token is expired" }
400	{ "message": "Token is invalid" }
400	{ "message": "Token absent" }
401	{ "message": "Unauthenticated." }

profile/photo

.

Request

Method	URL
POST PUT	api/profile/photo

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string
POST PUT	profile_photo	file [mimes:jpeg,png,jpg,gif]

Response

Status	Response
200	{ "message": "Profile photo was updated successfully" }
400	{ "message": "Token is expired" }
400	{ "message": "Token is invalid" }
400	{ "message": "Token absent" }
401	{ "message": "Unauthenticated." }
422	{ "message": "The given data was invalid.", "errors": [[["The profile photo field is required."]]] }

profile/photo

Request

Method	URL
DELETE	api/profile/photo

Type	Params	Values
HEAD	Authorization	string
HEAD	Accept	string

Response

Status	Response
200	{ "message": "Profile photo was successfully deleted" }
400	{ "message": "Token is expired" }
400	{ "message": "Token is invalid" }
400	{ "message": "Token absent" }
401	{ "message": "Unauthenticated." }

Glossary

Conventions

- **Client** - Client application.
- **Status** - HTTP status code of response.
- All the possible responses are listed under 'Responses' for each method. Only one of them is issued per request server.
- All response are in JSON format.
- All request parameters are mandatory unless explicitly marked as [optional]
- The type of values accepted for a *request* parameter are shown the the values column like this [**10**|<any number>]. The | symbol means OR. If the parameter is [optional], the default value is shown in blue bold text, as **10** is written in [**10**|<any number>].

Status Codes

All status codes are standard HTTP status codes. The below ones are used in this API.

2XX - Success of some kind

4XX - Error occurred in client's part

5XX - Error occurred in server's part

Status Code	Description
200	OK
201	Created
202	Accepted (Request accepted, and queued for execution)
400	Bad request
401	Authentication failure
403	Forbidden
404	Resource not found
405	Method Not Allowed
409	Conflict
412	Precondition Failed

413	Request Entity Too Large
422	Unprocessable Entity
500	Internal Server Error
501	Not Implemented
503	Service Unavailable