

Bioinformatics I

Lecture 05:

Alignment in Linear Space and Normalized Sequence Alignment

slides by Dr. Sebastian Will

Bioinformatics Group, University Freiburg

Summer 2012

Global Sequence Alignment in Linear Space

The Algorithm of Hirschberg

Recall Global Sequence Alignment

IN: sequences $a = a_1 \dots a_n$ and $b = b_1 \dots b_m$ in Σ^*

we defined: alignment $\mathcal{A} = (a^\diamond, b^\diamond)$ of a and b

cost function $w(\mathcal{A}) = w(a^\diamond, b^\diamond)$

$$w(a^\diamond, b^\diamond) := \sum_{1 \leq k \leq |\mathcal{A}|} w(a_k^\diamond, b_k^\diamond)$$

$$w(x, y) = \begin{cases} \delta & x, y \in \Sigma, x \neq y \\ \gamma & x = - \text{ or } y = - \\ 0 & \text{otherwise} \end{cases}$$


OUT: alignment \mathcal{A}^* of a and b with minimal cost $w(\mathcal{A}^*)$

- Algorithm?
- Complexity?


Minimum Cost in $O(n^2)$ Space

	0					j						m
0												
i												
n												

Minimum Cost in $O(n^2)$ Space




Minimum Cost in $O(n^2)$ Space



$$D(i, j) = \min \begin{cases} D(i-1, j-1) + w(a_i, b_j) \\ D(i-1, j) + \gamma \\ D(i, j-1) + \gamma \end{cases}$$

Minimum Cost in $O(n^2)$ Space



$$D(i, j) =$$

$$\min \begin{cases} D(i-1, j-1) + w(a_i, b_j) \\ D(i-1, j) + \gamma \\ D(i, j-1) + \gamma \end{cases}$$

Observations:


- Need only row $i-1$ to fill row i
- Can forget rows $i' < i-1$

$\Rightarrow D(n, m)$ in **LINEAR SPACE**

Minimum Cost in Linear Space

Pseudocode

```
for  $j := 0$  to  $m$  do  
     $D^0[j] := j\gamma$  // init row 0  
end for  
for  $i := 1$  to  $n$  do  
     $D^1[0] := i\gamma$  // init column 0  
    for  $j := 1$  to  $m$  do  
         $D^1[j] := \min \begin{cases} D^0[j-1] + w(a_i, b_j) \\ D^0[j] + \gamma \\ D^1[j-1] + \gamma \end{cases}$   
    end for  
    swap vectors  $D^0$  and  $D^1$  //(!)  
end for
```




Stores only two vectors D^0 and D^1 ,
i.e. LINEAR SPACE

Minimum Cost in Linear Space

Pseudocode

```
for  $j := 0$  to  $m$  do  
     $D^0[j] := j\gamma$  // init row 0  
end for  
for  $i := 1$  to  $n$  do  
     $D^1[0] := i\gamma$  // init column 0  
    for  $j := 1$  to  $m$  do  
         $D^1[j] := \min \begin{cases} D^0[j-1] + w(a_i, b_j) \\ D^0[j] + \gamma \\ D^1[j-1] + \gamma \end{cases}$   
    end for  
    swap vectors  $D^0$  and  $D^1$  //(!)  
end for
```




Stores only two vectors D^0 and D^1 ,
i.e. LINEAR SPACE

Minimum Cost in Linear Space

Pseudocode

```
for  $j := 0$  to  $m$  do  
   $D^0[j] := j\gamma$  // init row 0  
end for  
for  $i := 1$  to  $n$  do  
   $D^1[0] := i\gamma$  // init column 0  
  for  $j := 1$  to  $m$  do  
    
$$D^1[j] := \min \begin{cases} D^0[j-1] + w(a_i, b_j) \\ D^0[j] + \gamma \\ D^1[j-1] + \gamma \end{cases}$$
  
  end for  
  swap vectors  $D^0$  and  $D^1$  //(!)  
end for
```


Stores only two vectors D^0 and D^1 ,
i.e. LINEAR SPACE



Even less space:
store only **one row** and
one variable
(pseudocode not given)


Best Alignment in Linear Space

- No direct traceback!
- Trace intersects row i : where?
 - Compute row i in $O(n)$ space
 \Rightarrow prefix alignment scores:
 $D(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_1, \dots, a_i \text{ and } b_1, \dots, b_j\}$
 - Compute suffix alignment scores (1!)
 $D'(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_{i+1}, \dots, a_n \text{ and } b_{j+1}, \dots, b_m\}$
- AND combine with prefix alignment (2!)
 \Rightarrow total alignment score "through (i, j) " is $D(i, j) + D'(i, j)$
 - look for minimum $D(i, j) + D'(i, j) \Rightarrow (i, j)$ on trace
- "naive" linear space alignment
"do this for each row": $O(n^3)$ time!




Best Alignment in Linear Space

- No direct traceback!
- Trace intersects row i : where?
 - Compute row i in $O(n)$ space
 \Rightarrow prefix alignment scores:
 $D(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_1, \dots, a_i \text{ and } b_1, \dots, b_j\}$
 - Compute suffix alignment scores (1!)
 $D'(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_{i+1}, \dots, a_n \text{ and } b_{j+1}, \dots, b_m\}$
- AND combine with prefix alignment (2!)
 \Rightarrow total alignment score “through (i, j) ” is $D(i, j) + D'(i, j)$
- look for minimum $D(i, j) + D'(i, j) \Rightarrow (i, j)$ on trace
- “naive” linear space alignment
“do this for each row”: $O(n^3)$ time!




Best Alignment in Linear Space

- No direct traceback!
- Trace intersects row i : where?
 - Compute row i in $O(n)$ space
 \Rightarrow prefix alignment scores:
 $D(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_1, \dots, a_i \text{ and } b_1, \dots, b_j\}$
 - Compute suffix alignment scores (1!)
 $D'(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_{i+1}, \dots, a_n \text{ and } b_{j+1}, \dots, b_m\}$
- AND combine with prefix alignment (2!)
 \Rightarrow total alignment score “through (i, j) ” is $D(i, j) + D'(i, j)$
- look for minimum $D(i, j) + D'(i, j) \Rightarrow (i, j)$ on trace
- “naive” linear space alignment
“do this for each row”: $O(n^3)$ time!



Best Alignment in Linear Space

- No direct traceback!
- Trace intersects row i : where?
 - Compute row i in $O(n)$ space
 \Rightarrow prefix alignment scores:
 $D(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_1, \dots, a_i \text{ and } b_1, \dots, b_j\}$
 - Compute suffix alignment scores (1!)
 $D'(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_{i+1}, \dots, a_n \text{ and } b_{j+1}, \dots, b_m\}$
- AND combine with prefix alignment (2!)
 \Rightarrow total alignment score “through (i, j) ” is $D(i, j) + D'(i, j)$
 - look for minimum $D(i, j) + D'(i, j) \Rightarrow (i, j)$ on trace
- “naive” linear space alignment
 “do this for each row”: $O(n^3)$ time!



(1!):

$$D'(i, m) = i\gamma, \quad D'(n, j) = j\gamma$$

$$D'(i, j) =$$

$$\min \begin{cases} D'(i+1, j+1) + w(a_{i+1}, b_{j+1}) \\ D'(i+1, j) + \gamma \\ D'(i, j+1) + \gamma \end{cases}$$

Best Alignment in Linear Space

- No direct traceback!
- Trace intersects row i : where?
 - Compute row i in $O(n)$ space
 \Rightarrow prefix alignment scores:
 $D(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_1, \dots, a_i \text{ and } b_1, \dots, b_j\}$
 - Compute suffix alignment scores (1!)
 $D'(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_{i+1}, \dots, a_n \text{ and } b_{j+1}, \dots, b_m\}$
- AND combine with prefix alignment (2!)
 \Rightarrow total alignment score “through (i, j) ” is $D(i, j) + D'(i, j)$
 - look for minimum $D(i, j) + D'(i, j) \Rightarrow (i, j)$ on trace
- “naive” linear space alignment
 “do this for each row”: $O(n^3)$ time!

	A	G	C	T
A				
C				
C				
T				

(2!): by Example

$a = \text{ACCT}$, $b = \text{AGCT}$, $i = 2$


$$D(2, 3) = w \left(\begin{array}{c} \text{A-C} \\ \text{AGC} \end{array} \right)$$

$$D'(2, 3) = w \left(\begin{array}{c} \text{CT} \\ \text{-T} \end{array} \right)$$

$$D(2, 3) + D'(2, 3) = w \left(\begin{array}{c} \text{A-CCT} \\ \text{AGC-T} \end{array} \right)$$


Best Alignment in Linear Space

- No direct traceback!
 - Trace intersects row i : where?
 - Compute row i in $O(n)$ space
 \Rightarrow prefix alignment scores:
 $D(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_1, \dots, a_i \text{ and } b_1, \dots, b_j\}$
 - Compute suffix alignment scores (1!)
 $D'(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_{i+1}, \dots, a_n \text{ and } b_{j+1}, \dots, b_m\}$
- AND combine with prefix alignment (2!)
 \Rightarrow total alignment score “through (i, j) ” is $D(i, j) + D'(i, j)$
- look for minimum $D(i, j) + D'(i, j) \Rightarrow (i, j)$ on trace
 - “naive” linear space alignment
“do this for each row”: $O(n^3)$ time!




Best Alignment in Linear Space

- No direct traceback!
- Trace intersects row i : where?
 - Compute row i in $O(n)$ space
 \Rightarrow prefix alignment scores:
 $D(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_1, \dots, a_i \text{ and } b_1, \dots, b_j\}$
 - Compute suffix alignment scores (1!)
 $D'(i, j) = \min\{w(\mathcal{A}) \mid \mathcal{A} \text{ align. of } a_{i+1}, \dots, a_n \text{ and } b_{j+1}, \dots, b_m\}$
- AND combine with prefix alignment (2!)
 \Rightarrow total alignment score “through (i, j) ” is $D(i, j) + D'(i, j)$
 - look for minimum $D(i, j) + D'(i, j) \Rightarrow (i, j)$ on trace
- “naive” linear space alignment
“do this for each row”: $O(n^3)$ time!



Divide&Conquer: The Hirschberg Algorithm




pseudocode TRACE(a, b)

1. Find trace cell (i, j) in row $i := \lceil n/2 \rceil$
2. Divide problem “find trace for $a_1 \dots a_n$ and $b_1 \dots b_m$ ” into subproblems
 - a) TRACE($a_1 \dots a_{i-1}, b_1 \dots b_j$)
 - b) TRACE($a_{i+1} \dots a_n, b_j \dots b_m$)
3. Solve subproblems recursively (terminate at ≤ 1 rows)

Note: everything is done in LINEAR SPACE

Divide&Conquer: The Hirschberg Algorithm




pseudocode TRACE(a, b)

1. Find trace cell (i, j) in row $i := \lceil n/2 \rceil$
2. Divide problem “find trace for $a_1 \dots a_n$ and $b_1 \dots b_m$ ” into subproblems
 - a) TRACE($a_1 \dots a_{i-1}, b_1 \dots b_j$)
 - b) TRACE($a_{i+1} \dots a_n, b_j \dots b_m$)
3. Solve subproblems recursively (terminate at ≤ 1 rows)

Note: everything is done in LINEAR SPACE

Divide&Conquer: The Hirschberg Algorithm




pseudocode TRACE(a, b)

1. Find trace cell (i, j) in row $i := \lceil n/2 \rceil$
2. Divide problem “find trace for $a_1 \dots a_n$ and $b_1 \dots b_m$ ” into subproblems
 - a) TRACE($a_1 \dots a_{i-1}, b_1 \dots b_j$)
 - b) TRACE($a_{i+1} \dots a_n, b_j \dots b_m$)
3. Solve subproblems recursively (terminate at ≤ 1 rows)

Note: everything is done in LINEAR SPACE

Hirschberg Runs in $O(n^2)$ Time



Proof:

by solving recursion for runtime $T(n, m)$:

$$T(0, m) = 0 \quad T(1, m) = m$$

$$T(n, m) = nm + T(\lceil n/2 \rceil - 1, j) + T(n - \lceil n/2 \rceil - 1, m - j)$$

Claim: $T(n, m) \leq 2nm$

Proof: by induction on n

Ind. start: $n=0, n=m$ \square

Ind. step:

$$\begin{aligned} T(n, m) &\leq_{\text{(I.H.)}} nm + 2(\lceil n/2 \rceil - 1)j + 2(n - \lceil n/2 \rceil - 1)(m - j) \\ &\leq nm + 2(\lceil n/2 \rceil - 1)(j + m - j) \\ &< nm + nm \end{aligned}$$

\square

Conclusions: Linear space alignment

- Computing optimal alignment scores in linear space is simple
- One can compute prefix *and* suffix alignment scores by DP
- Hirschberg algorithm: linear space but only twice the time
- Divide and conquer: general algorithmic principle
- Run-time of D&C algorithm shown by induction
- Extensions possible, e.g. affine gap cost

Normalized Local Sequence Alignment

[Arslan et al., Bioinformatics 2001]

**Fractional Programming
using Dinkelbach's Algorithm**

Recall Local Sequence Alignment

IN: sequences $a = a_1 \dots a_n$ and $b = b_1 \dots b_m$

define: a *local alignment* $\mathcal{A} = (a^\diamond, b^\diamond)$ of a and b
is a (global) alignment of subsequences of a and b
similarity function $s(\mathcal{A}) = s(a^\diamond, b^\diamond)$

$$s(a^\diamond, b^\diamond) := \sum_{1 \leq k \leq |\mathcal{A}|} s(a_k^\diamond, b_k^\diamond)$$

$$s(x, y) = \begin{cases} \gamma & x = - \text{ or } y = - \\ \sigma & x = y \\ \mu & x \neq y \end{cases}$$

OUT: local alignment \mathcal{A}^* of a and b with maximum similarity $s(\mathcal{A}^*)$

Local Alignment Example

- sequences

$a = \text{GCATTUGCCUU}$

$b = \text{CTTGACCATU}$

- similarity $s(x, y) = \begin{cases} -2 & x = - \text{ or } y = - \\ 3 & x = y \\ -1 & x \neq y \end{cases}$

- Local alignment with maximum similarity:

(global alignment of subsequences a_4, \dots, a_9 and b_2, \dots, b_7)

$a^\diamond = \text{TTUG-CC}$

$b^\diamond = \text{TT-GACC}$, $s(a^\diamond, b^\diamond) = 3 + 3 - 2 + 3 - 2 + 3 + 3 = 11$

- Another local alignment (g.a. of a_2, a_3, a_4 and b_7, b_8, b_9)

$$\mathcal{A} = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s(\mathcal{A}) = 3 + 3 + 3 = 9$$

Local Alignment Example

- sequences

$a = \text{GCATTUGCCUU}$

$b = \text{CTTGACCATU}$

- similarity $s(x, y) = \begin{cases} -2 & x = - \text{ or } y = - \\ 3 & x = y \\ -1 & x \neq y \end{cases}$

- Local alignment with maximum similarity:

(global alignment of subsequences a_4, \dots, a_9 and b_2, \dots, b_7)

$a^\diamond = \text{TTUG-CC}$

$b^\diamond = \text{TT-GACC}$, $s(a^\diamond, b^\diamond) = 3 + 3 - 2 + 3 - 2 + 3 + 3 = 11$

- Another local alignment (g.a. of a_2, a_3, a_4 and b_7, b_8, b_9)

$$\mathcal{A} = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s(\mathcal{A}) = 3 + 3 + 3 = 9$$

Local Alignment Example

- sequences

$a = \text{GCATTUGCCUU}$

$b = \text{CTTGACCATU}$

- similarity $s(x, y) = \begin{cases} -2 & x = - \text{ or } y = - \\ 3 & x = y \\ -1 & x \neq y \end{cases}$

- Local alignment with maximum similarity:

(global alignment of subsequences a_4, \dots, a_9 and b_2, \dots, b_7)

$a^\diamond = \text{TTUG-CC}$

$b^\diamond = \text{TT-GACC}$, $s(a^\diamond, b^\diamond) = 3 + 3 - 2 + 3 - 2 + 3 + 3 = 11$

- Another local alignment (g.a. of a_2, a_3, a_4 and b_7, b_8, b_9)

$$\mathcal{A} = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s(\mathcal{A}) = 3 + 3 + 3 = 9$$

Local Alignment Example

- sequences

$a = \text{GCATTUGCCUU}$

$b = \text{CTTGACCATU}$

- similarity $s(x, y) = \begin{cases} -2 & x = - \text{ or } y = - \\ 3 & x = y \\ -1 & x \neq y \end{cases}$

- Local alignment with maximum similarity:

(global alignment of subsequences a_4, \dots, a_9 and b_2, \dots, b_7)


$a^\diamond = \text{TTUG-CC}$

$b^\diamond = \text{TT-GACC}$, $s(a^\diamond, b^\diamond) = 3 + 3 - 2 + 3 - 2 + 3 + 3 = 11$

- Another local alignment (g.a. of a_2, a_3, a_4 and b_7, b_8, b_9)



$$\mathcal{A} = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s(\mathcal{A}) = 3 + 3 + 3 = 9 \quad \text{Better?}$$

Drawbacks of “Smith-Waterman” Local Alignment: Shadowing



longer alignments "shadow" shorter ones


Drawbacks of “Smith-Waterman” Local Alignment: Shadowing



Non-overlapping and overlapping shadowing




Drawbacks of “Smith-Waterman” Local Alignment:

Mosaic Effect






poor "middle parts" hidden in overall scoring

Overcoming the Drawbacks of Local Alignment




Overcoming the Drawbacks of Local Alignment



“Smith-Waterman”-similarity does not consider length

Overcoming the Drawbacks of Local Alignment



“Smith-Waterman”-similarity does not consider length

Better “similarity”: $\frac{s(\mathcal{A})}{\text{length of subsequences in } \mathcal{A}}$

In example $a = \text{GCATTUGCCUU}$, $b = \text{CTTGACCATU}$, “shadowing”:

$$s \begin{pmatrix} \text{TTUG-CC} \\ \text{TT-GACC} \end{pmatrix} > s \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}$$

but:

$$\frac{s \begin{pmatrix} \text{TTUG-CC} \\ \text{TT-GACC} \end{pmatrix}}{|\text{TTUGCC}| + |\text{TTGACC}|} < \frac{s \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}}{|\text{CAT}| + |\text{CAT}|}$$

Overcoming Drawbacks: Normalized Similarity

Given:

- sequences $a = a_1 \dots a_n$ and $b = b_1 \dots b_m$
- local alignment $\mathcal{A} = (a^\diamond, b^\diamond)$ of a and b
= global alignment of subsequences of $a_i \dots a_j$ and $b_k \dots b_l$

Define:

- *length of alignment subsequences*

$$\llbracket \mathcal{A} \rrbracket := |a_i \dots a_j| + |b_k \dots b_l|$$

- *normalized similarity*

$$ns(\mathcal{A}) := \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L}$$

constant L controls dependency of $ns(\mathcal{A})$ on length

Overcoming Drawbacks: Normalized Similarity

Given:

- sequences $a = a_1 \dots a_n$ and $b = b_1 \dots b_m$
- local alignment $\mathcal{A} = (a^\diamond, b^\diamond)$ of a and b
= global alignment of subsequences of $a_i \dots a_j$ and $b_k \dots b_l$

Define:

- *length of alignment subsequences*

$$\llbracket \mathcal{A} \rrbracket := |a_i \dots a_j| + |b_k \dots b_l|$$

- *normalized similarity*

$$ns(\mathcal{A}) := \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L}$$

constant L controls dependency of $ns(\mathcal{A})$ on length

Overcoming Drawbacks: Normalized Similarity

Given:

- sequences $a = a_1 \dots a_n$ and $b = b_1 \dots b_m$
- local alignment $\mathcal{A} = (a^\diamond, b^\diamond)$ of a and b
= global alignment of subsequences of $a_i \dots a_j$ and $b_k \dots b_l$

Define:

- *length of alignment subsequences*

$$\llbracket \mathcal{A} \rrbracket := |a_i \dots a_j| + |b_k \dots b_l|$$

- *normalized similarity*

$$ns(\mathcal{A}) := \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L}$$

constant L controls dependency of $ns(\mathcal{A})$ on length

Effect of constant L

\mathcal{A}	$s(\mathcal{A})$	$ns(\mathcal{A})$			
		$L = 0$	$L = 1$	$L = 21$	$L = 50$
$\begin{pmatrix} \text{TTUG-CC} \\ \text{TT-GACC} \end{pmatrix}$	11	0.92	0.85	0.33	0.18
$\begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}$	9	1.5	1.29	0.33	0.16
$\begin{pmatrix} \text{C} \\ \text{C} \end{pmatrix}$	3	1.5	1	0.14	0.06

Normalized Local Alignment

IN: sequences $a = a_1 \dots a_n$ and $b = b_1 \dots b_m$

$$ns(\mathcal{A}) := \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L}$$

OUT: local alignment \mathcal{A}^* of a and b with maximum
normalized similarity $\lambda^* = ns(\mathcal{A}^*)$

no algorithm details today ...

Finding the Best Normalized Local Alignment

1. *Guess* λ^*

find best local alignment \mathcal{A}^*

$$\lambda^* := ns(\mathcal{A}^*)$$

2. *(Try to) improve*: find better λ^*

For this purpose, set $\lambda := \lambda^*$ and find new λ^* with $\lambda^* - \lambda \geq 0$.

Note: In one step, we cannot maximize

$$\lambda^* - \lambda = ns(\mathcal{A}) - \lambda = \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L} - \lambda.$$

Thus, maximize $(\lambda^* - \lambda)(\llbracket \mathcal{A} \rrbracket + L) = s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$
(over all local alignments \mathcal{A} ; let \mathcal{A}^* be the best alignment).

3. *Iterate* with new estimation $\lambda^* := ns(\mathcal{A}^*)$ until convergence
(i.e. $\lambda = \lambda^*$).

Remark: this algorithm is known as *Dinkelbach's algorithm*

Finding the Best Normalized Local Alignment

1. *Guess* λ^*

find best local alignment \mathcal{A}^*

$$\lambda^* := ns(\mathcal{A}^*)$$

2. *(Try to) improve*: find better λ^*

For this purpose, set $\lambda := \lambda^*$ and find new λ^* with $\lambda^* - \lambda \geq 0$.

Note: In one step, we cannot maximize

$$\lambda^* - \lambda = ns(\mathcal{A}) - \lambda = \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L} - \lambda.$$

Thus, maximize $(\lambda^* - \lambda)(\llbracket \mathcal{A} \rrbracket + L) = s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$
(over all local alignments \mathcal{A} ; let \mathcal{A}^* be the best alignment).

3. *Iterate* with new estimation $\lambda^* := ns(\mathcal{A}^*)$ until convergence
(i.e. $\lambda = \lambda^*$).

Remark: this algorithm is known as *Dinkelbach's algorithm*

Finding the Best Normalized Local Alignment

1. *Guess* λ^*
find best local alignment \mathcal{A}^*
 $\lambda^* := ns(\mathcal{A}^*)$
2. *(Try to) improve*: find better λ^*
For this purpose, set $\lambda := \lambda^*$ and find new λ^* with $\lambda^* - \lambda \geq 0$.
Note: In one step, we cannot maximize
$$\lambda^* - \lambda = ns(\mathcal{A}) - \lambda = \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L} - \lambda.$$

Thus, maximize $(\lambda^* - \lambda)(\llbracket \mathcal{A} \rrbracket + L) = s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$
(over all local alignments \mathcal{A} ; let \mathcal{A}^* be the best alignment).
3. *Iterate* with new estimation $\lambda^* := ns(\mathcal{A}^*)$ until convergence
(i.e. $\lambda = \lambda^*$).

Remark: this algorithm is known as *Dinkelbach's algorithm*

Finding the Best Normalized Local Alignment

1. *Guess* λ^*

find best local alignment \mathcal{A}^*

$$\lambda^* := ns(\mathcal{A}^*)$$

2. *(Try to) improve*: find better λ^*

For this purpose, set $\lambda := \lambda^*$ and find new λ^* with $\lambda^* - \lambda \geq 0$.

Note: In one step, we cannot maximize

$$\lambda^* - \lambda = ns(\mathcal{A}) - \lambda = \frac{s(\mathcal{A})}{\llbracket \mathcal{A} \rrbracket + L} - \lambda.$$

Thus, maximize $(\lambda^* - \lambda)(\llbracket \mathcal{A} \rrbracket + L) = s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$

(over all local alignments \mathcal{A} ; let \mathcal{A}^* be the best alignment).

3. *Iterate* with new estimation $\lambda^* := ns(\mathcal{A}^*)$ until convergence (i.e. $\lambda = \lambda^*$).

Remark: this algorithm is known as *Dinkelbach's algorithm*

Dinkelbach's algorithm Converges to Best Normalized Local Alignment

Define $s_\lambda(\mathcal{A}) := s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$

Theorem:

In step 2 of Dinkelbach's Algorithm,

- i) $s_\lambda(\mathcal{A}^*) \geq 0$
- ii) $\lambda = ns(\mathcal{A})$ is optimum if and only if $s_\lambda(\mathcal{A}^*) = 0$.

This implies λ^* converges to best normalized alignment score.

Proof: ...

Dinkelbach's algorithm Converges to Best Normalized Local Alignment

Define $s_\lambda(\mathcal{A}) := s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$

Theorem:

In step 2 of Dinkelbach's Algorithm,

- i) $s_\lambda(\mathcal{A}^*) \geq 0$
- ii) $\lambda = ns(\mathcal{A})$ is optimum if and only if $s_\lambda(\mathcal{A}^*) = 0$.

This implies λ^* converges to best normalized alignment score.

Proof:

- i) we know: $\lambda = ns(\mathcal{A})$ for some local alignment \mathcal{A} ,
therefore: $s_\lambda(\mathcal{A}) = s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L) = (\llbracket \mathcal{A} \rrbracket + L)(ns(\mathcal{A}) - \lambda)$
 $\llbracket \mathcal{A} \rrbracket + L > 0; ns(\mathcal{A}) = \lambda \Rightarrow ns(\mathcal{A}) - \lambda = 0$ Since $s_\lambda(\mathcal{A}) = 0$,
 $\max_{\mathcal{A}} s_\lambda(\mathcal{A}) \geq 0$ □

Dinkelbach's algorithm Converges to Best Normalized Local Alignment

Define $s_\lambda(\mathcal{A}) := s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$

Theorem:

In step 2 of Dinkelbach's Algorithm,

- i) $s_\lambda(\mathcal{A}^*) \geq 0$
- ii) $\lambda = ns(\mathcal{A})$ is optimum if and only if $s_\lambda(\mathcal{A}^*) = 0$.

This implies λ^* converges to best normalized alignment score.

Proof:

- ii) " \implies ": $s_\lambda(\mathcal{A}^*) = (\llbracket \mathcal{A}^* \rrbracket + L)(ns(\mathcal{A}^*) - \lambda) \leq 0$, since $\llbracket \mathcal{A}^* \rrbracket + L > 0$ and $ns(\mathcal{A}^*) - \lambda \leq 0$. With (i): $s_\lambda(\mathcal{A}^*) = 0$.

" \impliedby ": Let $\max_{\mathcal{A}} s_\lambda(\mathcal{A}) = 0$. Assume \mathcal{A} is not optimal, i.e. there is an \mathcal{A}' with $ns(\mathcal{A}') > \lambda$, then

$s_\lambda(\mathcal{A}') = (\llbracket \mathcal{A}' \rrbracket + L)(ns(\mathcal{A}') - \lambda) > 0$, since $\llbracket \mathcal{A}' \rrbracket + L > 0$ and $ns(\mathcal{A}') - \lambda > 0$, contradicting $\max_{\mathcal{A}} s_\lambda(\mathcal{A}) = 0$. □

How to maximize $s_\lambda(\mathcal{A}) := s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L)$?

Maximize $s_\lambda(\mathcal{A})$ by solving an instance of local alignment:

$$\begin{aligned} & s_\lambda(\mathcal{A}) \text{ maximum} \\ \equiv & s(\mathcal{A}) - \lambda(\llbracket \mathcal{A} \rrbracket + L) \text{ maximum} \\ \equiv & s(\mathcal{A}) - \lambda\llbracket \mathcal{A} \rrbracket - \lambda L \text{ maximum} \\ \equiv & s(\mathcal{A}) - \lambda\llbracket \mathcal{A} \rrbracket \text{ maximum} \\ \equiv & \sum_k s(a_k^\diamond, b_k^\diamond) - \lambda\llbracket \mathcal{A} \rrbracket \text{ maximum} \\ \equiv & \sum_k (s(a_k^\diamond, b_k^\diamond) - \{\lambda \text{ if } a_k^\diamond \neq -\} - \{\lambda \text{ if } b_k^\diamond \neq -\}) \text{ maximum} \\ \equiv & s'(\mathcal{A}) \text{ maximum, where } s' \text{ uses modified base similarity} \\ & s'(x, y) = \begin{cases} s(x, y) - 2\lambda & x, y \in \Sigma \\ s(x, y) - \lambda & x = - \text{ or } y = - \end{cases} \end{aligned}$$

Example

$a = \text{GCATTUGCCUU}$ and $b = \text{CTTGACCATU}$

$s(x, y) = \{3 \text{ match}; -1 \text{ mismatch}; -2 \text{ gap}\}; L := 10$

1. $\mathcal{A}^* = \begin{pmatrix} \text{TTUG-CC} \\ \text{TT-GACC} \end{pmatrix}, s(\mathcal{A}^*) = 11, ns(\mathcal{A}^*) = 11/22 = 0.5 \rightarrow \lambda$

2. solve local alignment of a and b for modified similarity
 $s'(x, y) = \{2 \text{ match}; -2 \text{ mismatch}; -2.5 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 9 - 16\lambda = 1,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625 \rightarrow \lambda$$

3. solve local alignment of a and b for new modified similarity
 $s'(x, y) = \{1.875 \text{ match}; -2.125 \text{ mismatch}; -2.5625 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 0,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625$$

4. convergence $\Rightarrow \lambda^* = 0.5625$.

Example

$a = \text{GCATTUGCCUU}$ and $b = \text{CTTGACCATU}$

$s(x, y) = \{3 \text{ match}; -1 \text{ mismatch}; -2 \text{ gap}\}; L := 10$

1. $\mathcal{A}^* = \begin{pmatrix} \text{TTUG-CC} \\ \text{TT-GACC} \end{pmatrix}, s(\mathcal{A}^*) = 11, ns(\mathcal{A}^*) = 11/22 = 0.5 \rightarrow \lambda$

2. solve local alignment of a and b for modified similarity
 $s'(x, y) = \{2 \text{ match}; -2 \text{ mismatch}; -2.5 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 9 - 16\lambda = 1,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625 \rightarrow \lambda$$

3. solve local alignment of a and b for new modified similarity
 $s'(x, y) = \{1.875 \text{ match}; -2.125 \text{ mismatch}; -2.5625 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 0,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625$$

4. convergence $\Rightarrow \lambda^* = 0.5625$.

Example

$a = \text{GCATTUGCCUU}$ and $b = \text{CTTGACCATU}$

$s(x, y) = \{3 \text{ match}; -1 \text{ mismatch}; -2 \text{ gap}\}; L := 10$

1. $\mathcal{A}^* = \begin{pmatrix} \text{TTUG-CC} \\ \text{TT-GACC} \end{pmatrix}, s(\mathcal{A}^*) = 11, ns(\mathcal{A}^*) = 11/22 = 0.5 \rightarrow \lambda$

2. solve local alignment of a and b for modified similarity
 $s'(x, y) = \{2 \text{ match}; -2 \text{ mismatch}; -2.5 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 9 - 16\lambda = 1,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625 \rightarrow \lambda$$

3. solve local alignment of a and b for new modified similarity
 $s'(x, y) = \{1.875 \text{ match}; -2.125 \text{ mismatch}; -2.5625 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 0,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625$$

4. convergence $\Rightarrow \lambda^* = 0.5625$.

Example

$a = \text{GCATTUGCCUU}$ and $b = \text{CTTGACCATU}$

$s(x, y) = \{3 \text{ match}; -1 \text{ mismatch}; -2 \text{ gap}\}; L := 10$

1. $\mathcal{A}^* = \begin{pmatrix} \text{TTUG-CC} \\ \text{TT-GACC} \end{pmatrix}, s(\mathcal{A}^*) = 11, ns(\mathcal{A}^*) = 11/22 = 0.5 \rightarrow \lambda$

2. solve local alignment of a and b for modified similarity
 $s'(x, y) = \{2 \text{ match}; -2 \text{ mismatch}; -2.5 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 9 - 16\lambda = 1,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625 \rightarrow \lambda$$

3. solve local alignment of a and b for new modified similarity
 $s'(x, y) = \{1.875 \text{ match}; -2.125 \text{ mismatch}; -2.5625 \text{ gap}\}$

$$\Rightarrow \text{new } \mathcal{A}^* = \begin{pmatrix} \text{CAT} \\ \text{CAT} \end{pmatrix}, s_\lambda(\mathcal{A}^*) = 0,$$

$$s(\mathcal{A}^*) = 9, ns(\mathcal{A}^*) = 9/16 = 0.5625$$

4. convergence $\Rightarrow \lambda^* = 0.5625$.

Conclusion: Normalized Alignment

- Normalized alignment helps to eliminate shadowing and mosaic effect
- General technique: Dinkelbach's Algorithm solves “Fractional programming” problems, where objective function is fraction
- Dinkelbach requires to solve parametric optimization problem (for $s_\lambda(\mathcal{A})$); works by distributing length-dependent terms
- Usually few iterations, but no worst-case bound; other methods are available (see Arslan, Bioinformatics, 2001)
- Normalized local alignment only a few times slower than local alignment
- Extensions to more complex scoring, e.g. affine gap cost