

Package ‘tpe’

August 29, 2013

Type Package

Title Tree preserving embedding

Version 1.0.1

Date 2013-03-15

Author Albert D. Shieh, Tatsunori B. Hashimoto, and Edoardo M. Airolidi

Maintainer Albert D. Shieh <adshieh@post.harvard.edu>

Description This package implements the greedy approximation for tree preserving embedding.

License MIT

LazyData yes

NeedsCompilation no

Repository CRAN

Date/Publication 2013-03-19 07:15:25

R topics documented:

tpe-package	2
digits	2
protein	3
radar	3
tpe1d	4
tpe2d	4
Index	6

tpe-package	<i>Tree preserving embedding</i>
-------------	----------------------------------

Description

This package implements the greedy approximation for tree preserving embedding.

Details

The functions `tpe1d` and `tpe2d` find one-dimensional and two-dimensional tree preserving embeddings respectively.

References

Shieh AD, Hashimoto TB, Airolidi EM (2011) Tree preserving embedding. *Proc Natl Acad Sci USA* 108:16916–16921.

digits	<i>Handwritten digits</i>
--------	---------------------------

Description

Euclidean distances between 1000 handwritten digits.

Usage

```
data(digits)
```

Format

A `dist` object with the dissimilarity matrix.

References

Hull JJ (1994) A database for handwritten text recognition research. *IEEE Trans Pattern Anal Mach Intell* 16:550–554.

protein

Protein sequences

Description

Inverse sequence alignment scores from the basic local alignment search tool (BLAST) between 124 protein sequences.

Usage

`data(protein)`

Format

A `dist` object with the dissimilarity matrix.

References

Pollack JD, Li Q, Pearl DK (2005) Taxonomic utility of a phylogenetic analysis of phosphoglycerate kinase proteins of archaea, bacteria, and eukaryota: Insights by bayesian analyses. *Mol Phylogenet Evol* 35:420–430.

radar

Radar signals

Description

Euclidean distances between 351 radar signals.

Usage

`data(radar)`

Format

A `dist` object with the dissimilarity matrix.

References

Sigillito VG, Wing SP, Hutton LV, Baker KB (1989) Classification of radar returns from the ionosphere using neural networks. *Johns Hopkins Apl Tech Dig* 10:262–266.

tpe1d	<i>One-dimensional tree preserving embedding</i>
-------	--

Description

Finds a one-dimensional tree preserving embedding of a dissimilarity matrix.

Usage

```
tpe1d(d, verbose=TRUE)
```

Arguments

d	A dist object with the dissimilarity matrix.
verbose	A logical value indicating whether to print progress.

Details

Implements the greedy approximation for one-dimensional tree preserving embedding.

Value

A matrix with the embedding coordinates.

References

Shieh AD, Hashimoto TB, Airoidi EM (2011) Tree preserving embedding. *Proc Natl Acad Sci USA* 108:16916–16921.

tpe2d	<i>Two-dimensional tree preserving embedding</i>
-------	--

Description

Finds a two-dimensional tree preserving embedding of a dissimilarity matrix.

Usage

```
tpe2d(d, verbose=TRUE)
```

Arguments

d	A dist object with the dissimilarity matrix.
verbose	A logical value indicating whether to print progress.

Details

Implements the greedy approximation for two-dimensional tree preserving embedding.

Value

A matrix with the embedding coordinates.

References

Shieh AD, Hashimoto TB, Airoidi EM (2011) Tree preserving embedding. *Proc Natl Acad Sci USA* 108:16916–16921.

Index

digits, [2](#)

dist, [2-4](#)

protein, [3](#)

radar, [3](#)

tpe (tpe-package), [2](#)

tpe-package, [2](#)

tpe1d, [2, 4](#)

tpe2d, [2, 4](#)