

Vanier College
Faculty of Careers and Technical Programs
Department of Computer Science Technology

Advanced UNIX

Lab #8

**Title: System Initialization, X-Windows
and Network Security**

**Student Names: Marissa Gonçalves
Amy Yip
Yulia Bakaleinik**

Submitted to Florin Pilat

November 13, 2020

Review Questions (p.378-381):

1. C) xvidtune
2. B) LILO needs to be reinstalled after it has been modified.
3. C) /etc/init.d
4. C) 0
5. D) /etc/inittab
6. C) startx
7. B) Either the MRB/GPT or the active partition can contain the boot loader.
8. D) (hd2, 1)
9. A) X.org
D) XFree86
10. A) /etc/rc2.d
11. A) /boot
12. C) init
13. B) init 1
14. A) seconds
15. D) grub2-mkconfig
16. C) Modify the daemon configuration file within the /etc/init directory.
17. B) systemctl stop lala.service
18. A) chkconfig --level 123 lala on
19. B) graphical.target
20. C) single

Project 8.3 (p.383-384):

Initial Commands

```
Ubuntu 14.04.1 LTS ubuntu tty1
ubuntu login: root
Password:
Last login: Tue Nov 10 18:08:56 EST 2020 on tty1
Welcome to Ubuntu 14.04.1 LTS (GNU/Linux 3.13.0-32-generic x86_64)

* Documentation:  https://help.ubuntu.com/

System information as of Tue Nov 10 18:11:47 EST 2020

System load:  2.47              Processes:            93
Usage of /:   6.9% of 17.38GB   Users logged in:     0
Memory usage: 4%               IP address for eth0: 192.168.2.103
Swap usage:   0%

Graph this data and manage this system at:
  https://landscape.canonical.com/

New release '16.04.7 LTS' available.
Run 'do-release-upgrade' to upgrade to it.
```

```
root@ubuntu:~# apt-get -y install postgresql
Reading package lists... Done
Building dependency tree
Reading state information... Done
postgresql is already the newest version.
0 upgraded, 0 newly installed, 0 to remove and 220 not upgraded.
```

```
root@ubuntu:~# apt-get -y install ssh
Reading package lists... Done
Building dependency tree
Reading state information... Done
ssh is already the newest version.
0 upgraded, 0 newly installed, 0 to remove and 220 not upgraded.
```

1.

```
Ubuntu 14.04.1 LTS ubuntu tty1
ubuntu login: root
Password:
Last login: Tue Nov 10 18:41:28 EST 2020 on tty1
Welcome to Ubuntu 14.04.1 LTS (GNU/Linux 3.13.0-32-generic x86_64)

* Documentation:  https://help.ubuntu.com/

System information as of Tue Nov 10 18:51:56 EST 2020

System load: 0.93           Memory usage: 3%    Processes:      81
Usage of /:  7.2% of 17.38GB Swap usage:   0%    Users logged in: 0

Graph this data and manage this system at:
https://landscape.canonical.com/

New release '16.04.7 LTS' available.
Run 'do-release-upgrade' to upgrade to it.

root@ubuntu:~#
```

2. Our current runlevel is in Multiuser Mode since the number 2 is displayed and our most recent runlevel is non-existent since “N” specifies that there is no previous runlevel.

```
root@ubuntu:~# runlevel
N 2
```

3. Basically, the contents in the /etc/init.d directory represent scripts that start or stop a specific daemon and each file from an /etc/rc[runlevel].d directory is a symbolic link to an executable rc script in this directory.

```
root@ubuntu:~# ls /etc/init.d
acpid          dns-clean      networking     rcS            sendsigs      umountnfs.sh
apparmor       friendly-recovery  ondemand      README         single        umountroot
appport        grub-common    postgresql     reboot         skeleton      unattended-upgrades
atd            halt           pppd-dns       resolvconf     ssh           urandom
console-setup  irqbalance     procps         rsync          sudo
cron           killprocs      rc             rsyslog        udev
dbus           kmod           rc.local       screen-cleanup umountfs
```

4. Essentially, the contents in the /etc/init directory represent the configuration files for each daemon, which indicates the standard wildcard notation to identify the runlevels in which the daemon should be started or stopped.

```
root@ubuntu:~# ls /etc/init
acpid.conf          mountall.sh.conf    rcS.conf
appport.conf        mountall-shell.conf rc-sysinit.conf
atd.conf            mountdevsubfs.sh.conf resolvconf.conf
bootmisc.sh.conf    mounted-debugfs.conf rsyslog.conf
checkfs.sh.conf     mounted-dev.conf    setvtrgb.conf
checkroot-bootclean.sh.conf mounted-proc.conf    shutdown.conf
checkroot.sh.conf   mounted-run.conf    ssh.conf
console.conf        mounted-tmp.conf    startpar-bridge.conf
console-font.conf   mounted-var.conf    systemd-logind.conf
console-setup.conf  mountkernfs.sh.conf tty1.conf
container-detect.conf mountnfs-bootclean.sh.conf tty2.conf
control-alt-delete.conf mountnfs.sh.conf    tty3.conf
cron.conf           mtab.sh.conf        tty4.conf
dbus.conf           networking.conf      tty5.conf
dmesg.conf          network-interface.conf tty6.conf
failsafe.conf       network-interface-container.conf udev.conf
flush-early-job-log.conf network-interface-security.conf udev-fallback-graphics.conf
friendly-recovery.conf passwd.conf          udev-finish.conf
hostname.conf       plymouth.conf        udevmonitor.conf
hwclock.conf        plymouth-log.conf    udevtrigger.conf
hwclock-save.conf   plymouth-ready.conf  ufw.conf
irqbalance.conf     plymouth-shutdown.conf upstart-file-bridge.conf
kmod.conf           plymouth-splash.conf upstart-socket-bridge.conf
mountall-bootclean.sh.conf plymouth-stop.conf  upstart-udev-bridge.conf
mountall.conf        plymouth-upstart-bridge.conf ureadahead.conf
mountall-net.conf    procps.conf          ureadahead-other.conf
mountall-reboot.conf rc.conf              wait-for-state.conf
```

5. The ssh daemon started in runlevels 2 (Multiuser Mode), 3 (Extended Multiuser Mode), 4 (Not Used) and 5 (Graphical Mode).

```
root@ubuntu:~# cat /etc/init/ssh.conf
# ssh - OpenBSD Secure Shell server
#
# The OpenSSH server provides secure shell access to the system.

description      "OpenSSH server"

start on runlevel [2345]
stop on runlevel [!2345]

respawn
respawn limit 10 5
umask 022

env SSH_SIGSTOP=1
expect stop

# 'sshd -D' leaks stderr and confuses things in conjunction with 'console log'
console none

pre-start script
    test -x /usr/sbin/sshd || { stop; exit 0; }
    test -e /etc/ssh/sshd_not_to_be_run && { stop; exit 0; }

    mkdir -p -m0755 /var/run/sshd
end script

# if you used to set SSHD_OPTS in /etc/default/ssh, you can change the
# 'exec' line here instead
exec /usr/sbin/sshd -D
```

6. The ssh daemon successfully restarted because this command uses the upstart init system, which means that the /etc/rc.d directories are not utilized and the /etc/init.d directory is able to execute the ssh script based on the information from the ssh.conf located in the /etc/init directory.

```
root@ubuntu:~# restart ssh
ssh start/running, process 1112
```

7. Yes, there are other traditional UNIX SysV daemons in runlevel 2 that are displayed since the number 2 is part of the directory name, which the contents include runlevel 2 scripts. The postgresql daemon is started after the apache2 daemon, since each daemon has a sequence number for execution in an orderly fashion. In this case, postgresql is started after apache2 because 19 is greater than 9.

```
root@ubuntu:~# ls /etc/rc2.d
README          S20rsync          S70dns-clean     S99grub-common   S99rc.local
S19postgresql   S20screen-cleanup S70pppd-dns      S99ondemand
```

8. There is an error message since this command uses the upstart init system, which doesn't utilize the /etc/rc.d directories. So, the postgresql daemon needs to be manipulated after system startup by using `restart` as an argument, thus not using the upstart init system.

```
root@ubuntu:~# restart postgresql
restart: Unknown job: postgresql
```

9. Yes, the postgresql daemon managed to restart successfully.

```
root@ubuntu:~# /etc/init.d/postgresql restart
* Restarting PostgreSQL 9.3 database server [ OK ]
```

10. Basically, the postgresql daemon was originally started in runlevels 0 (Halt), 1 (Single User Mode) and 6 (Reboot).

```
root@ubuntu:~# update-rc.d -f postgresql remove
Removing any system startup links for /etc/init.d/postgresql ...
/etc/rc0.d/K21postgresql
/etc/rc1.d/K21postgresql
/etc/rc2.d/S19postgresql
/etc/rc3.d/S19postgresql
/etc/rc4.d/S19postgresql
/etc/rc5.d/S19postgresql
/etc/rc6.d/K21postgresql
```

11.

```
root@ubuntu:~# update-rc.d postgresql defaults
Adding system startup for /etc/init.d/postgresql ...
/etc/rc0.d/K20postgresql -> ../init.d/postgresql
/etc/rc1.d/K20postgresql -> ../init.d/postgresql
/etc/rc6.d/K20postgresql -> ../init.d/postgresql
/etc/rc2.d/S20postgresql -> ../init.d/postgresql
/etc/rc3.d/S20postgresql -> ../init.d/postgresql
/etc/rc4.d/S20postgresql -> ../init.d/postgresql
/etc/rc5.d/S20postgresql -> ../init.d/postgresql
```

12. Yes, the `init` command could have been used instead of the `telinit` command, since the `init` command is an alias to the `telinit` command.

```
root@ubuntu:~# telinit 6
root@ubuntu:~# wait-for-state stop/waiting
* Stopping PostgreSQL 9.3 database server [ OK ]
* Stopping rsync daemon rsync [ OK ]
* Asking all remaining processes to terminate... [ OK ]
* All processes ended within 1 seconds... [ OK ]
```

13.

```
Ubuntu 14.04.1 LTS ubuntu tty1

ubuntu login: root
Password:
Last login: Tue Nov 10 18:53:47 EST 2020 on tty1
Welcome to Ubuntu 14.04.1 LTS (GNU/Linux 3.13.0-32-generic x86_64)

* Documentation:  https://help.ubuntu.com/

System information as of Tue Nov 10 19:10:31 EST 2020

System load: 1.18           Memory usage: 3%    Processes:      81
Usage of /:  7.2% of 17.38GB Swap usage:   0%    Users logged in: 0

Graph this data and manage this system at:
  https://landscape.canonical.com/

New release '16.04.7 LTS' available.
Run 'do-release-upgrade' to upgrade to it.
```


14.

```
root@ubuntu:~# poweroff

root@ubuntu:~# Broadcast message from root@ubuntu
(/dev/tty1) at 20:40 ...

The system is going down for power off NOW!
wait-for-state stop/waiting
```

Network Security Tasks:

Validating Files

1.

```
Fedora 26 (Workstation Edition)
Kernel 4.16.11-100.fc26.x86_64 on an x86_64 (tty2)

server13 login: root
Password:
Last login: Thu Nov  5 11:23:59 on tty2
[root@server13 ~]#
```

```
Ubuntu 14.04.1 LTS ubuntu tty2

ubuntu login: root
Password:
Last login: Tue Nov 10 20:40:13 EST 2020 on tty1
Welcome to Ubuntu 14.04.1 LTS (GNU/Linux 3.13.0-32-generic x86_64)

* Documentation:  https://help.ubuntu.com/

System information as of Tue Nov 10 20:45:04 EST 2020

System load: 0.87           Memory usage: 3%    Processes:      80
Usage of /:  7.2% of 17.38GB Swap usage:   0%    Users logged in: 0

Graph this data and manage this system at:
https://landscape.canonical.com/

New release '16.04.7 LTS' available.
Run 'do-release-upgrade' to upgrade to it.
```

2.

```
[root@server13 ~]# man md5sum
```

```
MD5SUM(1)                                User Commands                                MD5SUM(1)

NAME
    md5sum - compute and check MD5 message digest

SYNOPSIS
    md5sum [OPTION]... [FILE]...

DESCRIPTION
    Print or check MD5 (128-bit) checksums.

    With no FILE, or when FILE is -, read standard input.

    -b, --binary
        read in binary mode

    -c, --check
        read MD5 sums from the FILEs and check them

    --tag
        create a BSD-style checksum

    -t, --text
        read in text mode (default)

    Note: There is no difference between binary and text mode option on GNU system.

    The following five options are useful only when verifying checksums:

    --ignore-missing
        don't fail or report status for missing files

    --quiet
        don't print OK for each successfully verified file

    --status
        don't output anything, status code shows success

Manual page md5sum(1) line 1 (press h for help or q to quit)
```

```
MD5SUM(1)                                User Commands                                MD5SUM(1)

NAME
    md5sum - compute and check MD5 message digest

SYNOPSIS
    md5sum [OPTION]... [FILE]...

DESCRIPTION
    Print or check MD5 (128-bit) checksums.

    With no FILE, or when FILE is -, read standard input.

    -b, --binary
        read in binary mode

    -c, --check
        read MD5 sums from the FILEs and check them

    --tag
        create a BSD-style checksum

    -t, --text
        read in text mode (default)

    Note: There is no difference between binary and text mode option on GNU system.

    The following five options are useful only when verifying checksums:

    --ignore-missing
        don't fail or report status for missing files

    --quiet
        don't print OK for each successfully verified file

    --status
        don't output anything, status code shows success

[root@server13 ~]# _
```

```
root@ubuntu:~# man md5sum _
```

NAME

md5sum - compute and check MD5 message digest

SYNOPSIS

md5sum [OPTION]... [FILE]...

DESCRIPTION

Print or check MD5 (128-bit) checksums. With no FILE, or when FILE is -, read standard input.

-b, --binary

read in binary mode

-c, --check

read MD5 sums from the FILES and check them

--tag create a BSD-style checksum

-t, --text

read in text mode (default)

The following three options are useful only when verifying checksums:

--quiet

don't print OK for each successfully verified file

--status

don't output anything, status code shows success

-w, --warn

warn about improperly formatted checksum lines

--strict

with --check, exit non-zero for any invalid input

```

MD5SUM(1)                                User Commands                                MD5SUM(1)

NAME
    md5sum - compute and check MD5 message digest

SYNOPSIS
    md5sum [OPTION]... [FILE]...

DESCRIPTION
    Print or check MD5 (128-bit) checksums. With no FILE, or when FILE is -, read standard
    input.

    -b, --binary
        read in binary mode

    -c, --check
        read MD5 sums from the FILEs and check them

    --tag
        create a BSD-style checksum

    -t, --text
        read in text mode (default)

    The following three options are useful only when verifying checksums:

    --quiet
        don't print OK for each successfully verified file

    --status
        don't output anything, status code shows success

    -w, --warn
        warn about improperly formatted checksum lines

    --strict
        with --check, exit non-zero for any invalid input

root@ubuntu:~#

```

3.

```
[root@server13 ~]# cp /bin/bash /root
```

```
root@ubuntu:~# cp /bin/bash /root
```

4.

```
[root@server13 ~]# md5sum -b bash
704e0110eca67c37dcc798ad246ae271 *bash
```

```
root@ubuntu:~# md5sum -b bash
b8fc7876e5e69f356837d87de8a1427e *bash
```

5.

```
[root@server13 ~]# md5sum --b bash>bash.md5  
[root@server13 ~]# _
```

```
root@ubuntu:~# md5sum --b bash>bash.md5  
root@ubuntu:~#
```

6.

```
[root@server13 ~]# md5sum --check bash.md5  
bash: OK
```

```
root@ubuntu:~# md5sum --check bash.md5  
bash: OK
```

7.

```
[root@server13 ~]# echo "123" >> bash  
[root@server13 ~]# _
```

```
root@ubuntu:~# echo "123" >> bash  
root@ubuntu:~# _
```

8.

```
[root@server13 ~]# md5sum --check bash.md5  
bash: FAILED  
md5sum: WARNING: 1 computed checksum did NOT match
```

```
root@ubuntu:~# md5sum --check bash.md5  
bash: FAILED  
md5sum: WARNING: 1 computed checksum did NOT match
```

9.

```
[root@server13 ~]# rm bash  
rm: remove regular file 'bash'? y  
[root@server13 ~]#
```

```
root@ubuntu:~# rm bash  
root@ubuntu:~#
```

10.

```
[root@server13 ~]# logout
```

```
Fedora 26 (Workstation Edition)  
Kernel 4.16.11-100.fc26.x86_64 on an x86_64 (tty2)  
  
server13 login:
```

```
root@ubuntu:~# logout_
```

```
Ubuntu 14.04.1 LTS ubuntu tty2  
  
ubuntu login:
```

Using SSH

1.

```
Fedora 26 (Workstation Edition)
Kernel 4.16.11-100.fc26.x86_64 on an x86_64 (tty2)

server13 login: marissa
Password:
Last login: Thu Nov 12 11:33:56 on tty2
[marissa@server13 ~]$ ifconfig
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 192.168.2.104 netmask 255.255.255.0 broadcast 192.168.2.255
    inet6 fe80::8f4e:86ea:9e67:4eda prefixlen 64 scopeid 0x20<link>
    ether 08:00:27:ea:85:c7 txqueuelen 1000 (Ethernet)
    RX packets 183 bytes 21358 (20.8 KiB)
    RX errors 0 dropped 7 overruns 0 frame 0
    TX packets 90 bytes 10033 (9.7 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

virbr0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    inet 192.168.122.1 netmask 255.255.255.0 broadcast 192.168.122.255
    ether 52:54:00:53:64:64 txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

[marissa@server13 ~]$
```



```
Ubuntu 14.04.1 LTS ubuntu tty1

ubuntu login: marissa
Password:
Last login: Thu Nov 12 11:31:31 EST 2020 on tty1
Welcome to Ubuntu 14.04.1 LTS (GNU/Linux 3.13.0-32-generic x86_64)

 * Documentation:  https://help.ubuntu.com/

System information as of Thu Nov 12 11:31:31 EST 2020

System load:  0.04               Processes:            78
Usage of /:    7.2% of 17.38GB   Users logged in:     0
Memory usage:  4%               IP address for eth0: 192.168.2.103
Swap usage:    0%

Graph this data and manage this system at:
https://landscape.canonical.com/

New release '16.04.7 LTS' available.
Run 'do-release-upgrade' to upgrade to it.

marissa@ubuntu:~$ _
```

```
marissa@ubuntu:~$ ifconfig
eth0      Link encap:Ethernet  HWaddr 08:00:27:77:7a:d2
          inet addr:192.168.2.103  Bcast:192.168.2.255  Mask:255.255.255.0
          inet6 addr: fe80::a00:27ff:fe77:7ad2/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:341 errors:0 dropped:13 overruns:0 frame:0
          TX packets:48 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:39995 (39.9 KB)  TX bytes:4346 (4.3 KB)

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:65536  Metric:1
          RX packets:90 errors:0 dropped:0 overruns:0 frame:0
          TX packets:90 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:40433 (40.4 KB)  TX bytes:40433 (40.4 KB)
```

```
[marissa@server13 ~]$ ping 192.168.2.103
PING 192.168.2.103 (192.168.2.103) 56(84) bytes of data.
64 bytes from 192.168.2.103: icmp_seq=1 ttl=64 time=1.14 ms
64 bytes from 192.168.2.103: icmp_seq=2 ttl=64 time=0.625 ms
64 bytes from 192.168.2.103: icmp_seq=3 ttl=64 time=0.770 ms
64 bytes from 192.168.2.103: icmp_seq=4 ttl=64 time=0.689 ms
64 bytes from 192.168.2.103: icmp_seq=5 ttl=64 time=0.699 ms
64 bytes from 192.168.2.103: icmp_seq=6 ttl=64 time=0.823 ms
64 bytes from 192.168.2.103: icmp_seq=7 ttl=64 time=0.656 ms
^C
--- 192.168.2.103 ping statistics ---
7 packets transmitted, 7 received, 0% packet loss, time 6010ms
rtt min/avg/max/mdev = 0.625/0.772/1.143/0.164 ms
[marissa@server13 ~]$
```

```
root@ubuntu:~# ping 192.168.2.104
PING 192.168.2.104 (192.168.2.104) 56(84) bytes of data.
64 bytes from 192.168.2.104: icmp_seq=1 ttl=64 time=0.836 ms
64 bytes from 192.168.2.104: icmp_seq=2 ttl=64 time=1.15 ms
64 bytes from 192.168.2.104: icmp_seq=3 ttl=64 time=0.608 ms
64 bytes from 192.168.2.104: icmp_seq=4 ttl=64 time=0.913 ms
64 bytes from 192.168.2.104: icmp_seq=5 ttl=64 time=0.814 ms
64 bytes from 192.168.2.104: icmp_seq=6 ttl=64 time=0.758 ms
^C
--- 192.168.2.104 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5005ms
rtt min/avg/max/mdev = 0.608/0.847/1.157/0.170 ms
root@ubuntu:~# _
```

```

[marissa@server13 ~]$ /bin/systemctl status sshd.service
● sshd.service - OpenSSH server daemon
   Loaded: loaded (/usr/lib/systemd/system/sshd.service; disabled; vendor preset: disabled)
   Active: inactive (dead)
     Docs: man:sshd(8)
           man:sshd_config(5)
[marissa@server13 ~]$ /bin/systemctl start sshd.service
==== AUTHENTICATING FOR org.freedesktop.systemd1.manage-units ====
Authentication is required to start 'sshd.service'.
Authenticating as: Marissa (marissa)
Password:
==== AUTHENTICATION COMPLETE ====
[marissa@server13 ~]$ /bin/systemctl status sshd.service
● sshd.service - OpenSSH server daemon
   Loaded: loaded (/usr/lib/systemd/system/sshd.service; disabled; vendor preset: disabled)
   Active: active (running) since Thu 2020-11-12 12:18:02 EST; 11s ago
     Docs: man:sshd(8)
           man:sshd_config(5)
  Main PID: 1460 (sshd)
    Tasks: 1 (limit: 4915)
   CGroup: /system.slice/sshd.service
           └─1460 /usr/sbin/sshd -D

Nov 12 12:18:01 server13.domain.com systemd[1]: Starting OpenSSH server daemon...
Nov 12 12:18:02 server13.domain.com sshd[1460]: Server listening on 0.0.0.0 port 22.
Nov 12 12:18:02 server13.domain.com sshd[1460]: Server listening on :: port 22.
Nov 12 12:18:02 server13.domain.com systemd[1]: Started OpenSSH server daemon.

```

```

root@ubuntu:~# apt-get install systemd
Reading package lists... Done
Building dependency tree
Reading state information... Done
systemd is already the newest version.
0 upgraded, 0 newly installed, 0 to remove and 215 not upgraded.

```

```

root@ubuntu:~# apt-get install -y ssh
Reading package lists... Done
Building dependency tree
Reading state information... Done
ssh is already the newest version.
0 upgraded, 0 newly installed, 0 to remove and 215 not upgraded.

```

```

root@ubuntu:~# service ssh status
ssh start/running, process 865

```

2.

```

[marissa@server13 ~]$ cat /etc/passwd | grep marissa
marissa:x:1000:1000:Marissa:/home/marissa:/bin/bash

```

```

root@ubuntu:~# cat /etc/passwd | grep marissa
marissa:x:1000:1000:Marissa,,,:/home/marissa:/bin/bash

```

```
root@ubuntu:~# ssh marissa@192.168.2.104
The authenticity of host '192.168.2.104 (192.168.2.104)' can't be established.
ECDSA key fingerprint is 59:5e:60:e6:c1:dd:72:73:9b:1b:c6:b1:c6:55:fd:5a.
Are you sure you want to continue connecting (yes/no)? _
```

3.

```
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '192.168.2.104' (ECDSA) to the list of known hosts.
Connection closed by 192.168.2.104
root@ubuntu:~# _
```

4.

```
root@ubuntu:~# ssh marissa@192.168.2.104
marissa@192.168.2.104's password:
Last login: Thu Nov 12 13:13:03 2020 from 192.168.2.104
[marissa@server13 ~]$ cat /etc/fedora-release
Fedora release 26 (Twenty Six)
[marissa@server13 ~]$ whoami
marissa
[marissa@server13 ~]$ pwd
/home/marissa
[marissa@server13 ~]$ ls -l
total 44
drwxr-xr-x. 2 marissa marissa 4096 Sep 17 21:18 Desktop
drwxr-xr-x. 3 marissa marissa 4096 Sep 18 09:09 Documents
drwxr-xr-x. 2 marissa marissa 4096 Sep 17 21:18 Downloads
drwxr-xr-x. 2 marissa marissa 4096 Sep 17 21:18 Music
drwxrwxr-x. 4 marissa marissa 4096 Oct 1 12:38 mysamples2
-rw-rw-r--. 1 marissa marissa 0 Oct 1 13:37 newfile
drwxr-xr-x. 2 marissa marissa 4096 Sep 17 21:18 Pictures
drwxr-xr-x. 2 marissa marissa 4096 Sep 17 21:18 Public
drwxrwxr-x. 4 marissa marissa 4096 Oct 1 13:04 samples
-r-Sr-Sr--. 1 marissa marissa 0 Oct 8 08:27 specialfile
-rwxrwxr-x. 1 marissa marissa 440 Nov 5 14:49 tasks
drwxr-xr-x. 2 marissa marissa 4096 Sep 17 21:18 Templates
drwxr-xr-x. 2 marissa marissa 4096 Sep 17 21:18 Videos
[marissa@server13 ~]$
```

5.

```
[marissa@server13 ~]$ exit
logout
Connection to 192.168.2.104 closed.
root@ubuntu:~#
```

6.

```
root@ubuntu:~# cd .ssh
root@ubuntu:~/ssh# ls -l
total 4
-rw-r--r-- 1 root root 222 Nov 12 13:11 known_hosts
```

7.

```
root@ubuntu:~/ssh# cat known_hosts
11iKy85uq1rXYOPNT5NWft8ZqJnBqU=iWkmzbNxsA6ZnTc7Dj5ZVK48BMdU= ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBE9Xz8mjF+2CPofbyJxPe0zNyCyoS+EyENS7vqXDXHja7kFA4f1hzWq4AwSHwQe4T0rk6JiMcEGfsz79k4AQ/Cs=
```

8.

```
[marissa@server13 ~]$ ssh marissa@192.168.2.104
The authenticity of host '192.168.2.104 (192.168.2.104)' can't be established.
ECDSA key fingerprint is SHA256:BmWk0keEXni9BgqfyG7PqEJ6KkN7Ien0dtB2Gc4dXi8.
ECDSA key fingerprint is MD5:59:5e:60:e6:c1:dd:72:73:9b:1b:c6:b1:c6:55:fd:5a.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '192.168.2.104' (ECDSA) to the list of known hosts.
marissa@192.168.2.104's password:
Last login: Thu Nov 12 13:37:53 2020 from 192.168.2.103
[marissa@server13 ~]$ exit
logout
Connection to 192.168.2.104 closed.
[marissa@server13 ~]$ cd .ssh
[marissa@server13 .ssh]$ ls -l
total 4
-rw-r--r-- 1 marissa marissa 175 Nov 12 13:43 known_hosts
[marissa@server13 .ssh]$ cat known_hosts
192.168.2.104 ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBE9Xz8mjF+2CPofbyJxPe0zNyCyoS+EyENS7vqXDXHja7kFA4f1hzWq4AwSHwQe4T0rk6JiMcEGfsz79k4AQ/Cs=
[marissa@server13 .ssh]$
```

9.

```
root@ubuntu:~/ssh# vi known_hosts
```

i1iKy85uq1rXYOPNT5NWft8ZqJnBqU=iWkmzbNxsA6ZnTc7Dj5ZUK48BMdU= ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTIIbm1zdHAyNTYAAAAIbmlzdHAyNTYAAABBBE9Xz8mjF+ZCPofbyJxPe0zNyCyoS+EyENs7vqXDHXja7kFA4f1hzWq4AwSHwQe4T0rk6JiMcEGfsz79k4AQ/Cs=

"known_hosts" 1L, 222C

1,1

All

```
f1i62y5y06eP9Gs5XqGQHv6iFKImg=iFw+JFcETGSHRDMwFpGwGJbdb2Wg =cdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBBfo88CCXDD jLYHnMcQrMLuvnuS/rTqdOtBNQavXcISVSzgr4IT0Emy0+DaMh3ENLSptTANJA774xgwKOPf2yuDs=
```

bm:

10.

```
root@ubuntu:~# ssh marissa@192.168.2.104
@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@
@    WARNING: REMOTE HOST IDENTIFICATION HAS CHANGED!     @
@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@@
IT IS POSSIBLE THAT SOMEONE IS DOING SOMETHING NASTY!
Someone could be eavesdropping on you right now (man-in-the-middle attack)!
It is also possible that a host key has just been changed.
The fingerprint for the ECDSA key sent by the remote host is
47:b8:1d:30:b4:03:5b:d4:13:09:3a:c1:91:58:fa:f7.
Please contact your system administrator.
Add correct host key in /root/.ssh/known_hosts to get rid of this message.
Offending ECDSA key in /root/.ssh/known_hosts:1
  remove with: ssh-keygen -f "/root/.ssh/known_hosts" -R 192.168.2.104
ECDSA host key for 192.168.2.104 has changed and you have requested strict checking.
Host key verification failed.
```

11.

```
root@ubuntu:~/ssh# vi known_hosts_
```



```
root@ubuntu:~/ssh# ssh marissa@192.168.2.104
The authenticity of host '192.168.2.104 (192.168.2.104)' can't be established.
ECDSA key fingerprint is 47:b8:1d:30:b4:03:5b:d4:13:09:3a:c1:91:58:fa:f7.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '192.168.2.104' (ECDSA) to the list of known hosts.
marissa@192.168.2.104's password:
Last login: Thu Nov 12 14:27:03 2020 from 192.168.2.103
[marissa@server13 ~]$ exit
logout
Connection to 192.168.2.104 closed.
root@ubuntu:~/ssh# cat known_hosts
|1:8Vo2CwZ0BDTr7UnHlyI8s0lciJM=|KR5Uicrb7/YQP60xQFJiwUkZTrs= ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBFo88CCXDDjLYHnMcQrMLuvnuS/rTqdOtBNQauXcISUSzgR4IT0Emy0+DaMh3ENLSptTANJA774xgWKOPfZyuDs=
```


12.

```
marissa@ubuntu:~$ su
Password:
root@ubuntu:/home/marissa# cd
root@ubuntu:~# cd .ssh
root@ubuntu:~/.ssh# cp known_hosts /etc/ssh/ssh_known_hosts
root@ubuntu:~/.ssh# exit
exit
```

```
marissa@ubuntu:~$ su
Password:
root@ubuntu:/home/marissa# cd
root@ubuntu:~# rm ~/.ssh/known_hosts
root@ubuntu:~# _
```

13.

```
root@ubuntu:~# ssh marissa@192.168.2.104
marissa@192.168.2.104's password:
Last login: Thu Nov 12 14:30:15 2020 from 192.168.2.103
[marissa@server13 ~]$ exit
logout
Connection to 192.168.2.104 closed.
root@ubuntu:~# _
```

14.

```
root@ubuntu:~# exit
exit
marissa@ubuntu:~$ exit_
```

```
Ubuntu 14.04.1 LTS ubuntu tty1
```

```
ubuntu login:
```