

1.Uptime.c

```
mariu@DESKTOP-0K07MJA:~$ cd ~/xv6-labs-2025
mariu@DESKTOP-0K07MJA:~/xv6-labs-2025$ make qemu
mv -f fs.img fs.img.bk
mkfs/mkfs fs.img README user/findtest.sh user/sixfive.txt user/_cat us
/_kill user/_ln user/_ls user/_mkdir user/_rm user/_sh user/_stressfs
user/_logstress user/_forphan user/_dorphan user/_sleep user/_sixfive
ser/_memdump
nmeta 47 (boot, super, log blocks 31, inode blocks 13, bitmap blocks 1
balloc: first 1191 blocks have been allocated
balloc: write bitmap block at sector 46
qemu-system-riscv64 -machine virt -bios none -kernel kernel/kernel -m
egacy=false -drive file=fs.img,if=none,format=raw,id=x0 -device virtio

xv6 kernel is booting

hart 2 starting
hart 1 starting
init: starting sh
$ uptime
uptimeuptime: 29 ticks$ |
```

2.Updated find.c

```
$ find / ^.*sh$
//findtest.sh
//sh
$ |
```

3.No \$ when reading instructions from file:

```
hart 1 starting
hart 2 starting
init: starting sh
$ echo "ls" > script.sh
$ sh < script.sh
$ exec "ls" failed
```

Incorrect output

4.Wait:

```
$
$
$
$ sleep 10 &
$ wait
$ |
```

allows sleep to continue until completion

5. Tab completion:

```
init: starting sh
$ ec
echo$ l
ls.          1 1 1024
..           1 1 1024
README      2 2 2425
findtest.sh 2 3 91
sixfive.txt 2 4 19
cat          2 5 36512
echo        2 6 35360
forktest    2 7 17080
grep        2 8 39944
```

After pressing tab you have to press enter to complete the instruction

6. history updating:

```
$
$ sleep 10 &
$ wait
$ history
1  echo "ls" > script.sh

2  sh < script.sh

3  echo hello

4  #

5  sleep 10 &

6  history

$ |
```

was a command I incorrectly entered