

AquaPearl 500 Pro Installation Guide

Version 2.2

Pre-installation

Confirm 20-80 psi feed pressure, grounded 220-240 V socket, cold-water feed, drain access and dry cabinet clearance.

Verification note 1: Confirm 20-80 psi feed pressure, grounded 220-240 V socket, cold-water feed, drain access and dry cabinet clearance. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Confirm 20-80 psi feed pressure, grounded 220-240 V socket, cold-water feed, drain access and dry cabinet clearance. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Confirm 20-80 psi feed pressure, grounded 220-240 V socket, cold-water feed, drain access and dry cabinet clearance. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Professional installation

Standard professional installation booking fee is PKR 3,500 in covered service cities. Extra plumbing/electrical materials are quoted separately.

Verification note 1: Standard professional installation booking fee is PKR 3,500 in covered service cities. Extra plumbing/electrical materials are quoted separately. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Standard professional installation booking fee is PKR 3,500 in covered service cities. Extra plumbing/electrical materials are quoted separately. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Standard professional installation booking fee is PKR 3,500 in covered service cities. Extra plumbing/electrical materials are quoted separately. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure

and electrical requirements. Stop and request professional help when safe completion is uncertain.

Mounting

Use the supplied bracket on a stable vertical surface with service clearance and no sharp tubing bends.

Verification note 1: Use the supplied bracket on a stable vertical surface with service clearance and no sharp tubing bends. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Use the supplied bracket on a stable vertical surface with service clearance and no sharp tubing bends. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Use the supplied bracket on a stable vertical surface with service clearance and no sharp tubing bends. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Feed connection

Close cold-water supply, fit approved inlet adapter, make square tubing cuts, reopen slowly and inspect for leaks.

Verification note 1: Close cold-water supply, fit approved inlet adapter, make square tubing cuts, reopen slowly and inspect for leaks. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Close cold-water supply, fit approved inlet adapter, make square tubing cuts, reopen slowly and inspect for leaks. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Close cold-water supply, fit approved inlet adapter, make square tubing cuts, reopen slowly and inspect for leaks. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Drain saddle

Install at a suitable point before the trap, use the supplied gasket and route tubing without a low waste-water loop.

Verification note 1: Install at a suitable point before the trap, use the supplied gasket and route tubing without a low waste-water loop. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Install at a suitable point before the trap, use the supplied gasket and route tubing without a low waste-water loop. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Install at a suitable point before the trap, use the supplied gasket and route tubing without a low waste-water loop. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Electrical

Keep adapter and socket dry. Do not energise while hands/connectors are wet and do not improvise mains wiring.

Verification note 1: Keep adapter and socket dry. Do not energise while hands/connectors are wet and do not improvise mains wiring. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Keep adapter and socket dry. Do not energise while hands/connectors are wet and do not improvise mains wiring. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Keep adapter and socket dry. Do not energise while hands/connectors are wet and do not improvise mains wiring. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

First-run flushing

After leak checks, fill the system and flush at least 10 litres through the drinking faucet before drinking. Repeat the 10-litre flush after applicable filter changes.

Verification note 1: After leak checks, fill the system and flush at least 10 litres through the drinking faucet before drinking. Repeat the 10-litre flush after applicable filter changes. Before

continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: After leak checks, fill the system and flush at least 10 litres through the drinking faucet before drinking. Repeat the 10-litre flush after applicable filter changes. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: After leak checks, fill the system and flush at least 10 litres through the drinking faucet before drinking. Repeat the 10-litre flush after applicable filter changes. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Leak check

Inspect fittings during initial pressure, after ten minutes and after first tank fill. Isolate leaks from purifier body or electrical areas.

Verification note 1: Inspect fittings during initial pressure, after ten minutes and after first tank fill. Isolate leaks from purifier body or electrical areas. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Inspect fittings during initial pressure, after ten minutes and after first tank fill. Isolate leaks from purifier body or electrical areas. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Inspect fittings during initial pressure, after ten minutes and after first tank fill. Isolate leaks from purifier body or electrical areas. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Self-installation warranty

Self-installation does not automatically cancel warranty, but damage from incorrect pressure, supply, cross-threading or unauthorised modification is excluded.

Verification note 1: Self-installation does not automatically cancel warranty, but damage from incorrect pressure, supply, cross-threading or unauthorised modification is excluded. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Self-installation does not automatically cancel warranty, but damage from incorrect pressure, supply, cross-threading or unauthorised modification is excluded. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Self-installation does not automatically cancel warranty, but damage from incorrect pressure, supply, cross-threading or unauthorised modification is excluded. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Booking

Provide city, order/serial reference and installation-location details when booking professional service.

Verification note 1: Provide city, order/serial reference and installation-location details when booking professional service. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 2: Provide city, order/serial reference and installation-location details when booking professional service. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.

Verification note 3: Provide city, order/serial reference and installation-location details when booking professional service. Before continuing, confirm the previous step is dry, mechanically secure, and consistent with the stated pressure and electrical requirements. Stop and request professional help when safe completion is uncertain.