

AquaPearl 500 Pro Product Manual - Version 3.1

1. Product Overview

AquaPearl 500 Pro is a residential under-sink reverse-osmosis purifier with pump assistance, electronic filter monitoring and optional app connectivity. It is designed for point-of-use drinking and cooking water. The purifier should be installed in a dry, ventilated cabinet with service clearance. It is not a whole-house system or a medical device.

Operational note 1. AquaPearl 500 Pro is a residential under-sink reverse-osmosis purifier with pump assistance, electronic filter monitoring and optional app connectivity. It is designed for point-of-use drinking and cooking water. The purifier should be installed in a dry, ventilated cabinet with service clearance. It is not a whole-house system or a medical device. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. AquaPearl 500 Pro is a residential under-sink reverse-osmosis purifier with pump assistance, electronic filter monitoring and optional app connectivity. It is designed for point-of-use drinking and cooking water. The purifier should be installed in a dry, ventilated cabinet with service clearance. It is not a whole-house system or a medical device. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. AquaPearl 500 Pro is a residential under-sink reverse-osmosis purifier with pump assistance, electronic filter monitoring and optional app connectivity. It is designed for point-of-use drinking and cooking water. The purifier should be installed in a dry, ventilated cabinet with service clearance. It is not a whole-house system or a medical device. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

2. Box Contents

The retail package includes purifier assembly, starter sediment/carbon/membrane/mineral stages, faucet kit, feed-water adapter, drain saddle, colour-marked tubing, mounting bracket and screws, power adapter, leak-sensor pad, filter wrench, quick-start card and small parts bag. Promotional extras are not part of the standard box list.

Operational note 1. The retail package includes purifier assembly, starter sediment/carbon/membrane/mineral stages, faucet kit, feed-water adapter, drain saddle, colour-marked tubing, mounting bracket and screws, power adapter, leak-sensor pad, filter wrench, quick-start card and small parts bag. Promotional extras are not part of the standard box list. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. The retail package includes purifier assembly, starter sediment/carbon/membrane/mineral stages, faucet kit, feed-water adapter, drain saddle, colour-marked tubing, mounting bracket and screws, power adapter, leak-sensor pad, filter wrench, quick-start card and small parts bag. Promotional extras are not part of the standard box list. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. The retail package includes purifier assembly, starter sediment/carbon/membrane/mineral stages, faucet kit, feed-water adapter, drain saddle, colour-marked tubing, mounting bracket and screws, power adapter, leak-sensor pad, filter wrench, quick-start card and small parts bag. Promotional extras are not part of the standard box list. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

3. Technical Specifications

Rated purified flow is up to 1.2 litres per minute under nominal conditions. Integrated storage is 8 litres nominal. Feed-water pressure range is 20-80 psi. Electrical input is 220-240 V AC at 50 Hz through the supplied adapter. Pump operation is about 72 W. Body dimensions are approximately 410 x 265 x 445 mm.

Operational note 1. Rated purified flow is up to 1.2 litres per minute under nominal conditions. Integrated storage is 8 litres nominal. Feed-water pressure range is 20-80 psi. Electrical input is 220-240 V AC at 50 Hz through the supplied adapter. Pump operation is about 72 W. Body dimensions are approximately 410 x 265 x 445 mm. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. Rated purified flow is up to 1.2 litres per minute under nominal conditions. Integrated storage is 8 litres nominal. Feed-water pressure range is 20-80 psi. Electrical input is 220-240 V AC at 50 Hz through the supplied adapter. Pump operation is about 72 W. Body dimensions are approximately 410 x 265 x 445 mm. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. Rated purified flow is up to 1.2 litres per minute under nominal conditions. Integrated storage is 8 litres nominal. Feed-water pressure range is 20-80 psi. Electrical input is 220-240 V AC at 50 Hz through the supplied adapter. Pump operation is about 72 W. Body dimensions are approximately 410 x 265 x 445 mm. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

4. Control Panel

POWER indicates powered state. WATER pulses during active purification. FILTER changes from normal to amber maintenance warning and can appear red with a fault/maintenance code. WIRELESS pulses in pairing mode. SERVICE indicates a condition requiring review. RESET should be used only after the relevant maintenance action.

Operational note 1. POWER indicates powered state. WATER pulses during active purification. FILTER changes from normal to amber maintenance warning and can appear red with a fault/maintenance code. WIRELESS pulses in pairing mode. SERVICE indicates a condition requiring review. RESET should be used only after the relevant maintenance action. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. POWER indicates powered state. WATER pulses during active purification. FILTER changes from normal to amber maintenance warning and can appear red with a fault/maintenance code. WIRELESS pulses in pairing mode. SERVICE indicates a condition requiring review. RESET should be used only after the relevant maintenance action. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. POWER indicates powered state. WATER pulses during active purification. FILTER changes from normal to amber maintenance warning and can appear red with a fault/maintenance code. WIRELESS pulses in pairing mode. SERVICE indicates a condition requiring review. RESET should be used only after the relevant maintenance action. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

5. Operating Instructions

Open the feed valve slowly and verify visible fittings are dry. Connect power after plumbing is complete. On first run, allow filling and complete the flushing procedure in the Installation Guide before drinking. The pump can run while replenishing storage after heavy use. Unusually long continuous operation should be investigated.

Operational note 1. Open the feed valve slowly and verify visible fittings are dry. Connect power after plumbing is complete. On first run, allow filling and complete the flushing procedure in the Installation Guide before drinking. The pump can run while replenishing storage after heavy use. Unusually long continuous operation should be investigated. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. Open the feed valve slowly and verify visible fittings are dry. Connect power after plumbing is complete. On first run, allow filling and complete the flushing procedure in the Installation Guide before drinking. The pump can run while replenishing storage after heavy use. Unusually long continuous operation should be investigated. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. Open the feed valve slowly and verify visible fittings are dry. Connect power after plumbing is complete. On first run, allow filling and complete the flushing procedure in the Installation Guide before drinking. The pump can run while replenishing storage after heavy use. Unusually long continuous operation should be investigated. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

6. Filter Intervals

Sediment is normally replaced every 6 months or sooner when E-03 appears. Carbon is normally 12 months. The membrane is typically 24-36 months depending on feed water and use. Mineral/post-carbon stage is normally 12 months. These are maintenance intervals, not warranty periods, and cartridges are consumables.

Operational note 1. Sediment is normally replaced every 6 months or sooner when E-03 appears. Carbon is normally 12 months. The membrane is typically 24-36 months depending on feed water and use. Mineral/post-carbon stage is normally 12 months. These are maintenance intervals, not warranty periods, and cartridges are consumables. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. Sediment is normally replaced every 6 months or sooner when E-03 appears. Carbon is normally 12 months. The membrane is typically 24-36 months depending on feed water and use. Mineral/post-carbon stage is normally 12 months. These are maintenance intervals, not warranty periods, and cartridges are consumables. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. Sediment is normally replaced every 6 months or sooner when E-03 appears. Carbon is normally 12 months. The membrane is typically 24-36 months depending on feed water and use. Mineral/post-carbon stage is normally 12 months. These are maintenance intervals, not warranty periods, and cartridges are consumables. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

7. Cartridge Replacement

Close the inlet, switch off power and open the faucet briefly to reduce pressure. Identify the correct cartridge by model/stage, release it using the documented mechanism, install the correct replacement and reopen water slowly while checking for leaks. After sediment replacement, hold RESET for five seconds after seating is confirmed.

Operational note 1. Close the inlet, switch off power and open the faucet briefly to reduce pressure. Identify the correct cartridge by model/stage, release it using the documented mechanism, install the correct replacement and reopen water slowly while checking for leaks. After sediment replacement, hold RESET for five seconds after seating is confirmed. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. Close the inlet, switch off power and open the faucet briefly to reduce pressure. Identify the correct cartridge by model/stage, release it using the documented mechanism, install the correct replacement and reopen water slowly while checking for leaks. After sediment replacement, hold RESET for five seconds after seating is confirmed. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. Close the inlet, switch off power and open the faucet briefly to reduce pressure. Identify the correct cartridge by model/stage, release it using the documented mechanism, install the correct replacement and reopen water slowly while checking for leaks. After sediment replacement, hold RESET for five seconds after seating is confirmed. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

8. Cleaning and Descaling

Wipe the exterior with a soft damp cloth and mild detergent. Do not spray electrical openings or use abrasive pads and harsh solvents. Clean the faucet aerator about every three months or when flow pattern changes. Routine descaling is recommended every 6 months in normal service, earlier if visible scale or local hardness justifies it.

Operational note 1. Wipe the exterior with a soft damp cloth and mild detergent. Do not spray electrical openings or use abrasive pads and harsh solvents. Clean the faucet aerator about every three months or when flow pattern changes. Routine descaling is recommended every 6 months in normal service, earlier if visible scale or local hardness justifies it. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. Wipe the exterior with a soft damp cloth and mild detergent. Do not spray electrical openings or use abrasive pads and harsh solvents. Clean the faucet aerator about every three months or when flow pattern changes. Routine descaling is recommended every 6 months in normal service, earlier if visible scale or local hardness justifies it. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. Wipe the exterior with a soft damp cloth and mild detergent. Do not spray electrical openings or use abrasive pads and harsh solvents. Clean the faucet aerator about every three months or when flow pattern changes. Routine descaling is recommended every 6 months in normal service, earlier if visible scale or local hardness justifies it. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

9. Audible Alert Codes

E-01: inlet-water interruption. E-02: low inlet pressure. E-03: three short beeps plus red filter light, sediment pre-filter saturation. E-04: carbon-stage service. E-05: membrane performance warning. E-06: leak sensor active. E-07: pump overload. E-08: alternating continuous tone for electrical/control fault.

Operational note 1. E-01: inlet-water interruption. E-02: low inlet pressure. E-03: three short beeps plus red filter light, sediment pre-filter saturation. E-04: carbon-stage service. E-05: membrane performance warning. E-06: leak sensor active. E-07: pump overload. E-08: alternating continuous tone for electrical/control fault. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. E-01: inlet-water interruption. E-02: low inlet pressure. E-03: three short beeps plus red filter light, sediment pre-filter saturation. E-04: carbon-stage service. E-05: membrane performance warning. E-06: leak sensor active. E-07: pump overload. E-08: alternating continuous tone for electrical/control fault. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. E-01: inlet-water interruption. E-02: low inlet pressure. E-03: three short beeps plus red filter light, sediment pre-filter saturation. E-04: carbon-stage service. E-05: membrane performance warning. E-06: leak sensor active. E-07: pump overload. E-08: alternating continuous tone for electrical/control fault. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

10. Safety Warnings

Do not operate with a wet/damaged power adapter, exposed arcing, repeated breaker trips or water in electrical compartments. Close the feed valve before cartridge service. Keep electrical connections dry. Smoke, burning smell, E-08 or water in the power module require safe shutdown and human support. Do not open sealed electrical or pressure compartments.

Operational note 1. Do not operate with a wet/damaged power adapter, exposed arcing, repeated breaker trips or water in electrical compartments. Close the feed valve before cartridge service. Keep electrical connections dry. Smoke, burning smell, E-08 or water in the power module require safe shutdown and human support. Do not open sealed electrical or pressure compartments. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. Do not operate with a wet/damaged power adapter, exposed arcing, repeated breaker trips or water in electrical compartments. Close the feed valve before cartridge service. Keep electrical connections dry. Smoke, burning smell, E-08 or water in the power module require safe shutdown and human support. Do not open sealed electrical or pressure compartments. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. Do not operate with a wet/damaged power adapter, exposed arcing, repeated breaker trips or water in electrical compartments. Close the feed valve before cartridge service. Keep electrical connections dry. Smoke, burning smell, E-08 or water in the power module require safe shutdown and human support. Do not open sealed electrical or pressure compartments. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

11. Mobile App Pairing

Enable Bluetooth and local-network permissions. Keep the phone within three metres, hold CONNECT for three seconds until the wireless indicator pulses and select a 2.4 GHz Wi-Fi network in the Pearlz app. If pairing fails, confirm the router and phone can use 2.4 GHz and retry before factory-resetting the purifier.

Operational note 1. Enable Bluetooth and local-network permissions. Keep the phone within three metres, hold CONNECT for three seconds until the wireless indicator pulses and select a 2.4 GHz Wi-Fi network in the Pearlz app. If pairing fails, confirm the router and phone can use 2.4 GHz and retry before factory-resetting the purifier. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. Enable Bluetooth and local-network permissions. Keep the phone within three metres, hold CONNECT for three seconds until the wireless indicator pulses and select a 2.4 GHz Wi-Fi network in the Pearlz app. If pairing fails, confirm the router and phone can use 2.4 GHz and retry before factory-resetting the purifier. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. Enable Bluetooth and local-network permissions. Keep the phone within three metres, hold CONNECT for three seconds until the wireless indicator pulses and select a 2.4 GHz Wi-Fi network in the Pearlz app. If pairing fails, confirm the router and phone can use 2.4 GHz and retry before factory-resetting the purifier. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

AquaPearl 500 Pro Product Manual - Version 3.1

12. Service Records and Storage

For support, record serial number, firmware when available, displayed code, symptom timing and recent maintenance. For storage longer than one month, close the inlet, disconnect power, drain accessible water under service guidance, prevent freezing, inspect for damage and flush completely before drinking after recommissioning.

Operational note 1. For support, record serial number, firmware when available, displayed code, symptom timing and recent maintenance. For storage longer than one month, close the inlet, disconnect power, drain accessible water under service guidance, prevent freezing, inspect for damage and flush completely before drinking after recommissioning. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 2. For support, record serial number, firmware when available, displayed code, symptom timing and recent maintenance. For storage longer than one month, close the inlet, disconnect power, drain accessible water under service guidance, prevent freezing, inspect for damage and flush completely before drinking after recommissioning. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.

Operational note 3. For support, record serial number, firmware when available, displayed code, symptom timing and recent maintenance. For storage longer than one month, close the inlet, disconnect power, drain accessible water under service guidance, prevent freezing, inspect for damage and flush completely before drinking after recommissioning. Record the model, serial number, indicator state and recent maintenance. Do not infer warranty, certification or commercial exceptions that are absent from approved documentation. If the documented customer procedure is unsafe or insufficient, isolate the appliance when appropriate and contact authorised support.