

System Entities

Item:

- a discoverable unit in the digital repository.
- An item contains 0 or more components.
- If an item contains 1 or more components, it must also contain a structural metadata record.
- An item must contain one or more descriptive metadata records.
- An item is typed; the item type determines what components are valid.
- An item may have relationships with other items; ie. [item A] isMemberOfCollection [item B]
- An item will be assigned a status: Incomplete, Complete, Published, etc.
- An item can be qualified with arbitrary indicators ("Needs translation") that relate to the workflow of a given project.

Descriptive Metadata Record (DMR)

- unit of description
- Must be associated with a Metadata Profile

Component:

- an atomic unit of digital content. For example, an image, a page of a book, a text document, a pdf.
- A component contains a bitstream representing the content, or a URI pointing to a bitstream, as well as administrative metadata for the bitstream.

Relationship:

- a defined relationship linking two items in the repository
- examples of relationships: isMemberOfCollection; hasCollectionMember; isFeaturedItem; hasFeaturedItem; isPartOf; hasPart
- converse relationship types allow for bidirectional linking (ex. EAD finding aid to image, image to EAD finding aid)

ResultSet:

- an arbitrary grouping of items based on some criteria.
- Some examples of sets are all items that are members of the Gamble collection, all items that are tagged as owned by Dave K., all incomplete items, or any search result.

Item Types:

- Collection
- Category
- NamedSet

- Image, [Multi-Image]
- Book, [Page]
- Text
- Media (audio and video)
- Query
- Pointer (uri to point to another record)

Collection:

- a collection is an item with special properties.
- A collection has relationships with other items, relationships in the form of "item" isMemberOfCollection "collection". The relationships are one-to-many, meaning that each item can only be a member of, at most, one collection.
- A collection can contain multiple categories.
- A collection may have a metadata profile associated with it.

Category:

- a defined, persistent grouping of items within a collection
- A category has relationships with other items, relationships in the form of "item" isMemberOfCategory "category". The relationships are one-to-many, meaning that each item can only be a member of, at most, one category.
- A category may have a metadata profile associated with it.
- A category may be associated with descriptive metadata record.

Image:

- an image item contains descriptive metadata and one or more image components

Book:

- a book item contains descriptive metadata and one or more page (image?) components

Text:

- a text item contains descriptive metadata and one tei-encoded xml component

Media:

- a media item contains descriptive metadata and one or more audio/video components

Pointer:

- a record contains descriptive metadata and a URI component

NamedSet:

- a NamedSet contains descriptive metadata and relationships with Items

Query:

- a query item contains descriptive metadata and a representation of a search query

Metadata Application Profile:

- See [Trident/MetadataApplicationProfile](#).
- Metadata describing metadata use for an item. Profile is assigned to an item.
- The profile describes what metadata fields are used and which are required. The requirements are expressed with validation rules. A profile can contain 0 or more validation rules.
- The profile also includes what are considered valid values for metadata fields. In other words, the profile includes which authority lists should be used for which metadata fields.
- Validating DMR
- building DMR editing screen
- displaying DMR to end user
- providing guidance to cataloger
- formulating indexing rules

Validation Rule:

- a test that evaluates to true or false for descriptive metadata.
- The evaluation of validation rules will determine of whether or not given metadata is valid.

Trident Users

Trident will need to support the activities of several different types of users, each with a different role and with different sets of tasks. It is important that Trident provide UI that supports each user's tasks. Roles should have permissions relevant to their tasks to allow them to complete.

This document describes these users and their tasks in Tripod.

Admin

An admin manages the system. He/She creates collections, and users. An admin has access to all functions in trident and access to all collections in the repository

Tasks:

- Create/Update/Delete [Collection](#)
- Create/Update/Delete users

Collection Manager

Collection Managers facilitate the execution of projects. They need to be able to monitor collection progress, verify metadata records, create/edit/delete records, manage cataloger permissions, create/edit the collection level metadata, publish the collection.

Tasks:

- Monitor Collection progress
- Create/Update Collection [Collection](#)
- Verify [Items](#)
- Create/Retrieve/Update/Delete [Items](#)
- Add catalogers to the [Collection](#) (?)
- Add catalogers to the [Item](#) (?)
- Publish/Unpublish [Collection](#)
- Report problems with [Items](#)
- Define Metadata Profile for [Collection](#)
- Create/Update/Delete [Categories](#)

Cataloger

Catalogers create and maintain metadata records for items in the repository. Catalogers may need to be granted access to records in specific collections.

Tasks:

- View incomplete [Items](#)
- Create/Retrieve/Update/Delete [Items](#)

Limited Cataloger

A cataloger with limited permissions. This user may be a student employee.

Tasks

- View incomplete [Items](#)
- Update [Items](#)

Observer

An observer keeps track of a project's status but does not contribute to the item metadata or components. A collection sponsor may be an observer.

Tasks:

- Monitor Collection progress
- Report problems with [Items](#)
- Report problems with [Collections](#)

Digital Production Manager

The Digital Production Manager runs the digitization process. This includes grouping scannable objects, managing scanner operators, performing quality control assessments of scans, and adding components to items.

Tasks:

- Identify [Items](#) and [Components](#) for digitization
- Create scanning specifications
- Scan materials
- Create/Retrieve/Update [Items](#)
- Create/Retrieve/Update/Delete [Components](#)
- Add scanner operators to system and/or collection
- Group [Components](#)
- Check [Components](#) for quality/correctness

Scanner Operator

A scanner operator digitizes materials, adds components to an item, and create technical metadata. The current workflow has scanner operators checking out groups of items that are then scanned.

Tasks:

- Scan materials
- Create/Retrieve/Update [Items](#)
- Create/Retrieve/Update/Delete [Components](#)

- ◆ Add [Component](#) files to Trident
- ◆ Create Administrative Metadata for component
- Create [Component](#) derivatives