

RCS-e open source stack



Roadmap

Date: 03/08/2012


Author: Orange Labs, ASC Devices



Open source project

■ Open source published at:

<http://code.google.com/p/android-rcs-ims-stack/>



Main contributors

- Orange Labs
- Deutsche Telecom
- HTC
- Sony
- Motorola



History...

- 2007 / First RCS stack for J2ME platform.
- 2008-2009 / RCS 1.0 stack:
 - GSMA IOT: Helsinki (2008) / First participation.
 - GSMA IOT: Paris (2009).
 - GSMA IOT: Munich (2009).
- Jan. 2010 / First RCS stack for Android platform.
- 2010 / RCS 2.0 stack:
 - GSMA IOT: Paris (2010).
 - GSMA IOT: Beijing (2010).
 - GSMA IOT: Madrid (2010).
- Jan. 2011 / RCS 2.0 stack:
 - GSMA IOT: Helsinki (2011).
 - OrangeLabs stack is taken as Reference Implementation by GSMA.
- Feb. 2011 / Integrate the same SIP stack as Google Android 2.3.
- March 2011 / RCS-e stack implementation based on 2.0 stack started.
- April 2011 / First RCS-e 1.1 release available.
- Mai 2011: RCS-e stack published to open source community.
- End of 2011: native integration by several device manufacturers.



Roadmaps



Roadmap 2012

■ January 16: Sprint 14

- IOT tests.
- HTTPS provisioning module.
- Findbugs report.

■ January 30: Sprint 15

- IOT tests.
- HTTPS provisioning version management.
- DNS management (NAPTR & SRV).
- End user confirmation request API to accept terms of use.

■ February 10: Sprint 16

- IOT tests.

■ February 22: Sprint 17

- Bug fix after IOT tests.

■ March 12: Sprint 18

- Bug fix after IOT tests.
- Rename package of the NIST SIP stack to avoid concurrency problems with native NIST SIP stack.
- Update source code copyrights.



Roadmap 2012

■ March 30: Sprint 19

- IOT tests.
- GSMA RCS Implementation Guidelines.
- Nonce caching.

■ April 13: Sprint 20

- IOT tests.
- GSMA RCS Implementation Guidelines.

■ April 30: Sprint 21

- Provisioning terms.
- IOT tests.

■ May 21: Sprint 22

- Backup & restore RCS settings.
- Bug correction.

■ June 22: Sprint 23

- GSMA UI Connector.
- Bug correction.



Roadmap 2012

■ July 06: Sprint 24

- IOT test fest (Madrid).
- IPv6 tests.

■ August 14: Sprint 25 or v2.4.7

- GSMA Guidelines 3.0.
- IOT test fest issues.

■ August 31: Sprint 26 or v2.4.8

- GSMA Guidelines 3.0.
- IOT test fest issues.

■ Next sprints:

- RCS5 / Blackbird release



Main features list



Capability discovery

- Capability discovery via SIP OPTIONS.
- Capability discovery via Anonymous fetch.
- Periodic polling.
- First time discovery.
- Address book monitoring.
- Integration into native address book.
- Supported capabilities: CS video, IM, FT, Image share, Video share, Presence discovery, Social presence, RCS extensions.
- Update capabilities in case of error, end of session.
- Adapt capabilities thanks to network coverage.



Chat 1/2

- Chat 1-1.
- Chat group.
- File transfer.
- Chat and file transfer history.
- Multi-session management.
- Is-composing.
- List of participants in the session.
- Add 1 participant.
- Add N participants.
- Conference event subscription.
- Support of plain text UTF-8 format.
- Support of message/CPIM format.
- IMDN and message delivery report (“delivered”, “displayed”).



Chat 2/2

- Block/unblock contacts (black list).
- Spam folder for message received from blocked contacts.
- Store & Forward.
- Use an alias to initiate a chat session.
- Close a chat session after an inactivity timeout.



Richcall

- Image sharing.
- Live video & pre-recorded video sharing.
- Capability exchange during call.
- Call monitoring.
- H263 file parser.
- H263+ software codec (from Android opencore package).
- H.264 packetizer.
- H264 software codec (from Android opencore package).
- RTCP event management.
- Visio share from 2 individual video share sessions.
- Stop sharing if call hold or if a multiparty call (see new API methods).



Social presence

- Resource lists management (granted/blocked/revoked).
- Profile sharing management (status, photo-icon, freetext, favorite link, geoloc).
- Notifications management.
- Permanent and partial profile



Misc.1/2

- Address book integration via ContactContract API.
- Event log history (one content provider which aggregates Call/SMS/MMS/Chat & FT per contact).
- RCS account based on SyncAdapter API.
- Presence is now an optional package which may be activated by configuration.
- RTP stack is now part of the media player to avoid AIDL exchange between UI and stack.
- New SIP stack (NIST SIP stack deployed under Android 2.3).
- Backup and restore last RCS info if user account has changed.
- OTA provisioning via HTTPS.
- Session refresh management.



Misc. 2/2


- Support of GIBA & HTTP Digest for IMS attachment.
- Support several network access: mobile or Wi-fi.
- RCS API for multi-applications context.
- SIPS
- GRUU for multidevice management.



Implementation



Software architecture




Supported standards

- See list of supported standards at:

<http://android-rcs-ims-stack.googlecode.com/svn/trunk/core/SUPPORTED-STANDARDS.txt>




Metrics



Tools

- Bug tracking via Mantis.
- Continuous Integration via Hudson.
- RI application which offers a low level UI interface to test RCS stack and its protocols:



RI application





RCS-e applications



Screenshots



RCS account





RCS settings



Native address book integration 1/2

**Native
address
book
from HTC**



Local provisioning application

Only for debug

Provisioning

Profile Stack Service Logger

IMS authentication procedure:
DIGEST

IMS username:
+34890890022

IMS display name:
+34890890022

IMS private URI:
+34890890022@sip.osp.com

IMS password:
nsnims2008

IMS home domain:

Provisioning

Profile Stack Service Logger

Is-composing timeout for chat (seconds):
15

Session refresh expire period (seconds):
3600

Capability refresh timeout (seconds):
86400

Capability polling period (seconds):
3600

Capability discovery mode:
options

☒ Rich call mode

Provisioning


Profile Stack Service Logger

☒ Trace activation

☒ SIP trace activation

☒ Media trace activation

Trace level:
DEBUG

 Save

