



LOOKUPVALUE()



Returns a value from another table by searching for one or more matching conditions.



LOOKUPVALUE(
result_column,
search_column,
search_value
)



LOOKUPVALUE(
Products[ProductName],
Products[ProductID],
Sales[ProductID]
)



XLOOKUP()



Searches for a value in one range and returns the corresponding value from another range.



XLOOKUP(lookup_value, lookup_array, return_array, [if_not_found],
[match_mode], [search_mode])



XLOOKUP(A2, E:E, F:F, "SKU not found",0)

Difference



- 🍏 Searches tables in the data model
- 🍏 Often uses relationships
- 🍏 Works inside calculated columns and measures



- 🍏 Searches worksheet ranges
- 🍏 Uses cell references
- 🍏 Works inside worksheet cells



IF()

Returns one value if a condition is TRUE and another if FALSE.



IF()

Returns one value if a condition is TRUE and another if FALSE.



IF(
logical_test,
value_if_true,
value_if_false
)



IF(logical_test, value_if_true, value_if_false)



LOOKUPVALUE(
Sales[Amount] > 5000,
"High",
"Low",
)



IF(A2>5000, "High", "Low")

Difference



🍏 References columns



🍏 References cells



SWITCH()

Evaluates multiple conditions without nested IF statements.



SWITCH()

Evaluates multiple conditions without nested IF statements.



SWITCH(
expression,
value1, result1
value2, result2
else
)



SWITCH(expression, value1, result1, value2, result2, default)



SWITCH(
Sales[Month],
1, "Q1"
2, "Q2"
"Other"
)



SWITCH(A2, 1,"Q1", 2, "Q2", "other")

Difference



🍏 References columns



🍏 References cells



IFERROR()

Returns an alternative value if an expression produces an error.



IFERROR()

Evaluates multiple conditions without nested IF statements.



IFERROR(
value,
value_if_error
)



IFERROR(value, value_if_error)



IFERROR(
Sales[Revenue] / Sales[Quantity],
"No QTY!"
)



IFERROR(A2/B2, 0)

Difference



🍏 Handles errors in DAX expressions



🍏 Handles worksheet formula errors



ISBLANK()

Checks whether a value is blank.



ISBLANK()

Returns True or False.



ISBLANK(
value
)



ISBLANK(cell)



IF(
ISBLANK(Customer[Phone],
"Missing",
"Available"
)



ISBLANK(A2)

Difference



🍏 Checks blank values in columns or expressions



🍏 Checks whether a specific cell is empty