



Node.js Streams & Buffers



Mohamed Mukthar Ahmed

1



Streams & Buffers



Outline

What are Streams?

The stream Module

Why streams?

Stream-powered APIs

Different Types of Streams

Creating a readable stream

Creating a writeable stream

Piping

What is a Buffer?

Why do we need a buffer?

Accessing buffer content

Changing content of a buffer

Buffer Slicing

Copy a buffer



Mohamed Mukthar Ahmed

2



Mohamed Mukthar Ahmed

3

What are streams?



- **Streams** are one of the **fundamental concepts** that **power Node.js** applications.
- They are a **way** to handle
 - reading/writing files,
 - network communications, or
 - any kind of end-to-end information exchange
- in an efficient way.
- Streams are not a concept unique to Node.js. They were introduced in the **UNIX** operating system decades ago.
- Programs can interact with each other passing streams through the **pipe operator (|)**.

Mohamed Mukthar Ahmed

4

Use Case



- In the traditional way, when you tell the program to read a file, the file is read into memory, from start to finish, and then you process it.
- Using streams you **read it piece by piece**, processing its content without keeping it all in memory.
- **Use Case**
 - Let's take a “**streaming**” services such as **YouTube** or **Netflix** for example: these services don't make you download the video and audio feed all at once. Instead, your browser receives the video as a continuous flow of chunks, allowing the recipients to start watching and/or listening almost immediately.
 - However, streams are not only about working with media or big data. They also give us the power of '**composability**' in our code.

Mohamed Mukthar Ahmed

5

Node.js stream Module



- The Node.js **stream** module provides the foundation upon which all **streaming APIs** are built.
- All **streams** are instances of **EventEmitter**

Mohamed Mukthar Ahmed

6

Why Streams?



- Streams basically provide **two major advantages** over using other data handling methods:
 - **Memory efficiency**
 - You don't need to load large amounts of data in memory before you are able to process it
 - **Time efficiency**
 - It takes way less time to start processing data, since you can start processing as soon as you have it, rather than waiting till the whole data payload is available

Mohamed Mukthar Ahmed

7

Stream-powered Node.js APIs



- Due to their **advantages**, many Node.js core modules provide native stream handling capabilities, most notably:
 - **process.stdin** returns a stream connected to **stdin**
 - **process.stdout** returns a stream connected to **stdout**
 - **process.stderr** returns a stream connected to **stderr**
 - **fs.createReadStream()** creates a **readable stream** to a file
 - **fs.createWriteStream()** creates a **writable stream** to a file

Mohamed Mukthar Ahmed

8

Different Types of Streams



- There are **FOUR** classes of streams:
- **Readable**: a stream which could be used for read data from it. In other words, its **readonly**.
- **Writable**: a stream which could be used for write data to it. It is **writeonly**.
- **Duplex**: a stream which can read and write data, basically its a combination of a Readable and Writable stream.
- **Transform**: a Duplex stream which reads data, transforms the data, and then writes the transformed data in the desired format.


Mohamed Mukthar Ahmed

9

Different Types of Streams



- There are **FOUR** classes of streams:



Mohamed Mukthar Ahmed

10

Creating a readable stream



- We first require the Readable stream, and we initialize it.


```
const Stream = require('stream')
```

```
const readableStream = new Stream.Readable()
```

- Now that the stream is initialized, we can send data to it:

```
readableStream.push('ping!')
```

```
readableStream.push('pong!')
```



Mohamed Mukthar Ahmed

11

Two Reading Modes



- According to Streams API, readable streams effectively operate in one of two modes: **flowing** and **paused**.
- In **flowing mode**, data is read from the underlying system automatically and provided to an application as quickly as possible using events via the **EventEmitter** interface.
- In **paused mode**, the **stream.read()** method must be called explicitly to read chunks of data from the stream.

Mohamed Mukthar Ahmed

12

Code Example



```
const fs = require("fs");
var data = '';

const readerStream = fs.createReadStream('./assets/file1.txt'); //

readerStream.setEncoding('UTF8'); // Set the encoding to be utf8.

// Handle stream events --> data, end, and error
readerStream.on('data', function(chunk) {
  data += chunk;
});

readerStream.on('end', function() {
  console.log(data);
});

readerStream.on('error', function(err) {
  console.error(err.stack);
});

console.log("Program Ended");
```

Mohamed Mukthar Ahmed

13

Code Example




```
const fs = require('fs');
const readableStream = fs.createReadStream('./assets/file1.txt');
var data = '';
var chunk;

readableStream.on('readable', function() {
  while ((chunk=readableStream.read(1)) != null) {
    data += chunk;
    console.log(data);
  }
});

readableStream.on('end', function() {
  console.log(data)
});
```

Mohamed Mukthar Ahmed

14



15




Creating a writable stream



- To write data to a **writable stream** you need to call **write()** on the stream instance.
- Calling the **writable.end()** method signals that no more data will be written to the Writable.

```
// Write 'hello, ' and then end with 'world!'.
const fs = require('fs');
const file = fs.createWriteStream('example.txt');
file.write('hello, ');
file.end('world!');
// Writing more now is not allowed!
```



16

Piping




- **Piping** is a mechanism where we provide the output of one stream as the input to another stream.
- It is normally used to get data from one stream and to pass the output of that stream to another stream.
- There is no limit on piping operations. In other words, piping is used to process streamed data in multiple steps.
- In **Node 10.x** was introduced **stream.pipeline()**. This is a module method to pipe between streams.

*The **pipeline** should be used instead of **pipe**, as **pipe** is unsafe.*

Mohamed Mukthar Ahmed

17

Piping



Mohamed Mukthar Ahmed

18

Piping



```

File Edit Selection View Go Run ... stream_ex8.js - NodeJS-Demos - Visual ...
JS stream_ex6.js JS stream_ex7.js JS stream_ex8.js X JS stream_ex1.js
JS stream_ex8.js > ...
1  /*
2    Author : Mohamed Mukthar Ahmed
3    Date   :
4    Purpose: Using the pipeline() method instead of pipe()
5  */
6  const { pipeline } = require('stream');
7  const fs = require('fs');
8  const zlib = require('zlib');
9
10 pipeline(
11   fs.createReadStream('./assets/file1.txt'),
12   zlib.createGzip(),
13   fs.createWriteStream('./assets/file1.gz'),
14   (err) => {
15     if (err) {
16       console.error('Pipeline failed', err);
17     } else {
18       console.log('Pipeline succeeded !');
19     }
20   }
21 );

```

Mohamed Mukthar Ahmed

19

What is a Buffer?



- A **buffer** is an **area of memory**.
- Most JavaScript developers are much less familiar with this concept.
- It represents a fixed-size chunk of memory (can't be resized) allocated outside of the V8 JavaScript engine.
- You can think of a buffer like an array of integers, each representing a byte of data.
- It is implemented by the Node.js **Buffer** class.

Mohamed Mukthar Ahmed

20

Why do we need a buffer?



- Buffers were introduced to help developers **deal with binary data**.
- Buffers in Node.js are **not related** to the concept of buffering data.

How to create a buffer?

- A buffer is created using the **Buffer.from()**, **Buffer.alloc()**, and **Buffer.allocUnsafe()** methods.
- You can also just initialize the buffer passing the size.

```
const buf = Buffer.from('Hey!');
const buf = Buffer.alloc(1024);
```

Mohamed Mukhtar Ahmed

21

Access the content of a buffer



- A buffer, being an array of bytes, can be accessed like an array:

```
const buf = Buffer.from('Hey!');
console.log(buf[0]); // 72
console.log(buf[1]); // 101
console.log(buf[2]); // 121
```

- Those numbers are the UTF-8 bytes that identify the characters in the buffer (H → 72, e → 101, y → 121).
- Get the **length** of a buffer

```
const buf = Buffer.from('Hey!');
console.log(buf.length);
```

- Iterate over the contents of a buffer

Mohamed Mukhtar Ahmed

22

Access the content of a buffer

- Iterate over the contents of a buffer

```
const buf = Buffer.from('Hey!');
for (const item of buf) {
  console.log(item); // 72 101 121 33
}
```

- Changing the content of a buffer
- You can write to a buffer a whole string of data by using the **write()** method:

```
const buf = Buffer.alloc(4);
buf.write('Hey!');
```

Mohamed Mukthar Ahmed

23

Changing the content of a buffer

- Just like you can access a buffer with an array syntax, you can also set the contents of the buffer in the same way:

```
const buf = Buffer.from('Hey!');
buf[1] = 111; // o in UTF-8
console.log(buf.toString()); // Hoy!
```

Mohamed Mukthar Ahmed

24

Buffer Slicing



- If you want to create a **partial visualization** of a buffer, you can create a **slice**.
- A slice is not a copy: the original buffer is still the source of truth. If that changes, your slice changes.
- Use the **subarray()** method to create it. The first parameter is the starting position, and you can specify an optional second parameter with the end position.

```
const buf = Buffer.from('Hey!');
buf.subarray(0).toString(); // Hey!
const slice = buf.subarray(0, 2);
console.log(slice.toString()); // He
buf[1] = 111; // o
console.log(slice.toString()); // Ho
```

Mohamed Mukthar Ahmed

25

Copy a buffer



- Copying a buffer is possible using the **set()** method:

```
const buf = Buffer.from('Hey!');
const bufcopy = Buffer.alloc(4);
// allocate 4 bytes
bufcopy.set(buf);
```

- By default you copy the whole buffer. If you only want to copy a part of the buffer, you can use **.subarray()** and the offset argument that specifies an offset to write to:

```
const buf = Buffer.from('Hey?');
const bufcopy = Buffer.from('Moo!');
bufcopy.set(buf.subarray(1, 3), 1);
console.log(bufcopy.toString());
// 'Mey!'
```

Mohamed Mukthar Ahmed

26