



Forms



Mohamed Mukthar Ahmed

208



Forms

Outline

Forms are Crucial

Template-driven and Reactive

Choosing an approach

Key Differences

Common Form foundation classes

Setup – Template-driven Forms

Form Component & Template

Setup – Reactive Forms

Form Component & Template

The onSubmit Event

The ngSubmit Directive

Form Validation

Q&A



Mohamed Mukthar Ahmed

209

■ Forms are Crucial



- The most **crucial** aspect of your web application
- Handling user input with forms is the **cornerstone** of many common applications.
- Applications use forms
 - to enable users to log in,
 - to update a profile,
 - to enter sensitive information, and
 - to perform many other data-entry tasks.
- Angular provides **two different approaches** to handling user input through forms:
 - **Template-driven**
 - **Reactive**

Mohamed Mukthar Ahmed

210

■ Forms are Crucial



- Thankfully, **Angular** has tools to build forms
 - **Form** foundation **classes** encapsulate the inputs in our forms and give us objects to work with them
 - **Validators** give us the ability to validate inputs, any way we'd like
 - **Observers** let us watch our form for changes and respond accordingly

Mohamed Mukthar Ahmed

211

■ Choosing an approach



- **Template-driven** forms and **Reactive** forms process and manage form data differently.
- Each approach offers different **advantages**.
- **Template-driven** forms
 - Rely on **directives** in the template to create and manipulate the underlying object model.
 - They are useful for adding a simple form to an app, such as an **email list signup** form.
 - They're straightforward to add to an app, but they **don't scale** as well as reactive forms.
 - If you have very basic form requirements and logic that can be managed solely in the template, template-driven forms could be a good fit.

Mohamed Mukthar Ahmed

212

■ Choosing an approach



- **Template-driven** forms and **Reactive** forms process and manage form data differently.
- Each approach offers different advantages.
- **Reactive** forms
 - Provide **direct, explicit access** to the underlying form's object model.
 - Compared to template-driven forms, they are **more robust**: they're more scalable, reusable, and testable.
 - If forms are a key part of your application, or you're already using **reactive patterns** for building your application, use reactive forms.

Mohamed Mukthar Ahmed

213

Key Differences



- The table summarizes the **key differences** between template-driven and reactive forms.

Key Difference		
Factors	Template-Driven	Reactive
Setup of form model	Implicit, created by directive	Explicit, created in component class
Data model	Unstructured and mutable	Structured and immutable
Data flow	Asynchronous	Synchronous
Form validation	Directives	Functions

Mohamed Mukthar Ahmed

214

Common Form foundation classes



- Both template-driven and reactive forms are built on the following **base classes**

Foundation Classes	
Class	Details
FormControl	Tracks the value and validation status of an individual form control
FormGroup	Tracks the same values and status for a collection of form controls
FormArray	Tracks the same values and status for an array of form controls
ControlValueAccessor	Creates a bridge between Angular FormControl instances and built-in DOM elements

Mohamed Mukthar Ahmed

215

■ Setup - Template-driven Forms



- In template-driven forms, the form model is **implicit**, rather than explicit.
- The directive **NgModel** creates and manages a **FormControl** instance for a given form element.
- The following component implements the same input field for a single control, using template-driven forms.

Mohamed Mukthar Ahmed

216

■ Template-driven Form Component



```
1  import { Component, OnInit } from '@angular/core';
2
3  @Component({
4    selector: 'app-template-form',
5    templateUrl: './template-form.component.html',
6    styleUrls: ['./template-form.component.css']
7  })
8
9  export class TemplateFormComponent implements OnInit {
10    favoriteColor: string = '';
11
12    constructor() { }
13
14    ngOnInit(): void {
15    }
16
17  }
```

Mohamed Mukthar Ahmed

217

■ Setup - Template-driven Forms



- In a template-driven form the **source of truth** is the template.
- You do not have **direct programmatic access** to the **FormControl** instance


```
1 Favorite Color: <input type="text" [(ngModel)]="favoriteColor">
2 <div *ngIf="favoriteColor">
3   <p>Your favourite color: {{ favoriteColor }}</p>
4 </div>
```

- Observe the use of **NgModel** directive.

Mohamed Mukthar Ahmed


218

■ Template-Driven Form



Mohamed Mukthar Ahmed

219



Mohamed Mukthar Ahmed

220



Setup - Reactive Forms



- With **reactive** forms, you define the form model directly in the component class.
- The **[formControl]** directive links the explicitly created **FormControl** instance to a specific form element in the view, using an internal value accessor.
- The following component implements an input field for a single control, using reactive forms.
- In this example, the form model is the **FormControl** instance.

Mohamed Mukthar Ahmed

221

Reactive Form Component



```
1 import { Component, OnInit } from '@angular/core';
2 import { FormControl } from '@angular/forms';
3
4 @Component({
5   selector: 'app-reactive-form',
6   templateUrl: './reactive-form.component.html',
7   styleUrls: ['./reactive-form.component.css']
8 })
9
10 export class ReactiveFormComponent implements OnInit {
11   favoriteColorControl = new FormControl('');
12   constructor() { }
13
14   ngOnInit(): void {
15   }
16
17 }
```

Mohamed Mukhtar Ahmed

222

Reactive Form Template



```
1 Favorite Color:
2 <input type="text" [formControl]="favoriteColorControl">
3 <br />
4 <br />
5 <div *ngIf="favoriteColorControl">
6   Your favorite color : {{ favoriteColorControl }}
7 </div>
```

Mohamed Mukhtar Ahmed

223

Setup - Reactive Forms




- In reactive forms, the **form model** is the source of truth.
- It provides the **value** and **status** of the form element at any given point in time, through the **[formControl]** directive on the input element.

Mohamed Mukthar Ahmed


224

Setup - Reactive forms



Mohamed Mukthar Ahmed

225



Mohamed Mukhtar Ahmed

226

The onSubmit Event



```
1 import { Component, OnInit } from '@angular/core';
2
3 @Component({
4   selector: 'app-demo-form',
5   templateUrl: './demo-form.component.html',
6   styleUrls: ['./demo-form.component.css']
7 })
8
9 export class DemoFormComponent implements OnInit {
10
11   constructor() { }
12
13   ngOnInit(): void {
14   }
15
16   onSubmit(form: any):void {
17     console.log('Value submitted :', form)
18   }
19 }
```

Mohamed Mukhtar Ahmed

227

The onSubmit Event




- Template uses the **ngSubmit** directive

```
1 <div>
2   <h2>Demo Form</h2>
3   <!--
4     <form #f="ngForm" (ngSubmit)="onSubmit(f.value)">
5     -->
6     <form #f="ngForm" (ngSubmit)="onSubmit(f.value)">
7       <div>
8         <label for="nameInput">Name </label>
9         <input type="text" id="nameInput"
10            placeholder="Name Please"
11            name="nameInput" ngModel>
12       </div>
13       <br />
14       <button type="submit">Submit</button>
15     </form>
16 </div>
```

Mohamed Mukhtar Ahmed

228



Mohamed Mukhtar Ahmed

229

Form Validation



- **Validation** is an integral part of managing any set of forms.
- Whether you're checking for required fields or querying an external API for an existing username etc.
- Angular provides a **set of built-in validators** as well as the ability to create **custom validators**.

Mohamed Mukthar Ahmed

230

Form Validation



- Angular provides a set of **built-in validators** as well as the ability to create **custom validators**.

Form Validation	
Form	Details
Template-driven forms	Tied to template directives, and must provide custom validator directives that wrap validation functions
Reactive forms	Define custom validators as functions that receive a control to validate

- For more information, see <https://angular.io/guide/form-validation>

Mohamed Mukthar Ahmed

231

Feedback Form - Validators



```
1 import { Component, OnInit } from '@angular/core';
2 import { FormControl, FormGroup, Validators } from '@angular/forms';
3
4 @Component({
5   selector: 'app-feedback-form',
6   templateUrl: './feedback-form.component.html',
7   styleUrls: ['./feedback-form.component.css']
8 })
9
10 export class FeedbackFormComponent implements OnInit {
11   feedbackForm = new FormGroup({
12     trgName: new FormControl(null, Validators.required),
13     feedback: new FormControl(null, [
14       Validators.required,
15       Validators.minLength(3),
16       Validators.maxLength(20)
17     ])
18   })
19
20   constructor() { }
21
22   ngOnInit(): void {
23   }
```

Mohamed Mukthar Ahmed

232

Feedback Form - Validators




```
1 <h2>Form Validation</h2>
2 <form [formGroup]="feedbackForm" (ngSubmit)="handleSubmit()">
3   Training Name:
4   <input type="text" formControlName="trgName">
5
6   <div *ngIf="feedbackForm.get('trgName').touched &&
7     feedbackForm.get('trgName').invalid">
8     Training name is required.
9   </div>
10
11   <br />
12   Feedback:
13   <input type="text" formControlName="feedback">
14
15   <div *ngIf="feedbackForm.get('feedback').invalid &&
16     feedbackForm.get('feedback').touched">
17     Feedback required with minimum FOUR characters
18   </div>
19
20   <br />
21   <input type="submit" value="Submit">
22 </form>
```

Mohamed Mukthar Ahmed

233

Feedback Form - Validators



Mohamed Mukthar Ahmed

234

Q&A



Mohamed Mukthar Ahmed

235