


Artificial Intelligence

Informed Search




Today

- Informed Search
 - Heuristics
 - Greedy Search
 - A* Search
- Graph Search




Recap: Search




Recap: Search

- **Search problem:**
 - States (configurations of the world)
 - Actions and costs
 - Successor function (world dynamics)
 - Start state and goal test
- **Search tree:**
 - Nodes: represent plans for reaching states
 - Plans have costs (sum of action costs)
- **Search algorithm:**
 - Systematically builds a search tree
 - Chooses an ordering of the fringe (unexplored nodes)
 - Optimal: finds least-cost plans



Example: Pancake Problem



Cost: Number of pancakes flipped

Example: Pancake Problem

BOUNDS FOR SORTING BY PREFIX REVERSAL

William H. GATES

Microsoft, Albuquerque, New Mexico

Christos H. PAPADIMITRIOU*†

Department of Electrical Engineering, University of California, Berkeley, CA 94720, U.S.A.


Received 18 January 1978

Revised 28 August 1978

For a permutation σ of the integers from 1 to n , let $f(\sigma)$ be the smallest number of prefix reversals that will transform σ to the identity permutation, and let $f(n)$ be the largest such $f(\sigma)$ for all σ in (the symmetric group) S_n . We show that $f(n) \leq (5n+5)/3$, and that $f(n) \geq 17n/16$ for n a multiple of 16. If, furthermore, each integer is required to participate in an even number of reversed prefixes, the corresponding function $g(n)$ is shown to obey $3n/2 - 1 \leq g(n) \leq 2n + 3$.


General Tree Search

```
function TREE-SEARCH(problem, strategy) returns a solution, or failure
  initialize the search tree using the initial state of problem
  loop do
    if there are no candidates for expansion then return failure
    choose a leaf node for expansion according to strategy
    if the node contains a goal state then return the corresponding solution
    else expand the node and add the resulting nodes to the search tree
  end
```



The One Queue

- All these search algorithms are the same except for fringe strategies
 - Conceptually, all fringes are priority queues (i.e. collections of nodes with attached priorities)
 - Practically, for DFS and BFS, you can avoid the $\log(n)$ overhead from an actual priority queue, by using stacks and queues
 - Can even code one implementation that takes a variable queuing object





Uninformed Search




Uniform Cost Search


- Strategy: expand lowest path cost
- The good: UCS is complete and optimal!
- The bad:
 - Explores options in every “direction”
 - No information about goal location



Video of Demo Contours UCS Empty



Video of Demo Contours UCS Pacman Small Maze






Informed Search




Search Heuristics

- A heuristic is:
 - A function that *estimates* how close a state is to a goal
 - Designed for a particular search problem
 - Examples: Manhattan distance, Euclidean distance for pathing



Example: Heuristic Function




Straight-line distance
to Bucharest

Arad	366
Bucharest	0
Craiova	160
Dobreta	242
Eforie	161
Fagaras	178
Giurgiu	77
Hirsova	151
Iasi	226
Lugoj	244
Mehadia	241
Neamt	234
Oradea	380
Pitesti	98
Rimnicu Vilcea	193
Sibiu	253
Timisoara	329
Urziceni	80
Vaslui	199
Zerind	374

$h(x)$

Example: Heuristic Function


Heuristic: the number of the largest pancake that is still out of place



Greedy Search



Example: Heuristic Function




Straight-line distance
to Bucharest

Arad	366
Bucharest	0
Craiova	160
Dobreta	242
Eforie	161
Fagaras	178
Giurgiu	77
Hirsova	151
Iasi	226
Lugoj	244
Mehadia	241
Neamt	234
Oradea	380
Pitesti	98
Rimnicu Vilcea	193
Sibiu	253
Timisoara	329
Urziceni	80
Vaslui	199
Zerind	374



$h(x)$

Greedy Search

- Expand the node that seems closest...





- What can go wrong?




Greedy Search


- Strategy: expand a node that you think is closest to a goal state
 - Heuristic: estimate of distance to nearest goal for each state
- A common case:
 - Best-first takes you straight to the (wrong) goal
- Worst-case: like a badly-guided DFS



Video of Demo Contours Greedy (Empty)



Video of Demo Contours Greedy (Pacman Small Maze)





A* Search



A* Search

Combining UCS and Greedy


- **Uniform-cost** orders by path cost, or *backward cost* $g(n)$
- **Greedy** orders by goal proximity, or *forward cost* $h(n)$



- **A* Search** orders by the sum: $f(n) = g(n) + h(n)$


When should A* terminate?

- Should we stop when we enqueue a goal?




- No: only stop when we dequeue a goal

Is A* Optimal?




- What went wrong?
- Actual bad goal cost < estimated good goal cost
- We need estimates to be less than actual costs!


Admissible Heuristics



Idea: Admissibility



Inadmissible (pessimistic) heuristics break optimality by trapping good plans on the fringe



Admissible (optimistic) heuristics slow down bad plans but never outweigh true costs


Admissible Heuristics

- A heuristic h is *admissible* (optimistic) if:

$$0 \leq h(n) \leq h^*(n)$$

where $h^*(n)$ is the true cost to a nearest goal

- Examples:




4



- Coming up with admissible heuristics is most of what's involved in using A* in practice.

Optimality of A* Tree Search




Optimality of A* Tree Search

Assume:

- A is an optimal goal node
- B is a suboptimal goal node
- h is admissible

Claim:


- A will exit the fringe before B



Optimality of A* Tree Search: Blocking

Proof:

- Imagine B is on the fringe
- Some ancestor n of A is on the fringe, too (maybe A!)
- Claim: n will be expanded before B
 1. $f(n)$ is less or equal to $f(A)$



$$f(n) = g(n) + h(n)$$

$$f(n) \leq g(A)$$

$$g(A) = f(A)$$

Definition of f-cost


Admissibility of h

$h = 0$ at a goal

Optimality of A* Tree Search: Blocking

Proof:

- Imagine B is on the fringe
- Some ancestor n of A is on the fringe, too (maybe A!)
- Claim: n will be expanded before B
 1. $f(n)$ is less or equal to $f(A)$
 2. $f(A)$ is less than $f(B)$



$$g(A) < g(B)$$

$$f(A) < f(B)$$


B is suboptimal

$h = 0$ at a goal

Optimality of A* Tree Search: Blocking

Proof:

- Imagine B is on the fringe
- Some ancestor n of A is on the fringe, too (maybe A!)
- Claim: n will be expanded before B
 1. $f(n)$ is less or equal to $f(A)$
 2. $f(A)$ is less than $f(B)$
 3. n expands before B
- All ancestors of A expand before B
- A expands before B
- A* search is optimal




$$f(n) \leq f(A) < f(B)$$


Properties of A^*

Properties of A^*

Uniform-Cost





A^*




UCS vs A* Contours


- Uniform-cost expands equally in all “directions”
- A* expands mainly toward the goal, but does hedge its bets to ensure optimality




Video of Demo Contours (Empty) -- UCS




Video of Demo Contours (Empty) -- Greedy



Video of Demo Contours (Empty) – A*



Video of Demo Contours (Pacman Small Maze) – A*



Comparison



Greedy




Uniform Cost



A*

Exercise 1



try yourself

straight-line distances

$$h(S-G)=10$$

$$h(A-G)=7$$

$$h(D-G)=1$$

$$h(F-G)=1$$

$$h(B-G)=10$$

$$h(E-G)=8$$

$$h(C-G)=20$$

The graph above shows the step-costs for different paths going from the start (S) to the goal (G). On the right you find the straight-line distances.


1. Draw the search tree for this problem. *Avoid repeated states.*
2. Give the order in which the tree is searched (e.g. S-C-B...-G) for A* search. Use the straight-line dist. as a heuristic function, i.e. $h=SLD$, and indicate for each node visited what the value for the evaluation function, f , is.

Exercise 2

1) Consider the search tree to the right.
There are 2 goal states, G1 and G2.
The numbers on the edges represent step-costs.
You also know the following heuristic estimates:
 $h(B \rightarrow G2) = 9$, $h(D \rightarrow G2) = 10$, $h(A \rightarrow G1) = 2$, $h(C \rightarrow G1) = 1$

a) *In what order will A* search visit the nodes? Explain your answer by indicating the value of the evaluation function for those nodes that the algorithm considers.*

SEARCH TREE



A* Applications




A* Applications


- Video games
- Pathing / routing problems
- Resource planning problems
- Robot motion planning
- Language analysis
- Machine translation
- Speech recognition
- ...




Video of Demo Pacman (Tiny Maze) – UCS / A*



Video of Demo Empty Water Shallow/Deep – Guess Algorithm





Creating Heuristics




Creating Admissible Heuristics

- Most of the work in solving hard search problems optimally is in coming up with admissible heuristics
- Often, admissible heuristics are solutions to *relaxed problems*, where new actions are available





- Inadmissible heuristics are often useful too

Graph Search




Tree Search: Extra Work!

- Failure to detect repeated states can cause exponentially more work.



Graph Search

- In BFS, for example, we shouldn't bother expanding the circled nodes (why?)




Graph Search


- Idea: never **expand** a state twice
- How to implement:
 - Tree search + set of expanded states (“closed set”)
 - Expand the search tree node-by-node, but...
 - Before expanding a node, check to make sure its state has never been expanded before
 - If not new, skip it, if new add to closed set
- Important: **store the closed set as a set**, not a list
- Can graph search wreck completeness? Why/why not?
- How about optimality?

A* Graph Search Gone Wrong?


State space graph



Search tree




Consistency of Heuristics




- Main idea: estimated heuristic costs \leq actual costs
 - Admissibility: heuristic cost \leq actual cost to goal
$$h(A) \leq \text{actual cost from A to G}$$
 - Consistency: heuristic “arc” cost \leq actual cost for each arc
$$h(A) - h(C) \leq \text{cost(A to C)}$$
- Consequences of consistency:
 - The f value along a path never decreases
$$h(A) \leq \text{cost(A to C)} + h(C)$$
 - A* graph search is optimal

Optimality of A* Graph Search




Optimality of A* Graph Search

- Sketch: consider what A* does with a consistent heuristic:
 - Fact 1: In tree search, A* expands nodes in increasing total f value (f-contours)
 - Fact 2: For every state s, nodes that reach s optimally are expanded before nodes that reach s suboptimally
 - Result: A* graph search is optimal



Optimality

- Tree search:
 - A* is optimal if heuristic is admissible
 - UCS is a special case ($h = 0$)
- Graph search:
 - A* optimal if heuristic is consistent
 - UCS optimal ($h = 0$ is consistent)
- Consistency implies admissibility
- In general, most natural admissible heuristics tend to be consistent, especially if from relaxed problems




A*: Summary



A*: Summary

- A* uses both backward costs and (estimates of) forward costs
- A* is optimal with admissible / consistent heuristics
- Heuristic design is key: often use relaxed problems



Tree Search Pseudo-Code

```
function TREE-SEARCH(problem, fringe) return a solution, or failure
  fringe ← INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  loop do
    if fringe is empty then return failure
    node ← REMOVE-FRONT(fringe)
    if GOAL-TEST(problem, STATE[node]) then return node
    for child-node in EXPAND(STATE[node], problem) do
      fringe ← INSERT(child-node, fringe)
    end
  end
```



Graph Search Pseudo-Code

```
function GRAPH-SEARCH(problem, fringe) return a solution, or failure
  closed  $\leftarrow$  an empty set
  fringe  $\leftarrow$  INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  loop do
    if fringe is empty then return failure
    node  $\leftarrow$  REMOVE-FRONT(fringe)
    if GOAL-TEST(problem, STATE[node]) then return node
    if STATE[node] is not in closed then
      add STATE[node] to closed
      for child-node in EXPAND(STATE[node], problem) do
        fringe  $\leftarrow$  INSERT(child-node, fringe)
      end
    end
  end
```

Optimality of A* Graph Search

- Consider what A* does:
 - Expands nodes in increasing total f value (f-contours)
Reminder: $f(n) = g(n) + h(n) = \text{cost to } n + \text{heuristic}$
 - Proof idea: the optimal goal(s) have the lowest f value, so it must get expanded first


There's a problem with this argument. What are we assuming is true?



Optimality of A* Graph Search

Proof:

- New possible problem: some n on path to G^* isn't in queue when we need it, because some worse n' for the same state dequeued and expanded first (disaster!)
- Take the highest such n in tree
- Let p be the ancestor of n that was on the queue when n' was popped
- $f(p) < f(n)$ because of **consistency**
- $f(n) < f(n')$ because n' is suboptimal
- p would have been expanded before n'
- Contradiction!



All search strategies

Algorithm	Complete?	Optimal?	Time complexity	Space complexity
BFS	Yes	If all step costs are equal	$O(b^d)$	$O(b^d)$
UCS	Yes	Yes	Number of nodes with $g(n) \leq C^*$	
DFS	No	No	$O(b^m)$	$O(bm)$
IDS	Yes	If all step costs are equal	$O(b^d)$	$O(bd)$
Greedy	No	No	Worst case: $O(b^m)$ Best case: $O(bd)$	
A*	Yes	Yes	Number of nodes with $g(n)+h(n) \leq C^*$	