

360? Turns Out We Only Needed 8

Varying data **cleaning** and **normalization** methods
to identify the crucial **ROIs** contributing to our **MLP**
model's **accuracy**

Age of Perceptron Members

Alex Sospedra, Kartik Rai,
Marjan Rashidi, Tim Mousseau

Megapod: Calm Tickseed | **TA:** Jacob Morra

Project Background

Background Literature

- Machine learning (ML) methods are widely used to decode cognitive processes from fMRI studies (Liang et al., 2018).
- Rastegarnia et al. (2023) trained nine ML decoder models to predict whether inter-subject BOLD activations predicted different task conditions and found that **Multilayer perceptron (MLP)** achieved the best accuracy.

Guiding Research Questions

- When training an MLP model, do specific **data cleaning** and **normalization** methods lead to better results?
- Could we train our MLP model to conduct **whole-brain reduction** to determine which regions most contributed to its accuracy?

Project Approach

Hypotheses

Phase 1: Cleaning & Normalization

- 'Original' cleaning method will yield the most accurate modeling predictions.
- Subject-wise normalization will be a better approach as it allows for the consideration of absolute BOLD values between subjects.

Phase 2: Whole-Brain Reduction

- Regions associated with specific visual processing (Liang et al., 2018) and emotional processing (Sylvester et al., 2017; Zheng et al., 2017) will play a significant role in discrimination accuracy.

Data Set: HCP 2021

- Emotion Processing Task
- 100 Subjects
- 2 Conditions (Fearful, Neutral)
- 6 Blocks of 18 Trials across 2 Runs*

Phase 1: Cleaning & Normalization

3 Data Cleaning Methods

'Original'

'Hard'

'Cleverer'

X

2 'When' Normalization Methods

Before

X

3 'How' Normalization Methods

**Whole
Sample**


**Subject
-Wise**

Baseline


After

Phase 1: Key Findings (I)




Loss per epoch for MLP metrics
with 'hard_way' cleaning and 'whole-sample' scaling, done before splitting



Confusion Matrix for MLP metrics
with 'hard_way' cleaning and 'whole-sample' scaling, done before splitting




Phase 1: Key Findings (II)




Phase 1: Key Findings (III)


Interaction Plot for ScaleVSsplit = before



Interaction Plot for ScaleVSsplit = after



Phase 2: MLP Architecture



Phase 2: Removing Non-Significant ROIs

MLP Training

- At each round and each iteration, the network was trained with **1 ROI removed**.
- Significant ROIs were identified based on the model's accuracy, and these ROIs were selected for training in the next round.
- In each round, we trained the neural network with **two-thirds** of the ROIs from the previous round (e.g., if there were 360 regions in the previous round, there would be 240 regions in the current round).

Round 1

360 ROIs

At each iteration, the NN was trained with **359** ROIs (1 different ROI removed) – **360** models were trained

Round 2

240 ROIs

At each iteration, the NN was trained with **239** ROIs – **240** models were trained

Round 3

160 ROIs

At each iteration, the NN was trained with **159** ROIs – **160** models were trained

Round 11


8 ROIs

At each iteration, the NN was trained with **7** ROIs – **8** models were trained


Phase 2 Results

- 8 significant brain regions in the last round
- The neural network was trained with 7 brain regions in each iteration
- Results of the neural network showed high accuracy after training the network with significant ROIs only


Round 1– 359 Brain Regions



Round 11 – 7 Brain Regions



Random Sampling – 600
Samples – 7 Brain Regions







Phase 2: From 360 to 8 ROIs

Left

Entorhinal Cortex

Para hippocampal
gyrus

Visual Cortex
(V5 Area)



Right

Posterior Midcingulate Cortex

Visual Cortex (V3 Area)




Lateral Occipital Cortex

Superior Temporal Sulcus

Temporo-Parieto-Occipital
Junction

Phase 2: Why These 8 ROIs?

- **Retinotopic Cluster- V3** (Swisher et al., 2007)
 - Visual processing of **shapes**
- **Posterior Midcingulate Cortex** (Maddock et al., 2003)
 - Emotional **salience** and **fear** learning
- **Superior Temporal Sulcus Dorsal Posterior** (Pitcher et al., 2017)
 - Face processing and **connected** to the **amygdala**
- **Temporo-Parieto-Occipital Junction** (Beauchamp, 2005)
 - Recognizing stimuli patterns and integrating visual cues related to **fear**
- **Lateral Occipital Cortex** (Grill-Spector et al., 2001)
 - Intact object processing with clear **shape interpretations**
- **Middle Temporal- V5** (Kravitz et al., 2013)
 - Processing of depth and visual motion
- **Entorhinal Cortex** (Wilson et al., 2013)
 - Aids in recognizing **novel objects** based on contextual features
- **Para hippocampal gyrus** (Baker et al., 2018)
 - Encoding stimuli, with greater activation for **objects** than faces



References

- Baker, C. M., Burks, J. D., Briggs, R. G., Milton, C. K., Conner, A. K., Glenn, C. A., Sali, G., McCoy, T. M., Battiste, J. D., O'Donoghue, D. L., & Sughrue, M. E. (2018). A Connectomic Atlas of the Human Cerebrum—Chapter 6: The Temporal Lobe. *Operative Neurosurgery*, 15(Suppl 1), S245–S294. <https://doi.org/10.1093/ons/opy260>
- Beauchamp, M. S. (2005). See me, hear me, touch me: Multisensory integration in lateral occipital-temporal cortex. *Current Opinion in Neurobiology*, 15(2), 145–153. <https://doi.org/10.1016/j.conb.2005.03.011>
- Grill-Spector, K., Kourtzi, Z., & Kanwisher, N. (2001). The lateral occipital complex and its role in object recognition. *Vision Research*, 41(10), 1409–1422. [https://doi.org/10.1016/S0042-6989\(01\)00073-6](https://doi.org/10.1016/S0042-6989(01)00073-6)
- Kravitz, D. J., Saleem, K. S., Baker, C. I., Ungerleider, L. G., & Mishkin, M. (2013). The ventral visual pathway: An expanded neural framework for the processing of object quality. *Trends in Cognitive Sciences*, 17(1), 26–49. <https://doi.org/10.1016/j.tics.2012.10.011>
- Liang, Y., Liu, B., Li, X., & Wang, P. (2018). Multivariate Pattern Classification of Facial Expressions Based on Large-Scale Functional Connectivity. *Frontiers in Human Neuroscience*, 12. <https://doi.org/10.3389/fnhum.2018.00094>
- Maddock, R. J., Garrett, A. S., & Buonocore, M. H. (2002). Posterior cingulate cortex activation by emotional words: fMRI evidence from a valence decision task. *Human Brain Mapping*, 18(1), 30–41. <https://doi.org/10.1002/hbm.10075>
- Pitcher, D., Japee, S., Rauth, L., & Ungerleider, L. G. (2017). The Superior Temporal Sulcus Is Causally Connected to the Amygdala: A Combined TBS-fMRI Study. *The Journal of Neuroscience*, 37(5), 1156–1161. <https://doi.org/10.1523/JNEUROSCI.0114-16.2016>
- Rastegarnia, S., St-Laurent, M., DuPre, E., Pinsard, B., & Bellec, P. (2023). Brain decoding of the Human Connectome Project tasks in a dense individual fMRI dataset. *NeuroImage*, 283, Article 120395. <https://doi.org/10.1016/j.neuroimage.2023.120395>
- Swisher, J. D., Halko, M. A., Merabet, L. B., McMains, S. A., & Somers, D. C. (2007). Visual Topography of Human Intraparietal Sulcus. *Journal of Neuroscience*, 27(20), 5326–5337. <https://doi.org/10.1523/JNEUROSCI.0991-07.2007>
- Sylvester, C. M., Petersen, S. E., Luby, J. L., & Barch, D. M. (2017). Face processing in adolescents with positive and negative threat bias. *Psychological medicine*, 47(5), 800–809. <https://doi.org/10.1017/S003329171600310X>
- Zheng, J., Anderson, K. L., Leal, S. L., Shestyuk, A., Gulsen, G., Mnatsakanyan, L., Vadera, S., Hsu, F. P., Yassa, M. A., Knight, R. T., & Lin, J. J. (2017). Amygdala-hippocampal dynamics during salient information processing. *Nature communications*, 8, 14413. <https://doi.org/10.1038/ncomms14413>
- Wilson, D. I., Langston, R. F., Schlesiger, M. I., Wagner, M., Watanabe, S., & Ainge, J. A. (2013). Lateral Entorhinal Cortex is Critical for Novel Object-Context Recognition. *Hippocampus*, 23(5), 352–366. <https://doi.org/10.1002/hipo.22095>