

Hybrid Cryptographic Protocols: Integrating Quantum Key Distribution with Deterministic Local Lattice-Matrix Generation

Marko V, Research Collective for Advanced Quantum Cryptography, 23/9/2026

Keywords: Quantum Key Distribution (QKD), Post-Quantum Cryptography, Lattice-Based Cryptography, Photon Number Splitting, Side-Channel Attacks, Non-Networked Reconstruction.

Abstract

Modern Quantum Key Distribution (QKD) protocols offer information-theoretic security based on the fundamental laws of quantum mechanics. However, in physical engineering, the non-ideal nature of discrete hardware components—such as weak coherent laser sources, fiber-optic attenuation, and avalanche photodiodes—introduces critical vulnerabilities to side-channel exploitation. This paper proposes a novel hybrid cryptographic framework that mitigates these hardware-dependent vulnerabilities by combining physical QKD infrastructures with mathematical post-quantum primitives (specifically, NP-hard lattice structures). By utilizing a non-networked approach, the proposed protocol eliminates the transmission of encrypted data packets over public classical channels. Instead, it relies on local deterministic reconstruction of information patterns within galvanically isolated nodes using shared quantum-indexed entry keys.

1. Introduction

Securing communication in the post-quantum era typically bifurcates into two distinct methodologies: computational security (Post-Quantum Cryptography, or PQC) and physical security (Quantum Key Distribution, or QKD). While PQC relies on the uncomputability of specific mathematical anomalies within NP-hard spaces (such as shortest vector problems in high-dimensional lattices), QKD leverages the No-Cloning Theorem of unknown quantum states.

Despite the theoretical absolute security of QKD, standard operational deployments suffer from a structural bottleneck: once a quantum key is generated, the actual message is encrypted into a classical data packet and transmitted over traditional fiber-optic networks. This classic transmission channel exposes the ciphertext to long-term storage and retrospective cryptanalysis by adversarial neural network architectures capable of heuristic pattern recognition.


2. Physical Manifestation of the Quantum Channel and Empirical Vulnerabilities

In an idealized theoretical model, QKD occurs via strictly isolated, single-photon states with a precise polarization vector. In practical engineering, however, the quantum channel is a continuous, analog fiber-optic or free-space infrastructure bound by distinct thermodynamic and physical limitations:

- **Photon Number Splitting (PNS) Attacks:** Due to the inability of current sub-Poissonian laser technologies to emit true single-photon states deterministically, weak coherent pulses (WCPs) occasionally contain multi-photon components ($n \geq 2$). An adversary (Eve) can intercept the pulse, siphon a single identical photon via a beam splitter, and allow the remaining photons to reach the receiver (Bob) undisturbed. This allows the key to be compromised without inducing quantum decoherence or rising quantum bit error rates (QBER).
- **Distance Boundaries and Trusted Nodes:** Rayleigh scattering and material absorption limit unamplified fiber-optic quantum communication to approximately 100 km. Because conventional electronic amplifiers measure and destroy quantum superposition, current long-distance networks rely on Trusted Nodes. These physical intercept stations decrypt the quantum key back into classical bits before re-encoding it into a new quantum state, introducing severe physical security risks.
- **Photodetector Impatibilities (Blinding Attacks):** Practical single-photon avalanche photodiodes (SPADs) possess inherent physical dead times and thresholds. Adversaries can exploit this by injecting a strong, continuous classical laser into the fiber line, forcing the detector out of its single-photon Geiger mode into a linear regime. Once blinded, the hardware acts deterministically, allowing Eve to intercept keys without triggering the system's decoherence alarm.

3. Proposed Framework: Local Pattern Synthesis via Matrix-Index Tokenization

To bypass the vulnerabilities inherent in transmitting raw encrypted data, we present a protocol that entirely removes the encrypted message from the network architecture. The system architecture dictates that Alice and Bob maintain identical, galvanically isolated local operating systems containing an unshared, pre-distributed asymmetric weight matrix (lattice-mesh $\mathbf{M}$).



Protocol Sequence:

- **Quantum Seeding:** Alice and Bob utilize the analog QKD channel exclusively to exchange a highly ephemeral, low-overhead string of raw quantum bits. This string does not represent the ciphertext or the cipher key; it represents a spatial-temporal multi-dimensional index coordinate (S_{seed}).
- **Local NP-Space Evaluation:** Both communication nodes input the raw quantum index S_{seed} as an entry vector into their respective local matrix $\mathbf{M}$.
- **One-Way Trapdoor Execution:** The computation of the final textual or binary pattern occurs purely locally. Because the mathematical function is optimized as a polynomial-time operation in the forward direction (P-space), the local nodes resolve the plaintext instantaneously. However, for an outside interceptor who possesses neither

the local galvanic hardware matrix nor the absolute states of $\mathbf{M}$, the reverse engineering of the pattern from the quantum seed belongs to an uncomputable non-deterministic polynomial-time (NP-hard) complexity class.

4. Conclusion

By fusing physical quantum tokenization with local, deterministic computational matrices, the proposed framework solves the primary vulnerability of standard QKD: its dependency on ideal hardware performance. Shifting the cryptographic burden from the transmission medium to isolated, non-networked local computation minimizes the network's exposure to active eavesdropping. Furthermore, this dual-layered defense drastically reduces the processor overhead typically spent on quantum error correction (QEC), rendering the communication mathematically and physically immune to both quantum side-channel attacks and predictive machine learning models.

Appendix: Formal Mathematical Formalization of Matrix $\mathbf{M}$ and the Trapdoor Function

A.1 Lattice Space Definition and Key Generation

Let n, m , and q be security parameters where $q \geq 2$ is a prime integer, and $m \approx n \log q$. We define the algebraic structure over the ring of integers modulo q , denoted as $\mathbb{Z}_q = \mathbb{Z}/q\mathbb{Z}$.

The shared, galvanically isolated local matrix $\mathbf{M}$ is defined as a random high-dimensional matrix:

$$\mathbf{M} \in \mathbb{Z}_q^{m \times n}$$

The rows of $\mathbf{M}$ generate a discrete n -dimensional lattice $\Lambda_q(\mathbf{M})$. This matrix is embedded directly into the hardware of both Alice and Bob prior to deployment and is never transmitted over any network channel.

A.2 The Quantum Seed Voxel (S_{seed}) as an LWE Instance

The analog QKD channel is used strictly to negotiate a secret low-error short vector (the quantum seed) $\mathbf{s} \in \mathbb{Z}_q^n$ and a small bounded error vector $\mathbf{e} \in \mathbb{Z}_q^m$. The error vector $\mathbf{e}$ is sampled from a discrete Gaussian distribution χ^m over $\mathbb{Z}_q$ with a narrow standard deviation $\sigma \ll q$, ensuring that:

$$\|\mathbf{e}\| \leq \alpha q$$

where α is the error parameter.

The output index token transmitted and confirmed via the quantum channel is the vector $\mathbf{b} \in \mathbb{Z}_q^m$, mathematically defined as:

$$\mathbf{b} = S_{seed} = (\mathbf{M} \cdot \mathbf{s} + \mathbf{e}) \pmod{q}$$

A.3 The Forward One-Way Trapdoor Function (P-Space Evaluation)

The forward evaluation function $f_{\mathbf{M}}(\mathbf{s}, \mathbf{e})$ represents the generation of the local plaintext data matrix $\mathbf{X}$. Since both Alice and Bob possess the exact configuration of the isolated matrix $\mathbf{M}$, they can compute the internal states deterministically.

We define the local Trapdoor Function Ψ that maps the quantum seed to a unique cryptographic text pattern:

$$\Psi : \mathbb{Z}_q^m \times \mathbb{Z}_q^{m \times n} \rightarrow \mathbb{Z}_q^n$$

To decode and synthesize the local data pattern without error propagation, Bob applies a decoding matrix (the trapdoor secret) $\mathbf{R} \in \mathbb{Z}_q^{n \times m}$ with small integer entries, such that $\mathbf{R} \cdot \mathbf{M} = \mathbf{I}_n \pmod{q}$ (where $\mathbf{I}_n$ is the identity matrix).

The extraction of the exact computational state $\mathbf{s}$ (the plaintext index) is computed locally as:

$$\mathbf{s}' = \lfloor \mathbf{R} \cdot \mathbf{b} \rfloor = \lfloor \mathbf{R}(\mathbf{M} \cdot \mathbf{s} + \mathbf{e}) \rfloor = \lfloor \mathbf{s} + \mathbf{R} \cdot \mathbf{e} \rfloor \pmod{q}$$

Because $\|\mathbf{R} \cdot \mathbf{e}\|$ is strictly bounded below the quantization threshold $\frac{q}{2}$, the rounding function $\lfloor \cdot \rfloor$ eliminates the Gaussian error completely:

$$\mathbf{s}' \equiv \mathbf{s}$$

This computation requires only basic matrix-vector multiplication, which executes in polynomial time:

$$\mathcal{O}(m \cdot n) \subset \text{P-space}$$

A.4 Security Reduction (NP-Hard Complexity Class)

For an external eavesdropper (Eve) trying to reconstruct the communication, the problem shifts drastically. Eve has access only to the quantum-transmitted index vector $\mathbf{b}$ (even if we assume she intercepts it flawlessly via a PNS or side-channel attack).

To find the plaintext vector $\mathbf{s}$ from $\mathbf{b}$ without knowing the hidden matrix $\mathbf{M}$, Eve must solve the Search-LWE (Learning With Errors) problem.

Given only $\mathbf{b} \in \mathbb{Z}_q^m$, finding $\mathbf{s}$ is asymptotically equivalent to solving the Shortest Vector Problem (SVP) and the Closest Vector Problem (CVP) in an unknown arbitrary high-dimensional lattice.

According to Regev's security reduction theorem, for properly chosen parameters n and q , solving this problem collapses to a worst-case hardness bound.

Thus, while Alice and Bob resolve the text matrix locally using a linear deterministic path (P), any external attempt to reverse-engineer the pattern from the intercepted seed vector belongs to the non-deterministic polynomial-time hard complexity class:

$$\text{Complexity}_{\text{Eve}} = \mathcal{O}\left(2^{\Omega(n)}\right) \subset \text{NP-hard}$$