

Papers, splines, and other ideas


Mark Blyth

Presentation overview

- ✶ Splines discretisation progress
- ✶ Some ideas: projects that will enhance CBC, and make it more powerful for studying neurons
 - ▶ Lots of exciting ideas; these ones are limited to the project-relevant ones

CBC code progress


- ✚ Rewritten for a new solver
- ✚ Works for Fourier



Splines discretisation progress


- ✖ Newton iterations fail to converge with splines discretisation
- ✖ Working hypothesis: splines models are structurally unstable; small perturbations cause big changes
 - ▶ Finite differences evaluates gradients by using small perturbations
 - ▶ Finite differences perturbations lead to discontinuous changes in the model

Splines discretisation progress



Spline model describes data fairly accurately

Splines discretisation progress



Control-target input is discontinuous during Jacobian estimation

Splines discretisation progress

- ✂ Newton iterations fail to converge with splines discretisation
- ✂ Working hypothesis: splines models are structurally unstable; small perturbations cause big changes
 - ▶ Finite differences evaluates gradients by using small perturbations
 - ▶ Finite differences perturbations lead to discontinuous changes in the model
- ✂ Currently a best-guess conjecture
 - ▶ Need to play about more to see if this is actually the case
 - ▶ Need to test different finite-differences stepsizes

Novel discretisers

Ideal: journal paper comparing. . .

- ✿ Splines

 - ▶ Knot selection methods?

- ✿ Wavelets

- ✿ Collocation

- ✿ Fourier

Compare for noise-robustness, dimensionality, computational speed

Idea 1: Extended novel discretisers

- ✶ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence

Idea 1: Extended novel discretisers

- ✶ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics

Idea 1: Extended novel discretisers

- ✂ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative

Idea 1: Extended novel discretisers

- ✎ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative
 - ▶ 'Intelligently' select the best discretisor

Idea 1: Extended novel discretisers

- ✿ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative
 - ▶ 'Intelligently' select the best discretisor
- ✿ Extension 2: reversible-jump MCMC for Fourier model identification

Idea 1: Extended novel discretisers

- ✎ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative
 - ▶ 'Intelligently' select the best discretisor
- ✎ Extension 2: reversible-jump MCMC for Fourier model identification
 - ▶ Automatically determine best number of Fourier harmonics for any given signal

Idea 1: Extended novel discretisers

- ✎ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative
 - ▶ 'Intelligently' select the best discretisor
- ✎ Extension 2: reversible-jump MCMC for Fourier model identification
 - ▶ Automatically determine best number of Fourier harmonics for any given signal
 - ▶ Similar to how BARS auto-chooses knot numbers and locations, but instead Fourier harmonics

Idea 1: Extended novel discretisers

- ✿ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative
 - ▶ 'Intelligently' select the best discretisor
- ✿ Extension 2: reversible-jump MCMC for Fourier model identification
 - ▶ Automatically determine best number of Fourier harmonics for any given signal
 - ▶ Similar to how BARS auto-chooses knot numbers and locations, but instead Fourier harmonics
- ✿ Why Bayesian?


Idea 1: Extended novel discretisers

- ✎ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative
 - ▶ 'Intelligently' select the best discretisor
- ✎ Extension 2: reversible-jump MCMC for Fourier model identification
 - ▶ Automatically determine best number of Fourier harmonics for any given signal
 - ▶ Similar to how BARS auto-chooses knot numbers and locations, but instead Fourier harmonics
- ✎ Why Bayesian?
 - ▶ Automatic Occam's razor

Idea 1: Extended novel discretisers

- ✿ Extension 1 [discussed in meetings]: selecting discretisation method based on model evidence
 - ▶ Produce Bayesian inference method for Fourier harmonics
 - ▶ Replace 'simple' splines / wavelets / collocation with Bayesian alternative
 - ▶ 'Intelligently' select the best discretisor
- ✿ Extension 2: reversible-jump MCMC for Fourier model identification
 - ▶ Automatically determine best number of Fourier harmonics for any given signal
 - ▶ Similar to how BARS auto-chooses knot numbers and locations, but instead Fourier harmonics
- ✿ Why Bayesian?
 - ▶ Automatic Occam's razor
 - ▶ Optimally balances goodness-of-fit against model complexity; ensures simplest, most generalizable discretisations; statistically optimal

The sweetspot problem



- ✂ Sweetspot problem: too few harmonics don't fit; too many harmonics overfit noise
- ✂ Bayesian Fourier model selection would find the sweet spot by automatically trading goodness-of-fit against model complexity

Idea 2: discretisation-free CBC

✶ As removed from NODYCON abstract

Idea 2: discretisation-free CBC

- ✶ As removed from NODYCON abstract
 - ▶ Project surrogate of system output onto fundamental harmonic

Idea 2: discretisation-free CBC

- ✶ As removed from NODYCON abstract
 - ▶ Project surrogate of system output onto fundamental harmonic
 - ▶ Subtract out surrogate's fundamental harmonic

Idea 2: discretisation-free CBC

- ✶ As removed from NODYCON abstract
 - ▶ Project surrogate of system output onto fundamental harmonic
 - ▶ Subtract out surrogate's fundamental harmonic
 - ▶ Replace fundamental harmonic with harmonic forcing term

Idea 2: discretisation-free CBC

- ✶ As removed from NODYCON abstract
 - ▶ Project surrogate of system output onto fundamental harmonic
 - ▶ Subtract out surrogate's fundamental harmonic
 - ▶ Replace fundamental harmonic with harmonic forcing term
 - ▶ Feed the modified surrogate back into the system as the new control target

Idea 2: discretisation-free CBC

- ✶ As removed from NODYCON abstract
 - ▶ Project surrogate of system output onto fundamental harmonic
 - ▶ Subtract out surrogate's fundamental harmonic
 - ▶ Replace fundamental harmonic with harmonic forcing term
 - ▶ Feed the modified surrogate back into the system as the new control target

- ✶ Should converge rapidly, implicitly represent an infinite number of harmonics, improve computational speed by avoiding DFT, improve noise-robustness by employing surrogate noise-filtering

Idea 2: discretisation-free CBC

- ✿ As removed from NODYCON abstract
 - ▶ Project surrogate of system output onto fundamental harmonic
 - ▶ Subtract out surrogate's fundamental harmonic
 - ▶ Replace fundamental harmonic with harmonic forcing term
 - ▶ Feed the modified surrogate back into the system as the new control target
- ✿ Should converge rapidly, implicitly represent an infinite number of harmonics, improve computational speed by avoiding DFT, improve noise-robustness by employing surrogate noise-filtering
- ✿ Further extension: something resembling a Picard iteration

Idea 3: noise-robust numerical solvers

- ✶ CBC strategies solve for $\text{input}=\text{output}$

Idea 3: noise-robust numerical solvers

- ✶ CBC strategies solve for input=output
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons

Idea 3: noise-robust numerical solvers

- ✶ CBC strategies solve for input=output
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output

Idea 3: noise-robust numerical solvers

✶ CBC strategies solve for input=output

- ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
- ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
- ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?

Idea 3: noise-robust numerical solvers

✶ CBC strategies solve for $\text{input} = \text{output}$

- ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
- ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
- ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
- ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?

Idea 3: noise-robust numerical solvers

- ✂ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✂ Solver approach: $\text{input} - \text{output} = 0$

Idea 3: noise-robust numerical solvers

- ✂ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✂ Solver approach: $\text{input} - \text{output} = 0$
- ✂ Minimizer approach: find input that minimizes $(\text{input} - \text{output})^2$

Idea 3: noise-robust numerical solvers

- ✂ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✂ Solver approach: $\text{input} - \text{output} = 0$
- ✂ Minimizer approach: find input that minimizes $(\text{input} - \text{output})^2$
- ✂ These two approaches are identical in the noise-free case

Idea 3: noise-robust numerical solvers

- ✂ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✂ Solver approach: $\text{input} - \text{output} = 0$
- ✂ Minimizer approach: find input that minimizes $(\text{input} - \text{output})^2$
- ✂ These two approaches are identical in the noise-free case
 - ▶ Control target is a solution to one if and only if it’s a solution to the other

Idea 3: noise-robust numerical solvers

- ✂ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✂ Solver approach: $\text{input} - \text{output} = 0$
- ✂ Minimizer approach: find input that minimizes $(\text{input} - \text{output})^2$
- ✂ These two approaches are identical in the noise-free case
 - ▶ Control target is a solution to one if and only if it’s a solution to the other
- ✂ Minimizer approach is better in the noisy case

Idea 3: noise-robust numerical solvers

- ✂ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✂ Solver approach: $\text{input} - \text{output} = 0$
- ✂ Minimizer approach: find input that minimizes $(\text{input} - \text{output})^2$
- ✂ These two approaches are identical in the noise-free case
 - ▶ Control target is a solution to one if and only if it’s a solution to the other
- ✂ Minimizer approach is better in the noisy case
 - ▶ If the system is subject to noise or stochastics, output will never truly equal input

Idea 3: noise-robust numerical solvers

- ✂ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✂ Solver approach: $\text{input} - \text{output} = 0$
- ✂ Minimizer approach: find input that minimizes $(\text{input} - \text{output})^2$
- ✂ These two approaches are identical in the noise-free case
 - ▶ Control target is a solution to one if and only if it’s a solution to the other
- ✂ Minimizer approach is better in the noisy case
 - ▶ If the system is subject to noise or stochastics, output will never truly equal input
 - ▶ Noninvasive solution will therefore minimize control action [*minimizer works*], but will not result in $\text{input} - \text{output} = 0$ [*solver won’t work*]

Idea 3: noise-robust numerical solvers

- ✶ CBC strategies solve for $\text{input} = \text{output}$
 - ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
 - ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
 - ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven’t converged, or just because of noise?
- ✶ Solver approach: $\text{input} - \text{output} = 0$
- ✶ Minimizer approach: find input that minimizes $(\text{input} - \text{output})^2$
- ✶ These two approaches are identical in the noise-free case
 - ▶ Control target is a solution to one if and only if it’s a solution to the other
- ✶ Minimizer approach is better in the noisy case
 - ▶ If the system is subject to noise or stochastics, output will never truly equal input
 - ▶ Noninvasive solution will therefore minimize control action [*minimizer works*], but will not result in $\text{input} - \text{output} = 0$ [*solver won’t work*]
 - ▶ Bonus: *lots* of research on stochastic gradient descent (stochastic optimization) to help with this

Idea 3: noise-robust numerical solvers

✶ CBC strategies solve for input=output

- ▶ Harder to solve if output is corrupted by noise, or subject to stochastic dynamics – both prevalent with neurons
- ▶ ‘True’ stochasticity – measurement noise means evaluating the IO map for the same input won’t necessarily give the same output
- ▶ How do we decide when we’ve found a solution to a system, if the system is stochastic?
- ▶ How do we decide if input \neq output because we haven’t converged, or just because of noise?

✶ Solver approach: input - output = 0

✶ Minimizer approach: find input that minimizes (input - output)²

✶ These two approaches are identical in the noise-free case

- ▶ Control target is a solution to one if and only if it’s a solution to the other

✶ Minimizer approach is better in the noisy case

- ▶ If the system is subject to noise or stochastics, output will never truly equal input
- ▶ Noninvasive solution will therefore minimize control action [*minimizer works*], but will not result in input-output=0 [*solver won’t work*]
- ▶ Bonus: *lots* of research on stochastic gradient descent (stochastic optimization) to help with this

✶ Research output: comparison of convergence time, noise-robustness for

Idea 4: alternative noise-robust numerical solvers

- ✦ Covers same issues as before, but in a different way

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven't converged, or just because of noise?

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)
- ✂ IDEA: surrogates-based approach

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)
- ✂ IDEA: surrogates-based approach
 - ▶ Build a surrogate of the $\text{input} \rightarrow \text{output}$ map

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)
- ✂ IDEA: surrogates-based approach
 - ▶ Build a surrogate of the input \rightarrow output map
 - ▶ Choose next function evaluation based on knowledge-gradient or expected improvement

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if $\text{input} \neq \text{output}$ because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)
- ✂ IDEA: surrogates-based approach
 - ▶ Build a surrogate of the input \rightarrow output map
 - ▶ Choose next function evaluation based on knowledge-gradient or expected improvement
 - ▶ With a probabilistic approach, this should converge much faster than Newton, and in a noise-robust way

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if input \neq output because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)
- ✂ IDEA: surrogates-based approach
 - ▶ Build a surrogate of the input \rightarrow output map
 - ▶ Choose next function evaluation based on knowledge-gradient or expected improvement
 - ▶ With a probabilistic approach, this should converge much faster than Newton, and in a noise-robust way
 - ▶ Use a splines model for the input-output map, as GPR doesn't handle MIMO well

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if input \neq output because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)
- ✂ IDEA: surrogates-based approach
 - ▶ Build a surrogate of the input \rightarrow output map
 - ▶ Choose next function evaluation based on knowledge-gradient or expected improvement
 - ▶ With a probabilistic approach, this should converge much faster than Newton, and in a noise-robust way
 - ▶ Use a splines model for the input-output map, as GPR doesn't handle MIMO well
 - ▶ Extension of Barton-Renson conference paper: uses explicit MIMO models, knowledge gradients, explicit noise modelling

Idea 4: alternative noise-robust numerical solvers

- ✂ Covers same issues as before, but in a different way
 - ▶ How do we decide when we've found a solution to a system, if the system is stochastic?
 - ▶ How do we decide if input \neq output because we haven't converged, or just because of noise?
- ✂ Newton iterations are slow, even with Jacobian updates
 - ▶ Especially big issue for larger-dimensional discretisations (as with neurons!)
- ✂ IDEA: surrogates-based approach
 - ▶ Build a surrogate of the input \rightarrow output map
 - ▶ Choose next function evaluation based on knowledge-gradient or expected improvement
 - ▶ With a probabilistic approach, this should converge much faster than Newton, and in a noise-robust way
 - ▶ Use a splines model for the input-output map, as GPR doesn't handle MIMO well
 - ▶ Extension of Barton-Renson conference paper: uses explicit MIMO models, knowledge gradients, explicit noise modelling
- ✂ Aim main paper at a numerical methods audience; possibly additional journal paper comparing CBC speeds, noise-robustnesses for various numerical solvers

Results

✂ Efficient discretisation methods

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

- ✂ Efficient discretisation methods
 - ▶ Alternative approaches to Fourier (splines, collocation, wavelets)

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

- ✂ Efficient discretisation methods
 - ▶ Alternative approaches to Fourier (splines, collocation, wavelets)
 - ▶ Allows the discretisation of spiking, neuron-like signals

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

- ✂ Efficient discretisation methods
 - ▶ Alternative approaches to Fourier (splines, collocation, wavelets)
 - ▶ Allows the discretisation of spiking, neuron-like signals
- ✂ Intelligent discretisation methods

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

✂ Efficient discretisation methods

- ▶ Alternative approaches to Fourier (splines, collocation, wavelets)
- ▶ Allows the discretisation of spiking, neuron-like signals

✂ Intelligent discretisation methods

- ▶ Bayesian'ly determine the best discretisor class [*eg. Fourier vs. splines*], best discretisation approach within that class [*eg. number of knots / harmonics*]

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

✂ Efficient discretisation methods

- ▶ Alternative approaches to Fourier (splines, collocation, wavelets)
- ▶ Allows the discretisation of spiking, neuron-like signals

✂ Intelligent discretisation methods

- ▶ Bayesian'ly determine the best discretisor class [*eg. Fourier vs. splines*], best discretisation approach within that class [*eg. number of knots / harmonics*]
- ▶ Allows the optimal discretisation of spiking, neuron-like signals, without needing a human in the loop

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

✂ Efficient discretisation methods

- ▶ Alternative approaches to Fourier (splines, collocation, wavelets)
- ▶ Allows the discretisation of spiking, neuron-like signals

✂ Intelligent discretisation methods

- ▶ Bayesian'ly determine the best discretisor class [*eg. Fourier vs. splines*], best discretisation approach within that class [*eg. number of knots / harmonics*]
- ▶ Allows the optimal discretisation of spiking, neuron-like signals, without needing a human in the loop
- ▶ Ensures CBC is accurate, by guaranteeing discretisation actually describes the target signal

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

- ✂ Efficient discretisation methods
 - ▶ Alternative approaches to Fourier (splines, collocation, wavelets)
 - ▶ Allows the discretisation of spiking, neuron-like signals
- ✂ Intelligent discretisation methods
 - ▶ Bayesian'ly determine the best discretisor class [eg. *Fourier vs. splines*], best discretisation approach within that class [eg. *number of knots / harmonics*]
 - ▶ Allows the optimal discretisation of spiking, neuron-like signals, without needing a human in the loop
 - ▶ Ensures CBC is accurate, by guaranteeing discretisation actually describes the target signal
- ✂ Noise-robust solvers for accurate CBC calculations

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Results

✂ Efficient discretisation methods

- ▶ Alternative approaches to Fourier (splines, collocation, wavelets)
- ▶ Allows the discretisation of spiking, neuron-like signals

✂ Intelligent discretisation methods

- ▶ Bayesian'ly determine the best discretisor class [*eg. Fourier vs. splines*], best discretisation approach within that class [*eg. number of knots / harmonics*]
- ▶ Allows the optimal discretisation of spiking, neuron-like signals, without needing a human in the loop
- ▶ Ensures CBC is accurate, by guaranteeing discretisation actually describes the target signal

✂ Noise-robust solvers for accurate CBC calculations

- ▶ Solve the CBC equations accurately, even faced with measurement noise [*and stochasticity?*]

These produce a neuron-capable continuation procedure; paired with a control strategy, they'll allow neuronal CBC

Testing the new methods

Any CBC rigs I could demonstrate these methods on?

Next steps

- ✿ Edit NODYCON paper
- ✿ Edit continuation paper
- ✿ Keep working on splines discretisation code
- ✿ Test other discretisor methods