

# The codimension of pseudo-plateau bursting

Mark Blyth

---

## Paper goals

- ✶ Determine the codimension-classification of pseudo-plateau bursting
- ✶ Propose a normal form for bursting


---

## Plan de jour

- ✦ 30 second intro to neurons
  - ▶ What do neurons do?
  - ▶ What are bursting neurons?
  - ▶ How and why do we categorise them?
- ✦ Section 2: Towards a normal form for bursting
- ✦ Section 3: Transitions between bursting classes
- ✦ Section 4: Codimension-classification of pseudo-plateau bursting
- ✦ Section 5: Conclusion

---


## Neurons spike



Neurons encode information in action potentials

---

## Ionic currents



Action potentials happen from ions flowing into and out of the cell

---

## Hodgkin-Huxley


$$\begin{aligned}\frac{dV}{dt} &= [I_{inj} - \bar{g}_{Na}m^3h(V - V_{Na}) - \bar{g}_Kn^4(V - V_K) - g_L(V - V_L)] / C \\ \frac{dn}{dt} &= \alpha_n(V)(1 - n) - \beta_n(V)n \\ \frac{dm}{dt} &= \alpha_m(V)(1 - m) - \beta_m(V)m \\ \frac{dh}{dt} &= \alpha_h(V)(1 - h) - \beta_h(V)h\end{aligned}$$

We can understand the causes of spike generation with differential equations

---

---

## Nonlinear dynamics




Neuron dynamics rely on limit cycles and equilibria

---

---

## Bifurcations




Equilibria and limit cycles can appear through bifurcations

---



---

## KEY POINT: bursting



Ionic currents can appear to drive the neuron over bifurcations – this is bursting!

---

---

## Why do cells burst?

- ✶ More reliable for transmitting over synapses
  - ▶ Higher signal-to-noise ratio
- ✶ Maintain an elevated  $Ca^{2+}$  state
  - ▶ Promotes neurotransmitter release
  - ▶ Promotes hormone release
- ✶ Occur in both the brain and elsewhere
  - ▶ pre-Botzinger complex bursters control respiration
  - ▶ Pituitary somatotroph bursters [*not neurons*] use bursts to release hormones

---


## Why do we categorise them?

Lots of work is done to categorise bursters, but why?

- ✿ Complete classification would describe all the ways a cell could be excitable
- ✿ Hints at similarities and differences between cells
  - ▶ Small parameter changes can sometimes shift cells into different burster categories
  - ▶ 'Close' cell categories usually perform similar tasks

## How do we categorise bursters?

bifurcations of limit cycles



	saddle-node on invariant circle	saddle <b>homoclinic</b> orbit	supercritical Andronov- <b>Hopf</b>	<b>fold</b> limit cycle
saddle-node ( <b>fold</b> )	fold/ circle	fold/ homoclinic	fold/ Hopf	fold/ fold cycle
saddle-node on invariant circle	circle/ circle	circle/ homoclinic	circle/ Hopf	circle/ fold cycle
supercritical Andronov- <b>Hopf</b>	Hopf/ circle	Hopf/ homoclinic	Hopf/ Hopf	Hopf/ fold cycle
subcritical Andronov- <b>Hopf</b>	subHopf/ circle	subHopf/ homoclinic	subHopf/ Hopf	subHopf/ fold cycle

bifurcations of equilibria

Under this scheme, there's 16 planar bursters

---

## Multiple timescale dynamics

The previous bursting data can be modelled by

$$\dot{x} = f(x, y) ,$$

$$\dot{y} = \epsilon g(x, y) ,$$


$$|\epsilon| \ll 1 .$$

✿ Assume  $\epsilon = 0$

✿ Spiking is switched off by bifurcations in  $x$

▶  $y$  becomes a parameter to cause these bifurcations

## How do we categorise bursters?



This is a fold-homoclinic burster

---

## A better classification

- ✶ Several bifurcations can happen at the same point

---

## A better classification

- ✦ Several bifurcations can happen at the same point
  - ▶ A singularity is a point where one or more bifurcations happen



---

## A better classification

- ✿ Several bifurcations can happen at the same point
  - ▶ A singularity is a point where one or more bifurcations happen
- ✿ If we add some small terms to a singularity (*unfold it*), we get a bifurcation space

---

## A better classification

- ✿ Several bifurcations can happen at the same point
  - ▶ A singularity is a point where one or more bifurcations happen
- ✿ If we add some small terms to a singularity (*unfold it*), we get a bifurcation space
  - ▶ We get a model where we can vary some parameters and see some bifurcations

---

## A better classification

- ✿ Several bifurcations can happen at the same point
  - ▶ A singularity is a point where one or more bifurcations happen
- ✿ If we add some small terms to a singularity (*unfold it*), we get a bifurcation space
  - ▶ We get a model where we can vary some parameters and see some bifurcations
- ✿ A burster will sit in the unfolding of some singularity

---

## A better classification

- ✿ Several bifurcations can happen at the same point
  - ▶ A singularity is a point where one or more bifurcations happen
- ✿ If we add some small terms to a singularity (*unfold it*), we get a bifurcation space
  - ▶ We get a model where we can vary some parameters and see some bifurcations
- ✿ A burster will sit in the unfolding of some singularity
  - ▶ More unfolding parameters = more complexity

---

## A better classification

- ✿ Several bifurcations can happen at the same point
  - ▶ A singularity is a point where one or more bifurcations happen
- ✿ If we add some small terms to a singularity (*unfold it*), we get a bifurcation space
  - ▶ We get a model where we can vary some parameters and see some bifurcations
- ✿ A burster will sit in the unfolding of some singularity
  - ▶ More unfolding parameters = more complexity
  - ▶ More unfolding parameters = higher codimension

---

## A better classification

Classify in terms of . . .

- ✿ Singularity codimension
  - ▶ Measures the complexity of the burster
- ✿ Bifurcations to turn spikes on and off
  - ▶ Describes the dynamics of the burster

---

## Plan de jour

- ✿ 30 second intro to neurons
- ✿ Section 2: Towards a normal form for bursting
- ✿ Section 3: Transitions between bursting classes
- ✿ Section 4: Codimension-classification of pseudo-plateau bursting
- ✿ Section 5: Conclusion

---

## Normal forms

✶ Biological models can be complex



---

## Normal forms

- ✿ Biological models can be complex
- ✿ We can often find simpler models that do the same thing

---

## Normal forms

- ✂ Biological models can be complex
- ✂ We can often find simpler models that do the same thing
  - ▶ *'Same thing'* usually means same bifurcation structure

---

## Normal forms

- ✿ Biological models can be complex
- ✿ We can often find simpler models that do the same thing
  - ▶ *'Same thing'* usually means same bifurcation structure
- ✿ A normal form is a simple model that shows prototypical example behaviours


---

## Normal forms

- ✿ Biological models can be complex
- ✿ We can often find simpler models that do the same thing
  - ▶ *'Same thing'* usually means same bifurcation structure
- ✿ A normal form is a simple model that shows prototypical example behaviours
- ✿ A burster normal form is a simple model that can describe the bifurcation structure of any bursting neuron

## Normal form requirements

bifurcations of limit cycles



	saddle-node on invariant circle	saddle <b>homoclinic</b> orbit	supercritical Andronov- <b>Hopf</b>	<b>fold</b> limit cycle
saddle-node ( <b>fold</b> )	fold/ circle	fold/ homoclinic	fold/ Hopf	fold/ fold cycle
saddle-node on invariant circle	circle/ circle	circle/ homoclinic	circle/ Hopf	circle/ fold cycle
supercritical Andronov- <b>Hopf</b>	Hopf/ circle	Hopf/ homoclinic	Hopf/ Hopf	Hopf/ fold cycle
subcritical Andronov- <b>Hopf</b>	subHopf/ circle	subHopf/ homoclinic	subHopf/ Hopf	subHopf/ fold cycle

A burster normal form must be able to operate as all of these classes

---

## Model form

✿ The proposed model has  $f(x, y)$  with a complex bifurcation structure. . .

$$\dot{x} = f(x, y) ,$$

✿ . . . and a simple  $g(x, y)$  to drive  $f$  over some bifurcations

$$y(t) = A \sin(\omega t)$$

---

## Appropriate models


- ✶ Golubitsky found a lot of bursters near the codimension-3 degenerate Bogdanov-Takens singularity:

$$f(x, y) = \begin{pmatrix} y \\ -y + \mu x - x^3 + y(\nu + 3x + x^2) \end{pmatrix}$$

- ✶ Has a rich enough bifurcation structure to show most bursting types

---

## How about this?




- ✿ Pituitary cells can also burst
- ✿ Looks similar to previous bursters
- ✿ No stable limit cycle!

► *How do we categorise this?*

This is pseudo-plateau bursting



## The codimension of pseudo-plateau bursting



- ✶ Pseudo-plateau bursting has a similar bifurcation structure to the others
- ✶ It doesn't seem to appear near a degenerate Bogdanov-Takens singularity!

---

## Singularity choices

- ✶ The original paper goal was to classify the pseudo-plateau burster
- ✶ The burster doesn't seem to appear in codim-3 degenerate Bodganov-Takens unfolding
  - ▶ The singularity must not be able to exhibit all known bursting types
  - ▶ It can't be a normal form!

Let's free up a parameter:

$$\dot{x} = \begin{pmatrix} y \\ -y + \mu_2 x - x^3 + y(\nu + bx - x^2) \end{pmatrix}$$

---

## A new model

We have

$$\dot{x}_1 = y$$

$$\dot{x}_2 = y + \mu_2 x - x^3 + y(\nu + bx - x^2)$$

$$y = A \sin(\omega t)$$

- ✶ This is the unfolding of a doubly-degenerate Takens-Bogdanov singularity
- ✶ It contains more dynamical richness – enough to show pseudo-plateau bursting
- ✶ How do we analyse it?

---

## Model analysis

We can't plot 4-dimensional bifurcation diagrams, so we need to get creative. . .

- ✶ The  $b$  axis consists of degenerate Bogdanov-Takens singularities

---

## Model analysis

We can't plot 4-dimensional bifurcation diagrams, so we need to get creative. . .

- ✂ The  $b$  axis consists of degenerate Bogdanov-Takens singularities
- ✂ Small  $b$  means we're near the doubly-degenerate BT singularity

---

## Model analysis

We can't plot 4-dimensional bifurcation diagrams, so we need to get creative. . .

- ✿ The  $b$  axis consists of degenerate Bogdanov-Takens singularities
- ✿ Small  $b$  means we're near the doubly-degenerate BT singularity
  - ▶ We have a richer bifurcation structure in the surrounding neighbourhood than for the degenerate BT

---

## Model analysis

We can't plot 4-dimensional bifurcation diagrams, so we need to get creative. . .

- ✿ The  $b$  axis consists of degenerate Bogdanov-Takens singularities
- ✿ Small  $b$  means we're near the doubly-degenerate BT singularity
  - ▶ We have a richer bifurcation structure in the surrounding neighbourhood than for the degenerate BT
- ✿ Let's look for bifurcations at the edge of this small- $b$  neighbourhood

---

## Model analysis

We can't plot 4-dimensional bifurcation diagrams, so we need to get creative. . .

- ✿ The  $b$  axis consists of degenerate Bogdanov-Takens singularities
- ✿ Small  $b$  means we're near the doubly-degenerate BT singularity
  - ▶ We have a richer bifurcation structure in the surrounding neighbourhood than for the degenerate BT
- ✿ Let's look for bifurcations at the edge of this small- $b$  neighbourhood
  - ▶ Take  $b$  small



---

## Model analysis

We can't plot 4-dimensional bifurcation diagrams, so we need to get creative. . .

- ✿ The  $b$  axis consists of degenerate Bogdanov-Takens singularities
- ✿ Small  $b$  means we're near the doubly-degenerate BT singularity
  - ▶ We have a richer bifurcation structure in the surrounding neighbourhood than for the degenerate BT
- ✿ Let's look for bifurcations at the edge of this small- $b$  neighbourhood
  - ▶ Take  $b$  small
  - ▶ Find the surface of a ball around the chosen  $b$


---

## Model analysis

We can't plot 4-dimensional bifurcation diagrams, so we need to get creative. . .

- ✿ The  $b$  axis consists of degenerate Bogdanov-Takens singularities
- ✿ Small  $b$  means we're near the doubly-degenerate BT singularity
  - ▶ We have a richer bifurcation structure in the surrounding neighbourhood than for the degenerate BT
- ✿ Let's look for bifurcations at the edge of this small- $b$  neighbourhood
  - ▶ Take  $b$  small
  - ▶ Find the surface of a ball around the chosen  $b$
  - ▶ We now have a 2d parameter space!

# Bifurcation structure



✂ This parameter subspace contains the pseudo-plateau burster

✂ The model is a good normal form candidate

---

## Section 2 summary

- ✿ A normal form is a simple model that can display a target bifurcation structure

---

## Section 2 summary

- ✿ A normal form is a simple model that can display a target bifurcation structure
- ✿ The degenerate Takens-Bogdanov singularity unfolding is [*probably*] not usable for a normal form

---

## Section 2 summary

- ✿ A normal form is a simple model that can display a target bifurcation structure
- ✿ The degenerate Takens-Bogdanov singularity unfolding is *[probably]* not usable for a normal form
  - ▶ The known unfoldings don't contain pseudo-plateau bursters

---

## Section 2 summary

- ✿ A normal form is a simple model that can display a target bifurcation structure
- ✿ The degenerate Takens-Bogdanov singularity unfolding is [*probably*] not usable for a normal form
  - ▶ The known unfoldings don't contain pseudo-plateau bursters
  - ▶ Unknown unfoldings might

---

## Section 2 summary

- ✿ A normal form is a simple model that can display a target bifurcation structure
- ✿ The degenerate Takens-Bogdanov singularity unfolding is [*probably*] not usable for a normal form
  - ▶ The known unfoldings don't contain pseudo-plateau bursters
  - ▶ Unknown unfoldings might
- ✿ A doubly-degenerate Bogdanov-Takens singularity *does* contain pseudo-plateau bursters



---

## Section 2 summary

- ✿ A normal form is a simple model that can display a target bifurcation structure
- ✿ The degenerate Takens-Bogdanov singularity unfolding is [*probably*] not usable for a normal form
  - ▶ The known unfoldings don't contain pseudo-plateau bursters
  - ▶ Unknown unfoldings might
- ✿ A doubly-degenerate Bogdanov-Takens singularity *does* contain pseudo-plateau bursters
  - ▶ It is as close as we can currently get to a normal form

---

## Plan de jour

- ✦ 30 second intro to neurons
- ✦ Section 2: Towards a normal form for bursting
- ✦ Section 3: Transitions between bursting classes
- ✦ Section 4: Codimension-classification of pseudo-plateau bursting
- ✦ Section 5: Conclusion

---

## We can transition between classes

- ✿ Plateau and pseudo-plateau bursting cells are similar, functionally and developmentally

---

## We can transition between classes

- ✦ Plateau and pseudo-plateau bursting cells are similar, functionally and developmentally
- ✦ So are their bifurcation structures: we can switch between the two classes by modifying a single parameter

---

## We can transition between classes

- ✦ Plateau and pseudo-plateau bursting cells are similar, functionally and developmentally
- ✦ So are their bifurcation structures: we can switch between the two classes by modifying a single parameter
  - ▶ This parameter is analogous to Calcium current activation

---




## We can transition between classes

- ✎ Plateau and pseudo-plateau bursting cells are similar, functionally and developmentally
- ✎ So are their bifurcation structures: we can switch between the two classes by modifying a single parameter
  - ▶ This parameter is analogous to Calcium current activation
- ✎ Similar cells have similar bifurcation structures

---

## We can transition between classes

- ✂ Plateau and pseudo-plateau bursting cells are similar, functionally and developmentally
- ✂ So are their bifurcation structures: we can switch between the two classes by modifying a single parameter
  - ▶ This parameter is analogous to Calcium current activation
- ✂ Similar cells have similar bifurcation structures
- ✂ Biological robustness: we can mess around with parameters and still see similar behaviour





---

## Plan de jour

- ✧ 30 second intro to neurons
- ✧ Section 2: Towards a normal form for bursting
- ✧ Section 3: Transitions between bursting classes
- ✧ Section 4: Codimension-classification of pseudo-plateau bursting
- ✧ Section 5: Conclusion

---

## Section 4

- ✿ The pseudo-plateau burster appears in a codimension-4 unfolding
  - ▶ It must be at most a codim-4 -category system
- ✿ There's different forms the unfolding could take; this section justifies why they aren't used

---

## Plan de jour

- ✿ 30 second intro to neurons
- ✿ Section 2: Towards a normal form for bursting
- ✿ Section 3: Transitions between bursting classes
- ✿ Section 4: Codimension-classification of pseudo-plateau bursting
- ✿ Section 5: Conclusion

---

## Conclusions

- ✦ We can categorise bursting cells according to their codimension

---

## Conclusions

- ✿ We can categorise bursting cells according to their codimension
- ✿ Pseudo-plateau bursting can't be categorised as a codim-3 burster

---

## Conclusions

- ✿ We can categorise bursting cells according to their codimension
- ✿ Pseudo-plateau bursting can't be categorised as a codim-3 burster
- ✿ The unfolding of a doubly-degenerate Bogdanov-Takens singularity can display pseudo-plateau bursting

---

## Conclusions

- ✶ We can categorise bursting cells according to their codimension
- ✶ Pseudo-plateau bursting can't be categorised as a codim-3 burster
- ✶ The unfolding of a doubly-degenerate Bogdanov-Takens singularity can display pseudo-plateau bursting
  - ▶ Burster must be at most codim-4

---

## Conclusions

- ✶ We can categorise bursting cells according to their codimension
- ✶ Pseudo-plateau bursting can't be categorised as a codim-3 burster
- ✶ The unfolding of a doubly-degenerate Bogdanov-Takens singularity can display pseudo-plateau bursting
  - ▶ Burster must be at most codim-4
  - ▶ The singularity unfolding can act as a burster normal form



---

## Conclusions

- ✎ We can categorise bursting cells according to their codimension
- ✎ Pseudo-plateau bursting can't be categorised as a codim-3 burster
- ✎ The unfolding of a doubly-degenerate Bogdanov-Takens singularity can display pseudo-plateau bursting
  - ▶ Burster must be at most codim-4
  - ▶ The singularity unfolding can act as a burster normal form
- ✎ Cells can easily transition between bursting classes, in biologically meaningful ways