

(More) surrogate modelling

Mark Blyth

Week's goal

Keep working through different regression models:

- ✂ Function-space distribution over kernels
- ✂ Matern kernels
- ✂ Bayesian free-knot splines
- ✂ Generalised spectral mixture kernels
- ✂ Switching kernel
- ✂ NARMAX
- ✂ Neural ODEs

Week's goal

✂ Function-space distribution over kernels

- ▶ Works, but no better than the other stationary kernels *[why not?]*

✂ Matern kernels

- ▶ Works, but doesn't average noise out *[lengthscale issue]*

✂ Bayesian free-knot splines

- ▶ Works well!

✂ Generalised spectral mixture kernels


- ▶ Couldn't get them to train

Matern kernel


- SEKernel is C^∞ smooth
- Matern kernel generalises this to arbitrary degrees of smoothness
- Matern $\frac{3}{2}$ and $\frac{5}{2}$ are most commonly used
 - Once- and twice- differentiable posteriors
- Lack of smoothness adds more flexibility
- Quick and easy to test!

Can sometimes smooth data

Hindmarsh-Rose fast




Hindmarsh-Rose fast




... but not always

Hodgkin-Huxley




Hodgkin-Huxley




... but not always

Real data



Real data



MSPEs


Exactly how good are any fits?

- ✦ Mean-square prediction error can quantify the goodness-of-fit with synthetic data
 - ▶ Split synthetic data into test and training
 - ▶ Fit model on training data
 - ▶ Find prediction error from test data


The downsampling step causes problems with a GPR fit

Model fits

Downsampled 666 to 333 datapoints



Simulated with 348 datapoints



MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✶ More datapoints were generated by tightening the ODE solver tolerance

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✂ More datapoints were generated by tightening the ODE solver tolerance
- ✂ ODE solvers use an adaptive stepsize

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✂ More datapoints were generated by tightening the ODE solver tolerance
- ✂ ODE solvers use an adaptive stepsize
 - ▶ More datapoints where the system is locally stiff

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✂ More datapoints were generated by tightening the ODE solver tolerance
- ✂ ODE solvers use an adaptive stepsize
 - ▶ More datapoints where the system is locally stiff
 - ▶ Datapoints are therefore chosen to be as informative as possible

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✂ More datapoints were generated by tightening the ODE solver tolerance
- ✂ ODE solvers use an adaptive stepsize
 - ▶ More datapoints where the system is locally stiff
 - ▶ Datapoints are therefore chosen to be as informative as possible
 - ▶ Placed at points with the largest margin for error, to zero this error

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✂ More datapoints were generated by tightening the ODE solver tolerance
- ✂ ODE solvers use an adaptive stepsize
 - ▶ More datapoints where the system is locally stiff
 - ▶ Datapoints are therefore chosen to be as informative as possible
 - ▶ Placed at points with the largest margin for error, to zero this error
- ✂ Changing *rtol* always gives a maximally informative dataset, for the number of points

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✖ More datapoints were generated by tightening the ODE solver tolerance
- ✖ ODE solvers use an adaptive stepsize
 - ▶ More datapoints where the system is locally stiff
 - ▶ Datapoints are therefore chosen to be as informative as possible
 - ▶ Placed at points with the largest margin for error, to zero this error
- ✖ Changing *rtol* always gives a maximally informative dataset, for the number of points
- ✖ Downsampling doesn't always give maximally informative data

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✂ More datapoints were generated by tightening the ODE solver tolerance
- ✂ ODE solvers use an adaptive stepsize
 - ▶ More datapoints where the system is locally stiff
 - ▶ Datapoints are therefore chosen to be as informative as possible
 - ▶ Placed at points with the largest margin for error, to zero this error
- ✂ Changing *rtol* always gives a maximally informative dataset, for the number of points
- ✂ Downsampling doesn't always give maximally informative data
 - ▶ Removes datapoints based on their indices, rather than informativeness

MSPEs

Validation results can't always be trusted - MSPE values are often too high.

Possible hand-wavy explanation:

- ✂ More datapoints were generated by tightening the ODE solver tolerance
 - ✂ ODE solvers use an adaptive stepsize
 - ▶ More datapoints where the system is locally stiff
 - ▶ Datapoints are therefore chosen to be as informative as possible
 - ▶ Placed at points with the largest margin for error, to zero this error
 - ✂ Changing *rtol* always gives a maximally informative dataset, for the number of points
 - ✂ Downsampling doesn't always give maximally informative data
 - ▶ Removes datapoints based on their indices, rather than informativeness
 - ✂ Less informative dataset means worse GPR fit
-

Fixing MSPE

Alternative approaches to MSPE:

- ✂ Leave-one-out cross validation
 - ▶ Computationally expensive
- ✂ Visual inspection
 - ▶ Subjective, imprecise
- ✂ Run two solvers, one for test and one for training data
 - ▶ Need to make sure there's no shared datapoints for this to work
 - ▶ Bad test if test and training points are very close to each other


MSPE only seems to break on PeriodicKernels or Hodgkin Huxley dataset

- ✂ Chosen approach: use MSPE as-is, but do it carefully


Real data

- ✿ Real data is the best test of a regression model
- ✿ Lack of ground-truth makes it harder to evaluate models on real data
- ✿ A heuristic method:
 - ▶ Fit model
 - ▶ Look at the model fit
 - ▶ Find residuals
 - ▶ Look at their distribution

Real data, splines model



Real data



✖ Nothing particularly alarming about the residuals

▶ That's all we can really say

✖ ~~H_0 : residuals are Gaussian~~
[rejected]

▶ Shapiro-Wilk p-value:
3.0734860972720244e-21

▶ D'Agostino's K^2 test:
4.3027710773715154e-37

Calculated MSPEs

Model	Matern32	Matern52	SEKernel	PeriodicKernel
Hodgkin Huxley	2.26(-2)	2.67 (-1)	5.57	9.25
Fitzhugh Nagumo	5.37 (-7)	2.34(-8)	2.97 (-4)	2.21 (-2)
HRFast	1.48 (-7)	4.30(-9)	2.37 (-6)	1.22 (-2)

- ✖ Calculated on noise-free models
- ✖ Matern kernels perform the best
- ✖ Can't compare MSPEs across neuron models, since it scales with the square of signal amplitude

Calculated MSPEs

Model	Matern32	Matern52	SEKernel	PeriodicKernel
Hodgkin Huxley	6.64	8.57	24.6	150
Fitzhugh Nagumo	3.95 (-3)	3.80e-3	4.85 (-3)	2.85 (-2)
HRFast	1.17 (-2)	1.16 (-2)	1.11e-2	2.18 (-2)

- ✂ Calculated on noise-perturbed models
- ✂ Matern kernels are generally good
- ✂ Representative values only; should really be ran lots of times to get an average

Splines

✶ ‘Tie’ together pieces of polynomials at knot-points

Splines

- ✿ ‘Tie’ together pieces of polynomials at knot-points
- ✿ Lower degree-of-freedom than GPR, so they forcibly remove noise [see later slide]

Splines

- ✿ ‘Tie’ together pieces of polynomials at knot-points
- ✿ Lower degree-of-freedom than GPR, so they forcibly remove noise [see later slide]
- ✿ No stationarity assumptions

Splines

- ✦ ‘Tie’ together pieces of polynomials at knot-points
- ✦ Lower degree-of-freedom than GPR, so they forcibly remove noise [see *later slide*]
- ✦ No stationarity assumptions
 - ▶ Can account for varying lengthscales by placing more knots at fast-changing points

Splines

- ✿ 'Tie' together pieces of polynomials at knot-points
- ✿ Lower degree-of-freedom than GPR, so they forcibly remove noise [see *later slide*]
- ✿ No stationarity assumptions
 - ▶ Can account for varying lengthscales by placing more knots at fast-changing points
- ✿ Successful splining needs good choices of knots

Splines

- ✿ 'Tie' together pieces of polynomials at knot-points
- ✿ Lower degree-of-freedom than GPR, so they forcibly remove noise [see later slide]
- ✿ No stationarity assumptions
 - ▶ Can account for varying lengthscales by placing more knots at fast-changing points
- ✿ Successful splining needs good choices of knots
 - ▶ Too many or too few knots will give bad results

Splines

- ✿ 'Tie' together pieces of polynomials at knot-points
- ✿ Lower degree-of-freedom than GPR, so they forcibly remove noise [see later slide]
- ✿ No stationarity assumptions
 - ▶ Can account for varying lengthscales by placing more knots at fast-changing points
- ✿ Successful splining needs good choices of knots
 - ▶ Too many or too few knots will give bad results
 - ▶ Poorly placed knots will mean splines can't capture signal

Splines

- ✂ 'Tie' together pieces of polynomials at knot-points
- ✂ Lower degree-of-freedom than GPR, so they forcibly remove noise [see later slide]
- ✂ No stationarity assumptions
 - ▶ Can account for varying lengthscales by placing more knots at fast-changing points
- ✂ Successful splining needs good choices of knots
 - ▶ Too many or too few knots will give bad results
 - ▶ Poorly placed knots will mean splines can't capture signal
- ✂ Can choose degree of smoothness, for smoothing splines

Splines

- ✿ ‘Tie’ together pieces of polynomials at knot-points
- ✿ Lower degree-of-freedom than GPR, so they forcibly remove noise [see later slide]
- ✿ No stationarity assumptions
 - ▶ Can account for varying lengthscales by placing more knots at fast-changing points
- ✿ Successful splining needs good choices of knots
 - ▶ Too many or too few knots will give bad results
 - ▶ Poorly placed knots will mean splines can’t capture signal
- ✿ Can choose degree of smoothness, for smoothing splines
 - ▶ Downside: no good way to choose this!

Free-knot splines

A clever approach: free-knot splines

- ✶ Automatically choose both location and number of knots

Free-knot splines

A clever approach: free-knot splines

- ✂ Automatically choose both location and number of knots
- ✂ A GPR paper said free-knot splines work well

Free-knot splines

A clever approach: free-knot splines

- ✂ Automatically choose both location and number of knots
- ✂ A GPR paper said free-knot splines work well
- ✂ Current splines method: Bayesian adaptive regression splines

Free-knot splines

A clever approach: free-knot splines

- ✂ Automatically choose both location and number of knots
- ✂ A GPR paper said free-knot splines work well
- ✂ Current splines method: Bayesian adaptive regression splines
 - ▶ Also called BARS, Bayesian free-knot splines

Free-knot splines

A clever approach: free-knot splines

- ✿ Automatically choose both location and number of knots
- ✿ A GPR paper said free-knot splines work well
- ✿ Current splines method: Bayesian adaptive regression splines
 - ▶ Also called BARS, Bayesian free-knot splines
- ✿ There's a few free-knot splines methods out there


Free-knot splines

A clever approach: free-knot splines


- ✂ Automatically choose both location and number of knots
- ✂ A GPR paper said free-knot splines work well
- ✂ Current splines method: Bayesian adaptive regression splines
 - ▶ Also called BARS, Bayesian free-knot splines
- ✂ There's a few free-knot splines methods out there
- ✂ I don't know how they work...

Splines vs GPR

Splines




GPR (SEKernel)




Splines vs GPR


Splines





GPR (SEKernel)



Real data, splines model



Not perfect, but good enough



Splines caveats

- ✦ BARS works well, without any hyperparameter tuning

Splines caveats

- ✶ BARS works well, without any hyperparameter tuning
- ✶ ISSUE: I don't know how or why it works

Splines caveats

- ✶ BARS works well, without any hyperparameter tuning
- ✶ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method

Splines caveats

- ✦ BARS works well, without any hyperparameter tuning
- ✦ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail

Splines caveats

- ✂ BARS works well, without any hyperparameter tuning
- ✂ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values

Splines caveats

- ✂ BARS works well, without any hyperparameter tuning
- ✂ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values
- ✂ ISSUE: haven't implemented it

Splines caveats

- ✿ BARS works well, without any hyperparameter tuning
- ✿ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values
- ✿ ISSUE: haven't implemented it
 - ▶ Relying on some old C code to make it run

Splines caveats

- ✶ BARS works well, without any hyperparameter tuning
- ✶ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values
- ✶ ISSUE: haven't implemented it
 - ▶ Relying on some old *C* code to make it run
 - ▶ *C* implementation evaluates the splines model at the training points, and returns them

Splines caveats

- ✶ BARS works well, without any hyperparameter tuning
- ✶ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values
- ✶ ISSUE: haven't implemented it
 - ▶ Relying on some old C code to make it run
 - ▶ C implementation evaluates the splines model at the training points, and returns them
 - ▶ Can't evaluate model at non-training points; doesn't give a continuous (interpolating) model, *can't be validated!*

Splines caveats

- ✶ BARS works well, without any hyperparameter tuning
- ✶ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values
- ✶ ISSUE: haven't implemented it
 - ▶ Relying on some old *C* code to make it run
 - ▶ *C* implementation evaluates the splines model at the training points, and returns them
 - ▶ Can't evaluate model at non-training points; doesn't give a continuous (interpolating) model, *can't be validated!*
- ✶ ISSUE: harder to encode periodicity

Splines caveats

- ✶ BARS works well, without any hyperparameter tuning
- ✶ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values
- ✶ ISSUE: haven't implemented it
 - ▶ Relying on some old *C* code to make it run
 - ▶ *C* implementation evaluates the splines model at the training points, and returns them
 - ▶ Can't evaluate model at non-training points; doesn't give a continuous (interpolating) model, *can't be validated!*
- ✶ ISSUE: harder to encode periodicity
 - ▶ Periodic kernels almost surely (probability 1) give periodic posteriors

Splines caveats

- ✶ BARS works well, without any hyperparameter tuning
 - ✶ ISSUE: I don't know how or why it works
 - ▶ Can't rigorously justify why it's a good method
 - ▶ Can't predict when it would work and when it would fail
 - ▶ Can't determine good hyperparameter values
 - ✶ ISSUE: haven't implemented it
 - ▶ Relying on some old C code to make it run
 - ▶ C implementation evaluates the splines model at the training points, and returns them
 - ▶ Can't evaluate model at non-training points; doesn't give a continuous (interpolating) model, *can't be validated!*
 - ✶ ISSUE: harder to encode periodicity
 - ▶ Periodic kernels almost surely (probability 1) give periodic posteriors
 - ▶ Periodic splines are a thing, maybe try periodic BARS?
-

Abandoned ideas

✂ Generalised spectral mixture kernels

- ▶ Couldn't get them to train

✂ Support vector regression

- ▶ Couldn't find any justification to use this over GPR

✂ Latent ODEs / neural ODEs / physics-informed NNs

- ▶ Would require state-space reconstruction, doesn't seem like a beneficial use of time

Other models for a paper

- ✦ NARMAX
- ✦ Wavelets
- ✦ Warping GPs
 - ▶ Either learn a warp...
 - ▶ ...or apply a simple transformation to the data (log, exp, logistic, ...)
- ✦ Deep GPs
- ✦ Hybrid methods
- ✦ Other nonparametric methods
 - ▶ RKHS, KNN, etc.

Next steps

- ✦ Dig into free-knot splines literature

Then...

Next steps

- ✎ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods

Then...

Next steps

- ✿ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✿ Understand how and why it works

Then...

Next steps

- ✦ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✦ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work

Then...

Next steps

- ✦ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✦ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work
 - ▶ Will help decide whether periodic BARS is possible

Then...

Next steps

- ✦ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✦ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work
 - ▶ Will help decide whether periodic BARS is possible
- ✦ Write up my own implementation

Then...

Next steps

- ✿ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✿ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work
 - ▶ Will help decide whether periodic BARS is possible
- ✿ Write up my own implementation
 - ▶ Allows for validation, interpolation

Then...

Next steps

- ✿ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✿ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work
 - ▶ Will help decide whether periodic BARS is possible
- ✿ Write up my own implementation
 - ▶ Allows for validation, interpolation

Then...

- ✿ Other data sources

Next steps

- ✿ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✿ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work
 - ▶ Will help decide whether periodic BARS is possible
- ✿ Write up my own implementation
 - ▶ Allows for validation, interpolation

Then...

- ✿ Other data sources
- ✿ Warping GPs, deep GPs, NARMAX, etc.

Next steps

- ✂ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✂ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work
 - ▶ Will help decide whether periodic BARS is possible
- ✂ Write up my own implementation
 - ▶ Allows for validation, interpolation

Then...

- ✂ Other data sources
- ✂ Warping GPs, deep GPs, NARMAX, etc.
- ✂ MATLAB wrapper?

Next steps

- ✿ Dig into free-knot splines literature
 - ▶ BARS and other free-knot methods
- ✿ Understand how and why it works
 - ▶ Useful for justifying why it's a good model, and when it will and won't work
 - ▶ Will help decide whether periodic BARS is possible
- ✿ Write up my own implementation
 - ▶ Allows for validation, interpolation

Then...

- ✿ Other data sources
- ✿ Warping GPs, deep GPs, NARMAX, etc.
- ✿ MATLAB wrapper?
 - ▶ Having ready-to-go codes might make a paper more popular

```
./model_tester.py -d HRFast -m MySEKernel
```

```
./model_tester.py -d HindmarshRose -m Matern32 -p CleanFitted  
-r 1e-6 -V
```

```
./model_tester.py -d FitzhughNagumo -m ModuloKernel -r 1e-6  
-n 0.1
```

```
./model_tester.py -d HodgkinHuxley -m PeriodicKernel -o
```

```
./model_tester.py -d 08o28004_channel_0_sweep_8.np -m  
MySEKernel -f 6.23e2 -l 5.71e-8 -n 0.1
```