

# A continuum approach to neuron modelling

Mark Blyth

---

# Overview

- ✦ Challenges with using the MEA
- ✦ Possible solutions (network- and microfluidic-based methods)
- ✦ A better solution (continuum)
- ✦ Literature precedent

---

## Main challenge with the MEA

- ✂ Loss of spatial resolution, since we can no longer measure and perturb individual cells
- ✂ Emergent behaviours mean we can't study dynamics of individual neurons; would have to study network dynamics instead
- ✂ Too many unknowns to build a realistic network model. . .

---

## Issues with the network model

- ✿ No geometric information
    - ▶ We can make a model of neuron networks, but there's no easy way to relate an agent in the network to the position of a living cell
    - ▶ This matters, as we can't predict the spatial dynamics, and therefore the effects of stimulating each electrode, without this information
  - ✿ No topological information
    - ▶ We don't know who connects to who, in our neuron network
    - ▶ This means we can't produce an accurate network model
  - ✿ Too many equations for simulations
    - ▶ 200,000 neurons is too many to simulate!
  - ✿ Too many parameters to accurately determine
    - ▶ Even just coupling strength adds between 200,000 and 40,000,000,000 ( $200,000^2$ ) extra parameters to the model
-

---

## Some possible solutions

- ✿ Constrain the network geometry using on-chip microchannels
  - ▶ This has been done in the literature
  - ▶ Doesn't tell us much about connection strengths
  - ▶ Would be a very hard device to make
  - ▶ Requires making another new device
- ✿ Use synchronisation-based network models
  - ▶ Changing one of 200,000 network connection strengths probably won't change much in the dynamics
  - ▶ Can use this lack of sensitivity to make simpler models of neuron synchronisation
  - ▶ But, this synchronisation models won't work for any case other than synchronisation (limits the dynamics with specific assumptions)

---

## A proposed alternative

- ✿ Assume we have an arbitrarily large number of neurons
- ✿ Every neuron connects to every other neuron within its local neighbourhood
- ✿ Treat it as a continuum (neural field, rather than point neurons)
- ✿ Build a PDE model

---

## Benefits of a continuum model (1)

- ✿ No need to know the network geometry; any given 'neuron' is identified by its point in the domain
  - ✿ No need to define a network topology; every 'neuron' interacts locally with those in its neighbourhood
  - ✿ Far fewer parameters are required to characterise the system
    - ▶ Don't need to specify a set of parameters for each agent in a network system
  - ✿ Becomes tractable to study much more sophisticated dynamics than with the network model (beyond simple synchronisation!)
  - ✿ We no longer care about what individual cells are doing, and can therefore get away with the lower spatial resolution of the electrodes
    - ▶ Instead, we're measuring the average continuum value across some small region, which is a sufficient measurement; don't need to know the state of every neuron in the network
-

---

## Benefits of a continuum model (2)

- ✿ No need to individually perturb single neurons - it suffices to model a current input across some subdomain of the PDE's space
- ✿ Microfluidic electrodes have a very natural mathematical interpretation
  - ▶ For an accurate model, neurons can be thought of as 'solving' the continuum PDE across their network
  - ▶ Numerical methods for solving the model would typically use orthogonal collocation
  - ▶ A set of meshpoints are defined, and orthogonal basis functions are chosen such that they solve the PDE at those mesh points
  - ▶ The electrodes are therefore a physical analog of these collocation mesh points!
  - ▶ Very natural transition between numerical methods, and physical experiments



---

## Literature precedent

### ✿ There's models for neural fields

- ▶ Bressloff, Paul C. "Spatiotemporal dynamics of continuum neural fields." *Journal of Physics A: Mathematical and Theoretical* 45.3 (2011): 033001.
- ▶ Seems to be based on some rather dubious assumptions (rate-based networks, assume SNIC neurons)

### ✿ There's also cable models for spatially extended neurons

- ▶ Designed to model signal propagation down an axon
- ▶ Could possibly produce a 2d spatially extended system as a continuum model?
- ▶ I don't yet know how important the synaptic dynamics are on continuum dynamics

---

## The Belousov-Zhabotinsky reaction

Chemical reaction, displaying complex dynamics away from equilibrium. I claim it behaves in the same way as neurons:

- ✂ Consider reactants as ‘ions inside a neuron’
- ✂ Consider products as ‘ions outside a neuron’
- ✂ Consider catalyst concentration as membrane potential
  - ▶ Stimulates the transition of reactants into products (and reverse)
  - ▶ Equivalently, stimulates the movement of ions into a cell (and out of it)

Dynamics of the BZ reaction are therefore analogous to neural dynamics

- ✂ Stirred system is like an ODE model
  - ▶ Can show mixed-mode bursting-like oscillations, and relaxation oscillations
- ✂ Unstirred system is like a spatially extended continuum neuron

---

## The Belousov-Zhanosinsky reaction

- ✿ This is analogy interesting, as there's lots of research on the various behaviours of the BZ reaction that could be reapplied to predict dynamics of a large neural population.
- ✿ BZ reaction is a reaction-diffusion system, which Alan does lots of research on
- ✿ There's a literature precedent for bifurcation analysis of it

---

## Controlling the BZ reaction

- ✿ The BZ reaction is a continuum system.
- ✿ Methods have been demonstrated for tracking its dynamics, suggesting that similar approaches may work for neural continuums
- ✿ These follow an OGY/ ETDF style approach.

Petrov, Valery, Michael J. Crowley, and Kenneth Showalter. "Tracking unstable periodic orbits in the Belousov-Zhabotinsky reaction." Physical review letters 72.18 (1994): 2955.

Petrov, Valery, Michael F. Crowley, and Kenneth Showalter. "An adaptive control algorithm for tracking unstable periodic orbits." International Journal of Bifurcation and Chaos 4.05 (1994): 1311-1317.

---

## Epilepsy, coherent structures, and Turing instabilities


- ✦ Epilepsy is characterised by waves travelling across the surface of the brain [SOURCE?]
  - ✦ Travelling waves are a type of ‘coherent structure’ (some structure that appears and persists in the dynamics)
  - ✦ More generally, Turing patterns refer to the appearance of coherent structures in reaction-diffusion systems (like BZ reaction!)
  - ✦ Since we’ve added a spatial domain, we now have new ways to bifurcate
    - ▶ Lose stability in temporal dimension - traditional bifurcation
    - ▶ Lose stability in spatial dimension - Turing instability
  - ✦ Turing patterns and instabilities form new bifurcations we could control and test for
    - ▶ ... possibly bifurcations that lead to epileptic dynamics?
-

---

## Studying continuum models

- ✿ Turing patterns are a very well studied area - lots of literature to draw from
- ✿ There's also lots of literature on PDEs
- ✿ (I conjecture) it would be considerably easier to study bifurcations in the PDEs than in a massive network

## Interlude for pretty pictures



---

## Some issues

- ✂ The continuum model discussed in previous review is rate-based; doesn't generalise to arbitrary neurons, only good for cortical (SNIC) neurons
- ✂ A spatially extended cubic Lienard model would give the dynamics of arbitrary neuron populations, if and only if synaptic dynamics are non-critical



---

## Possible project plan

- ✂ Produce a neuron normal form model
  - ▶ Krasi's cubic Lienard + a slow subsystem
- ✂ Generate a neural continuum model from a spatially extended normal form
- ✂ Analyse bifurcations etc. in the model, to get an idea of what the actual cells will do
- ✂ Develop a CBC approach to track those bifurcations

Note that a spatially extended neuron model might not be sufficient; the review cited earlier would be a good place to start on understanding good continuum models.

---

## Possible project plan

Nice but not necessarily essential:

- ✶ Bigger MEA (more cells = more like a continuum)
- ✶ More electrodes (more collocation meshpoints = more accurate model)