

Knots, collocation, writing

Mark Blyth

Week's activities

- ✂ Spline-Newton CBC with more knots
 - ▶ Goal: more numerical stability
 - ▶ Different results, but not really any better
- ✂ Updated continuation paper
 - ▶ Edited, formatted, submitted
- ✂ Looked into collocation references
- ✂ Started annual review report

Newton iteration issues

✿ Solution jumps

- ▶ Probably a finite-differences issue?
- ▶ But, Jacobian is always well-conditioned


✿ Converged solution doesn't actually solve continuation equations

- ▶ Newton iterations should, but don't, give a vector that, when passed to the continuation equations, give a zero output
- ▶ More iterations don't help
- ▶ Different convergence criteria don't improve things

✿ Idea: try more knots!


- ▶ More knots = more attainable accuracy = perhaps better chance of finding a solution

Baseline: 5 knots




- ✖ Minimum 3 interior knots for a valid BSpline model
- ✖ Solution jumps
- ✖ Converged Newton-iteration vectors don't solve the continuation equations accurately

20 knots



- ✂ Simulation is notably slower to run
- ✂ Solution still jumps
- ✂ Converged Newton-iteration vectors solve system to higher accuracy than before

30 knots



- ✖ Simulation is even slower to run
- ✖ Solution jumps at about the same place
- ✖ Converged Newton-iteration vectors again solve system to higher accuracy

Things to note

- ✂ SciPy solvers still get a solution with 5 knots
 - ▶ Means the equations can be solved, but not by a Newton solver
 - ▶ Doesn't quite make sense...
- ✂ Solution is jumping after the second fold
 - ▶ I'd have expected this to be one of the more numerically stable places

Other things to try

✿ Adaptive stepsize

- ▶ Should allow greater accuracy around difficult regions (eg. folds)


✿ Adaptive knots

- ▶ Essential for 'harder' (eg. neuronal) signals
- ▶ (Presumably) unimportant here

✿ Idea: Jacobian checking

- ▶ Use a secant predictor to estimate the next Jacobian
- ▶ If the finite-differences Jacobian differs much from the secant prediction, try FD again with a new stepsize
- ▶ Extension: adaptive-stepsize finite differences

5 knots, $K_p = 2$



Another thing to try: increasing the control gain

🔥 Slight improvement in results

Effects of control gain

- Was originally using $K_p = 1$
 - This worked fine for Duffing Fourier
 - Keeping K_p as low as possible seems to give the best-possible accuracy
- Using $K_p = 2$ delayed the 'jump'
 - Jump region is controllable with $K_p = 1$ for Fourier, but not splines
 - Still doesn't explain why non-Newton solvers could find a solution at $K_p = 1$!
- Intuitively, increasing K_p would make it *harder* to find a correct solution, not easier
 - In limit, large K_p means every control target solves the continuation equations, whether or not they're noninvasive
 - Intuition: smaller K_p gives a larger gradient at the fixed-point, and therefore a more accurate solution can be found

Standard continuation

Other work: considering a 'standard' (non-control-based) continuation of the Duffing oscillator

- ✦ Removes any issue from controllers being weird
- ✦ Simplifies down to just a discretisation and predictor/corrector problem
- ✦ Plan of action:
 1. Learn about collocation and periodic-orbit continuation *[in progress]*
 2. Learn about BSpline collocation for BVPs *[in progress]*
 3. Combine them
 4. Add in the extras (BSpline periodicity structure, choice of knots, choice of collocation meshpoints, if any)
 5. Code up and test
 6. Make the step 4 extras adaptive

Next steps

- ✦ Lab group presentation
- ✦ Annual review report
- ✦ Later...
 - ▶ More collocation
 - ▶ 'Standard' continuation
 - ▶ Adaptive algos