

# Bayesian methods for the control-based continuation of multiple-timescale systems

Mark Blyth



---

## Plan de jour

- ✧ CBC maths
- ✧ Surrogate modelling
- ✧ Novel discretisations



---

## Plan de jour


- ✂ CBC maths
- ✂ Surrogate modelling
- ✂ Novel discretisations



---

## What is CBC?



Dynamics are ‘what something does’





## What is CBC?

A bifurcation is a change in dynamics





---

## What is CBC?

Bifurcation analysis:

1. Find a feature



---

## What is CBC?

Bifurcation analysis:

1. Find a feature

- ▶ Eg. a rest-state or sustained oscillation



---

## What is CBC?

Bifurcation analysis:

1. Find a feature
  - ▶ Eg. a rest-state or sustained oscillation
2. Change a parameter slightly





---

## What is CBC?

Bifurcation analysis:

1. Find a feature
  - ▶ Eg. a rest-state or sustained oscillation
2. Change a parameter slightly
  - ▶ Eg. inject more current in a neuron



---

## What is CBC?

Bifurcation analysis:

1. Find a feature
  - ▶ Eg. a rest-state or sustained oscillation
2. Change a parameter slightly
  - ▶ Eg. inject more current in a neuron
3. Find where the feature moved to



---

## What is CBC?

Bifurcation analysis:

1. Find a feature
  - ▶ Eg. a rest-state or sustained oscillation
2. Change a parameter slightly
  - ▶ Eg. inject more current in a neuron
3. Find where the feature moved to
  - ▶ Eg. increase in rest-state membrane potential



---

## What is CBC?

Bifurcation analysis:

1. Find a feature
  - ▶ Eg. a rest-state or sustained oscillation
2. Change a parameter slightly
  - ▶ Eg. inject more current in a neuron
3. Find where the feature moved to
  - ▶ Eg. increase in rest-state membrane potential
4. Bifurcations occur when features change, appear, or disappear



---

## What is CBC?

### ✎ Numerical continuation:

- ▶ Features  $x$  defined given by  $f(x, \lambda) = 0$
- ▶ Change  $\lambda$ , see how  $x$  changes

George Box

All models are wrong, but some are useful



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller

- ▶ Put in target  $u^*(t)$



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller

- ▶ Put in target  $u^*(t)$
- ▶ Controller makes system follow  $u^*(t)$





---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller
  - ▶ Put in target  $u^*(t)$
  - ▶ Controller makes system follow  $u^*(t)$
2. Find noninvasive  $u^*(t)$



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller
  - ▶ Put in target  $u^*(t)$
  - ▶ Controller makes system follow  $u^*(t)$
2. Find noninvasive  $u^*(t)$ 
  - ▶ Noninvasiveness = no control action applied



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller
  - ▶ Put in target  $u^*(t)$
  - ▶ Controller makes system follow  $u^*(t)$
2. Find noninvasive  $u^*(t)$ 
  - ▶ Noninvasiveness = no control action applied
  - ▶ No control action = system behaves naturally



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller
  - ▶ Put in target  $u^*(t)$
  - ▶ Controller makes system follow  $u^*(t)$
2. Find noninvasive  $u^*(t)$ 
  - ▶ Noninvasiveness = no control action applied
  - ▶ No control action = system behaves naturally
3. Change a parameter



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller
  - ▶ Put in target  $u^*(t)$
  - ▶ Controller makes system follow  $u^*(t)$
2. Find noninvasive  $u^*(t)$ 
  - ▶ Noninvasiveness = no control action applied
  - ▶ No control action = system behaves naturally
3. Change a parameter
4. Find how noninvasive  $u^*(t)$  changed



---

## What is CBC?

Control-based continuation; model-free bifurcation analysis:

1. Build a system controller
  - ▶ Put in target  $u^*(t)$
  - ▶ Controller makes system follow  $u^*(t)$
2. Find noninvasive  $u^*(t)$ 
  - ▶ Noninvasiveness = no control action applied
  - ▶ No control action = system behaves naturally
3. Change a parameter
4. Find how noninvasive  $u^*(t)$  changed
  - ▶ Tracks system features, bifurcations without ever needing a model



---

# CBC

## Control-based continuation

A model-free bifurcation analysis method. Uses a controller to stabilise a system, and continuation to track features.

My project: use CBC to analyse the bifurcations that make neurons fire



---

## What is discretisation?

✎ Periodic orbits are functions satisfying  $f(t) = f(t + T)$





---

## What is discretisation?

✂ Periodic orbits are functions satisfying  $f(t) = f(t + T)$

✂ Tracking these means solving the functional equation

$$I[u^*] = \int_0^T [u(u^*, t)]^2 dt = 0 \text{ for function } u^*(t)$$



---

## What is discretisation?

✂ Periodic orbits are functions satisfying  $f(t) = f(t + T)$

✂ Tracking these means solving the functional equation

$$I[u^*] = \int_0^T [u(u^*, t)]^2 dt = 0 \text{ for function } u^*(t)$$

► This is hard!



---

## What is discretisation?

✂ Periodic orbits are functions satisfying  $f(t) = f(t + T)$

✂ Tracking these means solving the functional equation

$$I[u^*] = \int_0^T [u(u^*, t)]^2 dt = 0 \text{ for function } u^*(t)$$

▶ This is hard!

▶ *[interesting aside: optimal control developed some nice approaches for solving variational equations]*



---

## What is discretisation?

- ✂ Periodic orbits are functions satisfying  $f(t) = f(t + T)$
- ✂ Tracking these means solving the functional equation
$$I[u^*] = \int_0^T [u(u^*, t)]^2 dt = 0 \text{ for function } u^*(t)$$
  - ▶ This is hard!
  - ▶ *[interesting aside: optimal control developed some nice approaches for solving variational equations]*
- ✂ Discretisation lets us solve the problem by solving a finite set of equations



---

## What is discretisation?

Goal: solve  $I[u^*] = 0$

1. Translate problem to system of vector-valued equations
2. Solve system numerically
3. Translate solution back to a continuous function

Translation between continuous and vector-valued systems is discretisation



---

# What is discretisation?

## Definition (Discretisation)

The act of representing a continuous signal by a discrete counterpart

We want a discretisation that

- ✦ Has minimal discretisation error
- ✦ Is low-dimensional



---

## How do we discretise?

✎ Let  $\mathbf{u}^*$  be some vector 'representing' the signal  $u^*(t)$



---

## How do we discretise?

✎ Let  $\mathbf{u}^*$  be some vector ‘representing’ the signal  $u^*(t)$

► Eg. Fourier: let our periodic target be

$$u^*(t) = a_0 + \sum a_i \cos i\omega t + \sum b_i \sin i\omega t$$





---

## How do we discretise?

✂ Let  $\mathbf{u}^*$  be some vector ‘representing’ the signal  $u^*(t)$

► Eg. Fourier: let our periodic target be

$$u^*(t) = a_0 + \sum a_i \cos i\omega t + \sum b_i \sin i\omega t$$

✂ We can represent the signal by its Fourier harmonics  $\mathbf{u}^* = \{a_0, a_i, b_i\}$



---

## How do we discretise?

- ✿ Let  $\mathbf{u}^*$  be some vector 'representing' the signal  $u^*(t)$ 
  - Eg. Fourier: let our periodic target be
$$u^*(t) = a_0 + \sum a_i \cos i\omega t + \sum b_i \sin i\omega t$$
- ✿ We can represent the signal by its Fourier harmonics  $\mathbf{u}^* = \{a_0, a_i, b_i\}$
- ✿  $u^*(t)$  can be represented by  $\mathbf{u}^*$  with minimal error



---

## How do we discretise?

- ✿ Let  $\mathbf{u}^*$  be some vector 'representing' the signal  $u^*(t)$ 
  - ▶ Eg. Fourier: let our periodic target be
$$u^*(t) = a_0 + \sum a_i \cos i\omega t + \sum b_i \sin i\omega t$$
- ✿ We can represent the signal by its Fourier harmonics  $\mathbf{u}^* = \{a_0, a_i, b_i\}$
- ✿  $u^*(t)$  can be represented by  $\mathbf{u}^*$  with minimal error
  - ▶  $\mathbf{u}^*$  is a discretisation



---

## How do we discretise?

✂ Let  $\mathbf{u}^*$  be some vector ‘representing’ the signal  $u^*(t)$

- ▶ Eg. Fourier: let our periodic target be

$$u^*(t) = a_0 + \sum a_i \cos i\omega t + \sum b_i \sin i\omega t$$

✂ We can represent the signal by its Fourier harmonics  $\mathbf{u}^* = \{a_0, a_i, b_i\}$

✂  $u^*(t)$  can be represented by  $\mathbf{u}^*$  with minimal error

- ▶  $\mathbf{u}^*$  is a discretisation
- ▶ Represents a continuous function as finite-dimensional vector, with minimal error



---

## How do we discretise?

- ✂ Let  $\mathbf{u}^*$  be some vector 'representing' the signal  $u^*(t)$ 
  - ▶ Eg. Fourier: let our periodic target be
$$u^*(t) = a_0 + \sum a_i \cos i\omega t + \sum b_i \sin i\omega t$$
- ✂ We can represent the signal by its Fourier harmonics  $\mathbf{u}^* = \{a_0, a_i, b_i\}$
- ✂  $u^*(t)$  can be represented by  $\mathbf{u}^*$  with minimal error
  - ▶  $\mathbf{u}^*$  is a discretisation
  - ▶ Represents a continuous function as finite-dimensional vector, with minimal error
- ✂ The functional problem can be rewritten as  $I(\mathbf{u}^*) = 0$



---

## How do we discretise?

- ✂ Let  $\mathbf{u}^*$  be some vector ‘representing’ the signal  $u^*(t)$ 
  - ▶ Eg. Fourier: let our periodic target be
$$u^*(t) = a_0 + \sum a_i \cos i\omega t + \sum b_i \sin i\omega t$$
- ✂ We can represent the signal by its Fourier harmonics  $\mathbf{u}^* = \{a_0, a_i, b_i\}$
- ✂  $u^*(t)$  can be represented by  $\mathbf{u}^*$  with minimal error
  - ▶  $\mathbf{u}^*$  is a discretisation
  - ▶ Represents a continuous function as finite-dimensional vector, with minimal error
- ✂ The functional problem can be rewritten as  $I(\mathbf{u}^*) = 0$ 
  - ▶ Finite-vector equation, solvable!



---

## Issues with discretisation

- ✂ Solving the discretised system takes a long time when it is high-dimensional
- ✂ Neuron signals require lots of Fourier harmonics to discretise
- ✂ Higher-order harmonics are harder to get [*Nyquist cap*] and less accurate [*SNR*]



---

## Plan de jour

- ✦ CBC maths
- ✦ Surrogate modelling
- ✦ Novel discretisations





---

# The need for surrogates

- Recent work: local surrogate models for experimental data



---

# The need for surrogates

Recent work: local surrogate models for experimental data

## Definition (Surrogate models)

A local model for data, that can be used in place of experimental recordings



---

## The need for surrogates

- Recent work: local surrogate models for experimental data

### Definition (Surrogate models)

A local model for data, that can be used in place of experimental recordings

- Record experimental data



---

## The need for surrogates

- Recent work: local surrogate models for experimental data

### Definition (Surrogate models)

A local model for data, that can be used in place of experimental recordings

- Record experimental data
- Fit a surrogate model



---

## The need for surrogates

- Recent work: local surrogate models for experimental data

### Definition (Surrogate models)


A local model for data, that can be used in place of experimental recordings

- Record experimental data
- Fit a surrogate model
- Perform analysis, eg. discretisation, on model instead of data



## Why surrogates?

Real data are noisy






---

## Why surrogates?

Real data are 'fast'





---

## Why surrogates?

- ✦ We want to get rid of noise to get the best possible discretisation





---

## Why surrogates?

- ✦ We want to get rid of noise to get the best possible discretisation
  - ▶ Fourier should encode only signal, not signal + noise



---

## Why surrogates?

- ✂ We want to get rid of noise to get the best possible discretisation
  - ▶ Fourier should encode only signal, not signal + noise
- ✂ Fast signals mean lots of high-frequency energy



---

## Why surrogates?

- ✂ We want to get rid of noise to get the best possible discretisation
  - ▶ Fourier should encode only signal, not signal + noise
- ✂ Fast signals mean lots of high-frequency energy
  - ▶ High signal-to-noise ratio on the harmonics that give sharp spikes



---

## Why surrogates?

- ✂ We want to get rid of noise to get the best possible discretisation
  - ▶ Fourier should encode only signal, not signal + noise
- ✂ Fast signals mean lots of high-frequency energy
  - ▶ High signal-to-noise ratio on the harmonics that give sharp spikes
  - ▶ Simple low-pass filters would remove both noise *and* signal



---

## Why surrogates?

- ✿ We want to get rid of noise to get the best possible discretisation
  - ▶ Fourier should encode only signal, not signal + noise
- ✿ Fast signals mean lots of high-frequency energy
  - ▶ High signal-to-noise ratio on the harmonics that give sharp spikes
  - ▶ Simple low-pass filters would remove both noise *and* signal
- ✿ A good surrogate lets us remove noise in a statistically optimal way



---

## Why surrogates?

- ✿ We want to get rid of noise to get the best possible discretisation
  - ▶ Fourier should encode only signal, not signal + noise
- ✿ Fast signals mean lots of high-frequency energy
  - ▶ High signal-to-noise ratio on the harmonics that give sharp spikes
  - ▶ Simple low-pass filters would remove both noise *and* signal
- ✿ A good surrogate lets us remove noise in a statistically optimal way
  - ▶ Less noise = better discretisation



---

## A primer on Bayes

The laws of probability, applied to beliefs instead of proportions-of-outcomes

✿ [Frequentist] probability:

- ▶ How likely is something to happen?
- ▶ An event is known to happen some proportion of the time; how can I reason about its outcomes?

✿ [Bayesian] beliefs:

- ▶ Encoding uncertain beliefs; reasoning in the face of ignorance
- ▶ I have some beliefs about an event; how can I update my beliefs after seeing some evidence?
- ▶ Let's us combine beliefs and evidence to make better decisions



---

## Bayesian surrogates

- ✦ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  
 $y_i = f(t_i) + \varepsilon$





---

## Bayesian surrogates

- ✶ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples
$$y_i = f(t_i) + \varepsilon$$
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes



---

## Bayesian surrogates

- ✿ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  $y_i = f(t_i) + \varepsilon$ 
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes
- ✿ Prior: assume  $\varepsilon \sim \mathcal{N}(0, \sigma^2)$



---

## Bayesian surrogates

- ✂ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  $y_i = f(t_i) + \varepsilon$ 
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes
- ✂ Prior: assume  $\varepsilon \sim \mathcal{N}(0, \sigma^2)$ 
  - ▶ Single observation:  $y_i \sim \mathcal{N}(f(t_i), \sigma_n^2)$



---

## Bayesian surrogates

- ✿ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  $y_i = f(t_i) + \varepsilon$ 
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes
- ✿ Prior: assume  $\varepsilon \sim \mathcal{N}(0, \sigma^2)$ 
  - ▶ Single observation:  $y_i \sim \mathcal{N}(f(t_i), \sigma_n^2)$
  - ▶ All observations:  $\mathbf{y} \sim \mathcal{N}(f(\mathbf{t}), \Sigma_n^2)$



---

## Bayesian surrogates

- ✿ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  $y_i = f(t_i) + \varepsilon$ 
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes
- ✿ Prior: assume  $\varepsilon \sim \mathcal{N}(0, \sigma^2)$ 
  - ▶ Single observation:  $y_i \sim \mathcal{N}(f(t_i), \sigma_n^2)$
  - ▶ All observations:  $\mathbf{y} \sim \mathcal{N}(f(\mathbf{t}), \Sigma_n^2)$
- ✿ Let’s estimate  $y^* = f(t^*)$  at unseen data  $t^*$



---

## Bayesian surrogates

- ✿ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  $y_i = f(t_i) + \varepsilon$ 
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes
- ✿ Prior: assume  $\varepsilon \sim \mathcal{N}(0, \sigma^2)$ 
  - ▶ Single observation:  $y_i \sim \mathcal{N}(f(t_i), \sigma_n^2)$
  - ▶ All observations:  $\mathbf{y} \sim \mathcal{N}(f(\mathbf{t}), \Sigma_n^2)$
- ✿ Let's estimate  $y^* = f(t^*)$  at unseen data  $t^*$ 
  - ▶ Joint distribution:  $p(f(t^*), t^*, y, t) \sim \mathcal{N}(\mu, \Sigma_k^2)$



---

## Bayesian surrogates

- ✿ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  $y_i = f(t_i) + \varepsilon$ 
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes
- ✿ Prior: assume  $\varepsilon \sim \mathcal{N}(0, \sigma^2)$ 
  - ▶ Single observation:  $y_i \sim \mathcal{N}(f(t_i), \sigma_n^2)$
  - ▶ All observations:  $\mathbf{y} \sim \mathcal{N}(f(\mathbf{t}), \Sigma_n^2)$
- ✿ Let’s estimate  $y^* = f(t^*)$  at unseen data  $t^*$ 
  - ▶ Joint distribution:  $p(f(t^*), t^*, y, t) \sim \mathcal{N}(\mu, \Sigma_k^2)$
  - ▶ Conditional distribution:  $p(f(t^*)|t^*, y, t)$



---

## Bayesian surrogates


- ✿ We have a ‘true’ signal  $f(t)$ , but we can only see noise-corrupted samples  $y_i = f(t_i) + \varepsilon$ 
  - ▶  $f(t)$  is unknown, but we can reason about it with Bayes
- ✿ Prior: assume  $\varepsilon \sim \mathcal{N}(0, \sigma^2)$ 
  - ▶ Single observation:  $y_i \sim \mathcal{N}(f(t_i), \sigma_n^2)$
  - ▶ All observations:  $\mathbf{y} \sim \mathcal{N}(f(\mathbf{t}), \Sigma_n^2)$
- ✿ Let's estimate  $y^* = f(t^*)$  at unseen data  $t^*$ 
  - ▶ Joint distribution:  $p(f(t^*), t^*, y, t) \sim \mathcal{N}(\mu, \Sigma_k^2)$
  - ▶ Conditional distribution:  $p(f(t^*)|t^*, y, t)$
- ✿ This is Gaussian process regression!





## Gaussian process regression surrogates

Build a statistically optimal regression model from noisy observations





---

## GPR results

✶ GPR is Bayesian



---

## GPR results

✎ GPR is Bayesian

- ▶ Covariance function specifies our initial belief about the data



---

## GPR results

### ✦ GPR is Bayesian

- ▶ Covariance function specifies our initial belief about the data
- ▶ Conditioning step updates this belief after seeing data



---

## GPR results

- ✦ GPR is Bayesian
  - ▶ Covariance function specifies our initial belief about the data
  - ▶ Conditioning step updates this belief after seeing data
- ✦ Covariance functions generally assume stationarity



---

## GPR results

- ✦ GPR is Bayesian
  - ▶ Covariance function specifies our initial belief about the data
  - ▶ Conditioning step updates this belief after seeing data
- ✦ Covariance functions generally assume stationarity
  - ▶ Assume smooth, nice signals



---

## GPR results

- ✦ GPR is Bayesian
  - ▶ Covariance function specifies our initial belief about the data
  - ▶ Conditioning step updates this belief after seeing data
- ✦ Covariance functions generally assume stationarity
  - ▶ Assume smooth, nice signals
  - ▶ Neuron data are highly non-stationary



---

## GPR results

- ✂ GPR is Bayesian
  - ▶ Covariance function specifies our initial belief about the data
  - ▶ Conditioning step updates this belief after seeing data
- ✂ Covariance functions generally assume stationarity
  - ▶ Assume smooth, nice signals
  - ▶ Neuron data are highly non-stationary
- ✂ Stationary covariance = poorly encoded beliefs = low belief in posterior






---

## GPR results

- ✿ GPR is Bayesian
  - ▶ Covariance function specifies our initial belief about the data
  - ▶ Conditioning step updates this belief after seeing data
- ✿ Covariance functions generally assume stationarity
  - ▶ Assume smooth, nice signals
  - ▶ Neuron data are highly non-stationary
- ✿ Stationary covariance = poorly encoded beliefs = low belief in posterior
  - ▶ Bayes with bad priors = bad results!




## GPR results





## GPR results





---

## GPR results

- ✿ Stationary GPR, non-stationary data = overly flexible models



---

## GPR results

- ✿ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes



---

## GPR results

- ✿ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes
  - ▶ Stationary = equally flexible everywhere, even away from spikes



---

## GPR results

- ✿ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes
  - ▶ Stationary = equally flexible everywhere, even away from spikes
  - ▶ Overfit noise, instead of averaging it out



---

## GPR results

- ✿ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes
  - ▶ Stationary = equally flexible everywhere, even away from spikes
  - ▶ Overfit noise, instead of averaging it out
- ✿ Non-stationary would fix this





---

## GPR results

- ✿ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes
  - ▶ Stationary = equally flexible everywhere, even away from spikes
  - ▶ Overfit noise, instead of averaging it out
- ✿ Non-stationary would fix this
  - ▶ Flexible near spikes



---

## GPR results

- ✖ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes
  - ▶ Stationary = equally flexible everywhere, even away from spikes
  - ▶ Overfit noise, instead of averaging it out
- ✖ Non-stationary would fix this
  - ▶ Flexible near spikes
  - ▶ Inflexible away from them



---

## GPR results

- ✂ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes
  - ▶ Stationary = equally flexible everywhere, even away from spikes
  - ▶ Overfit noise, instead of averaging it out
- ✂ Non-stationary would fix this
  - ▶ Flexible near spikes
  - ▶ Inflexible away from them
  - ▶ Smooths out noise, while also modelling spikes



---

## GPR results

- ✂ Stationary GPR, non-stationary data = overly flexible models
  - ▶ Needs to change rapidly to accomodate spikes
  - ▶ Stationary = equally flexible everywhere, even away from spikes
  - ▶ Overfit noise, instead of averaging it out
- ✂ Non-stationary would fix this
  - ▶ Flexible near spikes
  - ▶ Inflexible away from them
  - ▶ Smooths out noise, while also modelling spikes
- ✂ Non-stationary GPR is hard!



---

# Splines

✖ Less flexible alternative: splines



---

# Splines

- ✖ Less flexible alternative: splines
- ✖ Choose some representative points



---

# Splines

- ✂ Less flexible alternative: splines
- ✂ Choose some representative points
- ✂ Place a piece of cubic polynomial between each point



---

# Splines

- ✂ Less flexible alternative: splines
- ✂ Choose some representative points
- ✂ Place a piece of cubic polynomial between each point
- ✂ Choose polynomials so that the function is smooth





---

# Splines

- ✦ Less flexible alternative: splines
- ✦ Choose some representative points
- ✦ Place a piece of cubic polynomial between each point
- ✦ Choose polynomials so that the function is smooth
- ✦ Finite, low degree-of-freedom, forcibly averages out noise



---

## Bayesian splines

✶ Choosing representative points is hard



---

## Bayesian splines

- ✦ Choosing representative points is hard
- ✦ Alternative: don't!



---

## Bayesian splines

- ✦ Choosing representative points is hard
- ✦ Alternative: don't!
  - ▶ Let  $\xi$  be a vector of representative points



---

## Bayesian splines

- ✦ Choosing representative points is hard
- ✦ Alternative: don't!
  - ▶ Let  $\xi$  be a vector of representative points
  - ▶ Find  $p(\xi|x, y)$



---

## Bayesian splines

- ✂ Choosing representative points is hard
- ✂ Alternative: don't!
  - ▶ Let  $\xi$  be a vector of representative points
  - ▶ Find  $p(\xi|x, y)$
  - ▶ Use that to estimate  $p(f|\xi, x, y)$



---


## Bayesian splines

- ✚ Choosing representative points is hard
- ✚ Alternative: don't!
  - ▶ Let  $\xi$  be a vector of representative points
  - ▶ Find  $p(\xi|x, y)$
  - ▶ Use that to estimate  $p(f|\xi, x, y)$
- ✚ This is Bayesian free-knot splines



## Splines as a surrogate

Result 1: splines outperform stationary GPR as neuronal data surrogate







---

## Plan de jour

- ✂ CBC maths
- ✂ Surrogate modelling
- ✂ Novel discretisations



---

## The issue with surrogates

My current work. . .

- ✶ Bayesian free-knot splines gives a good noise-free surrogate model



---

## The issue with surrogates

My current work. . .

- ✦ Bayesian free-knot splines gives a good noise-free surrogate model
  - ▶ Can apply Fourier discretisation on the surrogate



---

## The issue with surrogates

My current work. . .

- ✶ Bayesian free-knot splines gives a good noise-free surrogate model
  - ▶ Can apply Fourier discretisation on the surrogate
  - ▶ Can get arbitrarily many mostly-accurate Fourier coefficients



---

## The issue with surrogates

My current work. . .

- ✦ Bayesian free-knot splines gives a good noise-free surrogate model
  - ▶ Can apply Fourier discretisation on the surrogate
  - ▶ Can get arbitrarily many mostly-accurate Fourier coefficients
- ✦ Issue: too many coefficients are needed to discretise the signal



---

## The issue with surrogates

My current work. . .

- ✂ Bayesian free-knot splines gives a good noise-free surrogate model
  - ▶ Can apply Fourier discretisation on the surrogate
  - ▶ Can get arbitrarily many mostly-accurate Fourier coefficients
- ✂ Issue: too many coefficients are needed to discretise the signal
  - ▶ Too many = slow, inaccurate CBC



---

## The issue with surrogates

My current work. . .

- ✦ Bayesian free-knot splines gives a good noise-free surrogate model
  - ▶ Can apply Fourier discretisation on the surrogate
  - ▶ Can get arbitrarily many mostly-accurate Fourier coefficients
- ✦ Issue: too many coefficients are needed to discretise the signal
  - ▶ Too many = slow, inaccurate CBC
  - ▶ *Question: how many do we actually need?*



---

## The issue with surrogates

My current work. . .

- ✿ Bayesian free-knot splines gives a good noise-free surrogate model
  - ▶ Can apply Fourier discretisation on the surrogate
  - ▶ Can get arbitrarily many mostly-accurate Fourier coefficients
- ✿ Issue: too many coefficients are needed to discretise the signal
  - ▶ Too many = slow, inaccurate CBC
  - ▶ *Question: how many do we actually need?*
- ✿ We can reconstruct signal from splines models





---

## The issue with surrogates

My current work. . .

- ✦ Bayesian free-knot splines gives a good noise-free surrogate model
  - ▶ Can apply Fourier discretisation on the surrogate
  - ▶ Can get arbitrarily many mostly-accurate Fourier coefficients
- ✦ Issue: too many coefficients are needed to discretise the signal
  - ▶ Too many = slow, inaccurate CBC
  - ▶ *Question: how many do we actually need?*
- ✦ We can reconstruct signal from splines models
  - ▶ Is this a discretisation?



---

## Splines as a discretisation

✿ Splines models are of form  $\hat{f}(x) = \sum \beta_i b_i(x)$



---

## Splines as a discretisation

- ✦ Splines models are of form  $\hat{f}(x) = \sum \beta_i b_i(x)$ 
  - ▶  $b_i(x)$  form a set of basis functions over splines models



---

## Splines as a discretisation

- ✚ Splines models are of form  $\hat{f}(x) = \sum \beta_i b_i(x)$ 
  - ▶  $b_i(x)$  form a set of basis functions over splines models
- ✚ For a basis set  $b_i$ , can the associated  $\beta_i$  discretise a signal?



---

## Splines as a discretisation

- ✂ Splines models are of form  $\hat{f}(x) = \sum \beta_i b_i(x)$ 
  - ▶  $b_i(x)$  form a set of basis functions over splines models
- ✂ For a basis set  $b_i$ , can the associated  $\beta_i$  discretise a signal?
  - ▶ Result 2: probably...



---


## Splines as a discretisation

- ✿ Splines models are of form  $\hat{f}(x) = \sum \beta_i b_i(x)$ 
  - ▶  $b_i(x)$  form a set of basis functions over splines models
- ✿ For a basis set  $b_i$ , can the associated  $\beta_i$  discretise a signal?
  - ▶ Result 2: probably...
  - ▶ This is my current work



## Spline discretisation

8-dimensional discretisation; but does it work with continuation?





---

## Where next?

- ✂ Compare Fourier vs splines discretisation
  - ▶ What error for what discretisation-size?
- ✂ See if the discretisation breaks down with stochastic models
  - ▶ It probably will
- ✂ Test the discretisation with continuation