



Sequence Encoding Transformer




國立臺灣大學 資訊工程學系
陳縉儂 助理教授

<http://vivianchen.idv.tw>




Transformer Overview

- Non-recurrent encoder-decoder for MT
- PyTorch explanation by Sasha Rush
<http://nlp.seas.harvard.edu/2018/04/03/attention.html>



Transformer Overview


- Non-recurrent encoder-decoder for MT
- PyTorch explanation by Sasha Rush
<http://nlp.seas.harvard.edu/2018/04/03/attention.html>



Multi-Head Attention

- Idea: allow words to interact with one another
- Model
 - Map V , K , Q to lower dimensional spaces
 - Apply attention, concatenate outputs
 - Linear transformation

$$\begin{aligned}\text{MultiHead}(Q, K, V) &= \text{Concat}(\text{head}_1, \dots, \text{head}_h) W^O \\ \text{head}_i &= \text{Attention}(QW_i^Q, KW_i^K, VW_i^V)\end{aligned}$$



Scaled Dot-Product Attention


- Problem: when d_k gets large, the variance of $q^T k$ increases

→ some values inside softmax get large


→ the softmax gets very peaked

→ hence its gradient gets smaller

- Solution: scale by length of query/key vectors


$$A(q, K, V) = \sum_i \frac{\exp(q \cdot k_i)}{\sum_j \exp(q \cdot k_j)} v_i$$


$$A(Q, K, V) = \text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V$$



Transformer Overview



- Non-recurrent encoder-decoder for MT
- PyTorch explanation by Sasha Rush

<http://nlp.seas.harvard.edu/2018/04/03/attention.html>



Transformer Encoder Block


- Each block has
 - multi-head attention
 - 2-layer feed-forward NN (w/ ReLU)
- Both parts contain
 - Residual connection
 - Layer normalization (LayerNorm)



Change input to have 0 mean and 1 variance per layer & per training point

→ LayerNorm(x + sublayer(x))

$$\mu^l = \frac{1}{H} \sum_{i=1}^H a_i^l \quad \sigma^l = \sqrt{\frac{1}{H} \sum_{i=1}^H (a_i^l - \mu^l)^2} \quad h_i = f\left(\frac{g_i}{\sigma_i} (a_i - \mu_i) + b_i\right)$$






Encoder Input

- Problem: temporal information is missing
- Solution: **positional encoding** allows words at different locations to have different embeddings with fixed dimensions

$$PE_{(pos, 2i)} = \sin(pos/10000^{2i/d_{model}})$$

$$PE_{(pos, 2i+1)} = \cos(pos/10000^{2i/d_{model}})$$





Multi-Head Attention Details

encoder self attention



1. Multi-head Attention
2. **Q**uery=**K**ey=**V**alue

decoder self attention

1. **Masked** Multi-head Attention
2. **Q**uery=**K**ey=**V**alue

encoder-decoder attention

1. Multi-head Attention
2. Encoder Self attention=Key=Value
3. Decoder Self attention=Query



Training Tips

- Byte-pair encodings (BPE)
- Checkpoint averaging
- ADAM optimizer with learning rate changes
- Dropout during training at every layer just before adding residual
- Label smoothing
- Auto-regressive decoding with beam search and length penalties



MT Experiments

Model	BLEU		Training Cost (FLOPs)	
	EN-DE	EN-FR	EN-DE	EN-FR
ByteNet [18]	23.75			
Deep-Att + PosUnk [39]		39.2		$1.0 \cdot 10^{20}$
GNMT + RL [38]	24.6	39.92	$2.3 \cdot 10^{19}$	$1.4 \cdot 10^{20}$
ConvS2S [9]	25.16	40.46	$9.6 \cdot 10^{18}$	$1.5 \cdot 10^{20}$
MoE [32]	26.03	40.56	$2.0 \cdot 10^{19}$	$1.2 \cdot 10^{20}$
Deep-Att + PosUnk Ensemble [39]		40.4		$8.0 \cdot 10^{20}$
GNMT + RL Ensemble [38]	26.30	41.16	$1.8 \cdot 10^{20}$	$1.1 \cdot 10^{21}$
ConvS2S Ensemble [9]	26.36	41.29	$7.7 \cdot 10^{19}$	$1.2 \cdot 10^{21}$
Transformer (base model)	27.3	38.1	$3.3 \cdot 10^{18}$	
Transformer (big)	28.4	41.8	$2.3 \cdot 10^{19}$	



Parsing Experiments

Parser	Training	WSJ 23 F1
Vinyals & Kaiser et al. (2014) [37]	WSJ only, discriminative	88.3
Petrov et al. (2006) [29]	WSJ only, discriminative	90.4
Zhu et al. (2013) [40]	WSJ only, discriminative	90.4
Dyer et al. (2016) [8]	WSJ only, discriminative	91.7
Transformer (4 layers)	WSJ only, discriminative	91.3
Zhu et al. (2013) [40]	semi-supervised	91.3
Huang & Harper (2009) [14]	semi-supervised	91.3
McClosky et al. (2006) [26]	semi-supervised	92.1
Vinyals & Kaiser et al. (2014) [37]	semi-supervised	92.1
Transformer (4 layers)	semi-supervised	92.7
Luong et al. (2015) [23]	multi-task	93.0
Dyer et al. (2016) [8]	generative	93.3



Concluding Remarks

- **Non-recurrence** model is easy to parallelize
- **Multi-head attention** captures different aspects by interacting between words
- **Positional encoding** captures location information
- Each transformer block can be applied to diverse tasks

