



Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x: 1153, y: 103

Root 04:08:30

Router0

Physical Config CLI Attributes

IOS Command Line Interface

```
Router(config-if)#no shutdown
Router(config-if)#
%LINK-6-CHANGED: Interface FastEthernet0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to up
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#no shutdown
Router(config-if)#
%LINK-6-CHANGED: Interface FastEthernet0/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
ip address 100.10.10.1 255.0.0.0
Router(config-if)#ip address 100.10.10.1 255.0.0.0
Router(config-if)#
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/0
Router(config-if)#
Router(config-if)#exit
Router(config)#interface FastEthernet0/1
Router(config-if)#
Router(config-if)#exit
Router(config)#access-list 1 permit 192.168.0.0 0.0.0.255
Router(config)#ip nat pool white-address 100.10.11.77 100.10.11.99 netmask 255.255.255.0
Router(config)#ip nat inside source list 1 pool white-address
Router(config)#
% Invalid input detected at '^' marker.
Router(config)#ip nat inside source list 1 pool white-address
Router(config)#int fa0/0
Router(config-if)#ip nat inside
Router(config-if)#int fa0/1
Router(config-if)#ip nat outside
Router(config-if)#exit
Router(config)#
```

Copy Paste

Top

Auto

Time: 00:08:12

Realtime Simulation

Type Color Time(sec) Periodic Num Edit

Поиск

ENG 12:11

