



Cisco Packet Tracer

File Home Insert Design Layout Reference

Calibri (Body) 11 A A Aa

B I U abc X₂ X² Aa

Paste

Clipboard

Page 1 of 1 0 words English (United States)

Time: 00:24:43

Realtime Simulation

Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```
%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up

Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int fa0/1
Switch(config-if)#sw ac vl 10

% Invalid input detected at '^' marker.

Switch(config-if)#sw ac vl 10
% Access VLAN does not exist. Creating vlan 10
Switch(config-if)#no sh
Switch(config-if)#int fa0/2
Switch(config-if)#sw ac vl 20
% Access VLAN does not exist. Creating vlan 20
Switch(config-if)#no sh
Switch(config-if)#exit
Switch(config)#int gi0/1
Switch(config-if)#sw mode trunk
Switch(config-if)#no sh
Switch(config-if)#exit
Switch(config)#int gi0/1
Switch(config-if)#sw mode trunk
Switch(config-if)#
Switch(config-if)#exit
Switch(config)#interface FastEthernet0/1
Switch(config-if)#
```

Copy Paste

Top

Root 12:23:30

Realtime Simulation

Type Color Time(sec) Periodic Num Edit

Поиск

ENG 10:21

Cisco Packet Tracer

Switch0

Physical Config CLI Attributes

IOS Command Line Interface

```
Switch(config-if)#sw ac vl 10
% Access VLAN does not exist. Creating vlan 10
Switch(config-if)#no sh
Switch(config-if)#int fa0/3
Switch(config-if)#sw ac vl 20
Switch(config-if)#sw ac vl 20
% Invalid input detected at '^' marker.
Switch(config-if)#sw ac vl 20
% Invalid input detected at '^' marker.
Switch(config-if)#sw ac vl 20
% Access VLAN does not exist. Creating vlan 20
Switch(config-if)#no sh
Switch(config-if)#exit
Switch(config)#int gi0/1
Switch(config-if)#sw mode trunk
Switch(config-if)#no sh
Switch(config-if)#exit
Switch(config)#
%LINK-3-UPDOWN: Interface FastEthernet0/3, changed state to down
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to down
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to up
Switch(config)#int fa0/3
Switch(config-if)#sw mode trunk
Switch(config-if)#
%LINK-3-UPDOWN: Interface FastEthernet0/3, changed state to down
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to up
```

Copy Paste

Top

Scenario 0

New Delete

Toggle PDU List Window

Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit

Realtime Simulation

05:50:30

Cisco Packet Tracer

File Edit Options View Tools Extensions Window Help

Logical Physical x:377, y:155

2960-24TT Switch0

Time: 00:24:55

Switch1

Physical Config CLI Attributes

IOS Command Line Interface

```
Press RETURN to get started!

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/2, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up
%LINK-5-CHANGED: Interface FastEthernet0/3, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/3, changed state to up

Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int fa0/1
Switch(config-if)#sw ac vl 10
Switch(config-if)#no sh
Switch(config-if)#int fa0/2
Switch(config-if)#sw ac vl 20
Switch(config-if)#no sh
Switch(config-if)#exit
Switch(config)#int gi0/1
Switch(config-if)#sw mode trunk
Switch(config-if)#no shh
% Invalid input detected at '^' marker.
Switch(config-if)#no sh
Switch(config-if)#
```

Copy Paste

Top

Scenario 0

New Delete

Toggle PDU List Window

Fire Last Status Source Destination Type Color Time(sec) Periodic Num Edit

Realtime Simulation

12:30:00

10:21





