

An Autonomous Mobile Multipurpose Platform for use in Kiwifruit Orchards

Mark H. Jones, Matthew Seabright, Joshua Barnett, Alistair Scarfe, Prof. Mike Duke

Abstract

Other uses may be mechanical weed removal, targeted spraying, and crop scouting.

Keywords:

1. Introduction

Short-term labor requirements within the New Zealand kiwifruit industry peak twice a year corresponding with pollination and harvesting cycles. The majority of employment in this industry during these peaks is filled by seasonal or casual workers (Timmins, 2009). As kiwifruit is New Zealand's largest horticultural export by value (Statistics New Zealand, 2015), automation in kiwifruit harvesting and pollination should ease growth in this industry. Additionally, the New Zealand government aims to double exports from its primary industries between 2012 and 2025 and is actively investing in programmes to achieve this (Ministry for Primary Industries, 2015).

Previous work on automated harvesting of kiwifruit was demonstrated in 2012 (Scarfe, 2012). That work presents a harvesting platform with the capability of in-orchard kiwifruit harvesting from pergola type orchards. The robotic platform presented in this paper is a second generation unit based on that previous, more integrated, design of kiwifruit harvester. Modularity of the platform has been increased to so as to be able to fit either a harvesting module or a pollination module with relative ease. This work discusses only the base platform, where details of the harvesting and pollination modules will be published separately.

The robotic platform presented in this paper builds upon that design to create a second generation kiwifruit harvesting and pollinating robotic

platform. Stress robustness required of vehicles designed for in-field use. High cost associated with conversion of a tractor to an autonomous vehicle.

An electric four wheel steered robot is presented in Bak & Jakobsen (2004).

It has been stated that “since the robot development already includes a high complexity, the application itself should be of comparably low complexity” (Ruckelshausen et al., 2009).

“The implementation of additional mechatronic systems, such as weeding or seeding, will increase the complexity due to technical and logistical aspects and thus reduce the probability for the development of a robust system.” (Ruckelshausen et al., 2009).

2. Mechanical design

Skid steering inappropriate for orchard environments due to soft ground. Pivoting front axle used to maintain three points of contact at all times; no suspension. Limited to 10 km h^{-1} by the choice of motor and gearboxes on the drive-system. Operational speed of 5 km h^{-1} . Ackermann steering geometry with the ability to pivot about the centre of the rear wheels.

(Åstrand & Baerveldt, 2002) have used an ackermann steering system actuated by a single DC servo motor for their robotic beet-crop weeding platform. They have only two driving wheels placed at the rear of the system.

3. Hardware and sensors

GPS has proven to be unreliable when used under the dense canopy of a kiwifruit orchard. (Pedersen et al., 2006) shows the economics of using an GPS-RTK system, as seen in other agricultural systems (Bak & Jakobsen, 2004; Ruckelshausen et al., 2009), has considerable ongoing costs in the form of yearly fees. Forward and upwards facing LiDAR have been used for navigation and detection of the row and canopy.

4. Safety

Relay modules connected to the main computer via the system’s CAN bus give a means of shutting down subsystems. These relays monitor the platform’s CAN bus to ensure that synchronisation messages are being sent

out in a timely manner. In the event that the synchronisation messages begin to vary in frequency, or stop, the relays cut power to the subsystems. Both front drive motors are fitted with electromechanical brakes which engage when the power is cut. A wireless safety-rated controller, designed for use with cranes, has been adapted for use with driving robot platform. The controller provides the operator with a way of entering the platform into autonomous mode, manual control, triggering an emergency stop, or enabling/disabling auxiliary systems.

5. Software architecture

The control software is comprised of individual nodes, written in either C++ or Python, linked together using Robot Operating System (ROS) for interprocess communication. The system runs on Ubuntu Server 16.04 on an Intel NUC, a compact x86 based PC. A model of the robot platform has been developed for use with Gazebo simulation software. Such a model provides a way to test steering and movement strategies before deploying them on the hardware.

6. Random info

“Field scouting and mechanical weeding have been identified and described as the first two niche tasks likely to become autonomous” (Blackmore et al., 2004).

References

- Åstrand, B., & Baerveldt, A. J. (2002). An agricultural mobile robot with vision-based perception for mechanical weed control. *Autonomous Robots*, 13, 21–35.
- Bak, T., & Jakobsen, H. (2004). Agricultural Robotic Platform with Four Wheel Steering for Weed Detection. *o*, 87, 125–136.
- Blackmore, B. S., Fountas, S., Tang, L., & Have, H. (2004). Systems Requirements For a Small Autonomous Tractor. *Agricultural Engineering International: the CIGR Journal of Scientific Research and Development*, 4.

- Ministry for Primary Industries (2015). Our Strategy 2030 - growing and protecting New Zealand - The export goal.
- Pedersen, S. M., Fountas, S., Have, H., & Blackmore, B. S. (2006). Agricultural robots - System analysis and economic feasibility. *Precision Agriculture*, 7, 295–308.
- Ruckelshausen, A., Biber, P., Dorna, M., Gremmes, H., Klose, R., Linz, A., Rahe, F., Resch, R., Thiel, M., Trautz, D., Weiss, U., Doma, M., & Rahne, R. (2009). BoniRob: an autonomous field robot platform for individual plant phenotyping. *Proceedings of Joint International Agricultural Conference (2009)*, 9, 841–847.
- Scarfe, A. J. (2012). Development of an Autonomous Kiwifruit Harvester, .
- Statistics New Zealand (2015). Annual Fruit Exports Hit \$2 Billion for First Time.
- Timmins, J. (2009). *Seasonal Employment Patterns in the Horticultural Industry*. Technical Report August Statistics New Zealand.