

SE Comp A	Roll number : 9913												
Experiment no. : 10	Date of Implementation :												
Aim: Simple Transaction implementation													
Tool Used : PostgreSQL/Mysql													
Related Course outcome : At the end of the course, Students will be able to Use and Apply the concept of transaction, concurrency and recovery													
Rubrics for assessment of Experiment:													
Indicator Timeliness <ul style="list-style-type: none"> Maintains assignment deadline (3) 	Poor Assignment not done (0)	Average One or More than One week late (1-2)	Good Maintains deadline (3)										
Implementation of concepts (3)	N/A	< 80% complete (1-2)	100% complete (3)										
Originality <ul style="list-style-type: none"> Extent of plagiarism(2) 	Copied it from someone else(0)	At least few parts of it have been done without copying(1)	Experiment has been solved completely without copying (2)										
Knowledge <ul style="list-style-type: none"> In depth knowledge of the assignment(2) 	Unable to answer 2 questions(0)	Unable to answer 1 question (1)	Able to answer 2 questions (2)										
Assessment Marks : <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Timeliness</td> <td style="width: 70%;"></td> </tr> <tr> <td>Completeness and neatness</td> <td></td> </tr> <tr> <td>Originality</td> <td></td> </tr> <tr> <td>Knowledge</td> <td></td> </tr> <tr> <td>Total</td> <td></td> </tr> </table>				Timeliness		Completeness and neatness		Originality		Knowledge		Total	
Timeliness													
Completeness and neatness													
Originality													
Knowledge													
Total													
Total : (Out of 10)													
Teacher's Sign :													


EXPERIMENT 10	Transaction concept
Aim	To implement Simple Transaction concept
Tools	PostgreSQL/Mysql

Theory	<p>A transaction can be defined as a group of tasks. A single task is the minimum processing unit which cannot be divided further.</p> <p><i>Transactions</i> are a fundamental concept of all database systems. The essential point of a transaction is that it bundles multiple steps into a single, all-or-nothing operation. The intermediate states between the steps are not visible to other concurrent transactions, and if some failure occurs that prevents the transaction from completing, then none of the steps affect the database at all.</p> <p>Properties of Transactions</p> <p>Transactions have the following four standard properties, usually referred to by the acronym ACID –</p> <ul style="list-style-type: none"> ● Atomicity – Ensures that all operations within the work unit are completed successfully; otherwise, the transaction is aborted at the point of failure and previous operations are rolled back to their former state. ● Consistency – Ensures that the database properly changes states upon a successfully committed transaction. ● Isolation – Enables transactions to operate independently of and transparent to each other. ● Durability – Ensures that the result or effect of a committed transaction persists in case of a system failure. <p>In PostgreSQL, a transaction is set up by surrounding the SQL commands of the transaction with BEGIN and COMMIT commands. So our banking transaction would actually look like:</p> <pre> BEGIN; UPDATE accounts SET balance = balance - 100.00 WHERE name = 'Alice'; -- etc etc COMMIT; End; </pre>
--------	--

Theory

State Diagram :

A transaction in a database can be in one of the following states:



For example, consider a bank database that contains balances for various customer accounts, as well as total deposit balances for branches. Suppose that we want to record a payment of \$100.00 from Alice's account to Bob's account.

```
BEGIN;
```

```
--sql
```

```
SAVEPOINT my_savepoint;
```

```
UPDATE accounts SET balance = balance - 100.00
```

```
WHERE name = 'Alice';
```

```
UPDATE accounts SET balance = balance + 100.00
```

```
WHERE name = 'Bob';
```

```
ROLLBACK TO my_savepoint; or commit;
```

```
--UPDATE accounts SET balance = balance + 100.00
```

```
WHERE name = 'Wally';
```


```
COMMIT;
```

Theory	<h2 data-bbox="451 184 971 226">DOCXTransaction Control</h2> <p data-bbox="451 268 1429 304">The following commands are used to control transactions –</p> <ul data-bbox="500 346 1421 499" style="list-style-type: none"> • BEGIN TRANSACTION – To start a transaction. • COMMIT – To save the changes, alternatively you can use END TRANSACTION command. • ROLLBACK – To rollback the changes. <p data-bbox="451 535 1437 667">Transactional control commands are only used with the DML commands INSERT, UPDATE and DELETE only. They cannot be used while creating tables or dropping them because these operations are automatically committed in the database.</p> <h3 data-bbox="451 709 1039 741">The BEGIN TRANSACTION Command</h3> <p data-bbox="451 783 1442 915">Transactions can be started using BEGIN TRANSACTION or simply BEGIN command. Such transactions usually persist until the next COMMIT or ROLLBACK command is encountered. But a transaction will also ROLLBACK if the database is closed or if an error occurs.</p> <p data-bbox="451 957 1161 1020">The following is the simple syntax to start a transaction – BEGIN;</p> <p data-bbox="451 1062 479 1094">or</p> <p data-bbox="451 1136 722 1167">BEGIN TRANSACTION;</p> <h3 data-bbox="451 1209 747 1241">The COMMIT Command</h3> <p data-bbox="451 1245 1388 1308">The COMMIT command is the transactional command used to save changes invoked by a transaction to the database.</p> <p data-bbox="451 1318 1388 1381">The COMMIT command saves all transactions to the database since the last COMMIT or ROLLBACK command.</p> <p data-bbox="451 1392 1055 1455">The syntax for COMMIT command is as follows – COMMIT;</p> <p data-bbox="451 1497 479 1528">or</p> <p data-bbox="451 1570 698 1602">END TRANSACTION;</p>
--------	---


Theory	<p>The ROLLBACK Command</p> <p>The ROLLBACK command is the transactional command used to undo transactions that have not already been saved to the database.</p> <p>The ROLLBACK command can only be used to undo transactions since the last COMMIT or ROLLBACK command was issued.</p> <p>The syntax for ROLLBACK command is as follows –</p> <p>ROLLBACK;</p> <p>PostgreSQL Transaction (postgresqltutorial.com)</p> <p>PostgreSQL: Documentation: 15: 13.2. Transaction Isolation</p> <p>https://www.postgresql.org/docs/current/transaction-iso.html</p>
Task	<ol style="list-style-type: none"> 1. Create any sample table for transaction testing 2. Observe the effect of auto commit on /off on insert stmt(SET AUTOCOMMIT { = TO } { ON OFF }) 3. How to find out the current transaction mode(POSTGRESQL-MENU-QUERY-AUTOCOMMIT) 4. Start transaction, insert records in table and use roll back 5. Start new transaction and commit the current transaction 6. Use save point and use rollback to and commit 7. What happens to the current transaction if a start transaction is executed? 8. What happens to the current transaction if the session is ended? 9. How to view and change the current transaction isolation level? 10. Demonstrate datalocks in transaction and how long a transaction will wait for a data lock? (OPTIONAL) 11. Wa java/php program using jdbc/odbc to implement transaction java-mysql or php-mysql (jdbc/odbc)[https://www.php.net/manual/en/mysqli.begin-transaction.php] (OPTIONAL) 12. Transfer 5k from A's account to B's account using transaction concept 13. demonstrate different locks(MySQL :: MySQL 8.0 Reference Manual :: 15.7.2.4 Locking Reads) (OPTIONAL)

Links	https://www.postgresql.org/docs/9.1/sql-start-transaction.html https://www.postgresql.org/docs/8.3/tutorial-transactions.html https://pgdash.io/blog/postgres-transactions.html https://tapoueh.org/blog/2018/07/postgresql-concurrency-isolation-and-locking/ http://dba.fyicenter.com/faq/mysql/mysql_sql_transaction_management.html locks MySQL :: MySQL 8.0 Reference Manual :: 15.7.2.4 Locking Reads Processlist in postgresql - postgres > <code>select * from pg_stat_activity;</code> Terminate (kill) specific session in PostgreSQL database - PostgreSQL Data Dictionary Queries (dataedo.com) PostgreSQL: Documentation: 14: SET TRANSACTION
Post Lab Questions:	1. How Does MySQL/postgresql Handle Read Consistency? 2. What Are Transaction Isolation Levels IN MYSQL/ Postgresql 3. What Are Impacts on Applications from Locks, Timeouts, and DeadLocks?

1. DROP TABLE IF EXISTS accounts;
 BEGIN;
 CREATE TABLE accounts (
 id SERIAL PRIMARY KEY,
 account_name VARCHAR(100),
 balance DECIMAL(15, 2)
);
 COMMIT;
 ROLLBACK;
2. BEGIN;
 INSERT INTO accounts (account_name, balance) VALUES ('Account1', 1000);
 COMMIT;
 SELECT * FROM accounts;



3. `SELECT current_setting('transaction_isolation');`




4. `BEGIN;`

`INSERT INTO accounts (account_name, balance) VALUES ('Account4', 4000);`

5. `COMMIT;`

`SELECT * FROM accounts;`



6. BEGIN;

SAVEPOINT savepoint1;

INSERT INTO accounts (account_name, balance) VALUES ('Account5', 5000);

INSERT INTO accounts (account_name, balance) VALUES ('Account6', 6000);

ROLLBACK TO SAVEPOINT savepoint1;

SELECT * FROM accounts;

COMMIT;

SELECT * FROM accounts;

7. If a "start transaction" command is executed during a current transaction, it typically initiates a new transaction, effectively nesting the new transaction within the current one. This means that any changes made after the "start transaction" command will be part of the new transaction, and they can be committed or rolled back independently of the outer transaction.
8. If the session is ended during a current transaction without committing or rolling back the transaction explicitly, the transaction will typically be automatically rolled back by the database management system. This ensures data integrity and prevents any unintended changes from being permanently committed to the database.


```
9. SHOW TRANSACTION ISOLATION LEVEL;
SET TRANSACTION ISOLATION LEVEL READ UNCOMMITTED;
SET TRANSACTION ISOLATION LEVEL READ COMMITTED;
BEGIN;
UPDATE accounts SET balance = balance - 5000 WHERE account_name = 'A';
UPDATE accounts SET balance = balance + 5000 WHERE account_name = 'B';
COMMIT;
```

POSTLAB :

Q1 How Does MySQL/postgresql Handle Read Consistency?

MySQL and PostgreSQL both use Multi-Version Concurrency Control (MVCC) to ensure read consistency. In MySQL, different transaction isolation levels, like REPEATABLE READ, control consistency, while PostgreSQL defaults to READ COMMITTED isolation. Both systems provide mechanisms to ensure that transactions see a consistent view of the database despite concurrent modifications.

Q2 What Are Transaction Isolation Levels IN MYSQL/ Postgresql?

- MySQL:
 - READ UNCOMMITTED: Allows dirty reads.
 - READ COMMITTED: Prevents dirty reads, allows non-repeatable reads and phantom reads.
 - REPEATABLE READ: Prevents non-repeatable reads, allows phantom reads.
 - SERIALIZABLE: Prevents all anomalies: dirty reads, non-repeatable reads, and phantom reads.
- PostgreSQL:
 - READ UNCOMMITTED: Not directly supported.
 - READ COMMITTED: Prevents dirty reads.
 - REPEATABLE READ: Prevents non-repeatable reads.
 - SERIALIZABLE: Prevents all anomalies.

Q3 What Are Impacts on Applications from Locks, Timeouts, and DeadLocks?

- Locks: Can cause contention and blocking, leading to performance issues.
- Timeouts: Can result in incomplete transactions or failed operations.
- Deadlocks: Cause transactions to wait indefinitely for each other, potentially leading to application hangs or crashes.