

Using the Set Operators

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Objectives

After completing this lesson, you should be able to do the following:

- Describe set operators
- Use a set operator to combine multiple queries into a single query
- Control the order of rows returned


ORACLE

Copyright © 2009, Oracle. All rights reserved.

Objectives

In this lesson, you learn how to write queries by using set operators.

Set Operators



ORACLE

Copyright © 2009, Oracle. All rights reserved.

Set Operators

Set operators combine the results of two or more component queries into one result. Queries containing set operators are called *compound queries*.

Operator	Returns
UNION	All distinct rows selected by either query
UNION ALL	All rows selected by either query, including all duplicates
INTERSECT	All distinct rows selected by both queries
MINUS	All distinct rows that are selected by the first SELECT statement and not selected in the second SELECT statement

All set operators have equal precedence. If a SQL statement contains multiple set operators, the Oracle server evaluates them from left (top) to right (bottom) if no parentheses explicitly specify another order. You should use parentheses to specify the order of evaluation explicitly in queries that use the INTERSECT operator with other set operators.

Tables Used in This Lesson

The tables used in this lesson are:

- **EMPLOYEES:** Provides details regarding all current employees
- **JOB_HISTORY:** Records the details of the start date and end date of the former job, and the job identification number and department when an employee switches jobs

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Tables Used in This Lesson

Two tables are used in this lesson. They are the **EMPLOYEES** table and the **JOB_HISTORY** table.

The **EMPLOYEES** table stores the employee details. For the human resource records, this table stores a unique identification number and e-mail address for each employee. The details of the employee's job identification number, salary, and manager are also stored. Some of the employees earn a commission in addition to their salary; this information is tracked, too. The company organizes the roles of employees into jobs. Some of the employees have been with the company for a long time and have switched to different jobs. This is monitored using the **JOB_HISTORY** table. When an employee switches jobs, the details of the start date and end date of the former job, the job identification number, and the department are recorded in the **JOB_HISTORY** table.

The structure and data from the **EMPLOYEES** and **JOB_HISTORY** tables are shown on the following pages.

Tables Used in This Lesson (continued)

There have been instances in the company of people who have held the same position more than once during their tenure with the company. For example, consider the employee Taylor, who joined the company on 24-MAR-1998. Taylor held the job title SA_REP for the period 24-MAR-98 to 31-DEC-98 and the job title SA_MAN for the period 01-JAN-99 to 31-DEC-99. Taylor moved back into the job title of SA_REP, which is his current job title.

Similarly, consider the employee Whalen, who joined the company on 17-SEP-1987. Whalen held the job title AD_ASST for the period 17-SEP-87 to 17-JUN-93 and the job title AC_ACCOUNT for the period 01-JUL-94 to 31-DEC-98. Whalen moved back into the job title of AD_ASST, which is his current job title.

```
DESCRIBE employees
```

DESCRIBE employees		
Name	Null	Type
-----	-----	-----
EMPLOYEE_ID	NOT NULL	NUMBER(6)
FIRST_NAME		VARCHAR2(20)
LAST_NAME	NOT NULL	VARCHAR2(25)
EMAIL	NOT NULL	VARCHAR2(25)
PHONE_NUMBER		VARCHAR2(20)
HIRE_DATE	NOT NULL	DATE
JOB_ID	NOT NULL	VARCHAR2(10)
SALARY		NUMBER(8,2)
COMMISSION_PCT		NUMBER(2,2)
MANAGER_ID		NUMBER(6)
DEPARTMENT_ID		NUMBER(4)
11 rows selected		

Tables Used in This Lesson (continued)

```
SELECT employee_id, last_name, job_id, hire_date, department_id
FROM employees;
```

	EMPLOYEE_ID	LAST_NAME	JOB_ID	HIRE_DATE	DEPARTMENT_ID
1	200	Whalen	AD_ASST	17-SEP-87	10
2	201	Hartstein	MK_MAN	17-FEB-96	20
3	202	Fay	MK_REP	17-AUG-97	20
4	205	Higgins	AC_MGR	07-JUN-94	110
5	206	Gietz	AC_ACCOUNT	07-JUN-94	110
6	100	King	AD_PRES	17-JUN-87	90
7	101	Kochhar	AD_VP	21-SEP-89	90
8	102	De Haan	AD_VP	13-JAN-93	90
9	103	Hunold	IT_PROG	03-JAN-90	60
10	104	Ernst	IT_PROG	21-MAY-91	60
11	107	Lorentz	IT_PROG	07-FEB-99	60
12	124	Mourgos	ST_MAN	16-NOV-99	50
13	141	Rajs	ST_CLERK	17-OCT-95	50
14	142	Davies	ST_CLERK	29-JAN-97	50
15	143	Matos	ST_CLERK	15-MAR-98	50
16	144	Vargas	ST_CLERK	09-JUL-98	50
17	149	Zlotkey	SA_MAN	29-JAN-00	80
18	174	Abel	SA_REP	11-MAY-96	80
19	176	Taylor	SA_REP	24-MAR-98	80
20	178	Grant	SA_REP	24-MAY-99	(null)

```
DESCRIBE job_history
```

DESCRIBE job_history		
Name	Null	Type


EMPLOYEE_ID	NOT NULL	NUMBER(6)
START_DATE	NOT NULL	DATE
END_DATE	NOT NULL	DATE
JOB_ID	NOT NULL	VARCHAR2(10)
DEPARTMENT_ID		NUMBER(4)
5 rows selected		

Tables Used in This Lesson (continued)

```
SELECT * FROM job_history;
```

	EMPLOYEE_ID	START_DATE	END_DATE	JOB_ID	DEPARTMENT_ID
1	102	13-JAN-93	24-JUL-98	IT_PROG	60
2	101	21-SEP-89	27-OCT-93	AC_ACCOUNT	110
3	101	28-OCT-93	15-MAR-97	AC_MGR	110
4	201	17-FEB-96	19-DEC-99	MK_REP	20
5	114	24-MAR-98	31-DEC-99	ST_CLERK	50
6	122	01-JAN-99	31-DEC-99	ST_CLERK	50
7	200	17-SEP-87	17-JUN-93	AD_ASST	90
8	176	24-MAR-98	31-DEC-98	SA_REP	80
9	176	01-JAN-99	31-DEC-99	SA_MAN	80
10	200	01-JUL-94	31-DEC-98	AC_ACCOUNT	90

UNION Operator



The UNION operator returns results from both queries after eliminating duplications.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

UNION Operator

The UNION operator returns all rows that are selected by either query. Use the UNION operator to return all rows from multiple tables and eliminate any duplicate rows.

Guidelines

- The number of columns and the data types of the columns being selected must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- UNION operates over all of the columns being selected.
- NULL values are not ignored during duplicate checking.
- The IN operator has a higher precedence than the UNION operator.
- By default, the output is sorted in ascending order of the first column of the SELECT clause.

Using the UNION Operator

Display the current and previous job details of all employees.
Display each combination only once.

```
SELECT employee_id, job_id
FROM employees
UNION
SELECT employee_id, job_id
FROM job_history;
```

EMPLOYEE_ID	JOB_ID
1	100 AD_PRES
2	101 AC_ACCOUNT
...	
22	200 AC_ACCOUNT
23	200 AD_ASST
...	
28	206 AC_ACCOUNT

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Using the UNION Operator

The UNION operator eliminates any duplicate records. If records that occur in both the EMPLOYEES and the JOB_HISTORY tables are identical, the records are displayed only once. Observe in the output shown in the slide that the record for the employee with the EMPLOYEE_ID 200 appears twice because the JOB_ID is different in each row.

Consider the following example:


```
SELECT employee_id, job_id, department_id
FROM employees
UNION
SELECT employee_id, job_id, department_id
FROM job_history;
```

EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
...		
22	200 AC_ACCOUNT	90
23	200 AD_ASST	10
24	200 AD_ASST	90
...		

Using the UNION Operator (continued)

In the preceding output, employee 200 appears three times. Why? Notice the `DEPARTMENT_ID` values for employee 200. One row has a `DEPARTMENT_ID` of 90, another 10, and the third 90. Because of these unique combinations of job IDs and department IDs, each row for employee 200 is unique and therefore not considered to be a duplicate. Observe that the output is sorted in ascending order of the first column of the `SELECT` clause (in this case, `EMPLOYEE_ID`).

UNION ALL Operator



The UNION ALL operator returns results from both queries, including all duplications.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

UNION ALL Operator

Use the UNION ALL operator to return all rows from multiple queries.

Guidelines

The guidelines for UNION and UNION ALL are the same, with the following two exceptions that pertain to UNION ALL:

- Unlike UNION, duplicate rows are not eliminated and the output is not sorted by default.
- The DISTINCT keyword cannot be used.

Using the UNION ALL Operator

Display the current and previous departments of all employees.

```
SELECT employee_id, job_id, department_id
FROM employees
UNION ALL
SELECT employee_id, job_id, department_id
FROM job_history
ORDER BY employee_id;
```

	EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
1	100	AD_PRES	90
2	101	AD_VP	90
...			
23	200	AD_ASST	10
24	200	AC_ACCOUNT	90
25	200	AD_ASST	90
...			
30	206	AC_ACCOUNT	110

ORACLE

Copyright © 2009, Oracle. All rights reserved.

UNION ALL Operator (continued)


In the example, 30 rows are selected. The combination of the two tables totals to 30 rows. The UNION ALL operator does not eliminate duplicate rows. UNION returns all distinct rows selected by either query. UNION ALL returns all rows selected by either query, including all duplicates. Consider the query on the slide, now written with the UNION clause:

```
SELECT employee_id, job_id, department_id
FROM employees
UNION
SELECT employee_id, job_id, department_id
FROM job_history
ORDER BY employee_id;
```

The preceding query returns 29 rows. This is because it eliminates the following row (because it is a duplicate):

	EMPLOYEE_ID	JOB_ID	DEPARTMENT_ID
...			
20	176	SA_REP	80
...			
29	206	AC_ACCOUNT	110

INTERSECT Operator



The INTERSECT operator returns rows that are common to both queries.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

INTERSECT Operator

Use the INTERSECT operator to return all rows that are common to multiple queries.

Guidelines

- The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.
- Reversing the order of the intersected tables does not alter the result.
- INTERSECT does not ignore NULL values.

Using the INTERSECT Operator

Display the employee IDs and job IDs of those employees who currently have a job title that is the same as a previous job title.

```
SELECT employee_id, job_id
FROM employees
INTERSECT
SELECT employee_id, job_id
FROM job_history;
```

	EMPLOYEE_ID	JOB_ID
1	176	SA_REP
2	200	AD_ASST

ORACLE

Copyright © 2009, Oracle. All rights reserved.

INTERSECT Operator (continued)

In the example in this slide, the query returns only the records that have the same values in the selected columns in both tables.

What will be the results if you add the DEPARTMENT_ID column to the SELECT statement from the EMPLOYEES table and add the DEPARTMENT_ID column to the SELECT statement from the JOB_HISTORY table and run this query? The results may be different because of the introduction of another column whose values may or may not be duplicates.


Example

```
SELECT employee_id, job_id, department_id
FROM employees
INTERSECT
SELECT employee_id, job_id, department_id
FROM job_history;
```

	EMPLOYEE_ID	JOB_ID
1	176	SA_REP
2	200	AD_ASST

Employee 200 is no longer part of the results because the EMPLOYEES.DEPARTMENT_ID value is different from the JOB_HISTORY.DEPARTMENT_ID value.

MINUS Operator



The MINUS operator returns rows in the first query that are not present in the second query.

ORACLE

Copyright © 2009, Oracle. All rights reserved.

MINUS Operator

Use the MINUS operator to return rows returned by the first query that are not present in the second query (the first SELECT statement MINUS the second SELECT statement).

Note: The number of columns and the data types of the columns being selected by the SELECT statements in the queries must be identical in all the SELECT statements used in the query. The names of the columns need not be identical.

MINUS Operator

Display the employee IDs of those employees who have not changed their jobs even once.

```
SELECT employee_id
FROM employees
MINUS
SELECT employee_id
FROM job_history;
```

	EMPLOYEE_ID
1	100
2	103
3	104
...	
14	205
15	206

ORACLE

Copyright © 2009, Oracle. All rights reserved.

MINUS Operator (continued)

In the example in the slide, the employee IDs in the JOB_HISTORY table are subtracted from those in the EMPLOYEES table. The results set displays the employees remaining after the subtraction; they are represented by rows that exist in the EMPLOYEES table but do not exist in the JOB_HISTORY table. These are the records of the employees who have not changed their jobs even once.

Set Operator Guidelines

- The expressions in the `SELECT` lists must match in number and data type.
- Parentheses can be used to alter the sequence of execution.
- The `ORDER BY` clause:
 - Can appear only at the very end of the statement
 - Will accept the column name, aliases from the first `SELECT` statement, or the positional notation

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Set Operator Guidelines

- The expressions in the select lists of the queries must match in number and data type. Queries that use `UNION`, `UNION ALL`, `INTERSECT`, and `MINUS` operators in their `WHERE` clause must have the same number and type of columns in their `SELECT` list. For example:

```
SELECT employee_id, department_id
FROM   employees
WHERE  (employee_id, department_id)
       IN (SELECT employee_id, department_id
           FROM   employees
           UNION
           SELECT employee_id, department_id
           FROM   job_history);
```

- The `ORDER BY` clause:
 - Can appear only at the very end of the statement
 - Will accept the column name, an alias, or the positional notation
- The column name or alias, if used in an `ORDER BY` clause, must be from the first `SELECT` list.
- Set operators can be used in subqueries.

Oracle Server and Set Operators

- Duplicate rows are automatically eliminated except in `UNION ALL`.
- Column names from the first query appear in the result.
- The output is sorted in ascending order by default except in `UNION ALL`.

The Oracle logo, consisting of the word "ORACLE" in a bold, sans-serif font, is positioned on the right side of a red horizontal bar.

Copyright © 2009, Oracle. All rights reserved.

Oracle Server and Set Operators

When a query uses set operators, the Oracle server eliminates duplicate rows automatically except in the case of the `UNION ALL` operator. The column names in the output are decided by the column list in the first `SELECT` statement. By default, the output is sorted in ascending order of the first column of the `SELECT` clause.

The corresponding expressions in the select lists of the component queries of a compound query must match in number and data type. If component queries select character data, the data type of the return values is determined as follows:

- If both queries select values of data type `CHAR`, the returned values have data type `CHAR`.
- If either or both of the queries select values of data type `VARCHAR2`, the returned values have data type `VARCHAR2`.

Matching the SELECT Statements

Using the UNION operator, display the department ID, location, and hire date for all employees.

```
SELECT department_id, TO_NUMBER(null)
      location, hire_date
FROM   employees
UNION
SELECT department_id, location_id,  TO_DATE(null)
FROM   departments;
```

	DEPARTMENT_ID	LOCATION	HIRE_DATE
1	10	1700 (null)	
2	10	(null) 17-SEP-87	
3	20	1800 (null)	

...

26	190	1700 (null)	
27	(null)	(null) 24-MAY-99	

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Matching the SELECT Statements

Because the expressions in the select lists of the queries must match in number, you can use dummy columns and the data type conversion functions to comply with this rule. In the slide, the name `location` is given as the dummy column heading. The `TO_NUMBER` function is used in the first query to match the `NUMBER` data type of the `LOCATION_ID` column retrieved by the second query. Similarly, the `TO_DATE` function in the second query is used to match the `DATE` data type of the `HIRE_DATE` column retrieved by the first query.

Matching the SELECT Statement: Example

Using the UNION operator, display the employee ID, job ID, and salary of all employees.

```
SELECT employee_id, job_id,salary
FROM   employees
UNION
SELECT employee_id, job_id,0
FROM   job_history;
```

EMPLOYEE_ID	JOB_ID	SALARY
1	100 AD_PRES	24000
2	101 AC_ACCOUNT	0
3	101 AC_MGR	0
...		
29	205 AC_MGR	12000
30	206 AC_ACCOUNT	8300

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Matching the SELECT Statement: Example

The EMPLOYEES and JOB_HISTORY tables have several columns in common (for example, EMPLOYEE_ID, JOB_ID, and DEPARTMENT_ID). But what if you want the query to display the employee ID, job ID, and salary using the UNION operator, knowing that the salary exists only in the EMPLOYEES table?

The code example in the slide matches the EMPLOYEE_ID and JOB_ID columns in the EMPLOYEES and JOB_HISTORY tables. A literal value of 0 is added to the JOB_HISTORY SELECT statement to match the numeric SALARY column in the EMPLOYEES SELECT statement.

In the preceding results, each row in the output that corresponds to a record from the JOB_HISTORY table contains a 0 in the SALARY column.

Controlling the Order of Rows

Produce an English sentence using two UNION operators.

```
COLUMN a_dummy NOPRINT
SELECT 'sing' AS "My dream", 3 a_dummy
FROM dual
UNION
SELECT 'I'd like to teach', 1 a_dummy
FROM dual
UNION
SELECT 'the world to', 2 a_dummy
FROM dual
ORDER BY a_dummy;
```

	My dream	A_DUMMY
1	I'd like to teach	1
2	the world to	2
3	sing	3

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Controlling the Order of Rows

By default, the output is sorted in ascending order on the first column. You can use the ORDER BY clause to change this.

The ORDER BY clause can be used only once in a compound query. If used, the ORDER BY clause must be placed at the end of the query. The ORDER BY clause accepts the column name or an alias. Without the ORDER BY clause, the code example in the slide produces the following output in the alphabetical order of the first column:

	My dream	A_DUMMY
1	I'd like to teach	1
2	sing	3
3	the world to	2

Note: Consider a compound query where the UNION set operator is used more than once. In this case, the ORDER BY clause can use only positions rather than explicit expressions.

Summary

In this lesson, you should have learned how to use:

- UNION to return all distinct rows
- UNION ALL to return all rows, including duplicates
- INTERSECT to return all rows that are shared by both queries
- MINUS to return all distinct rows that are selected by the first query but not by the second
- ORDER BY only at the very end of the statement

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Summary

- The UNION operator returns all rows selected by either query. Use the UNION operator to return all rows from multiple tables and eliminate any duplicate rows.
- Use the UNION ALL operator to return all rows from multiple queries. Unlike the case with the UNION operator, duplicate rows are not eliminated and the output is not sorted by default.
- Use the INTERSECT operator to return all rows that are common to multiple queries.
- Use the MINUS operator to return rows returned by the first query that are not present in the second query.
- Remember to use the ORDER BY clause only at the very end of the compound statement.
- Make sure that the corresponding expressions in the SELECT lists match in number and data type.

Practice 7: Overview

In this practice, you use the following set operators to create reports:

- UNION operator
- INTERSECTION operator
- MINUS operator

ORACLE

Copyright © 2009, Oracle. All rights reserved.

Practice 7: Overview

In this practice, you write queries using the set operators.

Practice 7

1. The HR department needs a list of department IDs for departments that do not contain the job ID ST_CLERK. Use set operators to create this report.

	DEPARTMENT_ID
1	10
2	20
3	60
4	80
5	90
6	110
7	190

2. The HR department needs a list of countries that have no departments located in them. Display the country ID and the name of the countries. Use set operators to create this report.

	COUNTRY_ID	COUNTRY_NAME
1	DE	Germany

3. Produce a list of jobs for departments 10, 50, and 20, in that order. Display the job ID and department ID using set operators.

	JOB_ID	DEPARTMENT_ID	DUMMY
1	AD_ASST	10	x
2	ST_CLERK	50	y
3	ST_MAN	50	y
4	MK_MAN	20	z
5	MK_REP	20	z

4. Create a report that lists the employee ID and job ID of those employees who currently have a job title that is the same as their job title when they were initially hired by the company (that is, they changed jobs but have now gone back to doing their original job).

	EMPLOYEE_ID	JOB_ID
1	176	SA_REP
2	200	AD_ASST

Practice 7 (continued)

5. The HR department needs a report with the following specifications:

- The last name and department ID of all employees from the EMPLOYEES table, regardless of whether or not they belong to a department
- The department ID and department name of all departments from the DEPARTMENTS table, regardless of whether or not they have employees working in them

Write a compound query to accomplish this.

	LAST_NAME	DEPARTMENT_ID	TO_CHAR(NULL)
1	Abel	80	(null)
2	Davies	50	(null)
3	De Haan	90	(null)
4	Ernst	60	(null)
5	Fay	20	(null)
6	Gietz	110	(null)
7	Grant	(null)	(null)
8	Hartstein	20	(null)
9	Higgins	110	(null)
10	Hunold	60	(null)
11	King	90	(null)
12	Kochhar	90	(null)
13	Lorentz	60	(null)
14	Matos	50	(null)
15	Mourgos	50	(null)
16	Rajs	50	(null)
17	Taylor	80	(null)
18	Vargas	50	(null)
19	Whalen	10	(null)
20	Zlotkey	80	(null)
21	(null)	10	Administration
22	(null)	20	Marketing
23	(null)	50	Shipping
24	(null)	60	IT
25	(null)	80	Sales
26	(null)	90	Executive
27	(null)	110	Accounting
28	(null)	190	Contracting

MANIKANDAN S (maniproveit@gmail.com) has a non-transferable
license to use this Student Guide.