API Documentation Template

API: create_general_pos_order_api

- **Introduction**:

In this API, we create order, picking, then make picking done and the order paid.

All these points will be done in one api.

- **Endpoint Reference:**
  - **Inputs:**
    1. invoice_ref: Char
    2. return: Char ('0' or '1')
    3. mobile: Char
    4. voucher_code: Char
    5. products: list of dictionnaries
       5.1. product_ref: Char
       5.2. product_price: Float
       5.3. quantity: Integer
       5.4. lot: Char
    6. code: Char
    7. order_date: Datetime (day-month-year hours:minutes:secondes)
    8. location_id: Integer

  - **Outputs:**
    1. return True if succeed
    2. if not invoice_ref:
       2.1. {'error': 'Request missing parameters'}
    3. if not location and session:
       3.1. {'error': 'General POS session is not configured'}
    4. if the order is not created:
       4.1. {'error': 'Something went wrong with the order creation'}
    5. if the customer is not exist:
       5.1. {'error': 'Customer not found'}
    6. if the codes not defined:
       6.1. {'error': 'Code is not defined'}

- **Authentication**:
  - QA:
    - url: https://iqos-stage-backup-5748791.dev.odoo.com
    - database: iqos-stage-backup-5748791
    - username:
    - password:

- **Request & Response Examples:**
  - **Inputs:**

```
products = [{'product_ref': '373336', 'product_price': 10000, 'quantity': 1, 'lot': 'Test1138Test1'},{'product_ref': '1049695', 'product_price': 10000,
'quantity': 1, 'lot': 'Test1139Test1'}, {'product_ref': '1049695', 'product_price': 10000, 'quantity': 1, 'lot': 'Test1139Test2'}]

mobile = '+96170526746'
invoice_ref = 'johntest_06.02.2023_general_2'
order ={'invoice_ref': invoice_ref,
        #'return': '0',
        'mobile': mobile,
        'voucher_code': '',
        'products': products,
        'code':'269077',
        'order_date': '20-08-2021 14:30:00',
        'location_id':73,
        # 'bundle': bundle
}
order = json.dumps(order)
create_general_pos_order_api = models.execute_kw(db, uid, password,
                    'pos.order', 'create_general_pos_order_api',
                    {'': ''},
                    {'kw_1': order}
                    )
return create_general_pos_order_api
```

  - **Outputs:**

```
order True
```

kindly check the file create_general_pos_order_api_qa_12.py

- **Error Responses:**

1. if not invoice_ref:
   1.1. {'error': 'Request missing parameters'}
2. if not location and session:
   2.1. {'error': 'General POS session is not configured'}
3. if the order is not created:
   3.1. {'error': 'Something went wrong with the order creation'}
4. if the customer is not existed:
   5.1. {'error': 'Customer not found'}
5. if the codes not defined:
   5.1. {'error': 'Code is not defined'}

- **Changes and Deprecations:**

1. You can create multiple codentify

- **Conclusion**:

This is general API to create an order and picking and make them done

API: user_creation_general

- **Introduction**:

In this API, will create a contact in odoo

- **Endpoint Reference:**
  - **Inputs:**
    1. mobile: Char
    2. email: Char
    3. birthdate: Date (year-month-day)
    4. code: Char
    5. terms_conditions: Integer
    6. firstname: Char
    7. lastname: Char
    8. source_channel: Integer
    9. retailer_id: Integer
    10. email_verified: Boolean
    11. gender: Char
    12. address: Char
    13. opt_in: Integer
    14. country: Char
    15. city: Char
    16. is_duty_free: Boolean

  - **Outputs:**
    1. if succeed, return dictionnary of:
       1.1. starter_kit: Integer
       1.2. eligibility_list: list of dictionnaries
            1.2.1. name: Char
            1.2.2. internal_ref: Char
            1.2.3. eligibility: Boolean
       1.3. consumer: Integer
       1.4. stage: Char
    2. if the code is not defined, return {'error': 'Code is not defined'}

- **Authentication**:
  - QA:
    - url: https://iqos-stage-backup-5748791.dev.odoo.com
    - database: iqos-stage-backup-5748791
    - username:
    - password:

- **Request & Response Examples:**
  - **Inputs:**

```
url ="https://iqos-stage-backup-5748791.dev.odoo.com"
db = 'iqos-stage-backup-5748791'
username = "PRD81_stage"
password = "p\T@dt3HDH!"
common = xmlrpc.client.ServerProxy('{}/xmlrpc/2/common'.format(url))
uid = common.authenticate(db, username, password, {})
models = xmlrpc.client.ServerProxy('{}/xmlrpc/2/object'.format(url))
print('uid', uid)
user_data = {'mobile':' +961705267466600','email': 'qqquuqqqqq@gmail.com','birthdate':'2001-10-20', 'code': 'test'}
user_creation = models.execute_kw(db, uid, password,
                                  'res.partner', 'user_creation_general',
                                  {'': ''},
                                  {'kw_1': user_data}
                                  )
print ('user_creation',user_creation)
```

  - **Outputs:**

```
user_creation {'starter_kit': 1, 'eligibility_list': [{'name': 'IQOS HOLDER 3 DUO WHITE SINGLE LINE UP', 'internal_ref':
 '1310', 'eligibility': True}, {'name': 'IQOS HOLDER 3 DUO GREY SINGLE LINE UP', 'internal_ref': '0766', 'eligibility':
True}, {'name': 'IQOS HOLDER 3 DUO BLUE SINGLE LINE UP', 'internal_ref': '1312', 'eligibility': True}, {'name': 'IQOS HO
LDER 3 DUO GOLD SINGLE LINE UP', 'internal_ref': '1313', 'eligibility': True}, {'name': 'IQOS P CHGR 3 DUO WHITE SINGLE
LINE UP', 'internal_ref': '0765', 'eligibility': True}, {'name': 'IQOS P CHGR 3 DUO GREY SINGLE LINE UP', 'internal_ref'
: '0766', 'eligibility': True}, {'name': 'IQOS P CHGR 3 DUO BLUE SINGLE LINE UP', 'internal_ref': '0767', 'eligibility':
 True}, {'name': 'IQOS P CHGR 3 DUO GOLD SINGLE LINE UP', 'internal_ref': '0768', 'eligibility': True}, {'name': 'IQOS 3
 Duo Gold Mobility Kit ', 'internal_ref': '1136', 'eligibility': True}, {'name': 'IQOS 3 Duo White Mobility Kit ', 'inte
rnal_ref': '1137', 'eligibility': True}, {'name': 'IQOS 3 Duo Blue Mobility Kit ', 'internal_ref': '1138', 'eligibility'
: True}, {'name': 'IQOS 3 Duo Grey Mobility Kit ', 'internal_ref': '1139', 'eligibility': True}, {'name': 'IQOS 3 Duo Mo
onlight Silver Mobility Kit', 'internal_ref': '1616', 'eligibility': True}, {'name': 'Kit Lil Solid 2.0 Cosmic Blue', 'i
nternal_ref': '2148', 'eligibility': True}, {'name': 'Kit Lil Solid 2.0 Stone Grey', 'internal_ref': '2149', 'eligibilit
y': True}, {'name': 'IQOS Duo The WE Edition', 'internal_ref': '2160', 'eligibility': True}], 'consumer': 375703, 'stage
': 'New'}
```

kindly check the file user_creation_general_qa_12.py

- **Error Responses:**
  1. if the code is not defined, return {'error': 'Code is not defined'}

- **Changes and Deprecations:**

- **Conclusion**:

This API to create a contact

API: check_valid_codentify_general

- **Introduction**:

This API to check the codentify in the database

- **Endpoint Reference:**
  - **Inputs:**
    1. products: list of dictionaries:
       a. codentify: Char
       b. product_ref: Char

  - **Outputs:**
    1. Missing Configuration of location and point of sale, return {'error': 'General Location is not confirgured on ODOO'}
    2. return True if the quant exists
    3. return False if one of these variables not exist:(codentify, product_ref, location, product, lot/serial number) or no quant

- **Authentication**:
  - QA:
    - url: https://iqos-stage-backup-5748791.dev.odoo.com
    - database: iqos-stage-backup-5748791
    - username:
    - password:

- **Request & Response Examples:**
  - Inputs:

```
url = "http://localhost:8069"
db = "pmi_v2"
username = "admin"
password = "AdminOdoo!@#$%12345"
common = xmlrpc.client.ServerProxy('{}/xmlrpc/2/common'.format(url))
uid = common.authenticate(db, username, password, {})
models = xmlrpc.client.ServerProxy('{}/xmlrpc/2/object'.format(url))
print('uid', uid)
products = [{'codentify':'6F49YL9BEZ88','product_ref':'373336'}]
product_data = {'products': products}
```

- Outputs:

```
True
```

kindly check the file check_valid_codentify_general_qa_12.py

- **Error Responses:**

1. return False if one of these variables not exist:(codentify, product_ref, location, product, lot/serial number) or no quant
2. Missing Configuration of location and point of sale:
   2.1. {'error': 'General Location is not confirgured on ODOO'}

- **Changes and Deprecations:**

1. Check for multiple codentify

- **Conclusion**:

It is important to check if the codentify if available in the database