
# PLAYSTATION3 Refurbish Standard

<b>—</b>	ь.	D ::	D	D I	01 1 1 1	[ A	NA
					Checked by		Memo
0	06.Nov.06			Yukie Niwa		Jota Ogawa	
1	14.Nov.06	1.1		Yukie Niwa			ErroLogList/CEX-DEX difference
2	06.Mar.07	1.2		Yukie Niwa			
3	07.Jun.18	1.3		Yukie Niwa			


No.			D	escripti	on							
	Contents											
	Flow 1. Co 2. Eri 3. BE 4. Re 5. Ins 6. Co 7. Ins 8. Wii 9. Ga -F -F 10. D -A -C 11. S 12. C 13. Is A. Pa <app insta<="" th=""><th>over view onsole Reset for Log Drive test/exchange new serial label stall Setup Software onsole setup stall System Software reless Test format PS1 Format PS2 Format PS3 Format PS3 Format PS3 Format PS4 Format PS5 Format PS5 Format PS5 Format PS5 Format PS5 Format PS5 Format PS6 Format</th><th>re for re</th><th>epair</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></app>	over view onsole Reset for Log Drive test/exchange new serial label stall Setup Software onsole setup stall System Software reless Test format PS1 Format PS2 Format PS3 Format PS3 Format PS3 Format PS4 Format PS5 Format PS5 Format PS5 Format PS5 Format PS5 Format PS5 Format PS6 Format	re for re	epair								
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
<u> </u>	<u> </u>			4	1			<u> </u>	, , , , , , <u> </u>			Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2		<u></u>				<u></u>				
<u></u>	18.Jun.07			<u></u>				<u>/</u> 9\				DATE 2006/Dec/29




No.			D	escripti	on					Standard		Equipment
1	Console R 1-1. Settir 1) From		off									Console Reset Jig
	2) Conr	nect Console Reset	Jig to P	S3 with	n USB cable	Э						(supplied from SCEI CS)
	1-2. Reset 1) Turn	t main power switch o	on. Tou	ch Pow	er button o	on, and then touch E	ject but	   ton with 	iin 0.2sec			
				ر رن 1	[1]							
		[2	2] [	w	ithin 0.2sec							
	and t	ccessful, the Blue LE the system will auton ove Console Reset J	maticall			een LED will blink		If cons	ole reset f	ails repeat again fr	om 1–1 1	
$\triangle$	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard
<u> </u>				<u>\$</u>				<u>\$</u>				DATE 2006/Nov/6


No.			D	escripti	on					Standard		Equipment
2	Error Log 2-1. Settin 1) Conn	g ect PS3 to Jig PC	with Eth	nernet o	able	•		on mot	ner board o ng is as fol		be	<ul> <li>"Console Communication USB"</li> <li>"Error Log Software"</li> <li>(PC Jig)</li> <li>Barcode reader</li> </ul>
		et Error log ect "Console Comn	nunicati	on USB	" to PS3			USB mi	ust be used	d on right port as sh	nown	
		ute "Error Log softvectiveSuite"	Conclusions III Fine() Care() Vere()  WHO() Care() Vere()  Fine() Col. Sec.  [Efficiency Col. Sec. ]	non((Codin) Wedow'数 Hebity Srah	Time a OK & MG &	Date Time - 2006/16/06 16:0007  Jack Time - 2006/16/06 16:0007						
	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN		DATE	REVISION	SIGN	PLAYSTATION3
	00.14 07	D 10		<u>A</u>				Â				Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2		<u>\$</u>				<u>\$</u>				DATE 2006/Dec/29


No.			D	escripti	on					Standard		Equipment
No. 2	4) After 5) Testi	seeber 219 content Close TCP/IP port    Sc_error_log.txt - 大主株   ファイル(ア) 編集(ア) 書文(ア) 編集(ア) 書文(ア) 編集(ア) 書文(ア) 編集(ア) 書文(ア) 編集(ア) 書文(ア) 編集(ア) 編集(ア) 編集(ア) 編集(ア) 編集(ア) 編集(ア) 編集(ア) 編集(ア) 編集(ア) また。   EEC COUNT] shortdown_could be counting by shortdown_could be counting shortdown_could be considered by s	### Pane   Pane	el during sult is dul it will will will will will will will	60 sec" is lisplayed in be in stored	a separate window. d in sc_error_log.txt		"PASS	"	Standard		Equipment
No.	7) Remo	er off PS3.   Console Comm			". \( \hat{\Date} \)	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
$\Delta$				<b>A</b>				Δ				Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2		<u>\$</u>				<u> </u>				DATE 2006/Dec/29
<u>/3\</u>				<u></u>				<u></u>				



No.	Description	Standard Equipment
3	BD Drive test 3-1. Test Setup 1) Connect BD Adjust Jig to PC with USB cable Server	PS3 BD ADJUST Jig (SVC-H3A601SS J2504879A) Power supply unit for BD ADJUST Jig
	2) Connect BD Drive to BD Adjust Jig  To PC  BD Drive    Solution   BD Drive	
No.	DATE REVISION SIGN No. DATE REVISION SIGN	No. DATE REVISION SIGN PLAYSTATION3  Refurbish Standard
<u>↑</u> <u>↑</u> <u>↑</u>	<u>\$</u>	A DATE 2006/Nov/6







No.			De	scripti	on					Standard		Equipment
	Test	test ndicated, insert DVD t starts automatically ention  10] DVD-ROM(DVD ROM Test bisc Parallel HLXR-4019) Insert		LXR−4	019) test	dsc						J2504884A : HLXR-4019
		ne DISC.		=								
		ndicated, insert DVD t starts automatically		est dis	С							J2504903A : DVD+R-8.5G -TEST DISC
		ention  13 ] DVD+R(BD Drive Final Test Disc DVD+R(DL)) Insert the DISC.		F								
		ndicated, insert DVD t starts automatically		test d	isc							J2504904A : DVD-RW-4.7G -TEST DISC
	Tes	ion 3 J DVD-RW(BD Drive Final st Disc DVD-RW(SL)) Insert DISC.		ľ			)-					
	DATE	REVISION	SIGN		DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
				<u>4\</u> <u>\$</u> \				<u>^</u>				Refurbish Standard
<u> </u>				<u>5\</u>				<u> </u>				DATE 2006/Nov/6

No.			D	escript	on					Standard		Equipment	
3	Test Attention	dicated, insert BD-F starts automatically		L:BCJZ	-99801)							J2504919A : BCJZ-99802	<u>A</u>
			75/QL\									JOSEPH DE DE OSO	
	Test	dicated, insert BD-F starts automatically starts automatically blacks.  BD-RE(SL)(BD Drive Final Disc BD-RE(SL)) Insert the					ì					J2504905A : BD-RE-25G -TEST DISC	
	Test	dicated, insert BD-F starts automatically										J2504906A : BD-R-25G -TEST DISC	
	Test DISC	] BD-R(SL)(BD Drive Final Disc BD-R(SL) ) Insert the :.					<b>—</b>						
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3	
<u>^</u>	06.Mar.07	Day 1.0		<u> </u>			+	<u> </u>				Refurbish Standard	
<u>/2\</u>	Ub.iviar.U7	Rev I.Z		<u> </u>	<del>                                     </del>		+	<u>/8\</u>				DATE 2006/Dec/29	

No.			D	escripti	on					Standard		Equipment
3		t <b>est</b> ndicated, insert BD-F starts automatically		est disc								J2504907A : BD-R-50G -TEST DISC
	[37 Test DIS		J2504881A : BCJZ-99701									
	Test  Attentio  III D  BD, then  Adju	starts automatically  iiagnostics 2 : Please set the VERTICAL POSITION, and [5] BD-ROM(SL)(BD istment Disc 25GB Sheet Z 99701) Insert the DISC.	,	Top sid								
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
$\Lambda$			5.3.1	4			5.3.1	<u>A</u>	<u>.</u>		0.0.1	Refurbish Standard
<u> </u>				<u>\$</u>				<u> A</u>				DATE 2006/Nov/6
<u> </u>				<u>^</u>				<u></u>				DATE 2000/1909/0

No.			De	scripti	on					Standard		Equipment
3	Test	test ndicated, insert CD-l starts automatically CD-ROM(YDHS CKET Discman YDHS 6) the DISC.		DS-6)	test disc							J2504887A : YHDS-6
	Test [13] Tes	ndicated, insert DVD starts automatically starts automatically DVD-ROM(SL)(DVD ROM tt Disc Single HLXR-4018) ent the DISC.	/	L:HLXF	R-4018) te	st disc						J2504883A : HLXR-4018
	19) Afte											
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard
<u>A</u>				\$ \$ \$				<u>\$</u>				DATE 2006/Nov/6

No.			De	escription	on					Standard		Equipment
No. <b>4</b>	1) Remo	el renew Label renew ove old serial label o	n rear p	panel		abel in exact same	place.		abels are o	Standard  nly to be replaced maged or unreadal	ole	Equipment
No. <u>∕</u> \^ <u>∕</u> 2\^ <u>∕</u> 3\^	DATE 06.Mar.07	REVISION Rev 1.2		No. <u>A</u>	DATE	REVISION	SIGN	No. <u>A</u> <u>B</u> <u>D</u>	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard DATE 2006/Nov/6

No.			D	escripti	on					Standard		Equipment
5	Setup Soft 5-1. Install 1) Conn	Setup Software nect "Setup Softwar	e USB"					USB mi	ust be used	l on right port as sho	own	"Setup Software USB"
	2) Boot	PS3										
	3) Insta	llation starts automa	atically									
		tup Software installa shuts down automat		success	sful				Power indica	ator LED blinks "Gre wn	en and	Yellow"
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
<u>₩</u>	DATE	INE VIOLOIV		<u>110.</u>	DATE	I C VIOIOIV	July	<u>₩</u>	DATE	THE VIOLOTY	DIGIN	Refurbish Standard
<u>^</u> <u>^</u>				<u>/\$\</u>				<u> </u>				DATE 0000 /NL /C
<u> </u>				<u></u>				<u>/</u> 9\				DATE 2006/Nov/6

No.			De	escripti	on					Standard		Equipment
6	Console S B-1. Settii 1) Conr	ng nect PS3 to Jig PC v	with Eth	er cabl				<ul> <li>"Console Communication USB"</li> <li>"Error Log Software"</li> <li>(PC Jig)</li> <li>Barcode reader</li> </ul>				
	B-2. Set 1) Conr	tup nect " Console Comi	municat	ion USE	3 media″			USB mi	ust be used	d on right port as sh	nown	
	2) Exec	ute "Console Setup	on Jig	PC		_						
	Objective s.exe											
	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN		DATE	REVISION	SIGN	PLAYSTATION3
<u>^</u>				<u> </u>				<u>^</u>				Refurbish Standard
<u> </u>				<u> </u>				<u> </u>				DATE 2006/Dec/29

No.			D	escripti	on					Standard		Equipment
No. <b>6</b>	4) After 5) Cons	serial barcode on remaining the serial barcode on remaining th	ear pane	during	60 sec" is of the second secon	isplayed on screen  Product  27430053  Serial  OS version	3. ∕2∕.			Standard		Equipment
No. <u>↑</u> <u>↑</u>	7) Remo	· · · · · · · · · · · · · · · · · · ·	D label or enter	No. <u></u>	lastsaved 2006-10-271 Excel version 11.6508	no use 4	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard
<u> </u>				<u></u>				<u></u>				DATE 2006/Dec/29

No.			Description	on					Standard		Equipment
7	7-1. Ins	System Software for Retail System Software for System Software for a System Software for the system Software for the system Software for the system Software for the system Software for Retail System Software for System Software for Retail System Software for System System Software for System Software for System Sy	or Refurbish	h USB″ to	PS3		USB m	ust be used	d on right port as s	hown	"System Software for repair USB"
	2) B	oot PS3									
	3) In	stallation starts automa	atically								
		successful, unit autom wer indicator LED cha						l, LED blink e is no shu	s "green and Yellov tdown	w″	
No.	DATE	REVISION	SIGN No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
<u>No.</u>	DATE	IVE A1910IA	SIGN No.	DAIL	IVEATOIA	SIGN		DAIL	IVE A1910IA	SIGN	Refurbish Standard
<u> </u>			<u>\$</u>				<u> </u>				
<u> </u>			Æ.				<u>/</u> 9\				DATE 2006/Nov/6

No.			D	escripti	on					Standard		Equipment
8	Wireless T 4) Remo	est ove Controller, wher	n Power	<sup>r</sup> Indicat	or LED blir	nks						
	5) Testi	ng starts automatic	ally,									
	6) Chec	k the WLAN Indicat	or LED	lights o	n green.	<b>≜</b>						
		ccessful, Unit autom er Indicator LED cha							informatio	dicator LED blinks " on is shown on the r  10. max=20, resl=25 10. max=20, resl=30 10. max=20, resl=32 10. max=20, resl=32		d Yellow"
								[ANT :A] [ANT :B] [ANT :D] Last error -ERROR	OK	2 vsiF 20, 1 30, 1 3, rss. 5 FFF)-bt_rssi_main 1143		
							ineu : F	all				
	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
<u>A</u>				Â				À				Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2	+	<u>\$</u>				<u>\$</u>				DATE 2006/Dec/29
	1	<u>l</u>	1	<u> </u>	1			رحی	1			

Vo.			Descri	ription					Standard		Equipment
!	1) Conn	tation Game test nect PS3 and TV mo nect controller to lef			llowing figure)	<b>2</b>					AV MULTI OUT cable composit PlayStation test DISC *NTSC/J PTPX 97105 :J-2504-162-A *NTSC/UC PUPX 93016 : J-2504-163-A *PAL PEPX 94015 : J-2504-164-A
	2) Inser	t "PlayStation Test	t disc″,				PS3 is	powered o	n automatically.		
	Chec	PS logo, Cube grapsk drawing  PlayStations Ligansed by Sony Computer Entertainment America SCEL TO		card 0 card 1	Ignore o	card 0/car	d 1:ERROR				
I		"R1" button of cor k image and sound	ntroller, RGB								
	DATE	REVISION	SIGN No	o. DATE	REVISION	SIGN		DATE	REVISION	SIGN	PLAYSTATION3
	00.14 07	D 10									Refurbish Standard
<u>.</u>	00.Mar.0/	Rev 1.2	<u> </u>				<u>/8\</u> /9\				DATE 2006/Dec/29
7	06.Mar.07	Rev 1.2	<u>A</u> <u>5</u>				<u>^</u> <u>&amp;</u> <u>_</u>				

No.			D	escripti	on					Standard		Equipment
9	Game Tes 7) Pres Chec	t s "L1" button of cor ck image and sound	ntroller,	Color b	oar pattern i	is shown						
	8) Push Selec After											
	1) Conr	tation2 Game test nect PS3 and TV mo ct controller to the s		AV MULTI OUT cable S video "PS2"Flying Bulbs DISC *NTSC/J PTPX-19009: J-2504-893-A *NTSC/UC PUPX 19005: J-2504-891-A *PAL PEPX-19006: J-2504-892-A								
	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN		DATE	REVISION	SIGN	PLAYSTATION3
<u>^</u>	06 M 07	D 1.0		<u>^</u> \$				Â				Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2		<u> </u>				<u> </u>				DATE 2006/Dec/29

No.			De	scription	on					Standard		Equipment		
9	Game 2)	e Test Insert "PS2"Flying Bulbs	s DISC											
	3)	Select [Game]->[PlaySt	ation2 for	rmat D	sc] on XI	MB								
	4)	Press "PS" button of co	ontroller f	or pair	ng									
	5)	After PlayStation2 logo, Check image and sound												
		PlayStation2												
	6)	6) Press "X" button of controller Confirm "LAYER 1 ACCESS TEST OK" message is shown												
		PS2 FLYING BU												
		OK	200 1201											
No.	DATI	E REVISION		<u> </u>	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard		
<u> </u>				<u>\$</u> <b>6</b> \				<u>&amp;</u>				DATE 2006/Nov/6		

No.			D	escripti	on					Standard		Equipment			
9	Sele	et h "PS" button of corect "Quit Game" er confirmation, select  Quit Game Assign Slots Switch Analog Mode		,	enu is show int to quit the game Yes No										
	8) Ejec	t DISC													
	9) Pres	Press "PS" button of controller for pairing													
	1) Con Con	Station3 Game test nect PS3 and TV mo nect Optical output t nect controller to the		D-Terminal cable (Or Multi AV out to component cable AV system											
	2) Inse	rt "PLAYSTATION3													
	3) Sele	ect and play "PRODU	ICTION	DISC"	on XMB										
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No. ∕∕∖	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard			
<u> </u>	06.Mar.07	Rev 1.2		<u></u> \$				<u> </u>							
<u>/3\</u>				<u></u>				<u></u>				DATE 2006/Dec/29			

No.			De	escription	on					Standard		Equipment
7		t · PlayStation3 logo p k image and sound	oicture c	of "elepl	nant" is sho	own			Z-99024 F/SD is ii	nserted before it starts	s. 🖄	"PLAYSTATION3 Production Disc" ver 3.0 1
		PLAYSTATION 3		$\Rightarrow$								*NTSC/J BCJZ-99007 :J-2504-912-A  *NTSC/UC
		s "L1""R1""L2""R2 bar pattern is show		n of cor	ntroller at tl	he same time,				99012/99015 not do screen pattern		BCJZ-99011 :J-2504-927-A
	6) Press	s "R1" button of cor ssing hatch"->Mono ed pattern". Check in	ntroller, ochrome	gradati	on"->"Mon	olor bar pattern" -> nochrome vertically		test.	ase eject	disc after 4) , then		*AU
				<b>→</b>								*RU
		s "L1""R1""START n to the "XMB"		CT″ bu <u>^</u>	tton of con	troller at the same	time,					
	8) Change display setting to "HDMI" [Setting]->[DisplaySetteing]->[VideoOutput]->[HDMI]  ⚠											
	DATE	REVISION	SIGN	No.		REVISION	SIGN	l .	DATE	REVISION	SIGN	PLAYSTATION3
$\triangle$	20.Nov.06 06.Mar.07			<u>^</u> \$				<u>^</u>				Repair Standard
<u>\$</u>	18.Jun.07			<u> </u>				<u> </u>				DATE 2007/Jun/18

No.			D	escripti	on					Standard		Equipment
10		S test lect PS3 and TV mo		n "HDM	I" input							HDMI cable Region Check Disc BCJV98001:J-2504-908-A
	3) Play	"Region Check Disc	on XI	ИΒ								
		egion is displayed k Image and sound										
	5) Eject	DISC										
	10-2. CPR 1) Inser 2) Play		CPRM test DISC  Please make the disk which contents are protected with CPRM in the repair center.									
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
<u> </u>	06.Mar.07	Rev 1.2		<u> </u>				<u> </u>				Repair Standard  DATE 2006/Dec/29

No.			D	escripti	on					Standard		Equipment
10	<b>DRM</b> 3)	<b>Test</b> Check drawing and sound	d at leas	st for 3s	secs							
		CHAPTER 1 TCR 00:00:10:	20									
	3)	Eject DISC										
		SACD test Insert SACD test disc										SACD test DISC
	2)	Play "Multi+2ch Test Tor		SATD-S5 :J-2504-898-A								
	3)	Change sound setting to	"HDMI	"								
		(政定)の(サウンド開定)で音声出力を光デジタル以外 ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・	に設定してくださ									
	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard
<u> </u>	-			<u>/4\</u> <u>/</u> 5\				<u>//\</u>			1	
<u>^</u> <u>^</u> <u>^</u>				<u> </u>				<u>A</u>				DATE 2006/Nov/6

No.			D	escripti	on					Standard		Equipment
10	DRM Test											
	e ca	ディスプレイ設定 : ①		=		** ######	まま テレビまたはAVアンプ間の番子 ドデジタル ボースカボテ または ・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・					
	"Sup	ot "Multi+2ch Test Ter Audio CD" .	Ź	t Ton	XMB and c							
		"Multi+2ch Test Tor	<b>3</b>	″ on XM	MB							
	6) Chec	ck sound										
	7) Eject	t Disc										
	8) Powe	er off PS3										
No.	DATE	REVISION	SIGN		DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
Â				<u> </u>				$\triangle$				Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2		<u>\$</u>				<u></u>				DATE 2006/Dec/29
<u>/3\</u>				<u> </u>				<u>\\ A</u> \	1			

No.			D	escripti	on					Standard	Equipment			
11	1) Set M slots	age Test for refurbis Memory Stick Duo a	nd Mini	SD med		•		Jig HDI => Cus		used D should only sted by Customer.	Storage Test For Refurbishment Write/Read/Verify Format BCJZ-99701:J-2504-881-A *Memory Stick duo、MiniSD(60G model onl			
	2) Inser	t BCJZ-99701 Test	Disc											
	3) Testi	ng automatically sta	ırts					SD/miniSD and Memory Stick access indicator LED lights Orange (60G model only)						
		cessful disc is ejec oximate length of te				shuts down.		If fails, Power indicator LED blinks on "Red and Yellow" and disc is ejected						
		ove "Storage Test fo ove MSDuo, MiniSD	or refur	bishmer	nt USB"			Detail information is shown on monitor						
									S3 HDD Inspeteration of the second of the se	setion For CS (60G) er 0.1	nfo			
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No. ∕∕∖	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard		
<u>A</u>				<u>/\$\</u>				<u> </u>						
<u> </u>				<u></u>				<u>/</u> 9\				DATE 2006/Nov/6		


No.			D	escripti	on					Standard		Equipment
12	Console Fi 12-1. Setti 1) Conn		with Eth	nernet c	able		DEI ver	Please	use the cal	ble bundled with the	<ul> <li>"Console Communication USB"</li> <li>"Error Log Software"</li> <li>(PC Jig)</li> <li>Barcode reader</li> </ul>	
	2) Set M	MS/SD/CF(*)						*60G m	odel only			
	12-2. Console Finalize  1) Connect "Console Communication USB media"								ust be used	d on right port as sh	own	
	DATE	REVISION	SIGN		DATE	REVISION	SIGN		DATE	REVISION	SIGN	PLAYSTATION3
	0014 07	D 10		<u>A</u>				Â				Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2	<u> </u>	<u>\$</u>				<u>&amp;</u>				DATE 2006/Dec/29
<u>/3\</u>				<u>^</u>				<u></u>				

No.			Des	cription						Standard		Equipment
12	Console Fi 2) Exection Objectives s.exe	ute "Console Finaliz										
	3) Scan serial barcode on rear panel  A) After message "weit connection during 60 and" in displayed boot PS3											
	4) After message "wait connection during 60 sec" is displayed, boot PS3.   "Console Finalize" procedure starts automatically and result is displayed on screen											
No.		REVISION Rev 1.2	SIGN A	7	ATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard DATE 2006/Dec/29


No.			D	escripti	on					Standard		Equipment
13	a)Co as s b)Bo	cedure onfirm the insulation infirm that the leaka shown in the service	age curre e manual rength v	ent is be oltage t	low a star	owing procedures sho ndard value (0.5mA). e Ground resistance	uld be	done.				
	,, ,,								alue of testi ure test	ng Equipment]		•Dielectric strength voltage test unit
		utral" and "LIVE" t						R	Region	UC2/J1/TW1	Others	
									oltage	1300V	1600V	
			kV	MS	2			breakir	ng current	10mA	10mA	
			$\overline{}$	OUT P	л		Test ti	me	1sec	3sec		
										C500V or more or more		
	Neutral LIVE								used for th	USB ports iis test		
		ļ								noke or abnorm sole.	al sounds	
	oned	on thass the	pressure	test a	iu irisulati	On resistance is TUIVIS	corm	ore)				
	DATE	REVISION	SIGN		DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
Â				<u> </u>				À				Refurbish Standard
<u> </u>	06.Mar.07	Rev 1.2		<u>\$</u>				<u>&amp;</u>				DATE 2006/Dec/29
<u>/3\</u>				<u>^</u>				<u></u>				

No.			D	escripti	on					Standard		Equipment
13	5) Remoi 13-3. Grou 1) Conn - Col USE - Col GN  2) Push 3) Check 4) Remoi 5) Remoi 5	ove USB cable.  ove AC power cable.  and resistance Test nect PS3 to ground r nnect "GND" of ground B (Shield of USB) pounder "OUTPUT" of ID of AC Inlet of PS  output  which of ground resistance Test which was a switch of ground resistance and the set of the set o	resistance of Re	ce testi istance S3.(*) d resista	g equipmen must be 90	g equipment to  GNE  t ,and start test.  m Ohms or less.)		Test cu Test tir Expecte Wear gl (*)Any can be	arrent: 25A me: 3sec ed value of oves. of the four used for th	ing equipment] resistance:90mOhi USB ports nis test		ground resistance testing equipment
No. ∕\rightarrow	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No. ∕∕∖	DATE	REVISION	SIGN	PLAYSTATION3
	06 May 07	Pov. 1.2		<u>∕4\</u> _ <u>\$</u> \								Refurbish Standard
	06.Mar.07	Rev 1.2	1					<u>&amp;</u>			1	DATE 2006/Dec/29
<u> </u>				<u>^</u>				<u></u>				


No.			D	escripti	on					Notes		Jig
A	Setting  1) Conn	ect the "RS-232C"	arcode r	reader to "J	S	CEI	baud ra bit size parity b Stop bin line fee	it: even t: 1bit d code: CR	S		"RS-232C"type barcode reader	
	1-4.Parts I 1) Exec	Reuse ute "Parts Reuse "p	orogram	<b>1.</b>								
		Reuse_s tup	Parts_Reuse_set pject   Parts_Reuse imber   26 c	e_setup oontent Please	read security code	ZML info author masa created: 2000-07-241 lastsaved: 11,500 lastsa						
	Please print "security barcode" which is provided by SCEI CS.											
	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN		DATE	REVISION	SIGN	PLAYSTATION3
<u>^</u>				<u> </u>				<u>^</u>				Refurbish Standard
<u> </u>				<u> 6</u>				<u>/\$\</u>				DATE 2007/Jun/18




No.	Descriptio	n	Standard	Equipment
Арр	Install driver for BD Drive Jig  1. Setting  1) Connect BD Adjust Jig to PC with USB  ooo o	cable		PS3 BD ADJUST Jig (SVC-H3A601SS J2504879A) Power supply unit for BD ADJUST Jig
		Folder"  [Next]		
	Turn John Prick 1997   Cond Prick 1997   E Man (1997 )	xt]		
No.  A  A  A	<u>A</u>		<u>^</u>	SIGN PLAYSTATION3 Refurbish Standard
<u></u>	<u> </u>		<u> </u>	DATE 2006/Nov/6



No.			D	escripti	on					Standard		Equipment
App	ERROR_L	OG/ConsoleSetup/(	Console	Finalize	Windows a	pplication => Installati	on					
	1) Extr	act encrypted zip file	е					All of p	rograms ca	an installed using s	ame proce	dure
	ERROR LO 061030 zip		mp¥PS3 ache iveSuites	ンオルダ 名前 A ERRC	D NJJE D NJJE D N NJ	サイズ 複雑 ファイル フォルダ 6,060 KB ZIP ファイル						
	PRUADO CH	使表示(少 ち列に入り(金) ツール() ヘルプ(金) ・ 大 ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・ ・	1.00 1.77 100 2.09	が大 権機 8 KB アヴリケーション 9 KB アヴリケーション 0 KB アヴリケーション 1 KB 構成設定 7 KB Windows インス	1840 2 1840 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	•□⊠ tup Wizard						
			WARNING: T Unauthorized	his computer progr duplication or distri	am is protected b	all ObjectiveSuites on your computer.  Xt]  extent possible undt  XBack Next >						
	D.4.T-	Inc. govo:	lores				01011		In	Inc. gove :	lores	
No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No. ∕∕\	DATE	REVISION	SIGN	PLAYSTATION3 Refurbish Standard
<u>^</u>				<u>\$</u>				<u>\$</u>				DATE 2006/Nov/6





No.			D	escripti	on				Standard			
Арр	ERROR_I	_OG/ConsoleSetup/	Console	inalize	Windows a	pplication => Serv	er authen	tication				
7.44	5) "au   77811/5   7811/5   6) Ser	uth_**.txt" is created  ル(P) 編集(P) 表示(W) お気に入り(A)  戻る・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・	I in instal  y-y-y-y-y-y-y-y-y-y-y-y-y-y-y-y-y-y-y	lation s × 均 証	ub folder "  ・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・	temp"						
	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	No.	DATE	REVISION	SIGN	PLAYSTATION3
<u>^</u>				<u> </u>				Δ				Refurbish Standard
<u> </u>				<u>\$</u>				<u> </u>				DATE 2006/Nov/6
<u> </u>				<u></u>				<u> 1</u>				DATE 2000/1909/0

Error Log code 2007/1/29 SCE CONFIDENTIAL

