

FIN3210 Week 3 Assignment

Ma Kexuan 120090651

October 5, 2023

```
[1]: import pandas as pd
import numpy as np
from linearmodels import PanelOLS
import matplotlib.pyplot as plt
from matplotlib.pyplot import MultipleLocator
```

```
[2]: df = pd.read_excel('FIN3210 Week 3 Stock returns.xlsx', sheet_name='data')
```

```
[3]: data = df.drop(['stkname', 'conme'], axis=1).copy()
data['month'] = pd.to_datetime(data['month'], format='%Y-%m').dt.to_period('M')
    ↪ # Transfer to datetime type with month based
data['year_quarter'] = data['month'].dt.strftime('%Y-Q%q') # Transfer to format
    ↪ year-quarter
data.head()
```

```
[3]:
```

	stkcd	month	retrf	mktrf	smb	hml	umd	size	\
0	9	2013-07	9.0756	1.8833	5.1896	-0.1922	6.1829	23.10871	
1	9	2013-08	-5.1363	4.5833	5.9407	0.0976	-5.5041	23.10871	
2	9	2013-09	3.5840	3.3833	0.5848	2.8554	8.8693	23.10871	
3	9	2014-01	-1.0932	-3.6167	5.6921	1.1126	8.9357	23.28204	
4	9	2014-02	19.0704	0.9833	3.8899	0.6902	-1.8764	23.28204	

	bm	return12	roa	lev	ppe	intang	numanalyst	\
0	0.438860	13.37412	0.007949	0.430605	0.086185	0.031575	0	
1	0.438860	13.37412	0.007949	0.430605	0.086185	0.031575	0	
2	0.438860	13.37412	0.007949	0.430605	0.086185	0.031575	0	
3	0.394303	46.59159	0.025973	0.432246	0.098660	0.029798	0	
4	0.394303	46.59159	0.025973	0.432246	0.098660	0.029798	0	


	instown	mv	year_quarter
0	6.4646	11874173952	2013-Q3
1	6.4646	11874173952	2013-Q3
2	6.4646	11874173952	2013-Q3
3	5.6741	11731143680	2014-Q1
4	5.6741	11731143680	2014-Q1

0.1 1) Using the data set of stock returns, sort stocks into quintiles by size every quarter, hold stocks over the quarter, and calculate monthly portfolio returns

```
[4]: # Divide into 5 groups
data['size_label'] = data.groupby('year_quarter')['size'].transform(lambda x:
    ↪pd.qcut(x, 5, labels=[1,2,3,4,5]))
# Use the size of last month to predict next month
data['last_size_label'] = data.groupby(['stkcd', 'year_quarter'])['size_label'].
    ↪shift(1)
# fill in NAN value
data.loc[data['last_size_label'].isnull(), 'last_size_label'] = data.
    ↪loc[data['last_size_label'].isnull(), 'size_label']
# Equal weighted result of portfolio return
port_res = data.groupby(['month', 'last_size_label'])['retrf'].mean().
    ↪reset_index()
port_res.head(10)
```

```
[4]:      month last_size_label      retrf
0  2012-04                1  2.688905
1  2012-04                2  5.861874
2  2012-04                3  7.099519
3  2012-04                4  3.920090
4  2012-04                5  2.800216
5  2012-05                1  1.778694
6  2012-05                2  2.056422
7  2012-05                3  3.618288
8  2012-05                4  3.030542
9  2012-05                5  4.962478
```

```
[5]: port_res['month'] = port_res['month'].astype(str)
plt.figure(figsize = (10,5))
for i in [1,2,3,4,5]:
    plt.plot(port_res.loc[port_res['last_size_label']==i, 'month'],
        port_res.loc[port_res['last_size_label']==i, 'retrf'],
        label = 'Portfolio{}'.format(i))
plt.xlabel('Year-Month')
plt.ylabel('Return')
plt.title('Return of different portfolios')
plt.xticks(rotation = 45)
x_major_locator=MultipleLocator(10)
ax = plt.gca()
ax.xaxis.set_major_locator(x_major_locator)
plt.legend()
plt.show()
```




0.2 2) Using the data set of stock returns, sort stocks into quintiles by institutional ownership every quarter, hold stocks over the quarter, and calculate monthly portfolio returns

```
[6]: data['inst_label'] = data.groupby('year_quarter')['instown'].transform(lambda x:
    ↪ pd.qcut(x, 5, labels=[1,2,3,4,5]))
data['last_inst_label'] = data.groupby(['stkcd', 'year_quarter'])['inst_label'].
    ↪ shift(1)
data.loc[data['last_inst_label'].isnull(), 'last_inst_label'] = data.
    ↪ loc[data['last_inst_label'].isnull(), 'inst_label']
port_res = data.groupby(['month', 'last_inst_label'])['retrf'].mean().
    ↪ reset_index()
port_res.head(10)
```

```
[6]:   month last_inst_label   retrf
0  2012-04                1  5.411529
1  2012-04                2  7.414722
2  2012-04                3  5.176190
3  2012-04                4  2.049471
4  2012-04                5  2.287461
5  2012-05                1  2.237273
6  2012-05                2  0.351318
7  2012-05                3  3.046009
8  2012-05                4  5.482549
9  2012-05                5  4.313619
```

```
[7]: port_res['month'] = port_res['month'].astype(str)
plt.figure(figsize = (10,5))
for i in [1,2,3,4,5]:
    plt.plot(port_res.loc[port_res['last_inst_label']==i, 'month'],
             port_res.loc[port_res['last_inst_label']==i, 'retrf'],
             label = 'Portfolio{}'.format(i))
plt.xlabel('Year-Month')
plt.ylabel('Return')
plt.title('Return of different portfolios')
plt.xticks(rotation = 45)
x_major_locator=MultipleLocator(10)
ax = plt.gca()
ax.xaxis.set_major_locator(x_major_locator)
plt.legend()
plt.show()
```



0.3 3) Using the data set of stock returns, perform panel regression, and regress stock returns on firm characteristics such as size, book-to-market ratio, return12, roa, leverage, ppe, intang, number of analysts, institutional ownership, controlling for or not for firm and year-month fixed effects. Cluster standard errors by firm and year-month (double clustering)

```
[8]: panel_data = data[['stkcd', 'month', 'retrf', 'size', 'bm', 'return12',
                        'roa', 'lev', 'ppe', 'intang', 'numanalyst', 'instown']].copy()
panel_data[['size', 'bm', 'return12', 'roa', 'lev', 'ppe', 'intang', 'numanalyst', 'instown']]_
    => panel_data.groupby('stkcd')[['size',
                                    'bm', 'return12', 'roa', 'lev', 'ppe', 'intang', 'numanalyst', 'instown']].
    >shift(1)
panel_data.dropna(inplace = True)
panel_data
```

```
[8]:
```

	stkcd	month	retrf	size	bm	return12	roa \
1	9	2013-08	-5.1363	23.10871	0.438860	13.374120	0.007949
2	9	2013-09	3.5840	23.10871	0.438860	13.374120	0.007949
3	9	2014-01	-1.0932	23.10871	0.438860	13.374120	0.007949
4	9	2014-02	19.0704	23.28204	0.394303	46.591590	0.025973
5	9	2014-03	-5.9711	23.28204	0.394303	46.591590	0.025973
...
87427	900956	2019-08	-5.3373	19.54512	5.124264	-4.492293	0.005443
87428	900956	2019-09	11.0761	19.54512	5.124264	-4.492293	0.005443
87429	900956	2019-10	12.3759	19.54512	5.124264	-4.492293	0.005443
87430	900956	2019-11	0.5954	19.41050	5.950344	-14.776860	0.010888
87431	900956	2019-12	7.2701	19.41050	5.950344	-14.776860	0.010888
...
1		lev	ppe	intang	numanalyst	instown	
2		0.430605	0.086185	0.031575	0.0	6.4646	
3		0.430605	0.086185	0.031575	0.0	6.4646	
4		0.430605	0.086185	0.031575	0.0	6.4646	
5		0.432246	0.098660	0.029798	0.0	5.6741	
...		0.432246	0.098660	0.029798	0.0	5.6741	
...
87427		0.598459	0.267594	0.025879	0.0	0.0000	
87428		0.598459	0.267594	0.025879	0.0	0.0000	
87429		0.598459	0.267594	0.025879	0.0	0.0000	
87430		0.425125	0.269671	0.025286	0.0	0.0000	
87431		0.425125	0.269671	0.025286	0.0	0.0000	

[85397 rows x 12 columns]

```
[9]: panel_data['month'] = pd.to_numeric(panel_data['month'].dt.strftime('%Y%m'))
panel_data.set_index(['stkcd', 'month'], inplace=True) # Control for firm and
    >year-month fixed effects
model = PanelOLS(panel_data['retrf'], panel_data[['size', 'bm', 'return12', 'roa',
```

```

        'lev','ppe','intang','numanalyst','instown']], entity_effects=True,
        time_effects=True)
res = model.fit(cov_type='clustered', cluster_entity=True, cluster_time=True) #
        Cluster standard errors
res.summary

```

```

[9]: <class 'linearmodels.compat.statsmodels.Summary'>
      ""

```

PanelOLS Estimation Summary

```

=====
Dep. Variable:          retrf      R-squared:              0.0133
Estimator:              PanelOLS   R-squared (Between):  -1228.5
No. Observations:       85397      R-squared (Within):   0.0171
Date:                   Thu, Oct 05 2023  R-squared (Overall): -45.250
Time:                   15:22:52      Log-likelihood        -3.2e+05
Cov. Estimator:         Clustered

                               F-statistic:          124.83
Entities:                2035      P-value              0.0000
Avg Obs:                  41.964    Distribution:         F(9,83262)
Min Obs:                   2.0000
Max Obs:                   92.000    F-statistic (robust): 14.436
                               P-value              0.0000
Time periods:             92      Distribution:         F(9,83262)
Avg Obs:                   928.23
Min Obs:                   377.00
Max Obs:                   1825.0

```

Parameter Estimates

```

=====
      Parameter  Std. Err.    T-stat    P-value    Lower CI    Upper CI
-----
size           -4.0216     0.4473   -8.9917    0.0000    -4.8983    -3.1450
bm              0.2309     0.8461    0.2729    0.7849    -1.4274     1.8893
return12       -0.0023     0.0030   -0.7629    0.4455    -0.0081     0.0036
roa             4.6914     3.1983    1.4668    0.1424    -1.5772    10.960
lev            -1.3608     0.6284   -2.1655    0.0304    -2.5925    -0.1291
ppe            -0.0489     1.0345   -0.0473    0.9623    -2.0765     1.9788
intang         3.0578     2.5080    1.2192    0.2228    -1.8579     7.9736
numanalyst     0.0113     0.0163    0.6901    0.4901    -0.0207     0.0432
instown        0.0086     0.0160    0.5349    0.5927    -0.0228     0.0399
=====

```

```

F-test for Poolability: 28.922
P-value: 0.0000
Distribution: F(2125,83262)

```

```

Included effects: Entity, Time

```

```
"""
```

```
[10]: model = PanelOLS(panel_data['retrf'], panel_data[['size', 'bm', 'return12',  
            'roa', 'lev', 'ppe', 'intang', 'numanalyst', 'instown']],  
            entity_effects=False, time_effects=False) # Not control for these two  
            ↪ effects  
            # Cluster standard errors  
res = model.fit(cov_type='clustered', cluster_entity=True, cluster_time=True)  
res.summary
```

```
[10]: <class 'linearmodels.compat.statsmodels.Summary'>
```

```
"""
```

PanelOLS Estimation Summary

```
=====
```

Dep. Variable:	retrf	R-squared:	0.0062
Estimator:	PanelOLS	R-squared (Between):	0.0578
No. Observations:	85397	R-squared (Within):	0.0027
Date:	Thu, Oct 05 2023	R-squared (Overall):	0.0062
Time:	15:22:53	Log-likelihood	-3.438e+05
Cov. Estimator:	Clustered		
		F-statistic:	59.151
Entities:	2035	P-value	0.0000
Avg Obs:	41.964	Distribution:	F(9,85388)
Min Obs:	2.0000		
Max Obs:	92.000	F-statistic (robust):	2.1815
		P-value	0.0203
Time periods:	92	Distribution:	F(9,85388)
Avg Obs:	928.23		
Min Obs:	377.00		
Max Obs:	1825.0		

Parameter Estimates

```
=====
```

	Parameter	Std. Err.	T-stat	P-value	Lower CI	Upper CI
size	-0.0107	0.0508	-0.2100	0.8337	-0.1102	0.0888
bm	1.4906	0.8773	1.6991	0.0893	-0.2288	3.2101
return12	0.0036	0.0141	0.2555	0.7983	-0.0241	0.0313
roa	5.3103	7.6867	0.6908	0.4897	-9.7556	20.376
lev	0.5546	1.8904	0.2934	0.7692	-3.1504	4.2597
ppe	0.1788	1.2655	0.1413	0.8877	-2.3016	2.6592
intang	0.3477	1.2780	0.2721	0.7855	-2.1571	2.8526
numanalyst	-0.0084	0.0157	-0.5371	0.5912	-0.0392	0.0224
instown	0.0436	0.0165	2.6450	0.0082	0.0113	0.0759

```
=====
```

"""

0.4 4) Using the data set of Online sales, aggregate monthly online sales over quarters, download reported quarterly total sales from CSMAR, and plot figures including both online sales and reported quarterly sales.

```
[11]: sales = pd.read_excel('FIN3210 Week 3 Online sales.xlsx', sheet_name=' ')
# Change the columns into rows in the dataframe
sales = sales.melt(id_vars=[' '], var_name='Brand', value_name='online_sales')
sales.rename({' ': 'month'}, axis=1, inplace=True)
sales
```

```
[11]:
```

	month	Brand	online_sales
0	2016-01-01	603899.SH	3888967.80
1	2016-02-01	603899.SH	3983190.45
2	2016-03-01	603899.SH	6395686.99
3	2016-04-01	603899.SH	4968614.43
4	2016-05-01	603899.SH	6566980.86
..
545	2020-03-01	002956.SZ	8621983.82
546	2020-04-01	002956.SZ	8476046.53
547	2020-05-01	002956.SZ	8540964.70
548	2020-06-01	002956.SZ	11706599.62
549	2020-07-01	002956.SZ	6767988.81

[550 rows x 3 columns]

```
[12]: sales['month'] = pd.to_datetime(sales['month'], format='%Y-%m').dt.
      ↪to_period('M')
sales['year_quarter'] = sales['month'].dt.strftime('%Y-Q%q')
sales['stkcd'] = sales['Brand'].str.extract('(\d+)').astype('int') # Extract
      ↪stock id
sales
```

```
[12]:
```

	month	Brand	online_sales	year_quarter	stkcd
0	2016-01	603899.SH	3888967.80	2016-Q1	603899
1	2016-02	603899.SH	3983190.45	2016-Q1	603899
2	2016-03	603899.SH	6395686.99	2016-Q1	603899
3	2016-04	603899.SH	4968614.43	2016-Q2	603899
4	2016-05	603899.SH	6566980.86	2016-Q2	603899
..
545	2020-03	002956.SZ	8621983.82	2020-Q1	2956
546	2020-04	002956.SZ	8476046.53	2020-Q2	2956
547	2020-05	002956.SZ	8540964.70	2020-Q2	2956
548	2020-06	002956.SZ	11706599.62	2020-Q2	2956
549	2020-07	002956.SZ	6767988.81	2020-Q3	2956

[550 rows x 5 columns]

```
[13]: sales = sales.groupby(['stkcd', 'year_quarter'])['online_sales'].sum().  
      ↪reset_index() # Aggregate to get the sum of sales in each quarter  
      sales
```

```
[13]:
```

	stkcd	year_quarter	online_sales
0	2511	2016-Q1	3.384803e+07
1	2511	2016-Q2	4.424781e+07
2	2511	2016-Q3	3.921140e+07
3	2511	2016-Q4	3.867866e+07
4	2511	2017-Q1	5.079266e+07
..
185	603899	2019-Q3	8.817731e+07
186	603899	2019-Q4	1.169147e+08
187	603899	2020-Q1	9.600548e+07
188	603899	2020-Q2	1.338863e+08
189	603899	2020-Q3	4.121578e+07

[190 rows x 3 columns]

```
[14]: report_sales = pd.read_csv('FS_Comins.csv')  
report_sales['Accper'] = pd.to_datetime(report_sales['Accper'],  
      ↪format='%Y-%m-%d').dt.to_period('M')  
report_sales['Accper'] = report_sales['Accper'].dt.strftime('%Y-Q%q')  
report_sales = report_sales.loc[report_sales['Typrep']=='A',:] # Count for all  
      ↪of the relevant companies  
report_sales.drop(['B001101000', 'Typrep'], axis=1, inplace=True)  
report_sales.reset_index(drop=True, inplace=True)  
report_sales.rename({'B001100000': 'report_sales_cum'}, axis=1, inplace=True)  
report_sales['year'] = pd.to_datetime(report_sales['Accper']).dt.year  
# Remove the first line, because it's the data of last year  
report_sales = report_sales.groupby(['Stkcd', 'year']).apply(lambda x: x.iloc[1:  
      ↪])  
report_sales.reset_index(drop=True, inplace=True)  
report_sales['report_sales_sft'] = report_sales.  
      ↪groupby(['Stkcd', 'year'])['report_sales_cum'].shift(1)  
# Calculate the quartly sales since the original data is cumulative  
report_sales['report_sales'] = report_sales['report_sales_cum'] -  
      ↪report_sales['report_sales_sft']  
# Fill in the NAN values of the first line using the original sales  
report_sales.loc[report_sales['report_sales'].isnull(),  
      'report_sales'] = report_sales.loc[report_sales['report_sales'].isnull(),  
      ↪'report_sales_cum']  
report_sales.drop(['report_sales_sft'], axis = 1, inplace = True)  
report_sales.reset_index(drop=True, inplace=True)  
report_sales
```

```
[14]:      Stkcd ShortName  Accper  report_sales_cum  year  report_sales
0      2511          2016-Q1    8.540908e+08  2016  8.540908e+08
1      2511          2016-Q2    1.771553e+09  2016  9.174619e+08
2      2511          2016-Q3    2.740959e+09  2016  9.694064e+08
3      2511          2016-Q4    3.809349e+09  2016  1.068390e+09
4      2511          2017-Q1    1.032247e+09  2017  1.032247e+09
..      ...          ...          ...          ...          ...
120    603899          2019-Q2    4.838623e+09  2019  2.483009e+09
121    603899          2019-Q3    7.947344e+09  2019  3.108721e+09
122    603899          2019-Q4    1.114110e+10  2019  3.193757e+09
123    603899          2020-Q1    2.083587e+09  2020  2.083587e+09
124    603899          2020-Q2    4.761424e+09  2020  2.677836e+09
```

[125 rows x 6 columns]

```
[15]: online_report = pd.merge(sales, report_sales, how='left',
    ↪left_on=['stkcd', 'year_quarter'], right_on=['Stkcd', 'Accper'])
online_report = online_report.loc[online_report['year_quarter'] != '2020-Q3']
online_report
```

```
[15]:      stkcd year_quarter  online_sales  Stkcd ShortName  Accper \
0      2511      2016-Q1  3.384803e+07  2511.0          2016-Q1
1      2511      2016-Q2  4.424781e+07  2511.0          2016-Q2
2      2511      2016-Q3  3.921140e+07  2511.0          2016-Q3
3      2511      2016-Q4  3.867866e+07  2511.0          2016-Q4
4      2511      2017-Q1  5.079266e+07  2511.0          2017-Q1
..      ...          ...          ...          ...          ...
184    603899      2019-Q2  8.132643e+07  603899.0          2019-Q2
185    603899      2019-Q3  8.817731e+07  603899.0          2019-Q3
186    603899      2019-Q4  1.169147e+08  603899.0          2019-Q4
187    603899      2020-Q1  9.600548e+07  603899.0          2020-Q1
188    603899      2020-Q2  1.338863e+08  603899.0          2020-Q2
```

```
      report_sales_cum  year  report_sales
0      8.540908e+08  2016.0  8.540908e+08
1      1.771553e+09  2016.0  9.174619e+08
2      2.740959e+09  2016.0  9.694064e+08
3      3.809349e+09  2016.0  1.068390e+09
4      1.032247e+09  2017.0  1.032247e+09
..      ...          ...          ...
184      4.838623e+09  2019.0  2.483009e+09
185      7.947344e+09  2019.0  3.108721e+09
186      1.114110e+10  2019.0  3.193757e+09
187      2.083587e+09  2020.0  2.083587e+09
188      4.761424e+09  2020.0  2.677836e+09
```

[180 rows x 9 columns]

```
[16]: stkcd_list = online_report['stkcd'].unique().astype('str').tolist()
for i in range(len(stkcd_list)):
    if len(stkcd_list[i])==4:
        stkcd_list[i] = '00'+stkcd_list[i]
stkcd_list
```

```
[16]: ['002511',
       '002557',
       '002695',
       '002956',
       '002959',
       '300783',
       '600872',
       '603719',
       '603866',
       '603899']
```

```
[17]: plt.figure(figsize=(20,16))
plt.subplot(2,2,1)
for stkcd in stkcd_list:
    int_stk = int(stkcd)
    plt.plot(online_report.loc[online_report['stkcd']==int_stk, 'year_quarter'],
             online_report.loc[online_report['stkcd']==int_stk,
             ↪'online_sales'], label = '{}'.format(stkcd))
plt.title('Online sales')
plt.xticks(rotation=45)
plt.xlabel('Year-Quarter')
plt.ylabel('Sales')
plt.legend()

plt.subplot(2,2,2)
for stkcd in stkcd_list:
    int_stk = int(stkcd)
    plt.plot(online_report.loc[online_report['stkcd']==int_stk, 'year_quarter'],
             online_report.loc[online_report['stkcd']==int_stk, 'report_sales'],
             label = '{}'.format(stkcd), linestyle = 'dashed')
plt.title('Report sales')
plt.xticks(rotation=45)
plt.xlabel('Year-Quarter')
plt.ylabel('Sales')
plt.legend()

plt.subplot(2,2,3)
for stkcd in stkcd_list:
    int_stk = int(stkcd)
    plt.plot(online_report.loc[online_report['stkcd']==int_stk, 'year_quarter'],
```

```

        online_report.loc[online_report['stkcd']==int_stk,
        ↪'report_sales_cum'],
        label = '{}'.format(stkcd), linestyle = 'dashdot')
plt.title('Report sales cumulative')
plt.xticks(rotation=45)
plt.xlabel('Year-Quarter')
plt.ylabel('Sales')
plt.legend()
plt.show()

```

