

# jamtransfer.com api instructions

## REQUEST 1 - GET FROM PLACE

Send parameter  
Sample of url request  
Sample of response  
Collected values

1  
1  
1  
2

## REQUEST 2 - GET TO PLACE

Send parameter  
Sample of url request  
Sample of response  
Collected values

2  
2  
2  
2

## REQUEST 3 - GET SERVICE

Send parameters  
Sample of url request  
Sample of response  
Collected values

2  
3  
3  
3

## REQUEST 4 - GET EXTRAS

Send parameter  
Sample of url request  
Sample of response  
Collected values

3  
4  
4  
4

## REQUEST 5 - SET ORDER

Send parameters  
Sample of url request  
Sample of php script

4  
4  
5  
5

## REQUEST 1 - GET FROM PLACE

### Send parameter

qry - leading three or more characters of desired starting location

### Sample of url request

<https://wis.jamtransfer.com/app/getFromPlacesEdge.php?qry=Nic&code=/your api code/>

### Sample of response

```
{  
    "248250": "Nice",  
    "145797": "Nice Airport",  
    "250445": "Nice Port",
```

```
        "252484": "Nice Ville Train Station",
        "251170": "Nicolosi, Sicily Island",
        "248018": "Nicosia", "251862": "Nicosia Lefkosa"
    }
```

## Collected values

Id of select location (e.g.145797)

## REQUEST 2 - GET TO PLACE

### Send parameter

fID - ID of selected location in Request 1 (e.g.145797)

### Sample of url request

<https://wis.jamtransfer.com/app/getToPlacesEdge.php?fID=145797&code=/your api code/>

### Sample of response

```
{
    "250446": "Agay",
    "253699": "Airole",
    "246982": "Aix en Provence",
    "250448": "Alassio",
    "250601": "Allos",
    .....
    "248251": "Cannes",
    .....
    "248255": "Villefranche sur Mer",
    "248266": "Villeneuve Loubet",
    "251186": "Vins sur Caramy",
    "252544": "Vintimiglia"
}
```

## Collected values

Id of select location (e.g.248251)

## REQUEST 3 - GET SERVICE

### Send parameters

FromID	ID of selected location in Request 1 (e.g. 145797)
ToID	ID of selected location in Request 1 (e.g. 248251)
PaxNo	Number of passengers (e.g 3)
transferDate	date of transfer in YYYY-MM-DD format
transferTime	time of transfer in YYYY-MM-DD format
returnTransfer	0 if NO, 1 if YES
returnDate	date of return transfer in YYYY-MM-DD format
returnTime	time of return transfer in YYYY-MM-DD format

## Sample of url request

<https://wis.jamtransfer.com/app/getServices.php?FromID=145797&ToID=248251&PaxNo=3&transferDate=2024-04-01&transferTime=15:30&returnTransfer=1&returnDate=2024-04-02&returnTime=16:00&code=/your api code/>

## Sample of response

```
{
  "38960":{"VehicleName":"Standard, 4 passengers","VehicleCapacity":"4","FinalPrice":"128.10"},
  "38961":{"VehicleName":"Standard, 8 passengers","VehicleCapacity":"8","FinalPrice":"152.50"},
  "38962":{"VehicleName":"Standard, 16 passengers","VehicleCapacity":"16","FinalPrice":"310.18"},
  "86996":{"VehicleName":"Premium, 4 passengers","VehicleCapacity":"4","FinalPrice":"153.68"},
  "87158":{"VehicleName":"Premium, 8 passengers","VehicleCapacity":"8","FinalPrice":"169.20"},
  "87239":{"VehicleName":"Premium, 14 passengers","VehicleCapacity":"14","FinalPrice":"372.24"},
  "87482":{"VehicleName":"First Class, 7 passengers","VehicleCapacity":"7","FinalPrice":"197.40"},
  "106508":{"VehicleName":"First Class, 3 passengers","VehicleCapacity":"3","FinalPrice":"165.82"},
  "533678":{"VehicleName":"Standard, 7 passengers","VehicleCapacity":"7","FinalPrice":"147.90"},
  "535063":{"VehicleName":"Premium, 7 passengers","VehicleCapacity":"7","FinalPrice":"164.10"}
}
```

## Collected values

ID of selected service (e.g.535063)

# REQUEST 4 - GET EXTRAS

## Send parameter

ServiceID - ID of selected service in Request 3 (e.g.535063)

## Sample of url request

<https://wis.jamtransfer.com/app/getExtras.php?ServiceID=535063&code=/your api code/>

## Sample of response

```
{
  "101":{"ServiceEN":"Infant Seat (0-9kg or 0-1 years)","Price":"2.00"},
  "102":{"ServiceEN":"Child Seat (9-18kg or 1-4 years)","Price":"2.00"},
  "103":{"ServiceEN":"Booster Seat (18-36kg or 4-12 years)","Price":"2.00"},
  "104":{"ServiceEN":"Bicycle","Price":"10.00"},
  "105":{"ServiceEN":"Extra stop in same town","Price":"10.00"},
  "322":{"ServiceEN":"Baby Stroller","Price":"0.00"},
  "323":{"ServiceEN":"Extra luggage (more than 1 piece per person)","Price":"0.00"},
  "325":{"ServiceEN":"Golf Bag","Price":"2.00"},
  "326":{"ServiceEN":"Skis\Snowboard","Price":"0.00"},
  "327":{"ServiceEN":"Wheelchair (folding type only)","Price":"0.00"},
  "4224":{"ServiceEN":"Waiting time per 1 starting hour","Price":"55.00"}
}
```

## Collected values

IDs of selected extras e.g. array (103,105) )

## Note:

To order multiple units of the same additional service, specify multiple IDs of that service in a array, eg (103,103,105)

# REQUEST 5 - SET ORDER

## Send parameters

JSON data

ServiceID	ID of selected service in Request 3 (e.g. 535063)
ExtrasIDS	array of ids of selected extras in Request 4 (e.g. array (103,105) )
PaxNo	Number of passengers (e.g. 3)
transferDate	date of transfer in YYYY-MM-DD format
transferTime	time of transfer in YYYY-MM-DD format
returnTransfer	0 if NO, 1 if YES
returnDate	date of return transfer in YYYY-MM-DD format

returnTime	time of return transfer in YYYY-MM-DD format
VehiclesNo	Number of vehicles
pickupAddress	address in Pickup location
dropoffAddress	address in Drop location
flightNumber	Official flight number
flightTime	Official flight time
returnFlightNumber	Official return flight number
returnFlightTime	Official return flight time
paxName	Passenger name
paxMobile	Passenger Mobile phone
paxEmail	Passenger Email
notes	Notes

## Sample of url request

<https://wis.jamtransfer.com/app/setOrder.php?code=/your api code/>

## Sample of php script

<?

```
// sample of array with requested data
```

```
$arr=array (
```

```
    "ServiceID" => 535063,
    "ExtrasIDS" => array (103,105),
    "PaxNo" => 3,
    "transferDate" => "2024-04-01",
    "transferTime" => "15:30",
    "returnTransfer" => 1,
    "returnDate" => "2024-04-02",
    "returnTime" => "16:00",
    "VehiclesNo" => 1,
    "pickupAddress" => "Terminal airport",
    "dropoffAddress" => "Test street",
    "flightNumber" => "TT111",
    "flightTime" => "15:20",
    "returnFlightNumber" => "TT112",
    "returnFlightTime" => "19:00",
```

```

        "paxName" => "John Smith",
        "paxMobile" => "+44 11111111",
        "paxEmail" => "jsmith@test.com",
        "notes" => "for test porpuse"
    );
    // url for request
    $url = "https://wis.jamtransfer.com/app/setOrder.php?code=/your api code/";
    $content = json_encode($arr);
    $curl = curl_init($url);
    curl_setopt($curl, CURLOPT_HEADER, false);
    curl_setopt($curl, CURLOPT_RETURNTRANSFER, true);
    curl_setopt($curl, CURLOPT_HTTPHEADER,
        array("Content-type: application/json"));
    curl_setopt($curl, CURLOPT_POST, true);
    curl_setopt($curl, CURLOPT_POSTFIELDS, $content);
    $json_response = curl_exec($curl);
    $status = curl_getinfo($curl, CURLINFO_HTTP_CODE);
    if ( $status != 200 ) {
        die("Error: call to URL $url failed with status $status, response $json_response, curl_error " .
            curl_error($curl) . ", curl_errno " . curl_errno($curl));
    }
    curl_close($curl);
    // response from https://wis.jamtransfer.com/app/setOrder.php
    print_r($json_response);

```

## Result of process

At the end of this process, the order data should be in the jamtransfer database, the same as in the classical booking process.