

Arrays


Kit Eason
www.kiteason.com
[@kitlovesfsharp](https://twitter.com/kitlovesfsharp)



pluralsight 
hardcore dev and IT training

What is an Array?

- Standard .NET type
- Length fixed on creation
- All elements of same type
- Array as a whole is immutable
 - `let myArray = [|8;6;7;5;3;0;9|]`
 - `myArray <- [|8;7;7;5;3;0;9|]` ❌
- Elements mutable
 - `myArray.[1] <- 7`



Creating an Array

- **From a literal**

- `let primes = [|1; 3; 5; 7; 11|]`

- **From a comprehension**

- `let someNumbers = [|1000..1020|]`

- `let smallEvens = [|for i in 1..100 do
if i%2 = 0 then yield i|]`

- **Using a function from the Array module**

- `Array.create`

- `Array.init`


- **With zero-valued elements**

- `Array.zeroCreate`

- **From another array or IEnumerable**

Accessing Array Elements


- `.[index]` notation
 - `let myValue = myArray.3`
- Update elements with `<-`
`myArray.[3]`



`myArray.[5] <- 12`

The Array Module

- Provides operations on arrays
- ≈ 70 different operations!
- No need to open a namespace
- Not implemented as methods/extension methods
- Equivalent operations for other structures




Array.map


- Takes an array
- Returns another of same length
- Returned array has results of applying function to each element
- Input array unaffected
- Can have side effects too

Array.mapi

- Like array map
- Provides the index of each element
- Great substitute for 'for' loops



Array.iter



- Iterates and calls a function with each element
- Doesn't return anything!
- Side effects only!
- `Array.iteri` if you need an index

Array.filter

- Takes an array
- Applies some function to each element
- Returns elements where function returned 'true'

Option Data Type


- None means 'no useful value'
- Some *value* means 'we have a value and this is it'

Array.choose

- **Takes an array of values**
- **Applies supplied function to each element**
 - Function must return an option type
- **Filters for 'Some' results**
- **Returns an array of the actual values**


Array.sum

- Returns the total value
- Type must support addition
 - Uses the applicable + operator
- Elements must have a Zero member



Array.sumBy


- Takes a function
- ...which returns some aspect of the elements to total





{TxnId=12009; Amount=459.36}
{TxnId=12010; Amount=133.29}
{TxnId=12011; Amount=-9.99}
{TxnId=12012; Amount=1000.00}
{TxnId=12013; Amount=218.23}
{TxnId=12014; Amount=109.99}
{TxnId=12015; Amount=3459.11}

Array.sort/Array.sortBy

- `Array.sort` sorts by the whole element
- `Array.sortBy` - specify own function to get something to sort by



Array.reduce and Array.fold



Array.reduce

- **Takes an array**
- **Creates a 'state' based on first element**
- **For each following element**
 - Combines the state and the current element in some way
 - Returns another state which is passed into the next iteration
- **Returns the final accumulated state**

Array.fold

- **Starts with**
 - Array
 - Some initial state e.g. a string prefix
- **Applies function to each element**
 - Combines state and first element in some way
 - Returns another state which is passed into the next iteration
- **Returns final accumulated state**

Interlude: Parameter Naming

- `Array.fold` and `reduce` - simpler if you use 'acc elem' naming
- Stick to `i` for `map` and `iter`
- Keep lambda arg names short




Array.zip

- Takes two equal length arrays
- Produces an array of the same length
- Tuples of elements from each input array
- Nothing to do with compression!
- `Array.zip3`
- `Array.unzip`


Multi-Dimensional Arrays

- **Rectangular array**
 - Rows all same length, columns all same length
- **Array2D module**
 - `let my2D =
 Array2D.init 12 12
 (fun x y -> (x+1) * (y+1))`
- **Accessing elements**
 - `printfn "%i" my2D.[3, 4]`
- **Array3D, Array4D modules**




Jagged Arrays

- **An array of arrays**
 - Not all inner arrays same length
- **Creating a jagged array**
 - `let jagged1 = [| [|1; 3; 9|]; [|4; 6|] |]`
 - `let jagged2 = Array.init 3 (fun x -> [|0..x|])`
- **Accessing elements**
 - `printfn "%i" jagged1.[0].[2]`
- **Type annotations**
 - 2D array: `int [,]`
 - Jagged array: `int [] []`




Summary

- Fixed length (except ResizeArray)



Summary

- Immutable by default *as a whole*
- Mutable *elements* by default



Summary

- **Create with... literal**

- `let arr = [|1; 2; 5|]`

- **...comprehension**

- `let someNumbers = [|1000..1020|]`

- `let smallEvens =
 [|for i in 1..100 do if i%2 = 0 then yield i|]`

- **...Array.create, Array.zeroCreate, Array.init**

- `let squares = Array.init 10 (fun x -> x * x)`


- **...from another collection**

- `let arr = myList |> Array.ofList`

Summary

- Access elements with `.[index]` notation

`myArray.[3]`



`myArray.[5] <- 12`

Array Module

- **Contains about 70 useful functions**
- **Must understand at least:**
 - `Array.map`
 - `Array.iter`
 - `Array.filter`
- **Doing something to an array? Look at the Array module first!**