Skip Connections Unlock d_{model}^2 Parameters per Layer

Marko Karbevski*†
In Simplicity Technologies
markokarbevski@insimplicity.tech
markokarbevski@gmail.com

Antonij Mijoski*
IRMA, Université de Strasbourg
antonij.mijoski@unistra.fr
antonijmijo@gmail.com

Abstract

Residual and skipless networks with the same blocks have the same parameters. Do they use them alike? Here we show that skip connections unlock d_{model}^2 parameters per block, or $d_{\text{model}}(d_{\text{model}}-1)/2$ under RMSNorm, where d_{model} is the dimension of the hidden states. Without skips, every hidden state has a free basis: the next block undoes any change of basis. A skip adds the old hidden state to the new one, tying these bases into one. Spending the free bases removes as many parameters exactly per hidden state without skips: 8.5 percent of a skipless ViT-B. Where these symmetries are the only redundancy, the skips raise the functional dimension, the number of directions in which parameters move the function, by as much. We prove this for one block and for $\tanh$ networks without normalization, and that the gain is at least this large for attention and GELU networks of any depth.

1 Introduction

Skip connections are a building block of almost every deep network trained today (He et al., 2016). The usual reason is training: skips make deep networks easier to optimize (Balduzzi et al., 2017; He et al., 2016; Orhan and Pitkow, 2018). Recent skipless models challenge this need. Ji et al. (2026) remove every skip from a ViT-B (Dosovitskiy et al., 2021) and train it on ImageNet-1k, where it outperforms the residual ViT-B in top-1 accuracy, and He and Hofmann (2024); He et al. (2023) train transformers without skips.

So what do skips change, besides training? A residual network adds the input h of every block to its output through an *identity skip*, $h + B(h)$, and a skipless network computes $B(h)$ alone. The two have the same parameters. We ask whether they use them alike. Throughout, a network starts with a linear embedding and ends with a linear readout, the unembedding, and its hidden states, in between, have dimension d_{model}. In a pre-RMSNorm network, every block and the readout read their input through RMSNorm, which divides each token by its root mean square, regularized by a constant $\varepsilon > 0$.

Hidden states have units. Think of the coordinates of a hidden state as units of measurement, such as meters or feet. Without normalization, every hidden state of a skipless network can change its units. Let G be an invertible $d_{\text{model}} \times d_{\text{model}}$ matrix, and let hidden states be row vectors h. If the matrix W that writes the output of a block becomes WG, and the matrix W' through which the next block reads it becomes $G^{-1}W'$, the next block sees $hG\,G^{-1}W' = hW'$, and the function does not change. A skip adds the old hidden state to the new one, and only quantities in the same units can be added. So the skips tie the units of all hidden states into one.

Free bases are removable parameters. Each such G can be spent to set a $d_{\text{model}} \times d_{\text{model}}$ submatrix of the weights to the identity, which removes d_{model}^2 parameters without changing the

*Author contributions. Marko Karbevski (MK) conceived and led the study, proved the results at depth (Theorems 4.3 to 4.5), and worked on the symmetry breaking across layers and its counting, the parameter counts at model scale, the experiments and the applications. Antonij Mijoski (AM) worked on the writing. All of MK's work on the results, the proofs and the experiments was done with AI assistants.

†Corresponding author.




Figure 1: Singular values of the Jacobian of the parameter-to-output map on 4000 Gaussian inputs, with and without skips at the same weights, for the running example; median and range over 20 draws of the weights. The skips add 48 to its rank, the functional dimension, and 18 under RMSNorm.

function. A skipless network of L blocks has $L+1$ hidden states, so $(L+1)d_{\text{model}}^2$ of its parameters are removable; a residual network keeps one free change of basis, so d_{model}^2. Under RMSNorm only orthogonal matrices pass through the normalization, and a QR factorization makes the submatrix triangular instead, which removes the $d_{\text{model}}(d_{\text{model}}-1)/2$ entries below its diagonal at each hidden state. With LayerNorm, which acts as RMSNorm in dimension $d_{\text{model}}-1$, this removes 8.5 percent of the skipless ViT-B, whose 24 blocks, 12 attention and 12 MLP blocks, have 25 hidden states (Section 3.5).

Fewer parameters, the same functions. For almost every choice of weights, removing these parameters does not change the function. What the skips change is the functional dimension, the number of independent directions in which the parameters move the function (Grigsby et al., 2025). Our running example has an embedding $\mathbb{R}^6 \to \mathbb{R}^4$, so $d_{\text{model}} = 4$, then $L = 3$ MLP blocks with 8 hidden GELU units each, and a readout $\mathbb{R}^4 \to \mathbb{R}^6$: $P = 240$ parameters. Of these, 64 are removable without skips and 16 with them. The functional dimension is 176 without skips and 224 with them (Figure 1): the skips unlock $Ld_{\text{model}}^2 = 48$ parameters.

Known symmetries. Permuting the hidden units or heads of a block, and flipping the signs of $\tanh$ units, preserve the function (Fefferman, 1994; Sussmann, 1992; Theus et al., 2025); these symmetries are finite and remove no parameters. Rescaling a ReLU unit preserves the function too (Godfrey et al., 2022; Rolnick and Kording, 2020) and removes one parameter, so a block of $4d_{\text{model}}$ units loses $4d_{\text{model}}$ parameters to rescalings, against d_{model}^2 to a change of basis. Rescalings and the changes of basis inside attention heads (Theus et al., 2025; Wang and Wang, 2025) act inside a block, alike with and without skips, so they cancel when the two networks are compared. Changes of basis at hidden states are known too (Zhao et al., 2023), and so is one rotation of the residual stream under RMSNorm (Ashkboos et al., 2024a; Theus et al., 2025), the one change of basis that the skips leave. In residual ReLU networks, permutations and rescalings of the hidden states preserve the function when they agree at all hidden states that the skips join (Godfrey et al., 2022, Remark 3.6). Beyond these, we count the Ld_{model}^2 dimensions of symmetry that the skips remove, and show when they become functional dimension.

Contributions.

1. *Exact reduction* (Section 3.1). The change of basis at each hidden state of a skipless network sets one $d_{\text{model}} \times d_{\text{model}}$ submatrix of its weights to the identity. Zhao et al. (2023) describe this symmetry, and Graef (2024) uses an instance of it to remove weights from skipless transformers; here it is a general tool.
2. *Learned skips are identity units* (Section 3.2). A learned skip adds hA in place of h, for a trainable $d_{\text{model}} \times d_{\text{model}}$ matrix A. It is a block of d_{model} hidden units whose activation is the identity. The same tool merges the matrices U and V that read and write these units into $A = UV$, and then turns A into the identity: without normalization, a network with invertible learned skips is a residual network. Under RMSNorm, learned skips become triangular.
3. *One change of basis is left* (Section 3.3). A residual network keeps one change of basis for

Proven	Value	Blocks	Result
Parameters removed exactly, without changing the function			
without skips	$(L+1)d_{\text{model}}^2$	all	Prop. 3.1
with pre-RMSNorm	$(L+1)d_{\text{model}}(d_{\text{model}}-1)/2$	all	Thm. 3.4(i)
learned skips	Ld_{model}^2, all of them	all	Thm. 3.2
with pre-RMSNorm	$Ld_{\text{model}}(d_{\text{model}}-1)/2$	all	Thm. 3.4(iv)
identity skips	d_{model}^2	all	Thm. 3.3(iii)
with pre-RMSNorm	$d_{\text{model}}(d_{\text{model}}-1)/2$	all	Thm. 3.4(iii)
Dimensions of symmetry removed by the skips			
any L	Ld_{model}^2	all	Thm. 3.3(ii)
with pre-RMSNorm	$Ld_{\text{model}}(d_{\text{model}}-1)/2$	all	Thm. 3.4(ii)
Functional dimension added by the skips			
$L=1$	exactly d_{model}^2	all	Thm. 4.2(i)
with pre-RMSNorm	at least $d_{\text{model}}(d_{\text{model}}-1)/2$	all	Thm. 4.2(ii)
$L\geq 2$	at least Ld_{model}^2	smooth	Thm. 4.3(ii)
	exactly Ld_{model}^2	$\tanh$	Thm. 4.4(i)
	exactly Ld_{model}^2	GELU, $\geq 2d_{\text{model}}$ units	Thm. 4.4(ii)
with pre-RMSNorm	at least $Ld_{\text{model}}(d_{\text{model}}-1)/2$	smooth	Thm. 4.3(ii)
Residual networks that equal a skipless network of the same widths			
any L	measure zero	smooth	Thm. 4.5(i)
with pre-RMSNorm	measure zero	smooth	Thm. 4.5(i)

Table 1: The results, for networks of L blocks with hidden states of dimension d_{model}, at generic parameters; scope in Section 2. All: every block in scope. Smooth: attention, $\tanh$, GELU, SwiGLU and GeGLU blocks. Measured at depth: Table 2.

all its hidden states. When the embedding and the readout count among the parameters, it is a counterexample to the statement of Wang and Wang (2025) that the symmetry group of a transformer is the product of the groups of its blocks.

4. *Skips unlock functional dimension* (Section 4). Where the symmetries are the only redundancy, the skips raise the functional dimension by d_{model}^2 per block, and by $d_{\text{model}}(d_{\text{model}}-1)/2$ under RMSNorm. Without normalization we prove this for one block, attention included, and for networks of $\tanh$ blocks or of GELU blocks with at least $2d_{\text{model}}$ hidden units. For networks of attention, $\tanh$, GELU, SwiGLU and GeGLU blocks, with or without RMSNorm, we prove that the gain is at least this large at any depth, so that almost no such residual network equals a skipless network of the same widths. We measure the gain in deeper MLPs and small transformers.

Table 1 lists the results. Section 2 fixes the setting, Section 3 removes parameters and Section 4 counts functional dimension; proofs are in the appendix.

2 Setup

A block reads a hidden state, applies a fixed map and writes back; a network chains blocks between an embedding and a readout, with or without skips.

Blocks. A hidden state is a matrix $h \in \mathbb{R}^{T\times d_{\text{model}}}$ whose rows h_t are the T tokens of a sequence. A block reads it with a trainable matrix W_{read}, the *read*, applies a fixed map f, and writes the result with a trainable matrix W_{write}, the *write*:

$$B(h) = f(hW_{\text{read}})\,W_{\text{write}}. \tag{1}$$

We keep the word block for these maps, and call a part of a matrix a submatrix. In an MLP block with m hidden units, its width, $W_{\text{read}} \in \mathbb{R}^{d_{\text{model}}\times m}$, $W_{\text{write}} \in \mathbb{R}^{m\times d_{\text{model}}}$, and f applies an activation to every unit of every token: $\tanh$, GELU, ReLU, or its square, ReLU^2. In a gated block the read has

$2m$ columns, a gate g_i and a value v_i for each unit, and unit i computes $\sigma(g_i)\, v_i$, with σ the ReLU in ReGLU, SiLU in SwiGLU and GELU in GeGLU (Shazeer, 2020). In an attention block with H heads of width d_h, the read holds the query, key and value matrices W_Q, W_K and W_V of all heads, f is the attention map, and the write is the output projection W_O; the width of the block is Hd_h.

Networks. Every network starts with a linear embedding $E \in \mathbb{R}^{d_{\text{in}} \times d_{\text{model}}}$ and ends with a linear readout $D \in \mathbb{R}^{d_{\text{model}} \times d_{\text{out}}}$, the unembedding: it maps an input $x \in \mathbb{R}^{T \times d_{\text{in}}}$ to $h_0 = xE$, passes it through L blocks, and returns $y = h_L D$. For $\ell = 1, \ldots, L$, a *skipless* network, a *residual* network and a network with *learned skips* compute

$$h_\ell = B_\ell(h_{\ell-1}), \qquad h_\ell = h_{\ell-1} + B_\ell(h_{\ell-1}), \qquad h_\ell = h_{\ell-1}A_\ell + B_\ell(h_{\ell-1}), \tag{2}$$

with a trainable $d_{\text{model}} \times d_{\text{model}}$ skip matrix A_ℓ. The skipless and the residual network have the same P parameters. A transformer layer has two blocks, its attention and MLP sub-layers, so L counts sub-layers, and *per block* means per layer of an MLP and per sub-layer of a transformer.

Normalization. In a *pre-RMSNorm* network the blocks and the readout read $N(h)$ in place of h, where N divides each row h_t of h by $\sqrt{\|h_t\|^2/d_{\text{model}} + \varepsilon}$, with $\varepsilon > 0$. Skips read h itself, so a residual network computes $h_\ell = h_{\ell-1} + B_\ell\big(N(h_{\ell-1})\big)$ and $y = N(h_L)D$. A learned gain after N is folded into the next read.

Scope. For simplicity, networks have no biases. Every MLP block has at least d_{model} hidden units, and all MLP blocks of a network are of one kind. All attention blocks have the same number of heads, of width at most d_{model} and of total width $Hd_h \geq d_{\text{model}}$, and act on sequences of at least two tokens. Inputs range over an open set of $\mathbb{R}^{T \times d_{\text{in}}}$, which excludes one-hot tokens, and $d_{\text{in}}, d_{\text{out}} \geq d_{\text{model}} \geq 2$. Most results hold more generally, and the appendix states them so. *Generic* parameters are those outside a set of Lebesgue measure zero. Attention, $\tanh$, GELU, SwiGLU and GeGLU blocks are *smooth*.

3 Free changes of basis remove parameters exactly

Without normalization, every change of basis that a network keeps can set a $d_{\text{model}} \times d_{\text{model}}$ submatrix of its weights to the identity without changing its function: one per hidden state without skips, and one in all with identity skips. A learned skip is itself such a submatrix, and becomes the identity. Under RMSNorm, these submatrices become triangular.

3.1 Without skips: one free submatrix per hidden state

Without normalization, nothing nonlinear happens between the write of one block and the read of the next, so the basis of the hidden state between them is free. For an invertible $d_{\text{model}} \times d_{\text{model}}$ matrix G, the *change of basis* G at h_ℓ maps

$$W \mapsto WG \;\text{ for the writes into } h_\ell, \qquad W \mapsto G^{-1}W \;\text{ for the reads of } h_\ell. \tag{3}$$

The writes into h_ℓ are W^{ℓ}_{write}, or E if $\ell = 0$, and the reads of h_ℓ are $W^{\ell+1}_{\text{read}}$, or D if $\ell = L$. The hidden state becomes $h_\ell G$, and each read computes $h_\ell G\, G^{-1}W = h_\ell W$ as before, so the function does not change (Figure 2b).

A symmetry can be spent. Pick d_{model} columns of the read of h_ℓ that form an invertible matrix W_1.

Proposition 3.1 (One free submatrix per hidden state)**.** *Without normalization, the change of basis $G = W_1$ at h_ℓ preserves the function of a skipless network and turns W_1 into the identity. At generic parameters every hidden state has such a W_1, and doing this at every hidden state removes $(L+1)d^2_{\text{model}}$ parameters.*

A special case of Proposition A.6, proved in Appendix A.3.

Rows of a write work too: if d_{model} rows of the write into h_ℓ form an invertible matrix, the change of basis by its inverse turns them into the identity. In a skipless transformer with $Hd_h = d_{\text{model}}$,




Figure 2: (a) A block with a learned skip is a block with d_{model} identity units, read by U and written by V. (b) Without skips, every hidden state has its own change of basis G_ℓ. (c) Identity skips carry each hidden state into the next, so one change of basis is left.

$G = W_Q$ before an attention block sets its queries to the identity, and $G = W_O^{-1}$ after it sets its output projection to the identity: $2d_{\text{model}}^2$ parameters per layer. This is how Graef (2024) removes 15 percent of the weights of a skipless Mistral-7B.

So, up to a set of weights of measure zero, the reduced networks compute the same functions with fewer parameters. Section 4 asks what this means for the size of a network.

3.2 Learned skips are blocks of identity units

A learned skip, which adds hA in place of h, is a block in disguise: d_{model} hidden units whose activation is the identity (Lin and Jegelka, 2018, Section 4). Read them with a matrix U and write them with a matrix V, so that $A = UV$. The block with this skip is then a wider block of the form (1) (Figure 2a):

$$h\,UV + f(hW_{\text{read}})\,W_{\text{write}} \;=\; \tilde{f}\big(h\,[\,U \mid W_{\text{read}}\,]\big)\begin{bmatrix} V \\ W_{\text{write}} \end{bmatrix}, \qquad \tilde{f}\big([\,u \mid z\,]\big) = \big[\,u \mid f(z)\,\big]. \quad (4)$$

The tool of Section 3.1 now applies twice.

Merge. Nothing nonlinear happens between U and V, so the identity units have their own change of basis, $(U, V) \mapsto (UK, K^{-1}V)$, and only $A = UV$ enters the function. When A is invertible, $K = V$ gives the read $UV = A$ and the write I: one matrix, the skip.

Reduce. The skip A_ℓ reads $h_{\ell-1}$ and writes h_ℓ, so changes of basis at the two hidden states map it to $G_{\ell-1}^{-1} A_\ell G_\ell$. As a $d_{\text{model}} \times d_{\text{model}}$ submatrix of a read of $h_{\ell-1}$, it becomes the identity under $G_{\ell-1} = A_\ell$, as in Proposition 3.1. This multiplies the skip before it, $A_{\ell-1}$, by A_ℓ. Sweeping from the readout back turns every skip into the identity, and the product of all skips ends up in the embedding. Let $\Lambda_\ell = A_{\ell+1} \cdots A_L$, with $\Lambda_L = I$.

Theorem 3.2 (Learned skips are identity skips)**.** *Without normalization, let every learned skip A_ℓ be invertible. The network with learned skips computes the same function as the residual network with the embedding $E\Lambda_0$, the reads $\Lambda_{\ell-1}^{-1} W_{\text{read}}^\ell$, the writes $W_{\text{write}}^\ell \Lambda_\ell$ and the readout D.*

A special case of Theorem A.4, proved in Appendix A.2.

So all Ld_{model}^2 parameters of the learned skips can go, and with them the trainable identity units. Without normalization, invertible learned skips therefore compute the same functions as identity skips; Section 4.2 shows that they also have the same functional dimension.

3.3 Identity skips tie the hidden states

After the sweep one change of basis is left, and it must be the same at all hidden states. With a change of basis $G_{\ell-1}$ at $h_{\ell-1}$ and G_ℓ at h_ℓ, a residual block computes

$$h_{\ell-1} G_{\ell-1} + B_\ell(h_{\ell-1})\,G_\ell \;=\; h_\ell G_\ell + h_{\ell-1}(G_{\ell-1} - G_\ell). \quad (5)$$

The skip carries $h_{\ell-1}$ in the basis $G_{\ell-1}$, and the block writes in the basis G_ℓ, like feet added to meters. Unless the two agree, the defect $h_{\ell-1}(G_{\ell-1} - G_\ell)$ reaches every later block.

Theorem 3.3 (One change of basis is left)**.** *Without normalization, let every block be nonzero for some value of its parameters, and let $G, G_0, \dots, G_L$ be invertible.*
(i) *The map $E \mapsto EG_0$, $W^\ell_{\text{read}} \mapsto G^{-1}_{\ell-1} W^\ell_{\text{read}}$, $W^\ell_{\text{write}} \mapsto W^\ell_{\text{write}} G_\ell$, $D \mapsto G_L^{-1} D$ preserves the function of every residual network if and only if $G_0 = G_1 = \cdots = G_L$.*
(ii) *The changes of basis that preserve the function at all parameters form a group of dimension $(L+1)d^2_{\text{model}}$ in a skipless network and d^2_{model} in a residual one.*
(iii) *In a residual network, the change of basis G at every hidden state preserves the function, and for $G = W_1$, with W_1 formed by d_{model} columns of any one read, it turns W_1 into the identity.*

Proof in Appendix A.2.

So the L skips remove Ld^2_{model} dimensions of symmetry. In the language of gauge theory, they turn a symmetry that is local in depth into a global one (Hashimoto et al., 2024). Where a block outweighs its skip, the defect is small, and separate changes of basis on its two sides are approximate symmetries (Gong et al., 2026, Section 6.4).

A counterexample. Wang and Wang (2025, Theorem 7) state that the symmetry group of a transformer is the product of the groups of its blocks. When the embedding and the readout count among the parameters, the change of basis that the skips leave is a counterexample: it changes the embedding, which no element of that product does. Two instances preserve the function of common transformers. A global permutation of the coordinates of the hidden states does for every placement of the normalization, as Verma and Elbayad (2024, Section 3.3) use to merge BERT models. A global rotation does in pre-RMSNorm models with an untied readout, the construction behind Theorem 1 of Ashkboos et al. (2024a) (Appendix C).

3.4 Under RMSNorm: orthogonal maps pass, triangles stay

With pre-RMSNorm, the network with learned skips computes

$$h_\ell = h_{\ell-1} A_\ell + B_\ell\big(N(h_{\ell-1})\big), \qquad y = N(h_L)\, D. \tag{6}$$

A change of basis G at h_ℓ now reaches the reads through N, as $N(h_\ell G)$. Orthogonal matrices pass: $N(hQ) = N(h)Q$ for every orthogonal Q, since N only rescales each row, and the read absorbs Q by $W \mapsto Q^\top W$. Since $\varepsilon > 0$, no other invertible matrix passes (Lemma A.2). So every hidden state keeps an orthogonal change of basis, $d_{\text{model}}(d_{\text{model}} - 1)/2$ dimensions. It cannot turn a submatrix into the identity, but a QR factorization shows that it can make it triangular.

Theorem 3.4 (Triangles under RMSNorm)**.** *Consider pre-RMSNorm networks.*
(i) *In a skipless network, let $W_1 = QR$, with Q orthogonal and R upper triangular. The change of basis Q at h_ℓ preserves the function and turns W_1 into R. Done at every hidden state, this removes $(L+1)d_{\text{model}}(d_{\text{model}} - 1)/2$ parameters.*
(ii) *Theorem 3.3(i) and (ii) hold for orthogonal $G_0, \dots, G_L$, with $d_{\text{model}}(d_{\text{model}} - 1)/2$ in place of d^2_{model}.*
(iii) *In a residual network, the change of basis Q at every hidden state preserves the function and turns W_1, d_{model} columns of any one read, into R.*
(iv) Triangular skips. *If every learned skip A_ℓ is invertible, there are orthogonal $Q_1, \dots, Q_L$, with $Q_0 = I$, such that every $Q^\top_{\ell-1} A_\ell Q_\ell$ is upper triangular, and the network with these skips, the reads $Q^\top_{\ell-1} W^\ell_{\text{read}}$, the writes $W^\ell_{\text{write}} Q_\ell$ and the readout $Q_L^\top D$ computes the same function.*

Proof in Appendix A.4.

What a learned skip carries. Write a skip as $A = RQ$, an upper triangular matrix times an orthogonal one. The orthogonal factor Q, of dimension $d_{\text{model}}(d_{\text{model}} - 1)/2$, is removable: part (iv) spends the changes of basis on it. The $d_{\text{model}}(d_{\text{model}} + 1)/2$ entries of R stay, and an identity skip fixes them as well. So under RMSNorm an identity skip does two things: it spends the change of basis at a hidden state, and it fixes the triangle, a constraint that Section 4.2 counts.

LayerNorm is RMSNorm after a projection that removes the mean of each row, and it reduces to RMSNorm of dimension $d_{\text{model}} - 1$ (Proposition A.8). Every count above then holds with $d_{\text{model}} - 1$ in place of d_{model}: $(d_{\text{model}} - 1)(d_{\text{model}} - 2)/2$ per hidden state.

3.5 What trained models give up

A skipless ViT-B. The skipless ViT-B of Ji et al. (2026) has $d_{\text{model}} = 768$ and 25 hidden states: one before each of its 24 blocks and one before the readout. With standard pre-LayerNorm blocks, which reduce to RMSNorm of dimension 767, each hidden state keeps an orthogonal change of basis. One triangular 767×767 submatrix of a read per hidden state removes $25 \cdot 767 \cdot 766/2 = 7.3$M parameters, 8.5 percent of the model. The residual ViT-B keeps one orthogonal change of basis, worth 0.3 percent (Table 5).

Llama-3.1. A pre-RMSNorm language model with an untied readout keeps one orthogonal change of basis, which makes one $d_{\text{model}} \times d_{\text{model}}$ submatrix triangular. This removes 8.4M parameters of Llama-3.1-8B, 34M of Llama-3.1-70B and 134M of Llama-3.1-405B, that is 0.10, 0.05 and 0.03 percent (Grattafiori et al., 2024): exact, but small.

4 Fewer parameters is not fewer functions

The parameters removed in Section 3 did not change the function. The functional dimension counts the rest, and where the symmetries are the only redundancy, each skip unlocks d_{model}^2 of it, and $d_{\text{model}}(d_{\text{model}} - 1)/2$ under RMSNorm.

4.1 Functional dimension

Functional dimension. Let F_θ be the function computed at parameters $\theta \in \mathbb{R}^P$. Following Grigsby et al. (2025), the *functional dimension* at θ is the largest rank of the Jacobian of $\theta \mapsto (F_\theta(x_1), \ldots, F_\theta(x_n))$ over finite batches of inputs, and the *redundancy* is P minus it. It counts the independent directions in which the parameters move the function. A continuous symmetry always adds to the redundancy: if a continuous family of maps of the parameters leaves the function unchanged, the directions in which it moves θ lie in the kernel of every such Jacobian.

Three matrices, one map. The linear network $x \mapsto xM_1M_2M_3$, with three $d_{\text{model}} \times d_{\text{model}}$ matrices, has $3d_{\text{model}}^2$ parameters and computes every linear map $x \mapsto xM$. Its functional dimension is therefore d_{model}^2 at generic parameters, and its redundancy $2d_{\text{model}}^2$. Merging $M_2' = M_2M_3$ leaves $2d_{\text{model}}^2$ parameters, the same functions and the same functional dimension. Spending a symmetry this way lowers the parameter count and leaves the functional dimension unchanged.

4.2 What the skips unlock

Blocks also have *symmetries inside*, which leave the hidden states alone. Besides permutations and sign flips, of dimension zero, they are the rescalings of the hidden units of ReLU and ReLU^2 blocks, of the values of gated units, and in ReGLU of their gates too, and in each attention head a change of basis between queries and keys and one between values and outputs (Elhage et al., 2021; Theus et al., 2025). Let s be their total dimension, summed over the blocks. It is the same with and without skips, and $s = 0$ for $\tanh$ and GELU blocks. Let $\mathcal{G}$ be the group of changes of basis that pass the reads: $\mathrm{GL}(d_{\text{model}})$ without normalization, of dimension d_{model}^2, and $\mathrm{O}(d_{\text{model}})$ under RMSNorm, of dimension $d_{\text{model}}(d_{\text{model}} - 1)/2$.

Theorem 4.1 (What the skips unlock)**. (i)** *At generic parameters, the functional dimension is at most $P - (L+1)\dim\mathcal{G} - s$ without skips and at most $P - \dim\mathcal{G} - s$ with identity skips.*
(ii) *If both bounds are attained, the skips raise the functional dimension by exactly $L \dim\mathcal{G}$.*

A special case of Theorem A.9, proved in Appendix A.6.

A network satisfies the *equality condition* if its bound in (i) is attained at generic parameters, that is, if its symmetries are its only redundancy. Under this condition each skip unlocks $\dim \mathcal{G}$ parameters, d_{model}^2 without normalization and $d_{\text{model}}(d_{\text{model}}-1)/2$ under RMSNorm: they are redundant in the skipless network and count in the residual one. In the running example, with $L = 3$ GELU blocks and $d_{\text{model}} = 4$, $P = 240$, $s = 0$ and the bounds are $240 - 64 = 176$ and $240 - 16 = 224$; Figure 1 shows both attained.

Learned skips. A network with learned skips has $P + Ld_{\text{model}}^2$ parameters, and its changes of basis act at every hidden state, so its functional dimension is at most $P + Ld_{\text{model}}^2 - (L+1)\dim \mathcal{G} - s$. Without normalization this is $P - d_{\text{model}}^2 - s$, the bound of the residual network, and with invertible skips the two functional dimensions are equal (Theorem A.4(ii)). Under RMSNorm the bound exceeds the residual one by $Ld_{\text{model}}(d_{\text{model}}+1)/2$, and where both are attained, each learned skip adds its triangle (Theorem A.7(iii)).

At equal parameter count. Under the equality condition, a residual network with P parameters has the functional dimension of a skipless network with $L\dim \mathcal{G}$ more, so comparisons at equal parameter count favor residual networks. Where the symmetries are the only redundancy, the skipless ViT-B of Ji et al. (2026) outperforms the residual one with about 8 percent less functional dimension (Appendix D).

4.3 When the bounds are attained

The equality condition is a hypothesis. We prove it in three cases.

Theorem 4.2 (One block)**.** *Let $L = 1$, with a* tanh*, GELU, ReLU, ReLU^2, ReGLU, SwiGLU, GeGLU or attention block.*
(i) *Without normalization, both networks satisfy the equality condition, and the skip raises the functional dimension by exactly d_{model}^2.*
(ii) *Under RMSNorm, the residual network satisfies the equality condition, and the skip raises the functional dimension by at least $d_{\text{model}}(d_{\text{model}}-1)/2$. A learned skip raises it by exactly $d_{\text{model}}(d_{\text{model}}+1)/2$ more.*

A special case of Theorem B.1, proved in Appendix B.

Theorem 4.3 (Residual networks at any depth)**.** *Let the blocks be smooth.*
(i) *The residual network satisfies the equality condition: at generic parameters its functional dimension is $P - \dim \mathcal{G} - s$.*
(ii) *The skips raise the functional dimension by at least $L\dim \mathcal{G}$, and by exactly $L\dim \mathcal{G}$ when the skipless network satisfies the equality condition too.*

Proof in Appendix A.7.

Theorem 4.4 (Exact gain for tanh and GELU)**.** *Without normalization, in the two cases below the skipless network satisfies the equality condition too, so the skips raise the functional dimension by exactly Ld_{model}^2.*
(i) *The blocks are* tanh *blocks.*
(ii) *The blocks are GELU blocks with at least $2d_{\text{model}}$ hidden units.*

Proof in Appendix A.7.

How the proofs go. With one block, the parameters enter the function only through the products ED, $W_{\text{write}}D$ and EW_{read}. A factorization of a matrix of rank d_{model} into two factors is unique up to a change of basis between them, so the skipless network keeps one change of basis at h_0 and one at h_1, and the term xED of the skip ties them into one. The rest of the proof isolates each hidden unit, by its kink or by how fast it approaches its limit along rays. At any depth, with small writes, a residual network is to first order the linear map xED plus one wide block that holds all its units and heads, which brings the one-block argument to every depth; without the skip, small writes leave no linear path from the embedding to the readout.

Measured	Depth L	Normalization	Added by the skips
$\tanh$, GELU, SwiGLU, GeGLU, $d_{\text{model}} = 4$	3	none, RMSNorm	$L \dim \mathcal{G}$
$\tanh$, $d_{\text{model}} = 16$	6	none, RMSNorm	$L \dim \mathcal{G}$
ReLU^2, ReGLU, exact rank	3, 8	none	Ld_{model}^2
ReLU	3	none	at least Ld_{model}^2
nanoGPT: attention and GELU	2 to 8	none, LayerNorm	$L \dim \mathcal{G}$

Table 2: Measured at random weights, without biases (Appendix E); exact rank: computed modulo a prime. $\dim \mathcal{G}$ is d_{model}^2 without normalization, $d_{\text{model}}(d_{\text{model}}-1)/2$ with RMSNorm and $(d_{\text{model}}-1)(d_{\text{model}}-2)/2$ with LayerNorm.

4.4 Measured at depth

For deeper networks we compute the rank of the Jacobian on a large batch of inputs (Appendix E); for ViT-B, this Jacobian would fill over 50 petabytes. The rank is a lower bound on the functional dimension, and Theorem 4.1(i) gives an upper bound. Where they meet, the functional dimension is known exactly, and in the networks of Table 2 the skips add $L \dim \mathcal{G}$.

There are two kinds of exceptions. Under RMSNorm with $\varepsilon = 10^{-5}$, some directions of skipless ReGLU networks have singular values below double precision. In one of eight skipless ReLU networks, five units active on the same inputs act as one linear map and add redundancy; for ReLU networks the functional dimension varies on sets of positive measure (Grigsby et al., 2023). For $\tanh$, GELU and gated MLP blocks we expect the equality condition to hold.

Conjecture 1 (Equality condition)**.** *Consider MLP networks with* $\tanh$*, GELU, SwiGLU, GeGLU or ReGLU blocks, on inputs that range over an open set. At generic parameters the skipless and the residual network both satisfy the equality condition, so the skips raise the functional dimension by exactly* $L \dim \mathcal{G}$*.*

For $\tanh$, GELU, SwiGLU and GeGLU blocks, the residual half of the conjecture is Theorem 4.3; without normalization, both halves hold for $\tanh$ blocks and for GELU blocks with at least $2d_{\text{model}}$ hidden units (Theorem 4.4). With one-hot token inputs under RMSNorm, the change of basis at the embedding is no longer restricted to orthogonal matrices, which adds $d_{\text{model}}(d_{\text{model}}+1)/2$ symmetries (Table 6).

4.5 A gap that separates function classes

A gap in functional dimension keeps two families of functions apart: for smooth blocks, a skipless network of the same widths has a lower functional dimension than a generic residual network.

Theorem 4.5 (Different function classes)**. (i)** *For networks of smooth blocks, without normalization or with pre-RMSNorm, and almost every choice of weights, a residual network equals no skipless network of the same widths.*
(ii) Too few extra units. *For networks of GELU blocks without normalization, and almost every choice of weights, a residual network of L blocks equals no skipless network of L blocks with fewer than $Ld_{\text{model}}/2$ more hidden units in all.*

A special case of Theorem A.14, proved in Appendix A.7.

In (ii), each extra GELU unit adds $2d_{\text{model}}$ parameters against a gap of Ld_{model}^2. A companion paper shows that, without normalization, d_{model} more ReLU or GELU units per block let a skipless network equal almost any residual one, and that for gated, ReLU^2 and $\tanh$ networks no number of units does (Mijoski and Karbevski, 2026).

5 Related work

Changes of basis at hidden layers. Zhao et al. (2023) define a change of basis at every hidden layer of an MLP, which preserves the function where the activation is linear and, for orthogonal changes,

where it is a radial rescaling (their Proposition C.1). They remark that the proposition adapts to networks with skips (their Appendix C.5); what the skips do to the symmetry is not worked out there. Written as identity units, (4), a skip fits their proposition as it stands, and the sweep of Theorem 3.2 combines their changes of basis at the identity units and at the hidden states.

Removing weights. Graef (2024) merges the queries and the output projections of skipless transformers, the pattern of Section 3.1. The change of basis at each hidden state also reaches the identity values and projections of the skipless blocks of He and Hofmann (2024), and triangular ones under normalization. SliceGPT inserts rotations into identity skips, so that neighboring blocks can carry different ones, and then deletes rows and columns, which approximates the original model (Ashkboos et al., 2024a, Sections 3.3 and 3.4); Theorem 3.2 takes the matrices of learned skips out, exactly. RMNet emulates the skips of trained convolutional networks with ReLU units (Meng et al., 2021), and LAuReL trains skips that differ from the identity by a low-rank matrix (Menghani et al., 2025); without normalization, Theorem 3.2 removes invertible ones.

The basis of the residual stream. The residual stream has no privileged basis (Elhage et al., 2021). SliceGPT proves that an RMSNorm transformer computes the same function after one rotation of every matrix that touches the stream (their Theorem 1), QuaRot and SpinQuant use this invariance for quantization (Ashkboos et al., 2024b; Liu et al., 2025), and model merging aligns residual streams with one global orthogonal matrix (Theus et al., 2025). All of these use the one change of basis that a residual network keeps. van Nierop (2024) counts the symmetries of LayerNorm transformers, with one rotation of the stream for the whole model.

Symmetries and residual networks in theory. Wang and Wang (2025) characterize the symmetries of attention and MLP blocks; for the full model, Section 3.3 gives counterexamples. Concurrently with and independently of our first version (7 October 2026, `https://github.com/MarkoKarbevski/skips_fix_gauges/commit/8128617`), Dahlgren et al. (2026) prove that residual networks with polynomial activations and without write matrices are generically identifiable up to finitely many sign flips; the changes of basis that our skips remove do not arise there. Marcotte et al. (2025) show that a block has the same conservation laws of gradient flow with and without its skip. Likewise, without an embedding and a readout the skip does not change the derivative of a block with respect to its parameters, so the gain needs an embedding and a readout around the block. MacDonald et al. (2023) show that identity skips keep the Jacobian of the parameter-to-output map of full row rank on linearly independent inputs; we study the kernel of the same Jacobian.

6 Conclusion

What do skips change in parameter space? They tie the bases of all hidden states into one. A skipless network keeps a free change of basis at every hidden state, d_{model}^2 removable parameters each, and a residual network keeps one. Where the symmetries are the only redundancy, the skips turn these parameters into d_{model}^2 dimensions of functions per block, $d_{\text{model}}(d_{\text{model}}-1)/2$ under RMSNorm. We prove this exactly for one block and for networks of $\tanh$ or wide GELU blocks without normalization, prove that smooth blocks at any depth gain at least this much, and measure the gain in deeper networks. The free bases can also be spent after training: 8.5 percent of a skipless ViT-B, every learned skip without normalization, and the orthogonal part of every learned skip under RMSNorm come out without changing the function.

Open questions. The equality condition at depth remains open for skipless networks beyond the $\tanh$ and wide GELU networks of Theorem 4.4 (Conjecture 1), and for ReLU-type blocks, whose functional dimension drops where units never switch on. Whether networks train better in the reduced forms is untested: a skipless network with one identity submatrix per hidden state, or triangular learned skips under RMSNorm, against full ones. Orthogonal skips change only training (Theorem A.7(ii)), while triangular ones add $d_{\text{model}}(d_{\text{model}}+1)/2$ dimensions each; which of the two brings more per parameter is open. Input-dependent skips, as in mHC (Xie et al., 2025), make the map between hidden states nonlinear and are beyond our scope.

Use of AI

The conception of the study is the authors' own. One author obtained their results, proofs and experiments working with AI assistants, through continuous conversation; the assistants were used to find, verify and simplify proofs and to write the code of the experiments, which the authors validated.

Code availability

The notebook that reproduces the numbers, tables and figures of this paper (Appendix E) will be released in a public Git repository, coming soon.

References

Saleh Ashkboos, Maximilian L. Croci, Marcelo Gennari do Nascimento, Torsten Hoefler, and James Hensman. SliceGPT: Compress large language models by deleting rows and columns. In *ICLR*, 2024a.

Saleh Ashkboos, Amirkeivan Mohtashami, Maximilian L. Croci, Bo Li, Pashmina Cameron, Martin Jaggi, Dan Alistarh, Torsten Hoefler, and James Hensman. QuaRot: Outlier-free 4-bit inference in rotated LLMs. In *NeurIPS*, 2024b.

David Balduzzi, Marcus Frean, Lennox Leary, J. P. Lewis, Kurt Wan-Duo Ma, and Brian McWilliams. The shattered gradients problem: If resnets are the answer, then what is the question? In *ICML*, pages 342–350, 2017.

Isabel Dahlgren, Giovanni Luca Marchetti, and Kathlén Kohn. Polynomial residual networks are generically identifiable. *arXiv:2610.33738*, 2026.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=YicbFdNTTy.

Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Nova DasSarma, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 2021. https://transformer-circuits.pub/2021/framework/index.html.

Charles Fefferman. Reconstructing a neural net from its output. *Revista Matemática Iberoamericana*, 10(3): 507–555, 1994.

Charles Godfrey, Davis Brown, Tegan Emerson, and Henry Kvinge. On the symmetries of deep learning models and their internal representations. In *NeurIPS*, 2022.

Wenbo Gong, Javier Zazo, Qijun Luo, Puqian Wang, James Hensman, and Chao Ma. ARO: A new lens on matrix optimization for large models. *arXiv:2602.09006*, 2026.

Nils Graef. Transformer tricks: Removing weights for skipless transformers. *arXiv:2404.12362v1*, 2024. Version 2 (2025) is titled "KV-weights are all you need for skipless transformers".

Aaron Grattafiori, Abhimanyu Dubey, et al. The Llama 3 herd of models. *arXiv:2407.21783*, 2024.

J. Elisenda Grigsby, Kathryn Lindsey, and David Rolnick. Hidden symmetries of ReLU networks. In *ICML*, 2023.

J. Elisenda Grigsby, Kathryn Lindsey, Robert Meyerhoff, and Chenxi Wu. Functional dimension of feedforward ReLU neural networks. *Advances in Mathematics*, 482:110636, 2025. arXiv:2209.04036.

Koji Hashimoto, Yuji Hirono, and Akiyoshi Sannai. Unification of symmetries inside neural networks: Transformer, feedforward and neural ODE. *Machine Learning: Science and Technology*, 5:025079, 2024.

Bobby He and Thomas Hofmann. Simplifying transformer blocks. In *ICLR*, 2024.

Bobby He, James Martens, Guodong Zhang, Aleksandar Botev, Andrew Brock, Samuel L. Smith, and Yee Whye Teh. Deep transformers without shortcuts: Modifying self-attention for faithful signal propagation. In *ICLR*, 2023.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, pages 770–778, 2016.

Yiping Ji, James Martens, Jianqiao Zheng, Ziqin Zhou, Peyman Moghadam, Xinyu Zhang, Hemanth Saratchandran, and Simon Lucey. Cutting the skip: Training residual-free transformers. In *ICLR*, 2026.

Andrej Karpathy. nanoGPT, files `model.py` and `train.py`. https://github.com/karpathy/nanoGPT, 2023. Accessed 28 September 2026.

Hongzhou Lin and Stefanie Jegelka. ResNet with one-neuron hidden layers is a universal approximator. In *NeurIPS*, 2018.

Zechun Liu, Changsheng Zhao, Igor Fedorov, Bilge Soran, Dhruv Choudhary, Raghuraman Krishnamoorthi, Vikas Chandra, Yuandong Tian, and Tijmen Blankevoort. SpinQuant: LLM quantization with learned rotations. In *ICLR*, 2025.

Lachlan E. MacDonald, Jack Valmadre, Hemanth Saratchandran, and Simon Lucey. On skip connections and normalisation layers in deep optimisation. In *NeurIPS*, 2023.

Sibylle Marcotte, Rémi Gribonval, and Gabriel Peyré. Transformative or conservative? conservation laws for ResNets and transformers. In *ICML*, 2025.

Fanxu Meng, Hao Cheng, Jiaxin Zhuang, Ke Li, and Xing Sun. RMNet: Equivalently removing residual connection from networks. *arXiv:2111.00687*, 2021.

Gaurav Menghani, Ravi Kumar, and Sanjiv Kumar. LAuReL: Learned augmented residual layer. In *ICML*, 2025.

Antonij Mijoski and Marko Karbevski. How many hidden units is a skip connection worth? Companion paper, 2026.

A. Emin Orhan and Xaq Pitkow. Skip connections eliminate singularities. In *ICLR*, 2018.

David Rolnick and Konrad P. Kording. Reverse-engineering deep ReLU networks. In *ICML*, 2020.

Noam Shazeer. GLU variants improve transformer. *arXiv:2002.05202*, 2020.

Héctor J. Sussmann. Uniqueness of the weights for minimal feedforward nets with a given input-output map. *Neural Networks*, 5(4):589–593, 1992.

Alexander Theus, Alessandro Cabodi, Sotiris Anagnostidis, Antonio Orvieto, Sidak Pal Singh, and Valentina Boeva. Generalized linear mode connectivity for transformers. In *NeurIPS*, 2025.

Leo van Nierop. Transformer models are gauge invariant: A mathematical connection between AI and particle physics. *arXiv:2412.14543*, 2024.

Neha Verma and Maha Elbayad. Merging text transformer models from different initializations. *Transactions on Machine Learning Research*, 2024. arXiv:2403.00986.

Hong Wang and Kelly Wang. Complete characterization of gauge symmetries in transformer architectures. In *Symmetry and Geometry in Neural Representations (NeurReps), Proceedings Track*, volume 282 of *PMLR*, pages 622–663, 2025.

Zhenda Xie, Yixuan Wei, Huanqi Cao, Chenggang Zhao, Chengqi Deng, Jiashi Li, Damai Dai, Huazuo Gao, Jiang Chang, Kuai Yu, Liang Zhao, Shangyan Zhou, Zhean Xu, Zhengyan Zhang, Wangding Zeng, Shengding Hu, Yuqing Wang, Jingyang Yuan, Lean Wang, and Wenfeng Liang. mHC: Manifold-constrained hyper-connections. *arXiv:2512.24880*, 2025.

Bo Zhao, Iordan Ganev, Robin Walters, Rose Yu, and Nima Dehmamy. Symmetries, flat minima, and the conserved quantities of gradient flow. In *ICLR*, 2023.

A Proofs

Throughout, the tokens of a hidden state are its rows; where every block acts on each token separately, as MLP blocks do, it suffices to take one token, $T = 1$, so that $h \in \mathbb{R}^{1\times d_{\text{model}}}$ is a row vector. Biases, when present, enter as $B_\ell(h) = f_\ell(hW^\ell_{\text{read}} + b^\ell_{\text{read}})W^\ell_{\text{write}} + b^\ell_{\text{write}}$, with row vectors b added to every token. Each subsection recalls the results of the main text named in its title, explains what the proof does, and then proves them; auxiliary results are stated where they are first used. Here a *mixed block* is a block with d_{model} identity units with trainable read U_ℓ and write V_ℓ, as in (4), and $\mathcal{G}$ is $\mathrm{GL}(d_{\text{model}})$ without normalization, $\mathrm{O}(d_{\text{model}})$ under RMSNorm with $\varepsilon > 0$, and $\mathrm{CO}(d_{\text{model}})$, the positive multiples of orthogonal matrices, under RMSNorm with $\varepsilon = 0$. The one-block theorem, Theorem B.1, is proved in Appendix B.

A.1 Changes of basis at junctions

The main text uses changes of basis at hidden states (Section 3.1) and at the identity units of a learned skip (Section 3.2). The following proposition states both, for skipless networks and networks of mixed blocks.

Proposition A.1 (Junctions)**. (i) Only UV matters.** *In a mixed block, $(U, V) \mapsto (UK, K^{-1}V)$ preserves the function for every $K \in \mathrm{GL}(d_{\text{model}})$.*
(ii) Hidden states are junctions. *In a skipless network, and in a network of mixed blocks, the map $W \mapsto WG$ on the matrices that write a hidden state and $W \mapsto G^{-1}W$ on those that read it preserves the function for every $G \in \mathcal{G}$. For $\varepsilon = 0$ and $G = cQ$, a read through RMSNorm maps to $Q^\top W$ instead.*
(iii) One group per junction. *The maps of (i) and (ii) commute when they act at different junctions. A skipless network therefore carries one copy of $\mathcal{G}$ per hidden state, and a network of mixed blocks one more copy of $\mathrm{GL}(d_{\text{model}})$ per block.*

Overview. A change of basis at a junction is undone by the reads of that junction, and changes at different junctions multiply the matrices they share from different sides, so they commute; biases add a translation. The only real work is under normalization, where a read sees $N(hG)$ rather than hG: Lemma A.2 determines which changes of basis can be moved through N.

Lemma A.2 (RMSNorm equivariance)**.** *Let $G \in \mathrm{GL}(d_{\text{model}})$.*
(i) *There is a matrix M with $N(hG) = N(h)M$ for all row vectors $h \neq 0$ if and only if $G \in \mathrm{CO}(d_{\text{model}})$ when $\varepsilon = 0$, and $G \in \mathrm{O}(d_{\text{model}})$ when $\varepsilon > 0$. Then $M = Q$, where $G = cQ$ with Q orthogonal.*
(ii) *If $\varepsilon > 0$ and $G = cQ$, then $\|N(hG) - N(h)Q\|/\|N(h)\| = \frac{\varepsilon}{2r^2}|1 - c^{-2}| + O(\varepsilon^2)$, where $r^2 = \|h\|^2/d_{\text{model}}$.*

Proof. Outline. We first take $\varepsilon = 0$, where $N(h)$ depends only on the direction of h, and show that a matrix that can be moved through N is orthogonal up to a positive scale. We then show that $\varepsilon > 0$ removes the scale, and expand the resulting error in ε.

Let $\varepsilon = 0$, so $N(h) = \sqrt{d}_{\text{model}}\, h/\|h\|$. If $G = cQ$ then $N(h\,cQ) = \sqrt{d}_{\text{model}}\, c\, hQ/(c\|h\|) = N(h)Q$. Conversely, if $hG/\|hG\| = hM/\|h\|$ for all $h \neq 0$, taking norms gives $\|hM\| = \|h\|$, so M is orthogonal, and $hGM^\top = (\|hG\|/\|h\|)\, h$: every nonzero row vector is a left eigenvector of $GM^\top$, so $GM^\top = cI$ with $c = \|hG\|/\|h\| > 0$, and $G = cM$. Let $\varepsilon > 0$. For $G = cQ$, $N(h\,cQ) = c\,hQ/\sqrt{c^2\|h\|^2/d_{\text{model}} + \varepsilon}$ and $N(h)Q = hQ/\sqrt{\|h\|^2/d_{\text{model}} + \varepsilon}$; these agree for all h if and only if $c = 1$. If $N(hG) = N(h)M$ for all h with $\varepsilon > 0$, letting $\|h\| \to \infty$ along rays reduces to the case $\varepsilon = 0$, so $G = cM$ with M orthogonal, and the computation just made forces $c = 1$. The expansion of the deviation is the Taylor expansion of $c\sqrt{r^2 + \varepsilon}/\sqrt{c^2r^2 + \varepsilon} - 1$ in ε. □

Lemma A.3 (Homogeneous blocks under RMSNorm)**.** *Let a skipless network with pre-RMSNorm, $h_\ell = B_\ell(N(h_{\ell-1}))$ for $\ell = 1, \ldots, L$ and $y = N(h_L)D$, have blocks that are positively homogeneous of degree k, and let $r_i^2 = \|h_i\|^2/d_{\text{model}}$. Apply the change of basis $G \in \mathrm{GL}(d_{\text{model}})$ at h_ℓ with $\ell < L$, or the scaling $G = cI$ at h_L with its read D unchanged. At every input whose hidden states*

are nonzero, the output becomes Λy with a scalar $\Lambda > 0$, and
(i) *$\Lambda = 1$ if $\varepsilon = 0$ or G is orthogonal;*
(ii) *for $G = e^{tS}$ with S symmetric and $\ell < L$,*

$$\frac{d}{dt}\log\Lambda\Big|_{t=0} = -\,k^{L-\ell}\,\frac{h_\ell S h_\ell^\top}{d_{\text{model}}\,(r_\ell^2+\varepsilon)}\prod_{i=\ell+1}^{L}\frac{\varepsilon}{r_i^2+\varepsilon},$$

and for the scaling $c = e^t$ at h_L it is $\varepsilon/(r_L^2+\varepsilon)$.

Proof. Since $N(h)$ is a positive multiple of h,

$$N(h_\ell G)\,G^{-1} = \gamma N(h_\ell), \qquad \gamma = \sqrt{\frac{r_\ell^2+\varepsilon}{\|h_\ell G\|^2/d_{\text{model}}+\varepsilon}}.$$

Block $\ell+1$ thus reads $\gamma N(h_\ell)$ and, being homogeneous, writes $\mu_{\ell+1}h_{\ell+1}$ with $\mu_{\ell+1} = \gamma^k$; for the scaling at h_L, set $\mu_L = c$. If a hidden state becomes $\mu_i h_i$ with $\mu_i > 0$, then $N(\mu_i h_i) = \beta_i N(h_i)$ with

$$\beta_i = \mu_i\sqrt{\frac{r_i^2+\varepsilon}{\mu_i^2 r_i^2+\varepsilon}},$$

so the next block writes $\mu_{i+1}h_{i+1}$ with $\mu_{i+1} = \beta_i^k$, and the readout gives $\Lambda = \beta_L$.

(i) If $\varepsilon = 0$, every β_i is 1. If G is orthogonal, $\gamma = 1$, so every μ_i and β_i is 1.

(ii) At $\mu_i = 1$, $\partial\log\beta_i/\partial\log\mu_i = \varepsilon/(r_i^2+\varepsilon)$, and $\frac{d}{dt}\log\gamma\big|_{t=0} = -h_\ell S h_\ell^\top/(d_{\text{model}}(r_\ell^2+\varepsilon))$, since $\|h_\ell e^{tS}\|^2 = \|h_\ell\|^2 + 2t\,h_\ell S h_\ell^\top + O(t^2)$. The chain rule along $\log\mu_{\ell+1} = k\log\gamma$, $\log\mu_{i+1} = k\log\beta_i$ and $\log\Lambda = \log\beta_L$ gives the product. □

Proof of Proposition A.1. (i) $(hUK)K^{-1}V = hUV$, and no other part of the network involves U or V. (ii) Fix a hidden state h_ℓ and apply the change of basis G there (Section 3.1). The writes into h_ℓ produce $h_\ell G$ in place of h_ℓ. A read that sees h_ℓ itself, such as the read of the identity units, computes $(h_\ell G)G^{-1}W = h_\ell W$. With pre-RMSNorm reads, a read sees $N(h_\ell G)$, which by Lemma A.2 equals $N(h_\ell)Q$ exactly when $G = cQ$ with Q orthogonal and $c = 1$ if $\varepsilon > 0$, and is then absorbed by $W \mapsto Q^\top W$. So nothing downstream changes, for every G in $\mathrm{GL}(d_{\text{model}})$ without normalization, in $\mathrm{CO}(d_{\text{model}})$ for $\varepsilon = 0$ and in $\mathrm{O}(d_{\text{model}})$ for $\varepsilon > 0$. With biases and without normalization, the affine change $h_\ell \mapsto h_\ell G + g$ is absorbed by $b_{\text{write}} \mapsto b_{\text{write}}G + g$ on the writes and by $(W, b) \mapsto (G^{-1}W,\ b - gG^{-1}W)$ on the reads, since $h_\ell W + b = (h_\ell G + g)G^{-1}W + b - gG^{-1}W$; this gives $\mathrm{Aff}(d_{\text{model}})$. (iii) The change of basis at the identity units of block ℓ multiplies U_ℓ on the right and V_ℓ on the left. The change at $h_{\ell-1}$ multiplies the reads of block ℓ, U_ℓ included, on the left, and the change at h_ℓ multiplies the writes of block ℓ, V_ℓ included, on the right. Multiplications on the left and on the right commute, and every matrix is multiplied on each side by the change at one junction only, so all these changes commute, and a matrix of the skipless network is touched by one hidden state only. The symmetries inside blocks (Section 4.2) multiply W_{read} on the right and W_{write} on the left, and commute with all of the above. □

A.2 The gauge fix (Theorems 3.2 and 3.3)

Theorems 3.2 and 3.3 collect what the main text uses of the following theorem. We write the parameters of a network of mixed blocks as $\theta = \big(E,\ (U_\ell, V_\ell, W^\ell_{\text{read}}, W^\ell_{\text{write}})_{\ell=1}^L,\ D\big)$, and those of a network with learned skips as $\big(E,\ (A_\ell, W^\ell_{\text{read}}, W^\ell_{\text{write}})_{\ell=1}^L,\ D\big)$. For invertible $G_0, \ldots, G_L$ and $K_1, \ldots, K_L$, let $T_{G,K}$ be the map

$$\begin{aligned} E &\mapsto EG_0, \qquad & W^\ell_{\text{read}} &\mapsto G_{\ell-1}^{-1}W^\ell_{\text{read}}, \qquad & W^\ell_{\text{write}} &\mapsto W^\ell_{\text{write}}G_\ell, \qquad & D &\mapsto G_L^{-1}D, \\ & & U_\ell &\mapsto G_{\ell-1}^{-1}U_\ell K_\ell, & V_\ell &\mapsto K_\ell^{-1}V_\ell G_\ell, & & \end{aligned} \tag{7}$$

which applies the change of basis G_ℓ at h_ℓ and K_ℓ at the identity units of block ℓ. On a network with learned skips, T_G acts by $A_\ell \mapsto G_{\ell-1}^{-1} A_\ell G_\ell$ in place of the second line. When every skip $A_\ell = U_\ell V_\ell$ is invertible, let $\Lambda_\ell = A_{\ell+1} \cdots A_L$, with $\Lambda_L = I$, and let

$$\Phi(\theta) = \big(E\Lambda_0,\ (\Lambda_{\ell-1}^{-1} W_{\text{read}}^\ell,\ W_{\text{write}}^\ell \Lambda_\ell)_{\ell=1}^L,\ D\big), \tag{8}$$

a parameter of the residual network, with the same formula for learned skips. With biases, Φ also sends the embedding bias b_E to $b_E\Lambda_0$ and each write bias b_{write}^ℓ to $b_{\text{write}}^\ell \Lambda_\ell$, and keeps each read bias. We write F_θ for the function of the network of mixed blocks at θ, and $F^{\text{res}}_{\Phi(\theta)}$ for that of the residual network at $\Phi(\theta)$.

Theorem A.4 (The gauge fix)**.** *Consider networks without normalization in (i) and (ii), and parameters θ whose skips A_ℓ are invertible.*
(i) Same function. *The maps $T_{G,K}$ preserve the function. With $G_\ell = \Lambda_\ell$ and $K_\ell = U_\ell^{-1}\Lambda_{\ell-1}$, $T_{G,K}$ sets every U_ℓ and V_ℓ to I and the other parameters to $\Phi(\theta)$, so $F_\theta = F^{\text{res}}_{\Phi(\theta)}$. For learned skips, T_G with $G_\ell = \Lambda_\ell$ sets every A_ℓ to I in the same way.*
(ii) What the gauge fix identifies. *Every parameter of the residual network is $\Phi(\theta)$ for some θ, and $\Phi(\theta) = \Phi(\theta')$ exactly when $\theta' = T_{G,K}(\theta)$ for some G and K with $G_L = I$. The derivative of Φ is onto at every θ. So the networks of mixed blocks with invertible skips and the residual networks compute the same set of functions, with the same functional dimension at θ and at $\Phi(\theta)$. The same holds for learned skips, without the K_ℓ, and for networks with biases.*
(iii) One change of basis is left. *With or without RMSNorm, let every block be nonzero for some value of its parameters, and let $G_0, \dots, G_L \in \mathcal{G}$. The map T_G of the embedding, the reads, the writes and the readout preserves the function of every residual network if and only if $G_0 = G_1 = \cdots = G_L$. Under RMSNorm with $\varepsilon = 0$, where $G_\ell = c_\ell Q_\ell$ with $c_\ell > 0$ and Q_ℓ orthogonal, T_G multiplies the reads and the readout by $Q_{\ell-1}^\top$ and $Q_L^\top$ in place of $G_{\ell-1}^{-1}$ and G_L^{-1}.*

Overview. Part (i) is an induction along the network: in the coordinates $h'_\ell = h_\ell \Lambda_\ell$ the identity units become identity skips, and we check that the residual recursion with transformed weights produces exactly these coordinates. Part (ii) lifts every direction on the residual side to one with the identity units held fixed, which makes the derivative of Φ onto, and solves for the maps $T_{G,K}$ that relate two parameters with the same image. Part (iii) switches off all branches but one, so that the output compares the bases on the two sides of that block, and a branch that is not identically zero forces them to agree. With biases every hidden state also carries a translation, which the skips do not tie (Lemma A.5).

Proof of Theorem A.4. Part (i), with biases and a skip bias. Merge the identity units, $A_\ell = U_\ell V_\ell$, and write the network as $h_\ell = h_{\ell-1}A_\ell + k_\ell + f_\ell(h_{\ell-1}W_{\text{read}}^\ell + b_{\text{read}}^\ell)W_{\text{write}}^\ell + b_{\text{write}}^\ell$ with $h_0 = xE + b_E$, where $k_\ell \in \mathbb{R}^{1\times d_{\text{model}}}$ is a skip bias ($k_\ell = 0$ is allowed). Every A_ℓ is invertible, hence every Λ_ℓ, and $\Lambda_{\ell-1} = A_\ell \Lambda_\ell$. Define new variables and new weights

$$h'_\ell = h_\ell \Lambda_\ell, \qquad E' = E\Lambda_0, \quad b'_E = b_E\Lambda_0, \qquad W'^\ell_{\text{read}} = \Lambda_{\ell-1}^{-1} W_{\text{read}}^\ell, \quad b'^\ell_{\text{read}} = b_{\text{read}}^\ell,$$
$$W'^\ell_{\text{write}} = W_{\text{write}}^\ell \Lambda_\ell, \quad b'^\ell_{\text{write}} = (b_{\text{write}}^\ell + k_\ell)\Lambda_\ell, \qquad D' = D.$$

We show by induction that the residual network with primed weights computes h'_ℓ. For $\ell = 0$, $h'_0 = (xE + b_E)\Lambda_0 = xE' + b'_E$. Assume $h'_{\ell-1} = h_{\ell-1}\Lambda_{\ell-1}$. The residual recursion with primed weights gives

$$\begin{aligned} &h'_{\ell-1} + f_\ell(h'_{\ell-1}W'^\ell_{\text{read}} + b'^\ell_{\text{read}})W'^\ell_{\text{write}} + b'^\ell_{\text{write}} \\ &\quad = h_{\ell-1}\Lambda_{\ell-1} + f_\ell(h_{\ell-1}W_{\text{read}}^\ell + b_{\text{read}}^\ell)W_{\text{write}}^\ell \Lambda_\ell + (b_{\text{write}}^\ell + k_\ell)\Lambda_\ell, \end{aligned}$$

and since $\Lambda_{\ell-1} = A_\ell\Lambda_\ell$ the right-hand side equals $h_\ell\Lambda_\ell$. Finally $h'_L D' = h_L D$ because $\Lambda_L = I$. This is the map $T_{G,K}$ of (7) with $G_\ell = \Lambda_\ell$ and $K_\ell = U_\ell^{-1}\Lambda_{\ell-1}$: it sends U_ℓ to $G_{\ell-1}^{-1}U_\ell K_\ell = I$ and V_ℓ to $K_\ell^{-1}V_\ell G_\ell = \Lambda_{\ell-1}^{-1}A_\ell\Lambda_\ell = I$, and the other matrices as above. For vanilla MLP blocks, these changes of basis are those of Proposition C.1 of Zhao et al. (2023), transposed to row vectors. Read

the network of mixed blocks as a feedforward network whose hidden layers alternate between the hidden states h_ℓ, with the identity as activation, and the hidden layers of the blocks, with the mixed activation $\tilde{f}\big(\big[\, u \;\big|\; z \,\big]\big) = \big[\, u \;\big|\; f(z) \,\big]$ of Section 2. The identity passes every matrix in $\mathrm{GL}(d_{\mathrm{model}})$ (their Example C.3), and $\tilde{f}$ passes $\mathrm{diag}(K, I)$ for every $K \in \mathrm{GL}(d_{\mathrm{model}})$, so their proposition gives these changes of basis G_ℓ and K_ℓ; for other blocks the same computation does. Propagating a change of basis through a skip is thus their change of basis at the identity units, chosen together with the changes of basis at the two hidden states that the skip joins. The forward version takes $G_\ell = \Pi_\ell^{-1}$ at h_ℓ, with $\Pi_\ell = A_1 \cdots A_\ell$ and $\Pi_0 = I$. By the same induction it gives the residual network with embedding E, reads $\Pi_{\ell-1} W_{\mathrm{read}}^\ell$, writes $W_{\mathrm{write}}^\ell \Pi_\ell^{-1}$, write biases $(b_{\mathrm{write}}^\ell + k_\ell)\Pi_\ell^{-1}$ and readout $\Pi_L D$. Any linear change of variables $h'_\ell = h_\ell K'_\ell$ that yields identity skips must satisfy $K'^{-1}_{\ell-1} A_\ell K'_\ell = I$, so $K'_\ell = \Lambda_\ell K'_L$: two such changes, the forward and the backward version among them, differ by a global change of basis and, when biases are present, by a translation at each hidden state (Lemma A.5).

Part (ii). The identity units carry no biases of their own, since these would only add to the write bias. For parameters θ of the mixed network with invertible A_ℓ, the map Φ of (8) is the change of variables of part (i) with $k_\ell = 0$, so $F_\theta = F^{\mathrm{res}}_{\Phi(\theta)}$. Every parameter of the residual network is reached: the θ with the same entries and $U_\ell = V_\ell = I$ has every $\Lambda_\ell = I$, so Φ returns these entries. The Fréchet derivative $\mathrm{D}_\theta \Phi(\theta)$ is onto at every θ. A direction η' of the residual parameters, with the entries η'_E, $\eta'^\ell_{\mathrm{read}}$, $\eta'^\ell_{\mathrm{write}}$ and η'_D at E', W'^ℓ_{read}, W'^ℓ_{write} and D', is $\mathrm{D}_\theta \Phi(\theta)\, \eta$ for the direction η of θ that is zero at every U_ℓ and V_ℓ and has the entries $\eta'_E \Lambda_0^{-1}$ at E, $\Lambda_{\ell-1} \eta'^\ell_{\mathrm{read}}$ at W^ℓ_{read}, $\eta'^\ell_{\mathrm{write}} \Lambda_\ell^{-1}$ at W^ℓ_{write} and η'_D at D, since along it every Λ_ℓ stays fixed; the biases are treated in the same way. The maps $T_{G,K}$ with $G_L = I$ send A_ℓ to $G_{\ell-1}^{-1} A_\ell G_\ell$ and hence Λ_ℓ to $G_\ell^{-1} \Lambda_\ell$, so they leave Φ unchanged. Conversely, let $\Phi(\theta') = \Phi(\theta)$, and set $G_\ell = \Lambda_\ell \Lambda'^{-1}_\ell$, so that $G_L = I$, and $K_\ell = U_\ell^{-1} G_{\ell-1} U'_\ell$. Then $E' = E G_0$, $W'^\ell_{\mathrm{read}} = G_{\ell-1}^{-1} W^\ell_{\mathrm{read}}$, $W'^\ell_{\mathrm{write}} = W^\ell_{\mathrm{write}} G_\ell$ and $D' = D$; $U'_\ell = G_{\ell-1}^{-1} U_\ell K_\ell$ by the choice of K_ℓ; and $A'_\ell = \Lambda'_{\ell-1} \Lambda'^{-1}_\ell = G_{\ell-1}^{-1} A_\ell G_\ell$ gives $V'_\ell = U'^{-1}_\ell A'_\ell = K_\ell^{-1} V_\ell G_\ell$. So $\theta' = T_{G,K}(\theta)$. Since $F_\theta = F^{\mathrm{res}}_{\Phi(\theta)}$ and every residual parameter is reached, the two networks compute the same functions. For every batch of inputs, the Jacobian of the mixed network at θ is the Jacobian of the residual network at $\Phi(\theta)$ times the derivative of Φ, by the chain rule; a matrix times a matrix that is onto has the rank of the first, so the two Jacobians have the same rank, and the two networks the same functional dimension. For learned skips the same argument applies without the K_ℓ.

Part (iii). A single global G is a symmetry: the skip carries $h_{\ell-1} G$ to $h_{\ell-1} G$, and the branch becomes $B_\ell(\,\cdot\, G^{-1})\, G$. Conversely, let $G_0, \ldots, G_L$ preserve the function for all parameter values; the change of basis conjugates each branch, $B_\ell \mapsto B_\ell(\,\cdot\, G_{\ell-1}^{-1})\, G_\ell$. First set every write W^k_{write}, and its bias if there is one, to zero. The network computes $x \mapsto xED$ and the transformed network $x \mapsto xEG_0 G_L^{-1} D$, and these agree for all D and E only if $G_L = G_0$. Now suppose $G_0 = \cdots = G_{\ell-1} =: G$ and set every write except that of block ℓ to zero. Then $h_L = h_{\ell-1} + B_\ell(h_{\ell-1})$ with $h_{\ell-1} = xE$, block ℓ reads $h_{\ell-1} G G_{\ell-1}^{-1} = h_{\ell-1}$, and the transformed network outputs $\big(h_{\ell-1} G + B_\ell(h_{\ell-1})\, G_\ell\big) G^{-1} D$. Equality with $\big(h_{\ell-1} + B_\ell(h_{\ell-1})\big) D$ for all D gives $B_\ell(h)\,(G_\ell G^{-1} - I) = 0$ for all h and all parameters of block ℓ. As the write of block ℓ ranges over all matrices, the outputs of a block whose computation does not vanish identically span $\mathbb{R}^{d_{\mathrm{model}}}$, so $G_\ell = G$, and by induction all G_ℓ are equal. With pre-RMSNorm reads the argument is the same, with each read transformed by the orthogonal factor of the change of basis (Section 2); when $\varepsilon = 0$ the first step compares only the orthogonal factors, since the readout sees $N(h_L)$, and the second step, in which the write of block ℓ can be scaled freely, equates the scales as well. □

We recall Theorem 3.2 from Section 3.2, where $\Lambda_\ell = A_{\ell+1} \cdots A_L$, and Theorem 3.3 from Section 3.3.

Theorem 3.2 (Learned skips are identity skips)**.** *Without normalization, let every learned skip A_ℓ be invertible. The network with learned skips computes the same function as the residual network with the embedding $E\Lambda_0$, the reads $\Lambda_{\ell-1}^{-1} W^\ell_{\mathrm{read}}$, the writes $W^\ell_{\mathrm{write}} \Lambda_\ell$ and the readout D.*

Proof of Theorem 3.2. This is the statement for learned skips in Theorem A.4(i), with $\Phi(\theta)$ written out by (8). □

Theorem 3.3 (One change of basis is left)**.** *Without normalization, let every block be nonzero for some value of its parameters, and let $G, G_0, \dots, G_L$ be invertible.*
(i) *The map $E \mapsto EG_0$, $W^\ell_{\text{read}} \mapsto G_{\ell-1}^{-1} W^\ell_{\text{read}}$, $W^\ell_{\text{write}} \mapsto W^\ell_{\text{write}} G_\ell$, $D \mapsto G_L^{-1} D$ preserves the function of every residual network if and only if $G_0 = G_1 = \cdots = G_L$.*
(ii) *The changes of basis that preserve the function at all parameters form a group of dimension $(L+1)d^2_{\text{model}}$ in a skipless network and d^2_{model} in a residual one.*
(iii) *In a residual network, the change of basis G at every hidden state preserves the function, and for $G = W_1$, with W_1 formed by d_{model} columns of any one read, it turns W_1 into the identity.*

Proof of Theorem 3.3. Part (i) is Theorem A.4(iii) with $\mathcal{G} = \mathrm{GL}(d_{\text{model}})$, part (ii) is Theorem A.9(i) with $\dim \mathcal{G} = d^2_{\text{model}}$, and part (iii) is Proposition A.6(ii). □

Lemma A.5 (Translations are not tied)**.** *In a residual network with biases and without normalization, a translation $h_\ell \mapsto h_\ell + g$ of any single hidden state preserves the function once the biases are adjusted. The symmetry group generated by changes of basis, translations and the symmetries inside blocks therefore has dimension $d^2_{\text{model}} + (L+1)d_{\text{model}} + s$, against $(L+1)(d^2_{\text{model}} + d_{\text{model}}) + s$ without skips, and the skips remove Ld^2_{model} dimensions, as without biases. Under RMSNorm no translation is a symmetry.*

Proof. Add g to the write bias of block ℓ, or to the embedding bias when $\ell = 0$; subtract gW^k_{read} from the read bias of every block $k > \ell$; subtract gD from the readout bias. The skips carry g forward unchanged, and every downstream read removes it, so the function is unchanged. Each hidden state therefore keeps its own translation with or without skips, and a skip ties only the linear part of $\mathrm{Aff}(d_{\text{model}})$, which gives the counts. Under RMSNorm a translation changes $N(h)$ by an amount that depends nonlinearly on h, which no read can undo. □

The checks give redundancies of 80 without skips and 32 with them ($\tanh$ networks with biases, $d_{\text{model}} = 4$, $L = 3$; Appendix E), and a translation at a single interior hidden state changes the function by a relative 2×10^{-16}.

A.3 One free block per hidden state (Proposition 3.1)

The following proposition is the general form of Proposition 3.1. Let W_1 be an invertible $d_{\text{model}} \times d_{\text{model}}$ block formed by d_{model} columns of a matrix that reads h_ℓ, or by d_{model} rows of a matrix that writes it.

Proposition A.6 (One free block per hidden state)**.** **(i)** *In a skipless network or a network of mixed blocks, the map $W \mapsto WG$ on the matrices that write h_ℓ and $W \mapsto G^{-1}W$ on those that read it turns W_1 into the identity for $G = W_1$ if W_1 is part of a read, and for $G = W_1^{-1}$ if it is part of a write. Under RMSNorm with $\varepsilon > 0$, $G = Q$ from a QR factorization $W_1 = QT$, or $W_1^\top = QT$ for a write, turns W_1 into a triangular matrix. Done at every hidden state, this removes d^2_{model}, respectively $d_{\text{model}}(d_{\text{model}} - 1)/2$, parameters per hidden state without changing the function.*
(ii) *In a residual network, the same map with one G at all hidden states preserves the function and turns one such block, in any read or write of the network, into the identity or a triangular matrix.*

Overview. The proposition spends the change of basis of Proposition A.1 at each hidden state on one square block of a read or of a write: the change of basis given by that block, or by its orthogonal factor under normalization, turns it into the identity or into a triangular matrix.

Proof of Proposition A.6. By Proposition A.1, a change of basis $G \in \mathcal{G}$ at h_ℓ preserves the function and replaces every read W of h_ℓ by $G^{-1}W$ and every write W into h_ℓ by WG. So the columns of a read that form W_1 become $G^{-1}W_1$, and the rows of a write that form W_1 become W_1G. Without normalization $\mathcal{G} = \mathrm{GL}(d_{\text{model}})$, and $G = W_1$ for a read, or $G = W_1^{-1}$ for a write, turns W_1 into I. Under RMSNorm with $\varepsilon > 0$, $\mathcal{G} = \mathrm{O}(d_{\text{model}})$ (Lemma A.2). For a read, let $W_1 = QT$ be a QR factorization, with T upper triangular; $G = Q$ gives $Q^\top W_1 = T$. For a write, let $W_1^\top = Q_0 R$ be a QR factorization; then $Q = Q_0^\top$ is orthogonal, $T = R^\top$ is lower triangular, $W_1 = TQ$, and

$G = Q^\top$ gives $W_1 Q^\top = T$. The identity fixes all d_{model}^2 entries of W_1, and the triangular form fixes the $d_{\text{model}}(d_{\text{model}} - 1)/2$ entries on one side of its diagonal. The change of basis at h_ℓ touches only the writes into h_ℓ and the reads of h_ℓ, and a matrix is touched on each side by one hidden state only (Proposition A.1(iii)), so the reductions at all hidden states can be made together, one block per hidden state. In a residual network, one change of basis $G \in \mathcal{G}$ applied at every hidden state preserves the function (Theorem A.4(iii)); it replaces every read W by $G^{-1}W$ and every write W by WG, and leaves the identity skips unchanged, since $G^{-1}IG = I$. The same choice of G then turns one block W_1, of any one layer, into the identity or into a triangular matrix. □

We recall Proposition 3.1 from Section 3.1.

Proposition 3.1 (One free submatrix per hidden state)**.** *Without normalization, the change of basis $G = W_1$ at h_ℓ preserves the function of a skipless network and turns W_1 into the identity. At generic parameters every hidden state has such a W_1, and doing this at every hidden state removes $(L+1)d_{\text{model}}^2$ parameters.*

Proof of Proposition 3.1. This is Proposition A.6(i) without normalization, for a block of a read. □

A.4 RMSNorm (Theorem 3.4)

Theorem 3.4(iv) is a case of the following theorem. Let $\Pi_\ell = A_1 \cdots A_\ell$, with $\Pi_0 = I$.

Theorem A.7 (RMSNorm with learned skips)**.** *Consider pre-RMSNorm networks with $\varepsilon \geq 0$, and the network with learned skips of (6), whose skips A_ℓ are invertible in (i) and (ii).*
(i) Triangular or symmetric skips. *Let $Q_0 = I$, and for $\ell = 1, \ldots, L$ let $Q_{\ell-1}^\top A_\ell = R_\ell Q_\ell^\top$ be an RQ factorization, with R_ℓ upper triangular with positive diagonal and Q_ℓ orthogonal. The network with the skips R_ℓ, the reads $Q_{\ell-1}^\top W_{\text{read}}^\ell$, the writes $W_{\text{write}}^\ell Q_\ell$ and the readout $Q_L^\top D$ computes the same function. So does the network built in the same way from the polar decompositions $Q_{\ell-1}^\top A_\ell = S_\ell Q_\ell^\top$, with S_ℓ symmetric positive definite in place of R_ℓ.*
(ii) Orthogonal skips are gauge. *If every Π_ℓ lies in $\mathcal{G}$, write $\Pi_\ell = c_\ell P_\ell$ with $c_\ell > 0$ and P_ℓ orthogonal, where $c_\ell = 1$ if $\varepsilon > 0$. Then the network computes the same function as the residual network with the embedding E, the reads $P_{\ell-1} W_{\text{read}}^\ell$, the writes $W_{\text{write}}^\ell \Pi_\ell^{-1}$ and the readout $P_L D$. Conversely, let the reads and the readout have rank d_{model}, and let invertible $G_0, \ldots, G_L$ turn every skip into the identity, $G_{\ell-1}^{-1} A_\ell G_\ell = I$. If the network, written in the variables $h_\ell G_\ell$, is a pre-RMSNorm residual network, then every Π_ℓ lies in $\mathcal{G}$.*
(iii) What each skip adds. *Under the equality condition for the networks with learned skips, with identity skips and without skips, the functional dimension of the network with learned skips exceeds that of the residual network by $L\,(d_{\text{model}}^2 - \dim \mathcal{G})$, and that of the residual network exceeds that of the skipless network by $L \dim \mathcal{G}$. These are $L\, d_{\text{model}}(d_{\text{model}}+1)/2$ and $L\, d_{\text{model}}(d_{\text{model}}-1)/2$ for $\varepsilon > 0$, and $L\,(d_{\text{model}}(d_{\text{model}}+1)/2 - 1)$ and $L\,(d_{\text{model}}(d_{\text{model}}-1)/2 + 1)$ for $\varepsilon = 0$.*

Overview. Part (i) runs the sweep in the proof of Theorem A.4(i) forward, with orthogonal matrices only, which remove the orthogonal factor of each skip and leave its triangular or symmetric factor. Part (ii) reruns the change of variables of that proof and locates the only step that can fail, the read through N; Lemma A.2 says exactly when a matrix can be moved through N. Part (iii) counts the symmetries with Proposition A.1 and Theorem A.9.

Proof of Theorem A.7. Part (i). For every $\varepsilon \geq 0$, multiplying the writes into h_ℓ, the skip A_ℓ included, on the right by an orthogonal Q_ℓ, and the reads of h_ℓ on the left by $Q_\ell^\top$, preserves the function (Proposition A.1(ii)): the raw read $A_{\ell+1}$ directly, and the reads through N because $N(hQ_\ell) = N(h)Q_\ell$ (Lemma A.2). With $Q_0 = I$ and the Q_ℓ of the statement, the skip A_ℓ becomes $Q_{\ell-1}^\top A_\ell Q_\ell = R_\ell$; the RQ factorization of the invertible matrix $Q_{\ell-1}^\top A_\ell$ exists, and is unique. The same computation with the polar decompositions gives $Q_{\ell-1}^\top A_\ell Q_\ell = S_\ell$: every invertible matrix X is $X = SQ^\top$ with $S = (XX^\top)^{1/2}$ symmetric positive definite and $Q^\top = S^{-1}X$ orthogonal, uniquely. The readout absorbs the last factor, $D \mapsto Q_L^\top D$. The recursion can also start at any h_k with any orthogonal Q_k, running forward as above for $\ell > k$ and backward for $\ell \leq k$ with the QR factorization

$A_\ell Q_\ell = Q_{\ell-1} R_\ell$ or the polar decomposition $A_\ell Q_\ell = Q_{\ell-1} S_\ell$; the embedding absorbs Q_0. With Q_k the rotation of Proposition A.6(i) for one block of a read or a write of h_k, that block becomes triangular too, and $(L+1)d_{\text{model}}(d_{\text{model}}-1)/2$ parameters are removed in all. If Q_0 and Q_L are fixed, as with a tied readout, the recursions from h_0 forward and from h_L backward meet at any one skip, which keeps its full matrix; without normalization the same holds in $\mathrm{GL}(d_{\text{model}})$, with identities in place of the R_ℓ.

Part (ii). Let the network be $h_\ell = h_{\ell-1} A_\ell + f_\ell(N(h_{\ell-1}) W^\ell_{\text{read}}) W^\ell_{\text{write}}$ and set $h'_\ell = h_\ell \Pi_\ell^{-1}$, the forward version of the change of variables in the proof of Theorem A.4(i), which turns every skip into the identity. The read of block ℓ in the new variables is $N(h'_{\ell-1}\Pi_{\ell-1}) W^\ell_{\text{read}}$. If every Π_ℓ, $\ell = 0, \dots, L$, lies in $\mathcal{G}$, Lemma A.2 gives $N(h'\Pi_{\ell-1}) = N(h')P_{\ell-1}$, so the reads $P_{\ell-1} W^\ell_{\text{read}}$, the writes $W^\ell_{\text{write}} \Pi_\ell^{-1}$ and the readout $P_L D$, since the readout reads $N(h_L)$, reproduce the induction of that proof, and the result is a pre-RMSNorm residual network. Conversely, $G_{\ell-1}^{-1} A_\ell G_\ell = I$ for every ℓ gives $G_\ell = \Pi_\ell^{-1} G_0$, so in the variables $h'_\ell = h_\ell G_\ell$ block ℓ reads $N(h'_{\ell-1} G_0^{-1} \Pi_{\ell-1}) W^\ell_{\text{read}}$, and the readout reads $N(h'_L G_0^{-1} \Pi_L)$. In a pre-RMSNorm residual network every read has the form $N(h')W$; as the reads and the readout have rank d_{model}, this gives matrices M_ℓ with $N(h' G_0^{-1} \Pi_\ell) = N(h') M_\ell$ for all h', and Lemma A.2 puts every $G_0^{-1}\Pi_\ell$ in $\mathcal{G}$. For $\ell = 0$ this puts G_0 in $\mathcal{G}$, and so every Π_ℓ lies in $\mathcal{G}$.

Part (iii). Apply Proposition A.1 to the pre-RMSNorm network with learned skips: the skip A_ℓ absorbs any change of basis, and the normalized reads restrict it to $\mathcal{G}$, which is $\mathrm{CO}(d_{\text{model}})$ when $\varepsilon = 0$ and $\mathrm{O}(d_{\text{model}})$ when $\varepsilon > 0$ (Lemma A.2), so each of the $L+1$ hidden states carries its own copy of $\mathcal{G}$. The network with learned skips has $L d_{\text{model}}^2$ more parameters than the residual network and L more copies of $\mathcal{G}$ in its symmetry group. If both satisfy the equality condition, the difference of their functional dimensions is therefore $L\,(d_{\text{model}}^2 - \dim \mathcal{G})$, which is $L\, d_{\text{model}}(d_{\text{model}}+1)/2$ when $\varepsilon > 0$ and $L\,(d_{\text{model}}(d_{\text{model}}+1)/2 - 1)$ when $\varepsilon = 0$. The difference between the residual and the skipless network is $L \dim \mathcal{G}$ by Theorem A.9(iii), which is $L\, d_{\text{model}}(d_{\text{model}}-1)/2$ when $\varepsilon > 0$ and $L\,(d_{\text{model}}(d_{\text{model}}-1)/2 + 1)$ when $\varepsilon = 0$. □

We recall Theorem 3.4 from Section 3.4.

Theorem 3.4 (Triangles under RMSNorm)**.** *Consider pre-RMSNorm networks.*
(i) *In a skipless network, let $W_1 = QR$, with Q orthogonal and R upper triangular. The change of basis Q at h_ℓ preserves the function and turns W_1 into R. Done at every hidden state, this removes $(L+1)d_{\text{model}}(d_{\text{model}}-1)/2$ parameters.*
(ii) *Theorem 3.3(i) and (ii) hold for orthogonal $G_0, \dots, G_L$, with $d_{\text{model}}(d_{\text{model}}-1)/2$ in place of d_{model}^2.*
(iii) *In a residual network, the change of basis Q at every hidden state preserves the function and turns W_1, d_{model} columns of any one read, into R.*
(iv) Triangular skips. *If every learned skip A_ℓ is invertible, there are orthogonal $Q_1, \dots, Q_L$, with $Q_0 = I$, such that every $Q_{\ell-1}^\top A_\ell Q_\ell$ is upper triangular, and the network with these skips, the reads $Q_{\ell-1}^\top W^\ell_{\text{read}}$, the writes $W^\ell_{\text{write}} Q_\ell$ and the readout $Q_L^\top D$ computes the same function.*

Proof of Theorem 3.4. For $\varepsilon > 0$, $\mathcal{G} = \mathrm{O}(d_{\text{model}})$ (Lemma A.2). Part (i) is Proposition A.6(i). In part (ii), Theorem 3.3(i) for orthogonal G_ℓ is Theorem A.4(iii), and Theorem 3.3(ii) is Theorem A.9(i) with $\dim \mathcal{G} = d_{\text{model}}(d_{\text{model}}-1)/2$. Part (iii) is Proposition A.6(ii), and part (iv) is Theorem A.7(i). □

A.5 LayerNorm reduces to RMSNorm (Proposition A.8)

The reduction of LayerNorm to RMSNorm is standard: the centering folds into the adjacent weights (Elhage et al., 2021), and centering every write gives an RMSNorm network whose hidden states are mean-free (Ashkboos et al., 2024a; Theus et al., 2025). We state it with the constants that the counts need. It is used in Section 3.4 and for ViT-B in Section 3.5 and Appendix D.

Proposition A.8 (LayerNorm reduces to RMSNorm)**.** *Let $Z = I - \frac{1}{d_{\text{model}}} \mathbf{1}\mathbf{1}^\top$ and $\mathcal{V} = \mathbf{1}^\perp$, and consider a pre-LayerNorm network, skipless or residual, whose reads and readout see $\mathrm{LN}(h) = \gamma \odot hZ / \sqrt{\|hZ\|^2/d_{\text{model}} + \varepsilon} + \beta$, with h, γ and β row vectors.*

(i) *Replacing each read W by $\mathrm{diag}(\gamma)W$ with the added bias βW, and each write W, write bias b and embedding E by WZ, bZ and EZ, gives a network that computes the same function, whose hidden states lie in $\mathcal{V}$, and whose reads see $N(h) = h/\sqrt{\|h\|^2/d_{\mathrm{model}} + \varepsilon}$.*
(ii) *In an orthonormal basis of $\mathcal{V}$, this network is a pre-RMSNorm network of width $d_{\mathrm{model}} - 1$, with every read multiplied by $\sqrt{d_{\mathrm{model}}/(d_{\mathrm{model}} - 1)}$ and ε replaced by $\varepsilon d_{\mathrm{model}}/(d_{\mathrm{model}} - 1)$.*
(iii) *If the gains γ have nonzero entries, the difference in redundancy between the skipless and the residual version of the LayerNorm network equals the difference for the reduced networks of (ii).*

Overview. LayerNorm sees only the mean-free part of the stream, so the mean can be removed from every write without changing the function. On the mean-free subspace LayerNorm is RMSNorm up to constants. The map from the parameters of the LayerNorm network to those of the reduced network has a derivative that is onto, and it is the same for the skipless and the residual version, so it preserves the difference in redundancy.

Proof. (i) Since $\mathrm{LN}(h) = \gamma \odot N(hZ) + \beta$, a read satisfies $\mathrm{LN}(h)\, W = N(hZ)\,\mathrm{diag}(\gamma)W + \beta W$. Every hidden state is a sum of writes, directly in a skipless network and through the skips in a residual one, so replacing every write, write bias and the embedding by its image under Z replaces every hidden state h by hZ. Since $Z^2 = Z$, every read then sees the same $N(hZ)$ as before, and the function is unchanged; the hidden states lie in $\mathcal{V}$. (ii) Let the columns of $\bar{U} \in \mathbb{R}^{d_{\mathrm{model}} \times (d_{\mathrm{model}}-1)}$ be an orthonormal basis of $\mathcal{V}$ and $h = y\bar{U}^\top$ with a row vector y. Then $\|h\|^2/d_{\mathrm{model}} + \varepsilon = \frac{d_{\mathrm{model}}-1}{d_{\mathrm{model}}}\big(\|y\|^2/(d_{\mathrm{model}} - 1) + \varepsilon d_{\mathrm{model}}/(d_{\mathrm{model}} - 1)\big)$, so $N(y\bar{U}^\top) = \sqrt{d_{\mathrm{model}}/(d_{\mathrm{model}} - 1)}\, N'(y)\bar{U}^\top$, where N' is RMSNorm of dimension $d_{\mathrm{model}} - 1$ with constant $\varepsilon d_{\mathrm{model}}/(d_{\mathrm{model}} - 1)$. A read $N(y\bar{U}^\top)W$ is the read $\sqrt{d_{\mathrm{model}}/(d_{\mathrm{model}} - 1)}\,\bar{U}^\top W$ of $N'(y)$, and a write WZ is the write $W\bar{U}$ in the coordinates y. (iii) The reduced parameters are $\sqrt{d_{\mathrm{model}}/(d_{\mathrm{model}} - 1)}\,\bar{U}^\top \mathrm{diag}(\gamma)W$ and $b + \beta W$ for each read, $W\bar{U}$ and $b\bar{U}$ for each write, $E\bar{U}$ for the embedding, and the analogous expressions for the readout. For γ with nonzero entries each is linear and onto in W, b or E, so the derivative of the map from the parameters of the LayerNorm network to those of the reduced network is onto. The LayerNorm network computes the reduced network's function composed with this map, so by the chain rule every batch Jacobian of the LayerNorm network is that of the reduced network times this derivative, and at corresponding parameters both have the same functional dimension, and the redundancy of the LayerNorm network is that of the reduced network plus the difference of the parameter counts. That difference is the same for the skipless and the residual versions, which have the same shapes. □

Section 6 of the notebook (Appendix E) checks each step on a residual pre-LayerNorm network with $d_{\mathrm{model}} = 6$: folding the gains changes the function by a relative 2×10^{-16}, centering the writes by 2×10^{-16}, and an orthogonal change of basis on $\mathcal{V}$ by 8×10^{-16}, while a generic orthogonal change that moves $\mathbf{1}$ changes it by 0.75.

A.6 What the skips unlock (Theorem 4.1)

Theorem 4.1 and Theorem 3.3(ii) are parts of the following theorem. The changes of basis and the symmetries inside blocks act *freely* at θ if no continuous family of them, other than the identity, fixes θ.

Theorem A.9 (What the skips remove)**. (i)** *The changes of basis that preserve the function at all parameters form a group of dimension $(L + 1)\dim \mathcal{G}$ in a skipless network and $\dim \mathcal{G}$ in a residual one, so the L skips remove $L \dim \mathcal{G}$ dimensions of symmetry.*
(ii) *If in both networks the symmetries act freely at generic parameters, the functional dimension at these parameters is at most $P - (L + 1)\dim \mathcal{G} - s$ without skips and $P - \dim \mathcal{G} - s$ with them.*
(iii) *If in addition both networks satisfy the equality condition, the skips raise the functional dimension by exactly $L \dim \mathcal{G}$, which is Ld_{model}^2 without normalization.*

Overview. Part (i) counts copies of $\mathcal{G}$: one per hidden state without skips, by Proposition A.1, and one with them, by Theorem A.4(iii). Part (ii) bounds the rank of every batch Jacobian by the number of parameters minus the number of independent directions in which the symmetries move

the parameters, which is the dimension of the symmetries when they act freely; Lemma A.10 proves that they do when the embedding has rank d_{model} and every block has width at least d_{model}. Part (iii) turns both bounds into equalities under the equality condition and subtracts.

Table 3: Parameters, dimension of the symmetries and, under the equality condition, functional dimension of the networks of Section 2, without normalization or biases; P counts the parameters of the skipless network. Each step of the gauge fix removes as many parameters as dimensions of symmetry, while deleting the identity units removes $2Ld_{\text{model}}^2$ parameters but only Ld_{model}^2 dimensions of symmetry. Given the value for the residual network, the others below it hold at corresponding parameters without further assumption (Theorem A.4(ii), Proposition A.6(ii)).

Network	Parameters	Symmetry	Functional dimension
skipless	P	$(L+1)d_{\text{model}}^2 + s$	$P - (L+1)d_{\text{model}}^2 - s$
mixed, with trainable identity units	$P + 2Ld_{\text{model}}^2$	$(2L+1)d_{\text{model}}^2 + s$	$P - d_{\text{model}}^2 - s$
learned skips	$P + Ld_{\text{model}}^2$	$(L+1)d_{\text{model}}^2 + s$	$P - d_{\text{model}}^2 - s$
residual	P	$d_{\text{model}}^2 + s$	$P - d_{\text{model}}^2 - s$
residual, one block fixed	$P - d_{\text{model}}^2$	s	$P - d_{\text{model}}^2 - s$

Lemma A.10 (Free action)**.** *Consider an MLP network, skipless or residual, without normalization or with pre-RMSNorm, with vanilla MLP blocks with* tanh*, GELU, ReLU or ReLU^2 activations, or with gated blocks with any gate, and the symmetries inside blocks of Section 4.2. If the embedding has rank d_{model} and every block has width at least d_{model}, then at generic parameters the changes of basis and the symmetries inside blocks act freely. The same holds if the readout has rank d_{model} and every block has width at least d_{model}.*

Proof. Permutations and sign flips are isolated, so it suffices to consider changes of basis and rescalings close to the identity. Let changes of basis $G_0, \dots, G_L$ and positive rescalings c_ℓ of hidden units (for ReLU and ReLU^2), of gates and values (for ReGLU) or of values (for the other gated blocks) fix a generic θ; for tanh and GELU there are no c_ℓ. The embedding transforms as $E \mapsto EG_0$, and E has rank d_{model}, so $G_0 = I$. Suppose $G_{\ell-1} = I$. The read of block ℓ then transforms as $W_{\text{read}}^\ell \mapsto W_{\text{read}}^\ell \operatorname{diag}(c_\ell)$, with entries 1 on the columns that are not rescaled, and no column of a generic W_{read}^ℓ vanishes, so $c_\ell = \mathbf{1}$. The write then transforms as $W_{\text{write}}^\ell \mapsto W_{\text{write}}^\ell G_\ell$, and W_{write}^ℓ has rank d_{model} because the block has width at least d_{model}, so $G_\ell = I$. By induction only the identity fixes θ. In a residual network the G_ℓ are equal (Theorem A.4(iii)) and the same argument applies. The second statement follows by the mirror induction from the readout, $D \mapsto G_L^{-1} D$: rescalings act freely on the rows of a generic write, except that for ReGLU a row fixes only the product cc' of the gate and value scales of its unit; each read, of rank d_{model} and with generic columns, then forces $G_{\ell-1} = I$ and the remaining scales to be 1. With RMSNorm the changes of basis lie in $\mathrm{CO}(d_{\text{model}})$ or $\mathrm{O}(d_{\text{model}})$, and the argument is unchanged. The width condition is needed: at a hidden state of a skipless network that is written and read at rank $m < d_{\text{model}}$, the changes of basis that fix the parameters form a family of dimension $(d_{\text{model}} - m)^2$, so they move the parameters in only $2d_{\text{model}}m - m^2$ independent directions, as Zhao et al. (2023, Proposition C.3) compute for one hidden layer. □

Remark A.11 (Attention blocks)*.* The lemma extends to transformers. Attention blocks also carry the per-head symmetries of Section 4.2, whose full group is characterized by Wang and Wang (2025) and which are not our subject. Once the input basis is fixed they act freely on $W_{Q,i}$ and $W_{V,i}$, which have full column rank, and the write W_O has rank d_{model}, so the forward induction goes through; in a mixture of experts the writes of all experts together have rank d_{model}. A numerical check on small skipless transformers confirms free action, including cases beyond the reach of the induction (Section 6 of the notebook, Appendix E).

Proof of Theorem A.9. Parts (i) and (ii). If a family of transformations of the parameters leaves the function unchanged, then the function does not change to first order along any direction in which the family moves θ, so these directions lie in the kernel of every batch Jacobian at θ, and the functional

dimension is at most P minus their number. For a skipless network, Proposition A.1 gives $L+1$ independent copies of $\mathcal{G}$, one per hidden state, and the directions in which they move θ are linearly independent of one another and of those of the symmetries inside blocks at generic parameters: the change of basis at h_ℓ multiplies W^ℓ_{write} on the right and $W^{\ell+1}_{\text{read}}$ on the left, the symmetries inside block ℓ multiply W^ℓ_{read} on the right and W^ℓ_{write} on the left, and by hypothesis they act freely at generic parameters (Lemma A.10). The number of independent directions is therefore $(L+1)\dim\mathcal{G}+s$. For a residual network, Theorem A.4(iii) leaves one copy, and the same argument gives $\dim\mathcal{G}+s$. *Part (iii).* Under the hypothesis, the inequalities of part (ii) are equalities, so the generic functional dimensions are $P-(L+1)\dim\mathcal{G}-s$ and $P-\dim\mathcal{G}-s$, and the difference is $L\dim\mathcal{G}$, which is d^2_{model} per skip without normalization, and with RMSNorm $d_{\text{model}}(d_{\text{model}}-1)/2$ when $\varepsilon>0$ and $d_{\text{model}}(d_{\text{model}}-1)/2+1$ when $\varepsilon=0$ (Lemma A.2); with biases the translations are redundant in both networks and the difference is again Ld^2_{model} (Lemma A.5). A network with learned skips without normalization has $P+Ld^2_{\text{model}}$ parameters and $L+1$ independent copies of $\mathrm{GL}(d_{\text{model}})$, since each A_ℓ absorbs $A_\ell \mapsto G_{\ell-1}^{-1}A_\ell G_\ell$; under the same hypothesis its functional dimension is $P+Ld^2_{\text{model}}-(L+1)d^2_{\text{model}}-s=P-d^2_{\text{model}}-s$, the same as the residual network, in agreement with Theorem A.4(ii). □

We recall Theorem 4.1 from Section 4.2.

Theorem 4.1 (What the skips unlock)**. (i)** *At generic parameters, the functional dimension is at most $P-(L+1)\dim\mathcal{G}-s$ without skips and at most $P-\dim\mathcal{G}-s$ with identity skips.*
(ii) *If both bounds are attained, the skips raise the functional dimension by exactly $L\dim\mathcal{G}$.*

Proof of Theorem 4.1. Within the scope of Section 2, the symmetries act freely at generic parameters (Lemma A.10, Remark A.11). So part (i) is Theorem A.9(ii), and part (ii) is Theorem A.9(iii). □

A.7 Depth (Theorems 4.3, 4.4 and 4.5)

Theorem A.14 below and Theorem 4.3 rest on two lemmas. The first turns a gap in functional dimension into disjointness. The second shows that with small writes the Jacobian of a residual network reaches the largest rank that its symmetries allow, by the argument of Theorem B.1 for one block.

Lemma A.12 (A rank criterion)**.** *Let $\theta\mapsto F_\theta$, $\theta\in\mathbb{R}^P$, and $\eta\mapsto G_\eta$, $\eta\in\mathbb{R}^{P'}$, be two families of networks with the same inputs and outputs, whose outputs are real-analytic in the parameters. Let a Lie group act smoothly on $\mathbb{R}^{P'}$ without changing G_η, with orbits of dimension at least k at generic η. If at some θ_0 the Jacobian of $\theta\mapsto(F_\theta(x))_{x\in X}$ has rank greater than $P'-k$ on some finite batch X, then for almost every θ no η satisfies $F_\theta=G_\eta$.*

Proof. Write $F_X(\theta), G_X(\eta)\in\mathbb{R}^n$ for the outputs on X. At generic η the map G_X is constant along an orbit of dimension at least k, so its Jacobian has rank at most $r_0=P'-k$; the rank is lower semicontinuous, so the bound holds at every η. The Jacobian of F_X reaches its largest rank r^*, which exceeds r_0 by hypothesis, outside the zero set of the sum of the squares of its minors of size r^*. This function is analytic and not identically zero, so its zero set has measure zero. Take θ outside it. By the constant rank theorem, F_X maps a neighborhood U of θ onto an embedded manifold Y of dimension r^*, and after shrinking U a linear projection $\pi:\mathbb{R}^n\to\mathbb{R}^{r^*}$ maps Y diffeomorphically onto an open set. The map $\pi\circ G_X$ has rank at most $r_0<r^*$, so all its values are critical, and by Sard's theorem its image has measure zero. So $G_X(\mathbb{R}^{P'})\cap Y$ has measure zero in Y, and so does its preimage under F_X in U, which contains every θ' in U with $F_{\theta'}=G_\eta$ for some η. Countably many such U cover the complement of the zero set. □

Lemma A.13 (Small writes)**.** *Let $d_{\text{model}}\geq 2$, let E and D have rank d_{model}, and let each block, in any order and of any width, be an attention block with heads of width at most d_{model}, causal or not, on sequences of at least two tokens, or an MLP block, with all MLP blocks* tanh*, all GELU, all SwiGLU or all GeGLU blocks. At generic parameters, multiply every write, and every write bias, by τ. For all small $\tau\neq 0$ the residual network without biases has functional dimension*

$P - d_{\text{model}}^2 - s$ *without normalization and* $P - d_{\text{model}}(d_{\text{model}} - 1)/2 - s$ *under pre-RMSNorm with* $\varepsilon > 0$*. Without normalization and attention blocks, biases lower the first value by* $(L+1)d_{\text{model}}$*. Without an embedding, a readout, biases and normalization it has functional dimension* $P - s$*.*

Proof. Write the write of block ℓ, for an attention block its output projection, as τV_ℓ. Let $W = [\, W_{\text{read}}^1 \mid \cdots \mid W_{\text{read}}^L \,]$ place the reads of the MLP blocks side by side and V stack their V_ℓ, so that $f(nW)V$ is one wide block that holds all units of the network, and let the heads of all attention blocks form one attention block. Divide the columns of the Jacobian that belong to the reads, for attention blocks the queries, keys and values, and to the read biases by τ, which keeps its rank, and let $\tau \to 0$. On a batch of inputs the limit is a linear map J_0 on $\mathbb{R}^P$; as in Appendix B, a direction η is flat if $J_0\,\eta = 0$ on every input.

MLP blocks without normalization. The stream is $h_\ell = xE + b_E + O(\tau)$, so the output is

$$y = xED + b_E D + b_D + \tau \sum_{\ell=1}^{L} \Big(f\big((xE + b_E)W_{\text{read}}^\ell + b_{\text{read}}^\ell\big)V_\ell + b_{\text{write}}^\ell \Big) D + O(\tau^2),$$

with the write biases written as $\tau b_{\text{write}}^\ell$. Hence $J_0\,\eta = \mathrm{D}_\phi G(\phi, x)\,\psi$ for the one-block function G of Lemma B.3 at $M = ED$, $\gamma = b_E D + b_D$, the columns c_i of EW, the entries β_i of $b_E W + b_{\text{read}}$ and the rows a_i of VD, in the direction ψ with

$$\psi_M = \eta_E D + E\eta_D, \qquad \psi_\gamma = \eta_{b_E} D + b_E \eta_D + \eta_{b_D} + \textstyle\sum_\ell \eta_{b_{\text{write}}^\ell} D,$$
$$\psi_C = E\eta_W, \qquad \psi_\beta = b_E \eta_W + \eta_{b_{\text{read}}}, \qquad \psi_A = \eta_V D,$$

where ψ_C, ψ_β and ψ_A collect the ψ_{c_i}, ψ_{β_i} and ψ_{a_i}, and the values of the gated units enter as the gates do. At generic parameters the hypotheses of Lemma B.3 hold, as for one block (Appendix B). For a flat η the lemma gives $\psi_M = 0$, $\psi_\gamma = 0$ and a rescaling at every unit. As E and D have rank d_{model}, $\psi_M = 0$ gives $\eta_E = EX$ and $\eta_D = -XD$ for some $X \in \mathbb{R}^{d_{\text{model}} \times d_{\text{model}}}$; ψ_C and ψ_A make η_W and η_V a rescaling of the units, which fixes $\eta_{b_{\text{read}}}$ through ψ_β; and $\psi_\gamma = 0$ fixes η_{b_D} once η_{b_E} and the L write biases are chosen. So the flat directions form a space of dimension $d_{\text{model}}^2 + s$, and $d_{\text{model}}^2 + (L+1)d_{\text{model}} + s$ with biases. Without an embedding and a readout, $M = I$ is fixed, and only the rescalings are left.

Attention blocks without normalization. Without biases, $y = xED + \tau \sum_\ell g_\ell(xE)D + O(\tau^2)$, where g_ℓ is block ℓ with the write V_ℓ. So $J_0\,\eta$ is the derivative of the residual network with one block that holds all heads and units, in the direction with the entries ψ_M, ψ_C and ψ_A above and, for each head i,

$$\psi_{B_i} = E\big(\eta_{Q,i} W_{K,i}^\top + W_{Q,i}\eta_{K,i}^\top\big)E^\top/\sqrt{d_h}, \qquad \psi_{C_i} = E\big(\eta_{V,i} W_{O,i} + W_{V,i}\eta_{O,i}\big)D,$$

at $B_i = EW_{Q,i}W_{K,i}^\top E^\top/\sqrt{d_h}$ and $C_i = EW_{V,i}W_{O,i}D$ as in Appendix B, where $W_{O,i}$ holds the rows of V_ℓ that belong to head i of block ℓ. On inputs whose tokens all equal x, head i gives every token xC_i, and its derivative is $x\psi_{C_i}$, since all its scores move alike. There the equation is that of the units with the linear part $M + \sum_i C_i$, and Lemma B.3 gives a rescaling at every unit. The units then drop out on every input. On inputs whose tokens other than the second equal the first, head i gives the second token the output of (10) with $k = 1$ if its block is causal and $k = T - 1$ otherwise; the constants $-\frac{1}{2}\log k$ act as biases of the $\tanh$ units, which Lemma B.3 allows, so Step 2 for attention blocks in Appendix B gives $\psi_M = 0$, $\psi_{B_i} = 0$ and $\psi_{C_i} = 0$. Cancelling E on the left and $E^\top$ or D on the right, the last two leave, as in Step 1 there, the directions of the changes of basis between the queries and keys and between the values and outputs of each head. So the flat directions form a space of dimension $d_{\text{model}}^2 + s$, and without an embedding and a readout of dimension s.

Under pre-RMSNorm. The stream is $h_\ell = xE + O(\tau)$, every block reads $N(xE) + O(\tau)$, and the output is

$$y = N(xE)D + \tau\, \mathrm{D}N(xE)\Big(\textstyle\sum_\ell g_\ell\big(N(xE)\big)\Big)D + O(\tau^2),$$

with N applied to every token. So $J_0\,\eta = \mathrm{D}N(h)\,\big(x\eta_E + k(n)\big)D + N(h)\eta_D$, with $h = xE$, $n = N(h)$ and $k(n)$ the derivative of the wide block along η at the input n. This is the equation

of the proof of Theorem B.1(ii) with $h_1 = xE$ and $\mathrm{D}_\theta h_1\, \eta = x\eta_E + k(n)$, and its Steps 1 to 5 go through, with $k(n)$ bounded in Step 2 since n stays in the ball, and with the units handled first, through equal tokens, in Step 4. In Step 3 the direction η^Y now has the entries EY and $-YD$ at E and D and no others, as $\mathrm{D}N(h)\,(hY) = N(h)Y$ for antisymmetric Y. So the flat directions are these, the rescalings of the units and the changes of basis inside the heads, a space of dimension $d_{\mathrm{model}}(d_{\mathrm{model}} - 1)/2 + s$.

In each case the kernel of J_0 shrinks as the batch grows and becomes stationary at the flat directions, so on some finite batch J_0 has rank P minus this dimension. By lower semicontinuity the Jacobian of the residual network on this batch has at least this rank for all small $\tau \neq 0$. Its symmetries bound the rank by the same number, since they move the parameters in independent directions when E has rank d_{model} and the queries and values of every head have full column rank: the global change of basis (Theorem A.4(iii)), the translations (Lemma A.5), the rescalings of the units and the changes of basis inside the heads. □

Theorem 4.5 is a case of the following theorem.

Theorem A.14 (GELU and smooth networks at depth)**. (i)** *For GELU blocks and almost every choice of weights, a composition of $L \geq 2$ residual blocks equals no composition of L blocks without skips of the same widths.*
(ii) *With an embedding and a readout, the same holds for networks of smooth blocks of any depth $L \geq 1$, also under pre-RMSNorm with $\varepsilon > 0$.*
(iii) Too few extra units. *For GELU blocks with an embedding and a readout, without normalization, and almost every choice of weights, a residual network of L blocks equals no skipless network of L blocks with fewer than $Ld_{\mathrm{model}}/2$ more hidden units in all.*

Proof of Theorem A.14(i) and (ii). By Lemma A.13, a residual network without biases has functional dimension $P - d_{\mathrm{model}}^2 - s$ at some parameters, where s counts the changes of basis inside the heads and the rescalings of the values of gated units, and a network of GELU blocks without an embedding and a readout has functional dimension P. In a skipless network of the same widths, with embedding E' and readout D', the changes of basis at h_0 and h_L, those inside the heads and the rescalings have orbits of dimension $2d_{\mathrm{model}}^2 + s$ at generic parameters, where E' and D' have rank d_{model} and the queries and values of every head have full column rank. As $P - d_{\mathrm{model}}^2 - s > P - 2d_{\mathrm{model}}^2 - s$, Lemma A.12 gives the claim. Without an embedding, a readout and attention blocks, for $L \geq 2$ the changes of basis at h_1 have orbits of positive dimension, since every block has at least one unit, so Lemma A.12 applies again. Under pre-RMSNorm with $\varepsilon > 0$ the networks stay analytic, Lemma A.13 gives the residual network functional dimension $P - d_{\mathrm{model}}(d_{\mathrm{model}} - 1)/2 - s$, and the orthogonal changes of basis at h_0 and h_L, which commute with the normalization, have orbits of dimension $d_{\mathrm{model}}(d_{\mathrm{model}} - 1) + s$ in the skipless network; as $d_{\mathrm{model}} \geq 2$, Lemma A.12 applies once more. □

Proof of Theorem A.14(iii). Let the residual network have blocks with $m_1, \ldots, m_L$ hidden units and P parameters. A skipless network whose blocks have $m'_\ell \geq d_{\mathrm{model}}$ hidden units has $P' = P + 2d_{\mathrm{model}} \sum_\ell (m'_\ell - m_\ell)$ parameters, and its changes of basis at $h_0, \ldots, h_L$ have orbits of dimension $(L+1)d_{\mathrm{model}}^2$ at generic parameters (Lemma A.10). By Lemma A.13 the residual network has functional dimension $P - d_{\mathrm{model}}^2$ at some parameters, which exceeds $P' - (L+1)d_{\mathrm{model}}^2$ exactly when $\sum_\ell (m'_\ell - m_\ell) < Ld_{\mathrm{model}}/2$. For each of the finitely many such choices of widths, Lemma A.12 gives a set of weights of measure zero, and so does their union. □

We recall Theorem 4.5 from Section 4.5.

Theorem 4.5 (Different function classes)**. (i)** *For networks of smooth blocks, without normalization or with pre-RMSNorm, and almost every choice of weights, a residual network equals no skipless network of the same widths.*
(ii) Too few extra units. *For networks of GELU blocks without normalization, and almost every choice of weights, a residual network of L blocks equals no skipless network of L blocks with fewer than $Ld_{\mathrm{model}}/2$ more hidden units in all.*

Proof of Theorem 4.5. Part (i) is Theorem A.14(ii), and part (ii) is Theorem A.14(iii). □

We recall Theorems 4.3 and 4.4 from Section 4.3.

Theorem 4.3 (Residual networks at any depth)**.** *Let the blocks be smooth.*
(i) *The residual network satisfies the equality condition: at generic parameters its functional dimension is* $P - \dim \mathcal{G} - s$.
(ii) *The skips raise the functional dimension by at least* $L \dim \mathcal{G}$*, and by exactly* $L \dim \mathcal{G}$ *when the skipless network satisfies the equality condition too.*

Proof of Theorem 4.3. Part (i). Let r be P minus the dimension of the symmetries of the residual network, the value in Lemma A.13. At generic parameters the symmetries move the parameters in independent directions, so the rank of the Jacobian is at most r on every batch. Lemma A.13 gives parameters and a finite batch on which it equals r. On this batch the rank is therefore at least r outside the zero set of the sum of the squares of the minors of size r, an analytic function that is not identically zero, so this zero set has measure zero. At generic parameters the functional dimension is thus r, which is the equality condition.

Part (ii). When every block has width at least d_{model}, the functional dimension of the skipless network is at most $P - (L+1)\dim \mathcal{G} - s$, and $(L+1)d_{\text{model}}$ lower with biases (Theorem A.9(ii), Remark A.11, Lemma A.5); with biases, the induction in the proof of Lemma A.10 also makes the translations act freely, through the entries at b_E and at the write biases. This gives the gain of at least $L \dim \mathcal{G}$, with equality when the skipless network satisfies the equality condition. □

Theorem 4.4 (Exact gain for $\tanh$ and GELU)**.** *Without normalization, in the two cases below the skipless network satisfies the equality condition too, so the skips raise the functional dimension by exactly* Ld_{model}^2.
(i) *The blocks are* $\tanh$ *blocks.*
(ii) *The blocks are GELU blocks with at least* $2d_{\text{model}}$ *hidden units.*

Proof of Theorem 4.4. By Theorem 4.3(i) the residual network satisfies the equality condition, so it remains to show it for the skipless network; the gain is then Ld_{model}^2, with or without biases.

Part (i), $\tanh$. With read biases b_ℓ and write biases c_ℓ, which may vanish, the skipless network computes

$$x^0 = x, \qquad x^\ell = \tanh\left(x^{\ell-1}A_\ell + \beta_\ell\right) \ (1 \le \ell \le L), \qquad y = x^L A_{L+1} + \beta_{L+1},$$

with $A_1 = EW_1$, $A_\ell = V_{\ell-1}W_\ell$ and $A_{L+1} = V_L D$, where W_ℓ and V_ℓ are the read and the write of block ℓ, and $\beta_1 = b_E W_1 + b_1$, $\beta_\ell = c_{\ell-1}W_\ell + b_\ell$ and $\beta_{L+1} = c_L D + b_D$. As $\sigma(z) = \tanh(z/2)$ is injective, two such networks have the same output exactly when the nets of Fefferman (1994) with the hidden layers $x^\ell = \sigma(2x^{\ell-1}A_\ell + 2\beta_\ell)$ and the output layer $\sigma(x^L A_{L+1} + \beta_{L+1})$ do, and then so do, for every input coordinate and every output, the nets with one input and one output that keep only these. At generic parameters every entry of every A_ℓ is nonzero, and no ratio of the weights that one unit sends to two units of a layer of width m is a fraction p/q with $1 \le q \le 100m^2$. These conditions are open, and they are those of his Theorem I.B.9, on nets with one input and one output, which puts no condition on the thresholds. So near generic parameters, two networks with the same output give, for every input coordinate and every output, nets with one input and one output that agree up to permutations of the units of each hidden layer and sign flips. These are the identity: at the first layer where a unit is moved or flipped, the weights it receives would move by a fixed amount, since none vanishes and the weights that one unit sends to two units differ in absolute value. So the two networks have the same A_ℓ and β_ℓ. When E, D and every read and write have rank d_{model}, the parameters with the same A_ℓ and β_ℓ are those reached by the changes of basis at the $L+1$ hidden states, and with biases by the translations there.

Take generic parameters and a batch on which the rank r of the Jacobian equals the functional dimension. Near these parameters the rank on this batch stays r, so its kernel is the space of directions that are flat for every input, and the parameters with the same outputs on the batch form a manifold of dimension $P - r$ along which the function does not change. So $P - r$ is at most the dimension of the symmetries, and the symmetries give the reverse inequality (Theorem A.9(ii), Lemma A.5).

Part (ii), GELU. Let block ℓ have $m_\ell + d_{\text{model}}$ units, with $m_\ell \geq d_{\text{model}}$, and take a residual network with blocks of m_ℓ units at generic parameters, with every write multiplied by τ as in Lemma A.13. Since $\sigma(z) - \sigma(-z) = z$, each of its blocks equals a block without skip with d_{model} more units: for d_{model} units i whose reads w_i form an invertible matrix, add the row γ_i of its inverse to the write of unit i, and add a unit with the read $-w_i$ and the write $-\gamma_i$. This construction is smooth in the residual parameters near these, where the chosen reads stay invertible, and gives a skipless network that computes the residual one. By the chain rule, the columns of the skipless Jacobian therefore span those of the residual Jacobian, which, with the read columns divided by τ, tend to the limit J_0 of Lemma A.13, of rank $P_R - d_{\text{model}}^2$ on some finite batch, where $P_R = P - 2Ld_{\text{model}}^2$ counts the parameters of the residual network. As $\sigma(z) - \sigma(-z) = z$ gives $\sigma'(-z) = 1 - \sigma'(z)$, and every block is the identity at $\tau = 0$, the reads of the added units give the further columns

$$\big(\sigma'(xEw_i) - 1\big)(xE\delta_i)\,\gamma_i D, \qquad \delta_i \in \mathbb{R}^{d_{\text{model}}},$$

in the limit. Suppose that $J_0\,\eta$ plus a sum of these vanishes for all x. Each added term has the Gaussian part of the term of ψ_{c_i} in Lemma B.3, with $E\delta_i$ in place of ψ_{c_i} and the row $\gamma_i D$ in place of a_i. In the proof of that lemma for GELU, the coefficient of t^2 for the slowest unit j becomes $u_j\big((n\psi_{c_j})\,a_j + (nE\delta_j)\,\gamma_j D\big)$. At generic parameters $\gamma_j D$ is not parallel to a_j, so $nE\delta_j = 0$ for all n in an open set, and $\delta_j = 0$ as E has rank d_{model}; the proof then goes on as before. So, on some finite batch, the added reads raise the rank in the limit by Ld_{model}^2, to $P_R - d_{\text{model}}^2 + Ld_{\text{model}}^2 = P - (L+1)d_{\text{model}}^2$. By lower semicontinuity the skipless network has this rank for small τ, which is the most its symmetries allow, and an analytic network keeps its largest rank at generic parameters. □

Remark A.15 (ReLU-type blocks). For ReLU, ReLU^2 and ReGLU blocks without normalization, the proof of Lemma A.13 goes through on a finite batch on which no pre-activation of the limit vanishes: Lemma B.3 covers these units, and for small τ every pre-activation keeps its sign on the batch, so the Jacobian is polynomial in the weights near these parameters. The residual network therefore has functional dimension $P - d_{\text{model}}^2 - s$ on an open set of weights that contains all small enough multiples of generic writes, and at almost every point of this set the skips add at least Ld_{model}^2 when every block has width at least d_{model}. The count fails on another open set. For $d_{\text{model}} = 2$, the block $h \mapsto h + 2\big(\text{ReLU}(-h_1), \text{ReLU}(-h_2)\big) = \big(|h_1|, |h_2|\big)$ maps the plane onto a quadrant, and a unit of the next block with the read $-(1,1)^\top$ never switches on. Its read and its write then leave $2d_{\text{model}} - 1$ more directions flat, and small changes of the weights keep this. Which weights keep the count is left for future work.

B The one-block theorem

This appendix states and proves the general form of Theorem 4.2. With one block, the skipless and the residual network are

$$x \mapsto f(xEW_{\text{read}})W_{\text{write}}D \qquad \text{and} \qquad x \mapsto \big(xE + f(xEW_{\text{read}})W_{\text{write}}\big)D$$

without normalization, and under pre-RMSNorm

$$x \mapsto N\big(f(N(xE)W_{\text{read}})W_{\text{write}}\big)D \qquad \text{and} \qquad x \mapsto N\big(xEA + f(N(xE)W_{\text{read}})W_{\text{write}}\big)D,$$

with the identity skip $A = I$. A learned skip $A \in \mathbb{R}^{d_{\text{model}} \times d_{\text{model}}}$ is full or upper triangular.

Theorem B.1 (One block)**.** *Let $d_{\text{model}} \geq 2$, let the input and output dimensions be at least d_{model}, and consider networks with one block: a* tanh*, GELU, ReLU, ReLU^2, ReGLU, SwiGLU or GeGLU block, or an attention block of H heads of width $d_h \leq d_{\text{model}}$, causal or not, on sequences of at least two tokens.*

(i) *Let the network have no normalization, with or without biases, and let the block have width at least d_{model}, where the width of an attention block is Hd_h. For generic parameters the skipless*

network has functional dimension $P - 2d_{\text{model}}^2 - s$ and the residual network $P - d_{\text{model}}^2 - s$; with biases on the embedding, the block and the readout, counted in P, both values are $2d_{\text{model}}$ lower, and $2d_{\text{model}} + 2Hd_h$ lower for attention. Both networks satisfy the equality condition, and the skip raises the functional dimension by exactly d_{model}^2.
(ii) *Let the network be pre-RMSNorm with $\varepsilon > 0$, without biases. For generic parameters the residual network has functional dimension $P - d_{\text{model}}(d_{\text{model}} - 1)/2 - s$, which is the equality condition. If the block has width at least d_{model}, the skip raises the functional dimension by at least $d_{\text{model}}(d_{\text{model}} - 1)/2$.*
(iii) *Let the network be pre-RMSNorm without biases, with a learned skip A, full or upper triangular. For generic parameters and $\varepsilon > 0$, its functional dimension exceeds that of the residual network of part (ii) by exactly $d_{\text{model}}(d_{\text{model}} + 1)/2$, and it satisfies the equality condition. For $\varepsilon = 0$ it exceeds that of the residual network with $\varepsilon = 0$ by at most $d_{\text{model}}(d_{\text{model}} + 1)/2 - 1$, with equality for ReLU, ReLU^2 and ReGLU blocks.*
(iv) *Let the network be pre-RMSNorm with $\varepsilon = 0$, without biases, with a ReLU, ReLU^2 or ReGLU block of width at least d_{model}. For generic parameters the skipless network has functional dimension $P - d_{\text{model}}^2 - d_{\text{model}}(d_{\text{model}} - 1)/2 - 1 - s$ and the residual network $P - d_{\text{model}}(d_{\text{model}} - 1)/2 - 1 - s$. Both networks satisfy the equality condition, and the skip raises the functional dimension by exactly d_{model}^2.*
(v) *Let the network be pre-RMSNorm with $\varepsilon = 0$, without biases, with a $\tanh$, GELU, SwiGLU, GeGLU or attention block. For generic parameters the skip raises the functional dimension by at least $d_{\text{model}}(d_{\text{model}} - 1)/2 + 1$, the dimension of $\mathrm{CO}(d_{\text{model}})$.*

In part (ii), for the skipless network we prove only the bound $P - d_{\text{model}}(d_{\text{model}} - 1) - s$ of Theorem A.9(ii), which our checks attain (Appendix E). With parts (ii) and (iii), a learned skip under RMSNorm with $\varepsilon > 0$ adds at least d_{model}^2 over no skip if the block has width at least d_{model}, as an identity skip does without normalization. Part (i) extends to a learned absolute position embedding, $h_0 = xE + E_{\text{pos}}$, for an attention block without biases, with P counting E_{pos} (*Position embeddings* below). Rotary encodings act inside the heads, where they reduce the change of basis between queries and keys; we leave them to future work.

What we use. The proof needs linear algebra and limits of functions of one real variable. We write $F(\theta, x)$ for the output of the network at the parameters $\theta \in \mathbb{R}^P$ and the input x, and $\mathrm{D}_\theta F(\theta, x)$ for the Fréchet derivative of $F(\cdot, x)$ at θ, a linear map on $\mathbb{R}^P$. The derivative is written with an upright D so that it is not confused with the readout matrix D of the network. For a direction $\eta \in \mathbb{R}^P$, $\mathrm{D}_\theta F(\theta, x)\,\eta$ is the derivative of $\tau \mapsto F(\theta + \tau\eta, x)$ at $\tau = 0$. We write η_E, η_D, η_{read}, η_{write}, ... for the entries of η at the positions of E, D, W_{read}, W_{write}, ..., and $\mathrm{D}_\theta Q\,\eta$ for the derivative along η of a matrix Q that depends on the parameters; for instance $\mathrm{D}_\theta M\,\eta = \eta_E D + E\eta_D$ for $M = ED$, by the product rule. Call η *flat* if $\mathrm{D}_\theta F(\theta, x)\,\eta = 0$ for every input x, and let $\mathcal{K}(\theta)$ be the space of flat directions. For the ReLU-type activations, $F(\theta, x)$ is differentiable in θ at the inputs x at which no hidden unit sits at its kink, which form an open set of full measure, and "every input" means every such input. For a batch of inputs $x_1, \ldots, x_n$, the Jacobian of $\theta \mapsto (F(\theta, x_1), \ldots, F(\theta, x_n))$ is the matrix of the linear map $\eta \mapsto (\mathrm{D}_\theta F(\theta, x_1)\,\eta, \ldots, \mathrm{D}_\theta F(\theta, x_n)\,\eta)$; it has P columns, and its kernel consists of the directions with $\mathrm{D}_\theta F(\theta, x_k)\,\eta = 0$ for the inputs of the batch. Adding inputs can only shrink this kernel, and a decreasing chain of subspaces of $\mathbb{R}^P$ stops, so some finite batch has kernel exactly $\mathcal{K}(\theta)$. By rank–nullity, the functional dimension at θ is therefore

$$P - \dim \mathcal{K}(\theta).$$

The theorem thus amounts to finding the flat directions. A statement holds for *generic* parameters if it fails only where some nonzero polynomial in the parameters vanishes, a set of measure zero.

Overview. For an MLP block, the parameters enter the function only through $M = ED$, $A = W_{\text{write}}D$ and $C = EW_{\text{read}}$. Step 1 finds the directions that keep these matrices fixed: they are the directions in which the changes of basis move the parameters, two of them without the skip and one with it. Step 2 shows that a flat direction changes M, A and C only along the symmetries of the hidden units: each unit is isolated, by its kink for the ReLU-type activations, and for $\tanh$, GELU, SwiGLU and GeGLU by how fast it approaches its limit on rays $x = tn$ with $t \to \infty$. Step 3 counts.

For an attention block the same steps run with one factorization per head, and inputs of two tokens turn Step 2 into the case of $\tanh$. For part (ii), large inputs first remove the final normalization and then separate the skip from the block. Part (iii) runs the same steps with a learned skip, which leaves a symmetric change of basis at h_0 in the input of the block; homogeneity or rays remove it.

Part (i) for MLP blocks

Reduction. With biases b_E, b_{read}, b_{write} and b_D, the skipless network computes $F(\theta, x) = f(xC + \beta)A + \gamma_0$ and the residual network $F(\theta, x) = xM + f(xC + \beta)A + \gamma$, where

$$M = ED, \qquad C = EW_{\text{read}}, \qquad A = W_{\text{write}}D,$$
$$\beta = b_E W_{\text{read}} + b_{\text{read}}, \qquad \gamma_0 = b_{\text{write}}D + b_D, \qquad \gamma = b_E D + \gamma_0.$$

Without biases $\beta = 0$ and $\gamma = \gamma_0 = 0$. For a vanilla block let c_i be the columns of C, one per hidden unit, a_i the rows of A, β_i the entries of β, and $z_i = xc_i + \beta_i$, so that $F(\theta, x) = xM + \gamma + \sum_i \sigma(z_i)\, a_i$. For generic parameters E, D, W_{read} and W_{write} have rank d_{model}, every a_i is nonzero, and the c_i are nonzero and pairwise non-collinear: they lie in the column space of E, of dimension $d_{\text{model}} \geq 2$, where two generic vectors are not collinear. For the gated blocks ReGLU, SwiGLU and GeGLU, in the same way, the value weights (e_i, β_i') of each unit, introduced below, have $e_i \neq 0$ and are not proportional to its gate weights (c_i, β_i).

Step 1: changes of basis. We need the following lemma.

Lemma B.2 (The directions that keep M, A and C)**.** *Let E, D, W_{read} and W_{write} have rank d_{model}. A direction η keeps C and A fixed to first order, $\mathrm{D}_\theta C\, \eta = 0$ and $\mathrm{D}_\theta A\, \eta = 0$, if and only if*

$$\eta_E = EX, \qquad \eta_{\text{read}} = -XW_{\text{read}}, \qquad \eta_{\text{write}} = W_{\text{write}}Y, \qquad \eta_D = -YD$$

for some $X, Y \in \mathbb{R}^{d_{\text{model}} \times d_{\text{model}}}$, and it keeps M fixed as well, $\mathrm{D}_\theta M\, \eta = 0$, if and only if moreover $X = Y$. With biases, it keeps β and γ_0, respectively β and γ, fixed as well if and only if moreover $\eta_{b_E} = b_E X + g_0$, $\eta_{b_{\text{read}}} = -g_0 W_{\text{read}}$, $\eta_{b_{\text{write}}} = b_{\text{write}}Y + g_1$ and $\eta_{b_D} = -g_1 D$, respectively $\eta_{b_D} = -(g_0 + g_1)D$, for some row vectors $g_0, g_1 \in \mathbb{R}^{1 \times d_{\text{model}}}$. The matrices X, Y and vectors g_0, g_1 are determined by the direction, so these directions form a space of dimension $2d_{\text{model}}^2$ without the skip and d_{model}^2 with it, and $2d_{\text{model}}$ more with biases.

Proof. Since W_{read} has rank d_{model}, it has a right inverse R, with $W_{\text{read}}R = I$, and E, of rank d_{model} with d_{model} columns, has a left inverse. From $\mathrm{D}_\theta C\, \eta = \eta_E W_{\text{read}} + E\eta_{\text{read}} = 0$, multiplying on the right by R gives $\eta_E = EX$ with $X = -\eta_{\text{read}}R$; then $E\eta_{\text{read}} = -EXW_{\text{read}}$, and cancelling E on the left gives $\eta_{\text{read}} = -XW_{\text{read}}$. In the same way, D has a right inverse and W_{write} a left inverse, and $\mathrm{D}_\theta A\, \eta = \eta_{\text{write}}D + W_{\text{write}}\eta_D = 0$ gives $\eta_{\text{write}} = W_{\text{write}}Y$ and $\eta_D = -YD$. Conversely these directions give $\mathrm{D}_\theta C\, \eta = EXW_{\text{read}} - EXW_{\text{read}} = 0$ and $\mathrm{D}_\theta A\, \eta = 0$. In the residual network $\mathrm{D}_\theta M\, \eta = \eta_E D + E\eta_D = E(X - Y)D$, which vanishes if and only if $X = Y$, by cancelling E on the left and D on the right. With biases, set $g_0 = \eta_{b_E} - b_E X$ and $g_1 = \eta_{b_{\text{write}}} - b_{\text{write}}Y$. Then $\mathrm{D}_\theta \beta\, \eta = \eta_{b_E} W_{\text{read}} + b_E \eta_{\text{read}} + \eta_{b_{\text{read}}} = g_0 W_{\text{read}} + \eta_{b_{\text{read}}}$, which vanishes exactly when $\eta_{b_{\text{read}}} = -g_0 W_{\text{read}}$, and in the same way $\mathrm{D}_\theta \gamma_0\, \eta = g_1 D + \eta_{b_D}$ and, with $Y = X$, $\mathrm{D}_\theta \gamma\, \eta = (g_0 + g_1)D + \eta_{b_D}$. Finally $\eta_E = EX$ determines X, $\eta_D = -YD$ determines Y, and then η_{b_E} and $\eta_{b_{\text{write}}}$ determine g_0 and g_1. □

These are the directions in which the changes of basis $I + \tau X$ at h_0 and $I + \tau Y$ at h_1 move the parameters, and, with biases, the translations at the two hidden states (Lemma A.5).

Step 2: one hidden layer. We need a lemma on the function

$$G(\phi, x) = xM + \gamma + \textstyle\sum_i \sigma(z_i)\, a_i, \qquad z_i = xc_i + \beta_i,$$

of the matrices $\phi = \big(M, \gamma, (c_i, \beta_i, a_i)_i\big)$ themselves. For a direction ψ of ϕ, with entries ψ_M, ψ_γ, ψ_{c_i}, ψ_{β_i} and ψ_{a_i}, the Fréchet derivative of $G(\cdot, x)$ at ϕ gives

$$\mathrm{D}_\phi G(\phi, x)\,\psi = x\psi_M + \psi_\gamma + \sum_i \big[\sigma(z_i)\,\psi_{a_i} + \sigma'(z_i)\,(x\psi_{c_i} + \psi_{\beta_i})\,a_i\big]. \tag{9}$$

A gated unit computes $\sigma(z_i)\,w_i\,a_i$ with a gate $z_i = xc_i + \beta_i$ and a value $w_i = xe_i + \beta'_i$, where $\sigma(z) = \max(z, 0)$ for ReGLU, $z/(1 + e^{-z})$ for SwiGLU and $z\Phi(z)$ for GeGLU, so that ϕ also contains the e_i and β'_i, and the terms of the unit in $\mathrm{D}_\phi G(\phi, x)\,\psi$ are $\sigma(z_i)\,w_i\,\psi_{a_i} + \sigma'(z_i)\,(x\psi_{c_i} + \psi_{\beta_i})\,w_i\,a_i + \sigma(z_i)\,(x\psi_{e_i} + \psi_{\beta'_i})\,a_i$.

Lemma B.3 (A flat direction only rescales units)**.** *Let every $a_i \neq 0$ and let the c_i be nonzero and pairwise non-collinear; for the gated blocks let also every $e_i \neq 0$, with (e_i, β'_i) not proportional to (c_i, β_i). If $\mathrm{D}_\phi G(\phi, x)\,\psi = 0$ for all x, then $\psi_M = 0$, $\psi_\gamma = 0$, and for every unit i:*
for $\tanh$ *and GELU, $\psi_{a_i} = 0$, $\psi_{c_i} = 0$ and $\psi_{\beta_i} = 0$;*
for ReLU, $(\psi_{c_i}, \psi_{\beta_i}) = \lambda_i(c_i, \beta_i)$ and $\psi_{a_i} = -\lambda_i a_i$ for some number λ_i;
for ReLU^2, $(\psi_{c_i}, \psi_{\beta_i}) = \lambda_i(c_i, \beta_i)$ and $\psi_{a_i} = -2\lambda_i a_i$;
for ReGLU, $(\psi_{c_i}, \psi_{\beta_i}) = \lambda_i(c_i, \beta_i)$, $(\psi_{e_i}, \psi_{\beta'_i}) = -\alpha_i(e_i, \beta'_i)$ and $\psi_{a_i} = (\alpha_i - \lambda_i)a_i$ for some numbers λ_i and α_i;
for SwiGLU and GeGLU, $\psi_{c_i} = 0$, $\psi_{\beta_i} = 0$, $(\psi_{e_i}, \psi_{\beta'_i}) = -\alpha_i(e_i, \beta'_i)$ and $\psi_{a_i} = \alpha_i a_i$ for some number α_i.

Proof. Let $H_i = \{x : z_i = 0\}$, a hyperplane since $c_i \neq 0$. Since the c_i are pairwise non-collinear, the H_i are pairwise non-parallel, so every H_i contains points that lie on no other H_k. We use one fact from linear algebra: an affine function that vanishes on an open piece of H_i is a multiple of z_i, since it vanishes on all of H_i and H_i has codimension one. We write $J(x) = \mathrm{D}_\phi G(\phi, x)\,\psi$, a function of x alone, which vanishes by assumption.

ReLU. Here $\sigma' = \mathbf{1}[z > 0]$ jumps at 0. Near a point x_0 of H_i that lies on no other H_k, every term of (9) is continuous except $\mathbf{1}[z_i > 0](x\psi_{c_i} + \psi_{\beta_i})\,a_i$, which jumps by $(x_0\psi_{c_i} + \psi_{\beta_i})\,a_i$ as x crosses H_i at x_0. As $J = 0$ is continuous, this jump vanishes, and since $a_i \neq 0$, the affine function $x\psi_{c_i} + \psi_{\beta_i}$ vanishes on an open piece of H_i, so $(\psi_{c_i}, \psi_{\beta_i}) = \lambda_i(c_i, \beta_i)$. The terms of unit i then add up to $\max(z_i, 0)\,(\psi_{a_i} + \lambda_i a_i)$, since $z\,\mathbf{1}[z > 0] = \max(z, 0)$. Across H_i, the gradient of J with respect to x jumps by the matrix $c_i(\psi_{a_i} + \lambda_i a_i)$, which must vanish, so $\psi_{a_i} = -\lambda_i a_i$. With every unit removed in this way, $J(x) = x\psi_M + \psi_\gamma = 0$ for all x gives $\psi_M = 0$ and $\psi_\gamma = 0$.

ReLU^2. The same argument one derivative higher: $\sigma'(z) = 2\max(z, 0)$ is continuous, and across H_i the gradient of $2\max(z_i, 0)(x\psi_{c_i} + \psi_{\beta_i})\,a_i$ jumps by $2c_i(x_0\psi_{c_i} + \psi_{\beta_i})\,a_i$, which forces $(\psi_{c_i}, \psi_{\beta_i}) = \lambda_i(c_i, \beta_i)$. The terms of unit i then add up to $\max(z_i, 0)^2(\psi_{a_i} + 2\lambda_i a_i)$, whose second derivative jumps across H_i, so $\psi_{a_i} = -2\lambda_i a_i$.

ReGLU. As (e_i, β'_i) is nonzero and not proportional to (c_i, β_i), the affine function w_i does not vanish on all of H_i, so it is nonzero on an open piece of H_i that meets no other H_k; we take x_0 there. Across H_i the terms of unit i jump by $(x_0\psi_{c_i} + \psi_{\beta_i})\,w_i(x_0)\,a_i$, so $(\psi_{c_i}, \psi_{\beta_i}) = \lambda_i(c_i, \beta_i)$ as before. The terms of unit i then add up to $\max(z_i, 0)\,V_i(x)$ with the affine function $V_i(x) = w_i(x)\,(\psi_{a_i} + \lambda_i a_i) + (x\psi_{e_i} + \psi_{\beta'_i})\,a_i$. The jump of their gradient across H_i is $c_i V_i(x_0)$, so V_i vanishes on an open piece of H_i, and $V_i(x) = z_i\,\nu_i$ for a row vector ν_i. The terms of unit i then add up to $\max(z_i, 0)^2\,\nu_i$, whose second derivative jumps across H_i, so $\nu_i = 0$ and $V_i = 0$ for all x: $w_i(x)\,(\psi_{a_i} + \lambda_i a_i) = -(x\psi_{e_i} + \psi_{\beta'_i})\,a_i$. Both sides are products of an affine function of x and a fixed row vector, and $a_i \neq 0$, so $\psi_{a_i} + \lambda_i a_i = \alpha_i a_i$ and $(\psi_{e_i}, \psi_{\beta'_i}) = -\alpha_i(e_i, \beta'_i)$ for some number α_i. Then $\psi_M = 0$ and $\psi_\gamma = 0$ as for ReLU.

$\tanh$. We restrict (9) to a ray $x = tn$, $t > 0$, with a direction n such that the numbers $u_k = nc_k$ are all nonzero and $|u_j| < |u_k|$ for one unit j and all $k \neq j$. For each j and each sign $s = \pm 1$, the directions n with $su_j > 0$ and this property form a nonempty open set: start from a point of the hyperplane $nc_j = 0$ where no other nc_k vanishes, and move a little to the side s. For

$z > 0$,

$$\tanh z = 1 - 2e^{-2z} + r(z), \quad 0 \le r(z) \le 2e^{-4z},$$
$$\tanh' z = 4e^{-2z} - q(z), \quad 0 \le q(z) \le 8e^{-4z},$$

from $\tanh z = (1 - e^{-2z})/(1 + e^{-2z})$ and $\tanh' = 1 - \tanh^2$, and $\tanh$ is odd. On the ray $z_k = u_k t + \beta_k$, so for large t the terms of unit k in (9) are

$$s_k \psi_{a_k} + e^{-2|u_k|t}\, e^{-2 s_k \beta_k} \big[-2 s_k \psi_{a_k} + 4\,(t\, n\psi_{c_k} + \psi_{\beta_k})\, a_k \big] + O\big((1+t)\, e^{-4|u_k|t}\big),$$

with s_k the sign of u_k. All terms of $J(tn)$ are therefore $t\, n\psi_M$, a constant, the bracket of unit j times $e^{-2|u_j|t}$, and terms that are $O\big((1+t)e^{-\rho t}\big)$ with $\rho = \min\big(4|u_j|, \min_{k \ne j} 2|u_k|\big) > 2|u_j|$. As $J(tn) = 0$ for all t, dividing by t and letting $t \to \infty$ gives $n\psi_M = 0$; then the constant vanishes; then multiplying by $e^{2|u_j|t}$ and letting $t \to \infty$ shows that the bracket of unit j, a polynomial of degree one in t, tends to zero, so both of its coefficients vanish: $(n\psi_{c_j})\, a_j = 0$ and $2\psi_{\beta_j} a_j = s\, \psi_{a_j}$. As $a_j \ne 0$, $n\psi_{c_j} = 0$ for all n in an open set, so $\psi_{c_j} = 0$; and the two signs $s = \pm 1$ give $\psi_{a_j} = 2\psi_{\beta_j} a_j = -2\psi_{\beta_j} a_j$, so $\psi_{\beta_j} = 0$ and $\psi_{a_j} = 0$. This holds for every unit j, and then $J(x) = x\psi_M + \psi_\gamma = 0$ gives $\psi_M = 0$ and $\psi_\gamma = 0$.

GELU. Here $\sigma(z) = z\Phi(z)$, with Φ the standard normal distribution function and $\varphi = \Phi'$ its density. The tail $\bar\Phi = 1 - \Phi$ satisfies $\varphi(z)(1/z - 1/z^3) \le \bar\Phi(z) \le \varphi(z)/z$ for $z > 0$, as one checks by differentiating, and $\Phi(-z) = 1 - \Phi(z)$ carries these bounds to $z < 0$. From these, as $|z| \to \infty$ on either side,

$$\sigma(z) = \max(z, 0) - \varphi(z) + O\big(\varphi(z)/z^2\big),$$
$$\sigma'(z) = \mathbf{1}[z > 0] + \varphi(z)\,(z - 1/z) + O\big(\varphi(z)/|z|^3\big).$$

Take a ray $x = tn$ as for $\tanh$. The terms of unit k in (9) split into a polynomial of degree at most one in t, from $\max(z, 0)$ and $\mathbf{1}[z > 0]$, and the Gaussian part

$$\varphi(z_k) \Big[u_k\,(n\psi_{c_k})\, t^2 + \big(u_k \psi_{\beta_k} + \beta_k\, n\psi_{c_k}\big)\, t + \beta_k \psi_{\beta_k} - (n\psi_{c_k})/u_k \Big] a_k \\ - \ \varphi(z_k)\, \psi_{a_k} \ + \ O\big(\varphi(z_k)/t\big).$$

Gaussian parts tend to zero faster than any power of t, so as $J(tn) = 0$ for all t, the polynomial part vanishes, and so does the sum of the Gaussian parts. For $k \ne j$, $\varphi(z_k)/\varphi(z_j) = \exp\big(-\frac{1}{2}(u_k^2 - u_j^2)\, t^2 + O(t)\big)$ tends to zero faster than any power of t, since $u_k^2 > u_j^2$. Dividing the sum of the Gaussian parts by $\varphi(z_j)$ and letting $t \to \infty$ therefore makes the coefficients of t^2, t and 1 in the bracket of unit j vanish, in this order: $u_j(n\psi_{c_j})\, a_j = 0$, so $n\psi_{c_j} = 0$; then $u_j \psi_{\beta_j}\, a_j = 0$, so $\psi_{\beta_j} = 0$; then $\psi_{a_j} = 0$. As for $\tanh$, $n\psi_{c_j} = 0$ on an open set gives $\psi_{c_j} = 0$, and finally $\psi_M = 0$ and $\psi_\gamma = 0$.

SwiGLU and GeGLU. Take a ray $x = tn$ as for $\tanh$, and write $v_k = ne_k$, so that $w_k = v_k t + \beta'_k$; as $e_j \ne 0$, also $v_j \ne 0$ on an open set of such n. For SwiGLU, $\sigma(z) = z - z/(1 + e^z)$ gives, as $|z| \to \infty$ with s the sign of z,

$$\sigma(z) = \max(z, 0) - |z| e^{-|z|} + O\big(|z| e^{-2|z|}\big),$$
$$\sigma'(z) = \mathbf{1}[z > 0] + s\,(|z| - 1)\, e^{-|z|} + O\big(|z| e^{-2|z|}\big).$$

The terms of unit k in (9) then split into a polynomial in t, from $\max(z, 0)$ and $\mathbf{1}[z > 0]$, and a rest that is $e^{-|z_k|}$ times a polynomial in t, up to $O(t^3 e^{-2|z_k|})$; for GeGLU, with the expansions of GELU, the rest is $\varphi(z_k)$ times a polynomial in t and $1/z_k$, up to $O(\varphi(z_k)/t)$. As for $\tanh$ and GELU, the polynomial parts vanish, and dividing the sum of the rests by $e^{-|z_j|}$, respectively $\varphi(z_j)$, and letting $t \to \infty$ shows that the rest of the slowest unit j vanishes. For SwiGLU this rest is $e^{-|z_j|}$ times

$$s\,(|z_j| - 1)\,(t\, n\psi_{c_j} + \psi_{\beta_j})\, w_j\, a_j - |z_j| \big((t\, n\psi_{e_j} + \psi_{\beta'_j})\, a_j + w_j\, \psi_{a_j} \big),$$

with s the sign of u_j and $|z_j| = |u_j|t + s\beta_j$, a polynomial of degree three in t, whose coefficients therefore vanish. The coefficient of t^3 is $s|u_j|\,(n\psi_{c_j})\,v_j\,a_j$, so $\psi_{c_j} = 0$ as for $\tanh$. The coefficient of t^2 is then $-|u_j|\big((n\psi_{e_j})\,a_j + v_j(\psi_{a_j} - s\psi_{\beta_j}a_j)\big)$. As it vanishes for all n in an open set, $\psi_{e_j} = -\alpha e_j$ and $\psi_{a_j} - s\psi_{\beta_j}a_j = \alpha a_j$ for a number α, the same for both signs since ψ_{e_j} is; the two signs then give $\psi_{\beta_j} = 0$. The coefficient of t is then $-|u_j|(\psi_{\beta'_j} + \alpha\beta'_j)\,a_j$, so $\psi_{\beta'_j} = -\alpha\beta'_j$. For GeGLU the rest of unit j is $\varphi(z_j)$ times the same bracket with $z_j - 1/z_j$ in place of $s(|z_j| - 1)$ and 1 in place of $|z_j|$, and its coefficients of t^3, t^2, t and 1 give, in this order, $\psi_{c_j} = 0$, $\psi_{\beta_j} = 0$, $(\psi_{e_j}, \psi_{a_j}) = (-\alpha e_j, \alpha a_j)$ and $\psi_{\beta'_j} = -\alpha\beta'_j$. In both cases the terms of unit j then vanish; this holds for every unit, and $\psi_M = 0$ and $\psi_\gamma = 0$ as for $\tanh$. □

The directions left by the lemma are exactly those of the rescalings of the units: for ReLU, scaling the input weights and the bias of unit i by $1 + \tau\lambda_i$ and its output weights by $1 - \tau\lambda_i$ changes the function only at second order in τ.

Step 3: counting. Let η be flat. The network depends on θ only through ϕ, its M, γ and the c_i, β_i and a_i formed from C, β and A, so by the chain rule $\mathrm{D}_\theta F(\theta, x)\,\eta = \mathrm{D}_\phi G(\phi, x)\,(\mathrm{D}_\theta\phi\,\eta)$, and Lemma B.3 applies to $\psi = \mathrm{D}_\theta\phi\,\eta$. The derivatives of M, A, C, β and γ along η are thus those of a rescaling of the hidden units. A rescaling of the units by numbers λ_i is also a direction in parameter space: it scales column i of W_{read} and entry i of b_{read} by λ_i and row i of W_{write} by $-\lambda_i$ for ReLU, by $-2\lambda_i$ for ReLU^2, and similarly for ReGLU and for the values of SwiGLU and GeGLU, and along it C, β and A have the same derivatives. Subtracting it from η leaves a direction along which M, A, C, β and γ have derivative zero, which Lemma B.2 describes. So every flat direction is the sum of a direction of the changes of basis and translations of Lemma B.2 and a rescaling of the units, and conversely all of these are flat, since they come from symmetries. The two kinds are independent: a rescaling that is also a direction of Lemma B.2 has $\eta_E = EX = 0$, so $X = 0$, and then $W_{\text{read}}\,\mathrm{diag}(\lambda) = 0$, so every $\lambda_i = 0$, because no column of W_{read} vanishes. Hence $\dim\mathcal{K}(\theta) = 2d_{\text{model}}^2 + s$ without the skip and $d_{\text{model}}^2 + s$ with it, with $2d_{\text{model}}$ more for each with biases, where s is the number of rescalings: m for ReLU, ReLU^2, SwiGLU and GeGLU, $2m$ for ReGLU, none for $\tanh$ and GELU. The functional dimension $P - \dim\mathcal{K}(\theta)$ has the values of the theorem. The symmetries account for all of $\mathcal{K}(\theta)$, which is the equality condition, and the difference between the two networks is d_{model}^2.

Part (i) for attention blocks

Reduction. Let $W_{Q,i}, W_{K,i}, W_{V,i} \in \mathbb{R}^{d_{\text{model}}\times d_h}$ and $W_{O,i} \in \mathbb{R}^{d_h\times d_{\text{model}}}$ be the projections of head i, and let

$$M = ED, \qquad B_i = EW_{Q,i}W_{K,i}^\top E^\top/\sqrt{d_h}, \qquad C_i = EW_{V,i}W_{O,i}D, \qquad S = \textstyle\sum_i C_i,$$

with M only in the residual network. Head i gives token t the scores $x_tB_ix_s^\top$, and the output at token t is $x_tM + \sum_i\sum_s a_{ts}^{(i)}\,x_sC_i$, so the parameters enter only through these matrices. We use inputs of two kinds: with a causal mask, any sequence, whose second token sees only the first two; without a mask, sequences whose tokens other than the second all equal the first. Let k be the number of tokens other than the second that the second token sees, $k = 1$ with a mask and $k = T - 1$ without. With $u = x_2$ and $v = x_2 - x_1$, head i puts the weight $1/(1 + k\,e^{-uB_iv^\top})$ on the second token and the rest on the copies of the first, and $1/(1 + e^{-z}) = \frac{1}{2} + \frac{1}{2}\tanh(z/2)$ gives the output at the second token

$$y_2 = uK - \tfrac{1}{2}\,vS + \tfrac{1}{2}\sum_i \tanh\left(\tfrac{1}{2}(uB_iv^\top - \log k)\right)vC_i, \qquad K = M + S. \tag{10}$$

With biases b_E on the embedding, $b_{Q,i}$, $b_{K,i}$, $b_{V,i}$ on the queries, keys and values, b_O on the output projection and b_D on the readout, $uB_iv^\top$ becomes $(uB_i + \beta_i)v^\top$ with $\beta_i = (b_EW_{Q,i} + b_{Q,i})W_{K,i}^\top E^\top/\sqrt{d_h}$, and the constant $\gamma = \sum_i(b_EW_{V,i} + b_{V,i})W_{O,i}D + b_OD + b_D$ is added, plus b_ED in the residual network. The key biases drop out, since they shift all scores of a token equally, and the value biases enter only through γ, since the weights of a token sum to one.

Step 1: the directions that keep M, B_i and C_i. For generic parameters E and D have rank d_{model}; every $W_{Q,i}$, $W_{K,i}$, $W_{V,i}$ and $W_{O,i}^\top$ has rank d_h, since $d_h \leq d_{\text{model}}$; and the queries $[W_{Q,1}, \ldots, W_{Q,H}] \in \mathbb{R}^{d_{\text{model}} \times H d_h}$ and the output projection $W_O \in \mathbb{R}^{H d_h \times d_{\text{model}}}$ of all heads have rank d_{model}, since $H d_h \geq d_{\text{model}}$. Write $\eta_{Q,i}$, $\eta_{K,i}$, $\eta_{V,i}$ and $\eta_{O,i}$ for the entries of a direction η at the positions of $W_{Q,i}$, $W_{K,i}$, $W_{V,i}$ and $W_{O,i}$, and consider a direction with $\mathrm{D}_\theta M\, \eta = 0$ and, for every head, $\mathrm{D}_\theta B_i\, \eta = 0$ and $\mathrm{D}_\theta C_i\, \eta = 0$. Multiplying $\mathrm{D}_\theta B_i\, \eta = 0$ on the left by the projection $I - EE^+$ onto the orthogonal complement of the column space of E, where E^+ is the pseudo-inverse, leaves $(I - EE^+)\, \eta_E\, W_{Q,i} W_{K,i}^\top E^\top = 0$. As $W_{K,i}^\top E^\top$ has full row rank, $(I - EE^+)\, \eta_E\, W_{Q,i} = 0$ for every head, and as the queries of all heads have rank d_{model}, $\eta_E = EX$ with $X = E^+ \eta_E$. In the same way, multiplying $\mathrm{D}_\theta C_i\, \eta = 0$ on the right by the projection $I - D^+ D$ gives $\eta_D = -YD$ with $Y = -\eta_D\, D^+$, because $E W_{V,i}$ has full column rank and the output projection has rank d_{model}. Substituting, and cancelling E on the left and $E^\top$ or D on the right,

$$(\eta_{Q,i} + X W_{Q,i}) W_{K,i}^\top + W_{Q,i} (\eta_{K,i} + X W_{K,i})^\top = 0,$$
$$(\eta_{V,i} + X W_{V,i}) W_{O,i} + W_{V,i} (\eta_{O,i} - W_{O,i} Y) = 0.$$

If P_1 and P_2 have full column rank and $Z_1 P_2^\top + P_1 Z_2^\top = 0$, then multiplying on the right by a right inverse of $P_2^\top$ gives $Z_1 = P_1 N$ for a square matrix N, and then $Z_2 = -P_2 N^\top$. Hence $\eta_{Q,i} = -X W_{Q,i} + W_{Q,i} N_i$, $\eta_{K,i} = -X W_{K,i} - W_{K,i} N_i^\top$, $\eta_{V,i} = -X W_{V,i} + W_{V,i} N_i'$ and $\eta_{O,i} = W_{O,i} Y - N_i' W_{O,i}$: the directions of the changes of basis $I + \tau X$ at h_0 and $I + \tau Y$ at h_1, and of $I + \tau N_i$ between the queries and keys and $I + \tau N_i'$ between the values and outputs of head i. In the residual network $\mathrm{D}_\theta M\, \eta = E(X - Y)D = 0$ gives $X = Y$. These directions are independent: $EX = 0$ forces $X = 0$, $YD = 0$ forces $Y = 0$, and then $W_{Q,i} N_i = 0$ and $W_{V,i} N_i' = 0$ force $N_i = N_i' = 0$. With biases, $\mathrm{D}_\theta \beta_i\, \eta = 0$ gives $\eta_{b_{Q,i}} = b_{Q,i} N_i - g W_{Q,i}$ with $g = \eta_{b_E} - b_E X$, since $W_{K,i}^\top E^\top$ has full row rank, and $\mathrm{D}_\theta \gamma\, \eta = 0$ determines η_{b_D}. This leaves g, η_{b_O} and the entries of η at the key and value biases free, $2 d_{\text{model}} + 2 H d_h$ dimensions, which the translations at h_0 and h_1, the shifts of the key biases and the value biases moved into the output bias span.

Step 2: two tokens. For generic parameters and generic v the vectors $B_i v^\top$ are nonzero and pairwise non-collinear, since $d_{\text{model}} \geq 2$, and every $v C_i$ is nonzero. For such a v, (10) is, as a function of u, a residual network with one hidden layer of $\tanh$ units, one per head, with input weights $\frac{1}{2} B_i v^\top$, biases $\frac{1}{2}(\beta_i v^\top - \log k)$, output weights $\frac{1}{2} v C_i$, linear part K and constant term $\gamma - \frac{1}{2} v S$. Along a flat direction η these have the derivatives $\frac{1}{2}(\mathrm{D}_\theta B_i\, \eta) v^\top$, $\frac{1}{2}(\mathrm{D}_\theta \beta_i\, \eta) v^\top$, $\frac{1}{2} v (\mathrm{D}_\theta C_i\, \eta)$, $\mathrm{D}_\theta K\, \eta$ and $\mathrm{D}_\theta \gamma\, \eta - \frac{1}{2} v (\mathrm{D}_\theta S\, \eta)$, and Lemma B.3 for $\tanh$ shows that all of these vanish. This holds for all v in an open set, so $\mathrm{D}_\theta B_i\, \eta = 0$, $\mathrm{D}_\theta \beta_i\, \eta = 0$ and $\mathrm{D}_\theta C_i\, \eta = 0$; hence $\mathrm{D}_\theta S\, \eta = 0$, $\mathrm{D}_\theta M\, \eta = \mathrm{D}_\theta K\, \eta - \mathrm{D}_\theta S\, \eta = 0$ and $\mathrm{D}_\theta \gamma\, \eta = 0$.

Step 3: counting. Every direction of Step 1 is flat, since it comes from a symmetry, and by Step 2 every flat direction, already on the inputs of (10), is one of them. So $\dim \mathcal{K}(\theta)$ is $2 d_{\text{model}}^2 + 2 H d_h^2$ without the skip and $d_{\text{model}}^2 + 2 H d_h^2$ with it, and $2 d_{\text{model}} + 2 H d_h$ more with biases.

Grouped-query attention. If the H query heads share G heads of keys and values, the same proof applies with B_i and C_i formed from the keys and values of the group of head i. Step 1 uses only the queries and the output projection of all heads, and in its last part a direction that keeps the products $W_{Q,i} W_{K,g}^\top$ over the heads i of group g has one N for the whole group, since $W_{K,g}$ has full column rank; likewise for the values. So $s = 2 G d_h^2$, and the biases add $2 d_{\text{model}} + 2 G d_h$.

Position embeddings. Let a learned position embedding add the row e_t of E_{pos} to token t of h_0, in a network with an attention block and no biases, and write η_{e_t} for the entry of a direction η at the position of e_t. As E has rank d_{model}, choose ϵ_t with $\epsilon_t E = e_t$: the network computes the network without position embedding on the tokens $\tilde{x}_t = x_t + \epsilon_t$. Along η, $h_{0,t} = \tilde{x}_t E$ has the derivative $\tilde{x}_t \eta_E + \nu_t$ with $\nu_t = \eta_{e_t} - \epsilon_t \eta_E$. This is the derivative of the network without position embedding along the other entries of η together with a shift κ_t of each token $\tilde{x}_t$, where $\kappa_t E = \nu_t$. Fix a token t that sees at least one other token, and inputs for which the tokens $\tilde{x}_s$, $s \neq t$, that token t sees all equal one vector w. The output at token t is symmetric in these tokens, so its derivative sees their shifts only through their mean $\bar{\kappa}$, and it is (10) with $u = \tilde{x}_t$, $v = u - w$ and k the number of these tokens. The shifts move u by κ_t and v by $\kappa_t - \bar{\kappa}$, which adds $\frac{1}{2} B_i (\kappa_t - \bar{\kappa})^\top$ to the derivatives of the

input weights, $\frac{1}{2}\kappa_t B_i v^\top$ to those of the biases and $\frac{1}{2}(\kappa_t - \bar\kappa)C_i$ to those of the output weights of the $\tanh$ units, and Step 2 again makes each of these derivatives vanish. For all v this gives $\mathrm{D}_\theta B_i\,\eta = 0$, $\mathrm{D}_\theta C_i\,\eta = 0$, $\kappa_t B_i = 0$ and $B_i(\kappa_t - \bar\kappa)^\top = 0$ for every head, and since the queries and the keys of all heads have rank d_{model}, $\nu_t = \kappa_t E = 0$ and $\bar\kappa E = 0$. This holds for every token $t \geq 2$, and for every token without a mask; with a mask, $\bar\kappa = \kappa_1$ at $t = 2$, so $\nu_1 = 0$ as well. So $\eta_{e_t} = \epsilon_t \eta_E = e_t X$ by Step 1, the change of basis at h_0 applied to E_{pos}, and the values of part (i) hold with P counting E_{pos}. A fixed encoding, which is not trained, must instead be preserved by the change of basis at h_0; if its rows span a space of dimension r, this removes $r d_{\text{model}}$ dimensions of symmetry from both networks, and the skip still adds d_{model}^2.

Part (ii)

Write $h_1 = xE + g(x)$, with $g(x) = f(N(xE)W_{\text{read}})W_{\text{write}}$ the output of the block, and $y = N(h_1)D$, with N applied to every token; for attention, x has T tokens, and for an MLP block one suffices. Let η be flat, and write $\mathrm{D}_\theta h_1\,\eta$ and $\mathrm{D}_\theta y\,\eta$ for the derivatives of h_1 and y along η at a given input, and $\mathrm{D}N(h)$ for the Fréchet derivative of N at h.

Step 1: the final normalization. Split $\eta_D = -YD + Z$, where $Y \in \mathbb{R}^{d_{\text{model}} \times d_{\text{model}}}$ and the rows of Z are orthogonal to the row space of D, which has dimension d_{model}. At every token, by the chain rule,

$$0 \;=\; \mathrm{D}_\theta y\,\eta \;=\; \big(\mathrm{D}N(h_1)\,(\mathrm{D}_\theta h_1\,\eta) - N(h_1)Y\big)D + N(h_1)Z,$$

and the two terms lie in complementary subspaces, so both vanish. As x varies, the rows $N(h_1)$ span $\mathbb{R}^{d_{\text{model}}}$, since at large inputs they approach $\sqrt{d_{\text{model}}}\,xE/\|xE\|$ and xE takes every direction, so $Z = 0$; and since D has full row rank, $\mathrm{D}N(h_1)\,(\mathrm{D}_\theta h_1\,\eta) = N(h_1)Y$. With $\rho^2 = \|h\|^2/d_{\text{model}} + \varepsilon$, the derivative of N at h is $\mathrm{D}N(h)\,k = k/\rho - h\,\langle h, k\rangle/(d_{\text{model}}\rho^3)$, which vanishes only for $k = 0$ when $\varepsilon > 0$, and the unique $\mathrm{D}_\theta h_1\,\eta$ with $\mathrm{D}N(h_1)\,(\mathrm{D}_\theta h_1\,\eta) = N(h_1)Y$ is

$$\mathrm{D}_\theta h_1\,\eta = h_1 Y + \frac{h_1 Y_s h_1^\top}{d_{\text{model}}\varepsilon}\,h_1, \qquad Y_s = \tfrac{1}{2}(Y + Y^\top),$$

as one checks by substituting $k = h_1 Y + \mu h_1$ and solving for the number μ.

Step 2: large inputs. Fix w with $wE \neq 0$, for attention one such row for every token, and let $x = tw$ with $t \to \infty$. The block reads $N(twE)$, which stays in the ball of radius $\sqrt{d_{\text{model}}}$, so $g(tw)$ stays bounded, and for attention the scores are bounded too. The derivative of $g(tw)$ along η is bounded as well: by the formula of Step 1, $\|\mathrm{D}N(h)\,k\| \leq 2\sqrt{d_{\text{model}}}\,\|k\|/\|h\|$, which is $O(1)$ for $h = twE$ and $k = tw\eta_E$. Hence $\mathrm{D}_\theta h_1\,\eta = t\,w\eta_E + O(1)$ at the input tw, while $h_1(tw) = t\,wE + O(1)$ and the right-hand side of Step 1 is $t^3\,(wEY_sE^\top w^\top)\,wE/(d_{\text{model}}\varepsilon) + O(t^2)$. So $wEY_sE^\top w^\top = 0$ for all w in an open set, hence $EY_sE^\top = 0$, and $Y_s = 0$ because E has rank d_{model}. The matrix Y is antisymmetric, and $\mathrm{D}_\theta h_1\,\eta = h_1 Y$.

Step 3: the skip. An antisymmetric Y is the derivative at $\tau = 0$ of the orthogonal changes of basis $I + \tau Y + O(\tau^2)$ that the residual network shares between h_0 and h_1 (Lemma A.2). They define a direction η^Y with the entries EY, $-YW_{\text{read}}$, $W_{\text{write}}Y$ and $-YD$ at E, W_{read}, W_{write} and D, along which the stream h_1 has the derivative $h_1 Y$. The direction $\eta' = \eta - \eta^Y$ is flat, with $\eta'_D = 0$ and $\mathrm{D}_\theta h_1\,\eta' = 0$ at every input. At the inputs tw, $\mathrm{D}_\theta h_1\,\eta' = t\,w\eta'_E + O(1)$, so $w\eta'_E = 0$ for all w in an open set, and $\eta'_E = 0$.

Step 4: the block. With $\eta'_E = 0$, the condition $\mathrm{D}_\theta h_1\,\eta' = 0$ says that the derivative of $n \mapsto f(nW_{\text{read}})W_{\text{write}}$ along the entries of η' at the weights of the block vanishes for every n in the image of $x \mapsto N(xE)$, which is the open ball of radius $\sqrt{d_{\text{model}}}$, since E has rank d_{model} and N maps $\mathbb{R}^{d_{\text{model}}}$ onto that ball for $\varepsilon > 0$. For $\tanh$, GELU, SwiGLU, GeGLU and attention this derivative is, along every line through the ball, a function of one variable given by a convergent power series around every point; it vanishes on an interval, hence on the whole line, so it vanishes for all inputs. For the ReLU-type activations without biases the kinks lie on hyperplanes through the center of the ball, and the arguments of Lemma B.3 are local. So Lemma B.3, with E and D replaced by the identity and $M = 0$, makes the entries of η' at each hidden unit a rescaling. For attention, each token $N(x_t E)$ ranges over the ball, and Step 2 for attention blocks, with E and D replaced by the

identity and $M = 0$, keeps every $W_{Q,i}W_{K,i}^\top$ and $W_{V,i}W_{O,i}$ fixed to first order; by Step 1 there, η' is a direction of the changes of basis inside the heads.

Step 5: counting. The flat directions are thus those of the orthogonal change of basis and of the symmetries inside the block. An antisymmetric Y with $EY = 0$ vanishes, since E has rank d_{model}, and the symmetries inside the block move generic weights in independent directions, so $\dim \mathcal{K}(\theta) = d_{\text{model}}(d_{\text{model}} - 1)/2 + s$. If the block has width at least d_{model}, the skipless network with the same shapes has functional dimension at most $P - d_{\text{model}}(d_{\text{model}} - 1) - s$ by Theorem A.9(ii), Lemma A.10 and, for attention, Remark A.11, so the skip adds at least $d_{\text{model}}(d_{\text{model}} - 1)/2$.

Part (iii)

Write $B(n) = f(nW_{\text{read}})W_{\text{write}}$ for the block as a function of its input n and of its weights, applied to every token for attention, so that $h_1 = xEA + g(x)$ with $g(x) = B(N(xE))$, and $y = N(h_1)D$. For a direction ψ of the weights of the block, $\mathrm{D}_\psi B(n)$ is the derivative of $B(n)$ along ψ at fixed n, and $\mathrm{D}B(n)\, k$ is the derivative of B at n along k at fixed weights. Let η be flat.

Steps 1 and 2 of part (ii) run with EA in place of E, which has rank d_{model} since A is invertible for generic parameters: $\eta_D = -YD$ with Y antisymmetric, and $\mathrm{D}_\theta h_1\, \eta = h_1 Y$ at every input.

Step 3: the skip. At the inputs tw of Step 2, $\mathrm{D}_\theta h_1\, \eta = t\, w(\eta_E A + E\eta_A) + O(1)$ and $h_1 Y = t\, wEAY + O(1)$, so $\eta_E A + E\eta_A = EAY$. Multiplying on the left by $I - EE^+$ gives $(I - EE^+)\, \eta_E = 0$, as A is invertible, so $\eta_E = EX$ with $X = E^+\eta_E$, and then $\eta_A = AY - XA$. At every input $\mathrm{D}_\theta h_1\, \eta = xEAY + \mathrm{D}_\theta g\, \eta$ and $h_1 Y = xEAY + g(x)Y$, so $\mathrm{D}_\theta g\, \eta = g(x)Y$. By the formula for $\mathrm{D}N$ in Step 1 of part (ii), which gives the same for $\varepsilon = 0$, the input $n = N(xE)$ of the block has the derivative

$$\mathrm{D}N(xE)\,(xEX) = nX - q(n)\, n, \qquad q(n) = nX_s n^\top / d_{\text{model}}, \quad X_s = \tfrac{1}{2}(X + X^\top).$$

Step 4: the symmetric part of X. Write $X = X_a + X_s$ with X_a antisymmetric. The rotations of h_0 and h_1 with the derivatives X_a and Y are symmetries. They define a flat direction η^{rot} with the entries EX_a at E, $AY - X_a A$ at A, $-X_a W_{\text{read}}$ at W_{read}, $W_{\text{write}}Y$ at W_{write} and $-YD$ at D. The flat direction $\eta' = \eta - \eta^{\text{rot}}$ has the entries EX_s, $-X_s A$ and 0 at E, A and D, so Step 3 applies to it with X_s in place of X and 0 in place of Y, and $\mathrm{D}_\theta g\, \eta' = 0$. The change nX_s of the input moves the block as the entries $X_s W_{\text{read}}$ at W_{read} do; for attention, X_s moves the queries, keys and values in the same way. So, with ψ the entries of η' at the weights of the block plus these,

$$\mathrm{D}_\psi B(n) = q(n)\, \mathrm{D}B(n)\, n \tag{11}$$

for every n in the image of N, the open ball of radius $\sqrt{d_{\text{model}}}$. For attention, $q(n)\, n$ stands for the matrix with the rows $q(n_t)\, n_t$, one per token.

We show that $q = 0$, hence $X_s = 0$. For ReLU, ReLU^2 and ReGLU, $B(\lambda n) = \lambda^k B(n)$ for $\lambda > 0$, with $k = 1$ or 2, so the right side of (11) is $k\, q(n)B(n)$. Replacing n by λn with $0 < \lambda \leq 1$ multiplies the left side by λ^k and the right side by λ^{k+2}, so both vanish, and $q = 0$ wherever $B \neq 0$. For the other blocks both sides are analytic in n, so (11) holds for all n, and we take $n = tm$ with $t \to \infty$, as in the proof of Lemma B.3. For GELU the right side is $t^3 q(m) \max(mW_{\text{read}}, 0)W_{\text{write}}$ up to terms that decay faster than any power of t, and the left side is a polynomial of degree at most one in t up to such terms, so $q(m) \max(mW_{\text{read}}, 0)W_{\text{write}} = 0$. SwiGLU and GeGLU units $\sigma(nc_i)\, (ne_i)\, a_i$ give $2t^4 q(m) \sum_{i:\, mc_i > 0} (mc_i)(me_i)\, a_i$ against a polynomial of degree two. For $\tanh$ the right side is $4t^3 q(m) \sum_i (mc_i)\, e^{-2|mc_i|t} a_i$ up to terms $O(t^3 e^{-4|mc_i|t})$; for the unit j with the smallest $|mc_j|$, the left side contributes a polynomial of degree one times $e^{-2|mc_j|t}$ (proof of Lemma B.3), so $q(m)(mc_j)\, a_j = 0$. For attention, on the two-token inputs of Step 2 for attention blocks with $u = tm$ and v fixed, the right side is $t^3 q(m)\, mS + O(t^2)$ and the left side is $O(t)$. In every case q vanishes on an open set for generic weights, so $X_s = 0$.

Step 5: counting. With $X_s = 0$, the direction η' moves only the weights of the block, and by (11) $B(n)$ has derivative zero along it on the whole ball. So η' lies in the space $\mathcal{K}_B$ of such directions, which is the space found in Step 4 of part (ii), and every direction of $\mathcal{K}_B$ is flat. Hence $\mathcal{K}(\theta)$ is spanned by the directions η^{rot} and $\mathcal{K}_B$, as for the residual network with its single rotation, and for

generic weights of the block $\mathcal{K}_B$ has the same dimension in both networks. The directions η^{rot} are independent of $\mathcal{K}_B$ and of each other, since $\eta_E = EX_a$ and $\eta_D = -YD$ determine X_a and Y. For a full A they have dimension $d_{\mathrm{model}}(d_{\mathrm{model}}-1)$. For an upper triangular A, $AY - X_a A$ must be upper triangular, which determines Y from X_a: for generic A the map from antisymmetric Y to the entries of AY below the diagonal is invertible, as it is for $A = I$. They then have dimension $d_{\mathrm{model}}(d_{\mathrm{model}}-1)/2$. So $\mathcal{K}(\theta)$ is larger than for the residual network by $d_{\mathrm{model}}(d_{\mathrm{model}}-1)/2$, respectively 0, while the network has d^2_{model}, respectively $d_{\mathrm{model}}(d_{\mathrm{model}}+1)/2$, more parameters. In both cases the functional dimension is larger by $d_{\mathrm{model}}(d_{\mathrm{model}}+1)/2$. For the blocks of the theorem, $\mathcal{K}_B$ consists of the symmetries inside the block (Step 4 of part (ii)), so the equality condition holds.

The case $\varepsilon = 0$. Now N maps onto the sphere of radius $\sqrt{d_{\mathrm{model}}}$, and the scalings of h_0 and h_1 are symmetries too, since $N(ch) = N(h)$ for $c > 0$. In Step 1, $\mathrm{D}N(h)$ vanishes along h, so $\mathrm{D}_\theta h_1\, \eta = h_1 Y + \mu\, h_1$ with a number μ at each input. Y is again antisymmetric, since $N(h_1)Y$ must be orthogonal to h_1, which is $t\, wEA + O(1)$ at the inputs tw. At these inputs g and its derivative along η do not depend on t, since $N(twE) = N(wE)$. The terms of order t give $w\Lambda = \mu_w\, wEA$ with $\Lambda = \eta_E A + E\eta_A - EAY$ and a number μ_w, for all w in an open set. Adding to w a vector w_0 with $w_0 E = 0$ leaves wEA unchanged, so $w_0\Lambda$ is a multiple of wEA for every such w, hence $w_0\Lambda = 0$, and $\Lambda = E\Lambda'$ with $\Lambda' = E^+\Lambda$. Every vector $v = wE$ of an open set is then a left eigenvector of $\Lambda' A^{-1}$, which is therefore cI for a number c, as in the proof of Lemma A.2: $\eta_E A + E\eta_A = EA(Y + cI)$. The constant terms then give $\mu = c$ wherever wEA and $g(w)$ are linearly independent. Steps 3 and 4 run with $Y + cI$ in place of Y and with $X_s = c_0 I + X_0$, where X_0 has trace zero; the scalings, with the derivatives c_0 at h_0 and c at h_1, join the rotations in η^{rot}; and (11) holds with X_0 in place of X_s on the sphere. For the residual network the same steps give $\eta_E = E(Y + cI)$, so $X_s = cI$ and $X_0 = 0$. Its flat directions are the rotation and the scaling of all hidden states, and the space $\mathcal{K}_B$ of directions of the block along which B has derivative zero on the sphere. For the learned skip, η^{rot} and $\mathcal{K}_B$ are flat, which gives at least $d_{\mathrm{model}}(d_{\mathrm{model}}-1)+2$, respectively $d_{\mathrm{model}}(d_{\mathrm{model}}-1)/2+2$, dimensions besides $\mathcal{K}_B$, against $d_{\mathrm{model}}(d_{\mathrm{model}}-1)/2+1$ for the residual network. So the difference is at most $d_{\mathrm{model}}(d_{\mathrm{model}}+1)/2 - 1$. For ReLU, ReLU^2 and ReGLU, both sides of (11) are positively homogeneous, of degrees k and $k+2$, so $\|n\|^2\, \mathrm{D}_\psi B(n) = k d_{\mathrm{model}}\, q(n) B(n)$ for all $n \neq 0$. On each region where no nc_k changes sign, both sides are polynomials in n. Across the hyperplane $nc_i = 0$, at a point of no other such hyperplane, only the terms of unit i change, so they satisfy the identity on their own: $\|n\|^2$ times a polynomial equals $k d_{\mathrm{model}}\, q(n)$ times $(nc_i)\, a_i$, $(nc_i)^2 a_i$ or $(nc_i)(ne_i)\, a_i$. Since $\|n\|^2$ has no real linear factor, it divides $q(n)$, so X_0 is a multiple of I, and $X_0 = 0$ because its trace vanishes. Then Step 5 gives equality.

Part (iv)

With $\varepsilon = 0$, $N(h) = \sqrt{d_{\mathrm{model}}}\, h/\|h\|$ depends only on the direction of h, and $B(\lambda n) = \lambda^k B(n)$ for $\lambda > 0$, so $N(B(N(h))) = N(B(h))$: the skipless network computes $x \mapsto N(B(xE))D$. Its normalization before the block drops out, which leaves the changes of basis $\mathrm{GL}(d_{\mathrm{model}})$ at h_0 and $\mathrm{CO}(d_{\mathrm{model}})$ at h_1, of dimension $d^2_{\mathrm{model}} + d_{\mathrm{model}}(d_{\mathrm{model}}-1)/2 + 1$, and the residual network keeps one $\mathrm{CO}(d_{\mathrm{model}})$ for both hidden states (Theorem A.4(iii)).

The residual network. The case $\varepsilon = 0$ of part (iii), with $A = I$, shows that a flat direction is the sum of a direction of the rotation and scaling of all hidden states and a direction ψ of the weights of the block along which B has derivative zero on the sphere of radius $\sqrt{d_{\mathrm{model}}}$. This derivative is positively homogeneous of degree k in n, so it vanishes for all $n \neq 0$, and Lemma B.3, with E and D replaced by the identity and $M = 0$, makes ψ a rescaling of the units. So $\dim \mathcal{K}(\theta) = d_{\mathrm{model}}(d_{\mathrm{model}}-1)/2 + 1 + s$.

The skipless network. Write $h_1 = B(xE) = f(xC)W_{\mathrm{write}}$ with $C = EW_{\mathrm{read}}$, and let η be flat. As in the case $\varepsilon = 0$ of part (iii), $\eta_D = -YD$ with Y antisymmetric, since h_1 takes all values in an open set, and $\mathrm{D}_\theta h_1\, \eta = h_1 Y + \mu\, h_1$ with a number μ at each input. On each open region of inputs where no unit changes sign, h_1 and $J = \mathrm{D}_\theta h_1\, \eta - h_1 Y$ are homogeneous polynomials in x of degree k, and for generic weights two entries of h_1 have no common factor; from $J_a h_b = J_b h_a$ for any two entries, h_a divides J_a, so $J = c\, h_1$ on the region for a number c.

Across the hyperplane $xc_i = 0$, at a point x_0 of no other such hyperplane, h_1 is continuous, and J is continuous for ReLU^2 and jumps by a multiple of a_i for ReLU and ReGLU; as $h_1(x_0)$ is not parallel to a_i for generic weights, the numbers c on the two sides agree. So $\mathrm{D}_\theta h_1\, \eta = h_1(Y + cI)$ at every input. Subtracting the change of basis $I + \tau(Y + cI)$ at h_1, with the entries $W_{\text{write}}(Y + cI)$ at W_{write} and $-YD$ at D, leaves a direction along which $f(xC)W_{\text{write}}$ has derivative zero, which moves C and W_{write} only along a rescaling of the units, by Lemma B.3 with $M = 0$. After subtracting that rescaling as well, Lemma B.2 gives $\eta_E = EX$ and $\eta_{\text{read}} = -XW_{\text{read}}$ for a matrix $X \in \mathbb{R}^{d_{\text{model}} \times d_{\text{model}}}$, the change of basis at h_0. These directions are independent, as in Step 3 of part (i), so $\dim \mathcal{K}(\theta) = d_{\text{model}}^2 + d_{\text{model}}(d_{\text{model}} - 1)/2 + 1 + s$. Both values are the counts, and their difference is d_{model}^2.

Part (v)

With $\varepsilon = 0$, $N(h) = \sqrt{d_{\text{model}}}\, h/\|h\|$ ignores the length of each token, so the block reads only rows on the sphere of radius $\sqrt{d_{\text{model}}}$. Let V_θ be the space of directions that move only the weights of the block and leave its output unchanged to first order at every input whose rows lie on this sphere; it contains the symmetries inside the block. We show that the flat directions of the residual network are those of $\mathrm{CO}(d_{\text{model}})$ and those of V_θ, while the skipless network has at least two copies of $\mathrm{CO}(d_{\text{model}})$ and V_θ. The bound then holds whatever V_θ is.

The residual network. Write $h_1 = xE + g(x)$, with $g(x) = f(N(xE)W_{\text{read}})W_{\text{write}}$, and $y = N(h_1)D$, and let η be flat. Step 1 of part (ii) runs as before, except that with $\varepsilon = 0$ the derivative $\mathrm{D}N(h)$ projects onto the vectors orthogonal to h and scales by $\sqrt{d_{\text{model}}}/\|h\|$, so its kernel is spanned by h. Hence $N(h_1)Y$ is orthogonal to h_1; as h_1 takes every value in an open set, $Y_s = 0$, and $\mathrm{D}_\theta h_1\, \eta = h_1 Y + \mu(x)\, h_1$ with a number $\mu(x)$, for attention one per token. Subtracting the rotation η^Y of Step 3 there leaves a flat η' with $\eta'_D = 0$ and $\mathrm{D}_\theta h_1\, \eta' = \mu'(x)\, h_1$.

Take the inputs $x = tw$ with $t > 0$. Since N is homogeneous of degree 0, the block output $g(tw) = g(w)$ and its derivative $\gamma(w)$ along η' do not depend on t, so

$$t\, w\eta'_E + \gamma(w) \;=\; \mu'(tw)\, \big(t\, wE + g(w)\big) \qquad \text{for all } t > 0.$$

For generic parameters wE and $g(w)$ are linearly independent for all w in an open set, since otherwise the block would map every point of the sphere to a multiple of itself. Comparing the parts along wE, along $g(w)$ and outside their span gives $w\eta'_E = c_w\, wE$ and $\gamma(w) = c_w\, g(w)$ with a number c_w. Then $w\eta'_E$ is parallel to wE for all w, so η'_E vanishes on the kernel of E, $\eta'_E = ET$ with vT parallel to v for every v, and $\eta'_E = cE$ with one number c. The scaling $E \mapsto (1+\tau)E$, $W_{\text{write}} \mapsto (1+\tau)W_{\text{write}}$ multiplies h_1 by $1 + \tau$ and is the scale in $\mathrm{CO}(d_{\text{model}})$. Subtracting c times its direction leaves a flat η'' that moves only the weights of the block, with $\mathrm{D}_\theta g\, \eta'' = 0$ at the inputs tw. Their normalized rows cover an open set of the sphere, and the derivative of the block along η'' is analytic on the sphere, so $\eta'' \in V_\theta$. The directions of $\mathrm{CO}(d_{\text{model}})$ move E by $E(Y + cI)$, which vanishes only for $Y = 0$ and $c = 0$. So $\mathcal{K}(\theta)$ is the direct sum of these directions and V_θ, and the residual network has functional dimension $P - \dim \mathrm{CO}(d_{\text{model}}) - \dim V_\theta$.

The skipless network. Its block also reads only rows on the sphere, so the directions of V_θ are flat, and so are the changes of basis in $\mathrm{CO}(d_{\text{model}})$ at h_0 and at h_1 (Proposition A.1). These directions are independent. A combination moves E by $E(Y_0 + c_0 I)$ and D by $-Y_1 D$, so $Y_0 = 0$, $c_0 = 0$ and $Y_1 = 0$. What is left is a multiple of the scaling $W_{\text{write}} \mapsto (1+\tau)W_{\text{write}}$ plus a direction of V_θ, and the scaling lies in V_θ only if the block vanishes on the sphere. So the skipless network has functional dimension at most $P - 2\dim \mathrm{CO}(d_{\text{model}}) - \dim V_\theta$.

Generic parameters. The dimension of V_θ depends only on the weights of the block and takes its smallest value v for generic weights. The generic functional dimensions are therefore $P - \dim \mathrm{CO}(d_{\text{model}}) - v$ with the skip and at most $P - 2\dim \mathrm{CO}(d_{\text{model}}) - v$ without it, and the skip adds at least $\dim \mathrm{CO}(d_{\text{model}}) = d_{\text{model}}(d_{\text{model}} - 1)/2 + 1$.

We recall Theorem 4.2 from Section 4.3.

Theorem 4.2 (One block)**.** *Let $L = 1$, with a* tanh*, GELU, ReLU, ReLU^2, ReGLU, SwiGLU, GeGLU or attention block.*

(i) *Without normalization, both networks satisfy the equality condition, and the skip raises the functional dimension by exactly* d_{model}^2.
(ii) *Under RMSNorm, the residual network satisfies the equality condition, and the skip raises the functional dimension by at least* $d_{\text{model}}(d_{\text{model}}-1)/2$. *A learned skip raises it by exactly* $d_{\text{model}}(d_{\text{model}}+1)/2$ *more.*

Proof of Theorem 4.2. Part (i) is Theorem B.1(i), and part (ii) is Theorem B.1(ii) and (iii). □

C The symmetry group of a transformer is not a product over layers

Wang and Wang (2025) characterize the symmetry group of a transformer block. For a full transformer they state that the group is the product of the groups of its blocks, since residual connections and LayerNorm prevent any coupling across layers (Wang and Wang, 2025, Theorem 7). They do not define the group of the full model. We take the model to be the map from tokens to outputs, so that the embedding and the readout are among its parameters, as in the models they name (GPT-2, BERT, LLaMA and Qwen) and in their end-to-end checks, which compare the logits and generated tokens of GPT-2 models. In this case two transformations of the whole stream, applied at every hidden state from the embedding to the readout, are counterexamples.

Table 4: Relative change of the output under the two transformations of the whole stream, worst case over three random transformers ($d_{\text{model}} = 8$, two heads, three layers, GELU MLPs of width 16, generic gains and biases). The notebook also checks the assumptions of Wang and Wang (2025) before and after each transformation, and that both transformations change the function of the bare stack of blocks. Notebook, Section 7 (Appendix E).

Model	Global permutation	Global rotation
pre-norm LayerNorm, untied readout	6×10^{-16}	2×10^{-15}
pre-norm RMSNorm, untied readout	5×10^{-16}	9×10^{-16}
pre-norm LayerNorm, tied readout	5×10^{-16}	fails, at least 0.16
post-norm LayerNorm, tied readout	9×10^{-16}	not applicable

1. A *global permutation* of the stream coordinates, with every read, write, normalization gain and bias permuted along. It preserves the function at every parameter value, for every placement of the normalization and with a tied or an untied readout. Verma and Elbayad (2024, Section 3.3) apply it to merge BERT models, embeddings included.
2. A *global rotation* Q, orthogonal and, for LayerNorm, fixing the all-ones vector. In a pre-norm model with an untied readout it preserves the function when every read W after a normalization with gain g becomes $\operatorname{diag}(g)^{-1}Q^{\top}\operatorname{diag}(g)\,W$ and every LayerNorm bias b becomes $b\operatorname{diag}(g)^{-1}Q\operatorname{diag}(g)$; the gains are unchanged. This is the construction behind Theorem 1 of Ashkboos et al. (2024a).

Both transformations change the token embedding: its columns, the coordinates of the stream, are permuted or rotated. No element of the product of per-block groups changes the embedding, so both lie outside that product. The LayerNorm transformers of Table 4 satisfy the assumptions of Wang and Wang (2025), including pairwise distinct gains and generic biases, and so do the transformed parameters.

Their proof transforms the output of one block and argues that the residual term prevents the transformation (Wang and Wang, 2025, Theorem 30); applied from the embedding onward, the transformation acts on the residual term as well. Their lemma on LayerNorm holds the gain and the bias fixed (Wang and Wang, 2025, Lemma 26); the permutation moves both, and in a pre-norm block the normalized vector is only read, so the rotation does not need LayerNorm to commute with it. For a stack of blocks that acts on a fixed input and is read in fixed coordinates, both transformations change the function, and the counterexample does not apply.

The two transformations are instances of the one change of basis that the skips leave (Theorem A.4(iii)), restricted to what the normalization lets through: the rotation needs a normalization that

reads the whole vector, and the permutation passes through per-channel gains as well. With a tied readout the rotation fails: the readout after the final gain would have to become $\mathrm{diag}(g)^{-1}Q^\top \mathrm{diag}(g)\,E^\top$, while tying fixes it to $Q^\top E^\top$.

D Counts at model scale

Table 5 applies the exact reduction of Proposition A.6 to published models. Without skips, every hidden state keeps its own change of basis, and each turns one block into a triangular matrix; with skips and an untied readout, the whole network keeps one (Section 3.3). Under RMSNorm each change of basis is orthogonal and frees $d_{\mathrm{model}}(d_{\mathrm{model}}-1)/2$ parameters, and under LayerNorm the same holds with $d_{\mathrm{model}}-1$ in place of d_{model} (Proposition A.8). Llama-3.1 uses RMSNorm (Grattafiori et al., 2024), and its parameter counts are from the released weights; for the two ViT-B, with $d_{\mathrm{model}}=768$ and $L=24$ sub-blocks, we assume standard pre-LayerNorm blocks.

Table 5: Parameters that can be removed from trained networks without changing their function. Notebook, Section 8 (Appendix E).

Model	Skips	Parameters	Removable exactly
ViT-B of Ji et al. (2026)	no	86.6M	7.3M (8.5 %)
ViT-B	yes	86.6M	0.29M (0.3 %)
Llama-3.1-8B	yes	8.0B	8.4M (0.10 %)
Llama-3.1-70B	yes	70.6B	34M (0.05 %)
Llama-3.1-405B	yes	405.9B	134M (0.03 %)

The gap between the two ViT-B, 24 copies of $\mathrm{O}(767)$ or 7.1M dimensions of symmetry, 8.1 percent of the parameters, is what the skips remove (Theorem A.9), and under the equality condition what the residual network gains in functional dimension. In general, a transformer layer with an MLP of width $4d_{\mathrm{model}}$ has about $12d_{\mathrm{model}}^2$ parameters, and under normalization the skips of its two sub-blocks remove about d_{model}^2 dimensions of symmetry, a twelfth of the parameters of the blocks.

Inside the attention blocks, with or without skips, each head also has a change of basis between its queries and keys and one between its values and outputs: $12 \cdot 2Hd_h^2 = 1.2$M dimensions for ViT-B. With the one copy of $\mathrm{O}(767)$ that the residual ViT-B keeps, this gives 1.5M, the count of van Nierop (2024, Eq. 17).

E Numerical checks and reproducibility

All computations are in double precision, in a notebook that will be released in a public Git repository, coming soon; its sections are listed at the end of this appendix. Unless stated otherwise, weights have independent $\mathcal{N}(0, 1/\text{fan-in})$ entries, inputs have independent $\mathcal{N}(0,1)$ entries, and networks compared with and without skips share their weights; the notebook gives the few exceptions.

Exactness checks. For Theorems A.4 and A.7 and Proposition A.6 the transformed weights are constructed as in the proofs, and both networks are evaluated on random inputs; the reported number is $\|f' - f\|/\|f\|$ over the batch, and values near 10^{-15} are floating-point rounding. At depth six, with biases, the sweep of Theorem A.4(i) turns identity units with trainable U and V into identity skips, with U and V equal to I up to 2×10^{-15} and the function unchanged up to 2×10^{-15}, and its forward version absorbs learned affine skips with skip biases up to 10^{-15}. In Theorem A.7(ii) a scaled orthogonal skip is absorbed to 10^{-9}, which is the RMSNorm constant $\varepsilon = 10^{-8}$ acting on the overall scale (Lemma A.2), and a generic skip fails at 0.43. For Lemma A.3, on skipless ReLU, ReLU^2 and ReGLU networks of the size of Figure 3 with $\varepsilon = 10^{-1}$, 10^{-3} and 10^{-6}, a change of basis $e^{0.3S}$ at h_0, h_1 or h_2, or the scaling $e^{0.3}$ at h_3, multiplies each output by the factor Λ of the proof up to 5×10^{-12}, and with $\varepsilon = 0$ leaves the function unchanged up to 10^{-13}; the derivatives match part (ii) up to 4×10^{-12} of the output (Section 17 of the notebook). The checks of Section 3

use a pre-RMSNorm network with $d_{\text{model}} = 8$, $L = 5$ $\tanh$ blocks of width 16 and learned skips near the identity, with $\varepsilon = 10^{-2}$. Making every skip triangular changes the function by 5×10^{-16}, and making it symmetric positive definite by 4×10^{-15}. With a readout tied to the embedding through the gain of the final normalization, making the first four skips triangular and leaving the last one full changes it by 7×10^{-16} and removes 112 parameters; making all five triangular and inserting one 8×8 matrix before the gain also changes it by 7×10^{-16} and removes $140 - 64 = 76$, and spending also the rotation that this matrix frees at h_0, on a triangular block of the embedding, and the gain, which it absorbs, changes it by 10^{-15} and removes 112, no more than without the matrix. Without normalization and with a tied readout, setting the first four skips and 8 rows of the embedding to the identity changes the function by 10^{-13} and removes 320 parameters. For identity skips, a global rotation changes the tied network by 0.22, and one inserted matrix restores it to 8×10^{-16}. Setting $r = 2$ rows of each low-rank factor U to the identity changes the function by 3×10^{-15}, and without normalization the sweep of Theorem A.4 turns the low-rank skips into identity skips with a change of 6×10^{-16}. In a separate residual network of two blocks without normalization ($d_{\text{model}} = 8$, width 16), a change of basis G with $\|I - G\| = 0.41$ at the two hidden states after the first block, so that only the skip of that block joins two bases, changes the output by 0.28, 0.25, 0.050 and 0.0046 when the branch of the first block is scaled by 0.1, 1, 10 and 100, which makes it about 0.05, 0.5, 5 and 50 times the size of the skip, of the order of $\|h\|\|I - G\|/\|B(h)\|$ when the branch dominates (Section 3.3).

Functional dimension. The parameter-to-output map is evaluated on a fixed batch of inputs, and its Jacobian with respect to all parameters is formed exactly by automatic differentiation, or by central finite differences with step 10^{-6} for the small $\tanh$ networks of Table 6. For exact Jacobians the rank is read at the largest gap of the spectrum, the largest ratio s_i/s_{i+1} of consecutive singular values, 10^5 to 10^{12} for the rows of Table 6; for finite differences at the relative threshold 10^{-7}, which lies inside the gap between the genuine singular values, above 10^{-6} of the largest, and the noise of the differences, below 10^{-8}. The rank on a batch is a lower bound on the functional dimension, and where P minus it equals the symmetry count, it is the functional dimension (Theorem A.9(ii)). The values of Theorem B.1(i) hold exactly for all five activations at $d_{\text{model}} = 4$, $m = 8$, in three seeds, with and without biases, with gaps of 10^{11} to 10^{14}; with biases the inputs must cross the kink of every unit, so these checks use inputs of scale 5. For one attention block ($d_{\text{model}} = 4$, input and output dimension 6, sequences of three tokens, $(H, d_h) = (2, 2)$, $(4, 1)$ and $(1, 4)$, causal and bidirectional, with and without biases, three seeds each), all 72 networks have the values of Theorem B.1(i), with gaps of at least 4×10^{11}. Under pre-RMSNorm with $\varepsilon = 10^{-2}$ ($d_{\text{model}} = 4$, three seeds each), the residual networks with one block have the value of Theorem B.1(ii) for all five activations and for attention, and the skipless ones have $P - d_{\text{model}}(d_{\text{model}} - 1) - s$, so the skip adds exactly $d_{\text{model}}(d_{\text{model}} - 1)/2$ in these checks. A direction that the network uses only on rare inputs, such as a rarely active unit, has small singular values, and resolving it takes far more than the minimum of about P/d_{out} inputs.

The networks of Figure 3. Every network of Figure 3 is drawn 20 times, and so are the same networks with GeGLU blocks and with GLU blocks, whose gate is the logistic sigmoid; both have the counts of SwiGLU. Except for the skipless ReGLU networks under RMSNorm, the rank equals the count in every draw, at gaps of at least 6×10^4 without normalization and 10^7 under RMSNorm with $\varepsilon = 10^{-5}$. In the skipless ReGLU networks under RMSNorm, at gaps between 40 and 2×10^4, the rank read at the largest gap is 263 in 14 draws, the count 264 in 5 and 253 in one, and with hidden units added 283 in 19 draws and the count 284 in one. With $\varepsilon = 10^{-12}$ the skipless ReGLU network has rank 233 in every draw, at gaps of at least 10^4: this is $P - Ld_{\text{model}}^2 - (d_{\text{model}}(d_{\text{model}} - 1)/2 + 1) - s$, the count of the network in which every normalization but the last is removed. The residual ReGLU network then has rank $281 = P - (d_{\text{model}}(d_{\text{model}} - 1)/2 + 1) - s$ in every draw (Section 4.4). With $\varepsilon = 10^{-2}$ the rank equals the count in every draw for all six activations, ReGLU included, at gaps of at least 2.8×10^9; the notebook also plots these spectra as in Figure 3.

The size of ε. RMSNorm divides a row $h^{(t)}$ by $\sqrt{r^2 + \varepsilon}$, where $r^2 = \|h^{(t)}\|^2/d_{\text{model}}$ is its mean square, so ε acts relative to r^2. With inputs of unit variance, the median of r^2 over the inputs, and then over the draws, is 0.74 at h_0 and between 0.15 and 0.33 after the blocks of the skipless networks,




Figure 3: Singular values of the Jacobian on 4000 inputs, for the networks of Figure 1 with four kinds of blocks, and without skips with hidden units added; left without normalization, right with pre-RMSNorm. Dashed lines mark the rank. It equals the symmetry count in every draw, except for skipless ReGLU networks under RMSNorm.

and it grows along the stream of the residual networks to between 1.6 and 1.9 at h_3; at these medians ε/r^2 lies between 5×10^{-6} and 7×10^{-5} for $\varepsilon = 10^{-5}$, and is about a thousand times larger for $\varepsilon = 10^{-2}$. In a skipless network every block reads a normalized state, so the scale of the inputs enters only at h_0; the stream of a residual network carries it to every hidden state. At $\varepsilon = 10^{-5}$ the singular values with indices 234 to 264 of the skipless ReGLU network, those of the 31 directions of Section 4.4, lie between $10^{-4.5}$ and $10^{-12.6}$ of the largest in the median over the draws, except the last, which lies at the floor. The factors $\varepsilon/(r^2+\varepsilon)$ that break these directions depend on the input, and they are large for the inputs whose hidden states have a small mean square: in every draw, between 11 and 592 of the 4000 inputs have a hidden state after a block with $r^2 < 10^{-3}$, where $\varepsilon/r^2 > 10^{-2}$, and in 13 of the 20 draws up to 378 inputs have one that is exactly zero, with every gate closed.

Trained networks. We also train the networks of Figure 3, with tanh, GELU, ReGLU and SwiGLU blocks, on four classification datasets with at least four classes: two generated with scikit-learn, and satimage and segmentation from the Penn Machine Learning Benchmarks, with the features as




Figure 4: Singular values of the Jacobian at trained weights, on 1000 inputs of each dataset: the GELU networks of Figure 3, trained on four datasets (rows); median and range over five seeds. The skips add Ld_{model}^2, and $Ld_{\text{model}}(d_{\text{model}} - 1)/2$ under RMSNorm, as at random weights.

inputs and one output per class. Training uses AdamW in single precision, a learning rate chosen on a validation set, early stopping and five seeds. A network counts as trained when it beats logistic regression with a tuned penalty on the test set, as 436 of 480 do. On inputs of the dataset and on Gaussian inputs alike, the rank equals the count in 398 of the 436, and the skips add 48 and 18 (Figure 4). Of the 38 exceptions, 36 are skipless ReGLU networks under RMSNorm; one residual GELU network is 8 below the count and one residual $\tanh$ network 1 below. Two further notebooks train these networks, store them and compute their Jacobians.

Learned skips. The $\tanh$ networks of Table 6 with learned skips or with trainable identity units have the functional dimension of the residual network, 224, as Theorem A.4(ii) requires. Under RMSNorm with $\varepsilon = 10^{-2}$, learned skips have $264 - 234 = 30 = 3\,d_{\text{model}}(d_{\text{model}} + 1)/2$ more functional dimension than identity skips, as Theorem A.7(iii) predicts. On residual networks without

Table 6: Functional-dimension checks. *Func. dim* is the rank of the Jacobian on the batch; where the redundancy, P minus it, equals the prediction, the rank meets the upper bound of Theorem A.9(ii) and is the functional dimension. Every network has an embedding and a separate readout, and no biases unless marked; normalization is pre-norm. A *mixed* skip is a pair of trainable identity units U, V per block. The MLP networks have $d_{\text{model}} = 4$, width 8, $L = 3$ unless marked, and input and output dimension 6, except the rows marked *large*, which have $d_{\text{model}} = 16$, $L = 6$, width 16 and input and output dimension 20. The transformers have $d_{\text{model}} = 8$, two heads of width four, MLP width 16, a vocabulary of 16 tokens and two layers; each attention block has $2Hd_h^2$ symmetries inside. †The exact rank modulo a prime certifies the value at two parameter points; without skips at $L = 3$, the rank in floating point sits at the double-precision floor. ‡The symmetry count is 268; an embedding table read through RMSNorm adds $d_{\text{model}}(d_{\text{model}} + 1)/2 = 36$, because N maps $\mathbb{R}^{d_{\text{model}}}$ onto an open ball, so the rows of the table can absorb any invertible map near the identity, and with continuous inputs the measured value is 268.

Network	Skip	Normalization	P	Func. dim	Redundant	Predicted
tanh	none	none	240	176	64	$(L{+}1)d_{\text{model}}^2 = 64$
tanh	identity	none	240	224	16	$d_{\text{model}}^2 = 16$
tanh	learned	none	288	224	64	$(L{+}1)d_{\text{model}}^2 = 64$
tanh	mixed	none	336	224	112	$(2L{+}1)d_{\text{model}}^2 = 112$
tanh, biases	none	none	286	206	80	$(L{+}1)(d_{\text{model}}^2{+}d_{\text{model}}) = 80$
tanh, biases	identity	none	286	254	32	$d_{\text{model}}^2 + (L{+}1)d_{\text{model}} = 32$
tanh	none	RMSNorm, $\varepsilon = 10^{-9}$	240	212	28	$(L{+}1)\dim \mathrm{CO}(4) = 28$
tanh	identity	RMSNorm, $\varepsilon = 10^{-9}$	240	233	7	$\dim \mathrm{CO}(4) = 7$
tanh	learned	RMSNorm, $\varepsilon = 10^{-9}$	288	260	28	$(L{+}1)\dim \mathrm{CO}(4) = 28$
tanh	none	RMSNorm, $\varepsilon = 10^{-2}$	240	216	24	$(L{+}1)\dim \mathrm{O}(4) = 24$
tanh	identity	RMSNorm, $\varepsilon = 10^{-2}$	240	234	6	$\dim \mathrm{O}(4) = 6$
tanh	learned	RMSNorm, $\varepsilon = 10^{-2}$	288	264	24	$(L{+}1)\dim \mathrm{O}(4) = 24$
ReLU^2	none	none	240	152	88†	$(L{+}1)d_{\text{model}}^2 + Lm = 88$
ReLU^2	identity	none	240	200	40†	$d_{\text{model}}^2 + Lm = 40$
ReGLU	none	none	336	224	112†	$(L{+}1)d_{\text{model}}^2 + 2Lm = 112$
ReGLU	identity	none	336	272	64†	$d_{\text{model}}^2 + 2Lm = 64$
ReLU^2, $L = 8$	none	none	560	352	208†	$(L{+}1)d_{\text{model}}^2 + Lm = 208$
ReLU^2, $L = 8$	identity	none	560	480	80†	$d_{\text{model}}^2 + Lm = 80$
ReGLU, $L = 8$	none	none	816	544	272†	$(L{+}1)d_{\text{model}}^2 + 2Lm = 272$
ReGLU, $L = 8$	identity	none	816	672	144†	$d_{\text{model}}^2 + 2Lm = 144$
tanh, large	none	none	3712	1920	1792	$(L{+}1)d_{\text{model}}^2 = 1792$
tanh, large	identity	none	3712	3456	256	$d_{\text{model}}^2 = 256$
tanh, large	none	RMSNorm, $\varepsilon = 10^{-2}$	3712	2872	840	$(L{+}1)\dim \mathrm{O}(16) = 840$
tanh, large	identity	RMSNorm, $\varepsilon = 10^{-2}$	3712	3592	120	$\dim \mathrm{O}(16) = 120$
Transformer	identity	RMSNorm, $\varepsilon = 10^{-2}$	1280	1124	156	$\dim \mathrm{O}(8) + 4Hd_h^2 = 156$
Transformer	none	RMSNorm, $\varepsilon = 10^{-2}$	1280	976	304‡	$5\dim \mathrm{O}(8) + 4Hd_h^2 = 268$

biases or normalization ($d_{\text{model}} = 4$, $L = 3$, width 8), spending the last change of basis on d_{model} columns of the first read leaves exactly the redundancy s of the symmetries inside the blocks, the last row of Table 3.

Low-rank skips. Networks with skips $I + UV^\top$ ($L = 3$ tanh blocks of width $2d_{\text{model}}$, $d_{\text{model}} = 4$ with $r = 1, 2$ and $d_{\text{model}} = 6$ with $r = 2, 3$, exact Jacobians) have redundancy $d_{\text{model}}^2 + 2Ld_{\text{model}}r$ without normalization, all of U and V besides the global change of basis, and $d_{\text{model}}(d_{\text{model}} - 1)/2 + Lr(2r - 1)$ under RMSNorm with $\varepsilon = 10^{-2}$. Besides the global rotation and the r^2 dimensions of the $\mathrm{GL}(r)$ inside each product, each skip adds $r(r - 1)$. To first order, rotations $I + \Omega_{\ell-1}$ and $I + \Omega_\ell$ of the two hidden states that it joins change it by $(\Omega_\ell - \Omega_{\ell-1}) - \Omega_{\ell-1}UV^\top + UV^\top\Omega_\ell$, which keeps it within rank r of the identity when $\Omega_\ell - \Omega_{\ell-1}$ lies in the tangent space $\{XV^\top + UY^\top\}$ of the matrices of rank r at $UV^\top$; the antisymmetric matrices in this space have dimension $r(r - 1)$ when $2r \le d_{\text{model}}$ and U, V are generic, which the notebook confirms in every case.

Where the redundancy exceeds the count. For ReLU networks the exact Jacobian is taken with the activation pattern held fixed. On skipless ReLU networks without biases ($d_{\text{model}} = 4$, $L = 3$, width 8), 7 of 8 random draws attain the bound of Theorem A.9(ii), redundancy 88 including the rescalings of hidden units, and all 8 residual draws attain their bound, 40. In the eighth skipless draw, five units of the last block are active on exactly the same inputs, those on which one unit of the block before is

active, so there they act as one linear map of $\mathbb{R}^4$: their 40 parameters carry $40 - 16 = 24$ dimensions of redundancy instead of the 5 rescalings of the count, and the redundancy is $88 + 19 = 107$. Such coincidences need a block that reads the output of another block, so they do not occur for one block, where Theorem B.1 applies; this is consistent with Grigsby et al. (2023). On the 3000 inputs of Section 1 of the notebook, a second draw also seems to exceed the bound, by 6, because one of its units is active on only 0.08 percent of the inputs; with 30,000 inputs or more it attains the bound, and the eighth draw stays at 107 (Section 15 of the notebook). Skipless networks whose first hidden state is an embedding table read through RMSNorm are also more redundant than their symmetries (Table 6).

Certificates at depth. The rows of Table 6 at $L = 8$ are certified as those at $L = 3$, with the activation pattern from ball arithmetic and the Jacobian from reverse mode (Section 16 of the notebook). Without skips these networks start from odd pairs of units, plus noise: ReLU^2 units (u, w) and $(-u, -w)$, and ReGLU units with gates u and $-u$ that share their value and write. With identity skips the weights are Gaussian, with the writes scaled by $1/L$. From Gaussian weights, the skipless ReGLU networks at $L = 8$ attain the count on 12,000 inputs, and the ReLU^2 ones do not. In each ReLU^2 draw, 1 to 5 units of the last three blocks stay off on 2×10^6 fresh inputs, and a unit that is never on leaves its 8 parameters redundant, 7 more than its rescaling. With inputs added on which the rarely active units fire, the rank stays below the count by 35, 7 and 29: 7 for each unit that stays off, and one more in the third draw.

DyT and nanoGPT. DyT networks ($d_{\text{model}} = 4$, $L = 3$ blocks of width 8, exact Jacobians, three draws) lose $L = 3$ dimensions to the skips, the scale of each hidden state, which the learnable α of the next DyT absorbs. The nanoGPT models of Table 7 follow the `model.py` of nanoGPT (Karpathy, 2023), with token and position embeddings, pre-LayerNorm blocks with $\varepsilon = 10^{-5}$, causal attention with four heads of size two, GELU MLPs of width $4d_{\text{model}}$, a final LayerNorm and a readout, and no biases; without normalization every LayerNorm is the identity. The Jacobians are exact, over all logits of 64 random token sequences per layer. With skips the redundancy is, per layer, 144 with LayerNorm: 32 from the changes of basis inside the heads, 16 from the LayerNorm gains against the next matrix, 56 from the zero mean of each LayerNorm output, seen by every column of the next matrix, and 40 from the mean of each write, which every later LayerNorm erases. Once per model come 60 more: the global rotation, 21; the means of the 16 embedding rows, 16; the final LayerNorm against the readout, 16; and a vector moved from the position to the token embedding, 7. Without normalization it is 32 per layer and $72 = 64 + 8$ per model. For one and two layers we construct all of these symmetries, and in every draw they span the null space of the Jacobian.

Table 7: Redundancy of nanoGPT ($d_{\text{model}} = 8$, four heads of size two, a vocabulary and a context of 8, no biases, untied readout): P minus the rank of the exact Jacobian, the same in all four draws of every network and equal to the prediction. N layers make $L = 2N$ blocks. With skips, each layer is redundant by 144 with LayerNorm and by 32 without normalization, and the model once more by 60 and 72 (Appendix E).

	$N = 1$	2	3	4	Prediction
LayerNorm					
P	984	1768	2552	3336	
without skips	246	432	618	804	$144N + 60 + 21L$
with skips	204	348	492	636	$144N + 60$
No normalization					
P	960	1728	2496	3264	
without skips	232	392	552	712	$32N + 72 + 64L$
with skips	104	136	168	200	$32N + 72$

Notebook. The notebook runs on a CPU in an environment pinned with uv, with Python 3.11. Its sections follow the note and are listed below, with their times on a CPU with two cores. The two long experiments save what Figure 3 and Table 7 need, from which the notebook draws the figure and the table in seconds unless it is asked to rerun them; the times below are those of the full computation.

Section of the notebook	What it reproduces	Time
1. The gauge fix, the counts and RMSNorm	exactness checks of Theorems A.4 and A.7 and Proposition A.6; finite-difference rows of Table 6; exact ReLU and degree-two Jacobians	1 min
2. The last row of Table 3	the last row of Table 3	23 s
3. A dominant block, and learned, tied and low-rank skips	the checks of Sections 3, 3.3 and 3.4	under 1 s
4. The redundancy of low-rank skips	the low-rank skips of Section 3.4	36 s
5. DyT reads	the DyT networks	9 s
6. Exact reductions after training	the reductions of Section 3.1 and Proposition A.8	under 1 s
7. The symmetry group of a transformer is not a product	Table 4	under 1 s
8. Counts at model scale	Table 5	under 1 s
9. One block	Theorem B.1, for MLP and attention blocks	44 s
10. Figure 3	Figures 1 and 3 and the checks of their networks	28 min
11. Exact Jacobians	the rows at $d_{\mathrm{model}} = 16$, the transformers and the embedding table of Table 6	4 min
12. Certificates modulo a prime	the certificates at $L = 3$ in Table 6	19 s
13. nanoGPT	Table 7 and the constructed symmetries	38 min
14. Skipless networks as limits of residual networks	the limits of the companion paper	under 1 s
15. ReLU draws above the count	the ReLU draws above the count in Appendix E	2 min
16. Certificates at depth	the certificates at $L = 8$ in Table 6	5 min
17. Homogeneous blocks under RMSNorm	the checks of Lemma A.3	2 s