

# 1 Introduction

## 1.1 Motivation

As a result of increasing human population and habitat loss, human-wildlife conflicts have become increasingly common in last several decades [1]. According to organization The World Wide Fund for Nature (WWF) human-wildlife conflicts are defined as: "any interaction between humans and wildlife that results in negative impacts on human social, economic or cultural life, on the conservation of wildlife populations, or on the environment" [2]. These conflicts range from mostly harmless, non-violent contacts, such as sightings of wildlife animals in urban areas, to destruction of crops and infrastructure, killings of livestock, and in worst cases, losses of human lives. In more severe cases these conflicts end in defensive or retaliatory killings of wildlife animals which can drive already endangered species to extinction.

Polar bears, tigers and elephants are generally considered to be most problematic [1]. In Arctic, as a consequence of reduction of their natural habitat, polar bears are drawn to human settlements, food dumps, while searching for food [3]. Unexpected encounters can turn deadly for both sides. As wide ranging animals, tigers need large areas where they can roam, hunt and breed [4]. When their natural prey population is depleted, they often turn their attention to poorly protected livestock. Their attacks often have economic, social and psychological consequences. According to WILDLABS, tigers killed 101 people between years 2013 and 2016, in India alone [4].

As herbivores, elephants might be seen as less problematic when compared to polar bears or tigers, but this assumption could not be further from the truth. Although ex-

act numbers vary between sources, casualties from human-elephant conflicts (HEC) are much higher compared to conflicts involving polar bears or tigers. According to WILDLABS, an average of 400 people and 100 elephants are killed every year in India [5]. Leading cause of death of elephants is electrocution (by electric fences, unprotected power lines), followed by train accidents, poaching and poisoning [6]. One of HEC hotspots is in Sonitpur District, Assam province, India. In 5300 km<sup>2</sup> large area around 200,000 people and 200 elephants share the same space [5]. Elephants often venture into paddy fields which represent livelihood for local communities. A single elephant can quickly trample fields of rice crops in few hours, causing big financial problems to already impoverished farmers [5].

Several measures have been taken to minimize human-elephant conflicts:

- Electrical fences, some solar powered, some directly connected to local power lines, latter are deadly for elephants
- Watch towers
- Trenches
- Chilli-based deterrents
- Regular patrols
- Usage of trained captive elephants to drive wild elephants into the forest
- Camera traps with motion sensors

Although above mentioned measures function to some degree, they are not effective enough, since they are unreliable or come into effect when the damage has already been done [7].

## 1.2 Early detection system

One important component of minimizing human-elephant conflicts is a reliable early detection system. System capable of detecting presence of nearby elephants would

warn nearby communities and give them enough time to prepare and respond nonviolently. Same kind of system would also provide information about common elephants paths, thus giving farmers knowledge how to better construct and place their fences, barricades, to minimize HEC. System should consist of several small, deployed devices with mounted cameras, that will detect elephants and one server, which will aggregate alerts and forward them somewhere where local community will see them. TODO: MAYBE A PICTURE OF SETUP???

Appropriate workflow would be that a deployed device makes a picture of its surrounding and sends it over wireless network to main server for processing. Although most of villages in Sonitpur district have access to cell phones and internet, the connectivity can be unreliable [5]. Furthermore devices will be placed quite far from main server, which makes sending large amount of data a problem. This limits choice of wireless networks to long range technologies. It is therefore preferable that elephant detection is done on a deployed device and only results (which can be big few bytes) are send over some radio network to main server. Deployed devices will be placed in forests, fields, with no access to electricity, therefore they need to be battery powered. Low maintenance of deployed devices is a desirable quality, which means that they should be functional for longer periods of time without any human interactions. To achieve that with limited power source, they should be energy efficient, equipped with solar panels and a low power radio. Device should spent most of their time in sleep mode, conserving energy, only waking up to make a photo, processing it and sending results to main server. As most of the human-elephant conflicts happen during night [5], thermal camera is needed.

Elephant recognition can be done with a help of convolutional neural network (CNN) running inference on a microcontroller. Making this possible and evaluating the solution is the focus of this master's thesis.

### 1.3 IRNAS and Arribada Initiative

Above described system is currently in development at IRNAS in collaboration with Arribada Initiative. Slovenia based Institute IRNAS offers a complete development service, starting with idea on paper and ending with the finished product. Its previous projects cover a wide range of different fields, from free space optical systems, bio-printing, to IoT solutions which cover industrial and nature conservative use cases. Arribada Initiative is a London based team, that uses open source solutions for purposes of nature conservation. As winner of WWF and WILDLABS Human Wildlife Conflict Tech Challenge [8], Arribada received funding to develop early detection system. They spent some time in Assam, India, where they did testing of proof-of-concept design [9]. They decided on devices with thermal cameras, as human-elephant conflicts often happen during the night. Sensor of choice was FLIR Lepton 2.5 and or 3.5. They also created large dataset of elephants pictures while filming elephants in Whipsnade's zoo in United Kingdom. This dataset will be important for training neural network and it will be discussed in TODO: ADD CHAPTER NUMBER. To create a final embedded system with on device machine learning, Arribada chose to work with IRNAS.

### 1.4 Background

It is worth describing the field of machine learning and its current position in world of small, embedded devices before continuing to objectives of this master's thesis. We will only mention some high level concepts of machine learning in this section, low level details specific to neural networks will be described in section TODO: ADD SECTION NUMBER.

#### 1.4.1 Machine learning in general

According to Arthur Samuel (qtd. in Geron [10]) machine learning is a field of study that gives computers the ability to learn without being explicitly programmed.

This ability to learn is the property of various machine learning algorithms. We will be using "machine learning" and "learning" terms interchangeably. In order to learn, these learning algorithms need to be trained on a collection of examples of some phenomenon [11]. These collections are called **datasets** and can be generated artificially or collected in nature.

An example of a learning algorithm is a system that can predict type of animal movement from an accelerometer sensor. To train such system, also known as a **model**, we need expose it to a dataset which would contain accelerometer measurements of different types of movement, such a walking, running, jumping and standing still. Input to the system could be either raw measurements from all three axis or components extracted from raw measurements such as frequency or amplitude. These inputs are also known as **features**, they are values that describe phenomenon being observed [11]. Output of the system would be a predicted type of movement. Although we would label each example of measurement data what type of movement it represents, we would not directly define the relationship between the two. Instead we would let the model to figure out connection by itself, through process of training. Trained model should be general enough so it can correctly predict type of movement on unseen accelerometer data.

There exists a large variety of different learning algorithms. We can broadly categorize them in several different ways, one of them depends on how much supervision learning algorithms need in training process. Algorithms like K-nearest neighbours, linear and logistic regression, support vector machines fall into category of supervised learning algorithms. Training data that is fed into them includes solutions, also known as **labels** [10]. Described example is a example of a supervised learning problem.

Algorithms like k-Means, Expectation Maximization, Principal Component Analysis fall into category of unsupervised learning algorithms. Here training data is unlabeled, algorithms are trying to find similarities in data by itself [10]. There exist other categories such as semi-supervised learning which is a combination of previous two and reinforcement learning, where model acts inside environment according to

learned policies [10].

Neural networks, algorithms inspired by neurons in human brains [10] [12], can fall into either of categories. They are appropriate for solving complex problems like image classification, speech recognition and autonomous driving, but they require large amount of data and computing power to function correctly. They fall into deep learning, which is a sub-field of machine learning.

Today machine learning algorithms are present in many software products that we often use. They can be found in email spam detection, recommendation algorithms on Facebook and YouTube, speech recognition on smartphones and virtual personal assistants.

Training of deep learning algorithms is computationally demanding and is usually done on powerful servers or computers with dedicated graphic processing units to speed up training time. After model has been trained, they can feed it data and get prediction in return. This process is also known as **inference**. Inference is computationally less intensive compared to training process, so with properly optimized models we can run inference on personal computers, smartphones, tablets and even directly in internet browsers.

#### 1.4.2 Machine learning on embedded devices

Machine learning on embedded devices is an emerging field, which nicely coincides with Internet of things (IoT). Resources about it are limited, especially when compared to vast number of resources connected with machine learning on computers or servers. Most of the information about it can be found in form of scientific papers, blog posts and machine learning framework documentation [13] [14] [15].

Running learning algorithms directly on smart devices comes with many benefits. One of them is reduced power consumption. In most IoT applications devices send raw sensor data over wireless network to the server, which processes it either for visualization or for making informed decisions about the system as whole. Wireless communication is one of more power hungry operations that an embedded device can

do, while computation is one of more energy efficient [15]. For example, a Bluetooth communication might use up to 100 milliwatts, while MobileNetV2 image classification network running 1 inference per second would use up to 110 microwatts [15]. As deployed devices are usually battery powered, it is important to keep any wireless communication to a minimum, minimizing the amount of data that we send is paramount. Instead sending everything we capture, is much more efficient to process raw data on the device and only send results.

Another benefit of using ML on embedded devices is decreased time between event and action. If device can extract high level information from raw data, it can act on it immediately, instead of sending it to the cloud and waiting for response. Getting an result now takes milliseconds, instead of seconds.

Such benefits do come with some drawbacks. Embedded devices are more resource constrained environment when compared to personal computers or servers. Because of limited processing power it is not feasible to train ML models directly on microcontrollers. Also is not feasible to do online learning with microcontrollers, meaning that they would learn while being deployed. Models also need to be small enough to fit on a device. Most of general purpose microcontrollers only offer several hundred kilobytes of flash, up to 2 megabytes. For comparison, MobileNet v1 image classification model, optimized for mobile phones, is 16.9 MB in size [16]. To make it fit on a microcontroller, we would have to simplify it.

Usual workflow, while developing machine learning models for microcontrollers, is to train a model on training data on some powerful computer or server. When we are satisfied with accuracy of the model we then quantize it (more about quantization in chapter TODO: ADD CHAPTER NUMBER) and convert it into format understandable to our microcontroller.

There are several frameworks, proprietary and open-sourced, that can be used to develop ML applications on microcontrollers. STMicroelectronics created X-CUBE-AI, a tool which converts pre-trained model created by one of various Deep Learning frameworks into an optimized library. X-CUBE-AI works only with STM32 microcontrollers and is proprietary. Another framework, TensorFlow Lite, was created

as an extension of TensorFlow, an open-source software library used for ML applications. It provides converter tools and C++ implementations of common ML operations, that can run on any microcontroller.

## 1.5 Objective

Objective of this master's thesis is to build a device that will be able to recognize elephants and humans from images captured by a thermal camera and report its results to a remote server. For that we will have to train a neural network model capable of classifying elephants and humans from thermal images. After we implement this model on a microcontroller, we will design a printed circuit board (PCB) that will connect microcontroller with various sensors and peripherals. Device will be battery powered, so minimizing power consumption will be necessary. Device will use LoRa radio to communicate with remote server.

## 1.6 Master's thesis outline

This chapter provided an overview of motivation, some background knowledge about machine learning and objectives of this thesis. Chapter 2 will provide theoretical description of system building blocks. Thermal camera FLIR Lepton, LoRa, neural networks, TensorFlow Lite and others will be discussed there. Chapter 3 will revolve around design and implementation of the device, from hardware and software point of perspective. In chapter 4 we will test our device and present results. Chapter 5 will present our findings, described limitations of our project and suggest paths for further research.



## Bibliography

- [1] Nyhus, P. J. Human–Wildlife Conflict and Coexistence. *Annual Review of Environment and Resources*, 41, (2016), 11, pages 143–171.
- [2] SARPO, WWF. Human Wildlife Conflict Manual. Available on:  
[https://wwf.panda.org/our\\_work/wildlife/human\\_wildlife\\_conflict/hwc\\_news/?84540/Human-Wildlife-Conflict-Manual](https://wwf.panda.org/our_work/wildlife/human_wildlife_conflict/hwc_news/?84540/Human-Wildlife-Conflict-Manual), [12.06.2020].
- [3] WILDLABS, WWF. Human Wildlife Conflict Tech Challenge: Polar Bear Case. Available on:  
<https://www.wildlabs.net/hwc-tech-challenge-polar-bear-case>, [14.06.2020].
- [4] WILDLABS, WWF. Human Wildlife Conflict Tech Challenge: Tiger Case. Available on:  
<https://www.wildlabs.net/hwc-tech-challenge-tiger-case>, [14.06.2020].
- [5] WILDLABS, WWF. Human Wildlife Conflict Tech Challenge: Asian Elephant Case. Available on:  
<https://www.wildlabs.net/hwc-tech-challenge-elephant-case>, [14.06.2020].
- [6] Ganesh, S. Human-elephant conflict kills 1,713 people, 373 pachyderms in 3 years. Available on: <https://www.thehindu.com/news/national/human-elephant-conflict-kills-1713-people-373-pachyderms-in-3-years/article26225515.ece>, [14.06.2020].

- [7] WILDLABS, WWF. Human Wildlife Conflict Tech Challenge. Available on: <https://www.wildlabs.net/hwc-tech-challenge>, [14.06.2020].
- [8] WILDLABS, WWF. HWC Tech Challenge Winners Announced. Available on: <https://www.wildlabs.net/resources/news/hwc-tech-challenge-winners-announced>, [20.06.2020].
- [9] Dangerfield A. Progress report – January 2019 – Thermal imaging for human-wildlife conflict. Available on: <https://www.wildlabs.net/resources/news/hwc-tech-challenge-winners-announced>, [20.06.2020].
- [10] Geron, A. *Hands-on machine learning with Scikit-Learn and TensorFlow: concepts, tools, and techniques to build intelligent systems, 2nd edition*. O'Reilly Media, Sebastopol, CA, 2019.
- [11] Burkov, A. *The Hundred-Page Machine Learning Book*. Andriy Burkov, 2019.
- [12] Li F., Karpathy A., “Cs231n: Convolutional neural net- works for visual recognition.” Stanford University course. Available on: <http://cs231n.stanford.edu/>, [25.06.2020].
- [13] Zhang, Y., Suda, N., Lai, L., and Chandra, V. Hello edge: Keyword spotting on microcontrollers. *ArXiv*, abs/1711.07128, 2017.
- [14] Louis, M. S., Azad, Z., Delshadtehrani, L., Gupta, S., Warden, P., Reddi, V. J., and Joshi, A. Towards deep learning using tensorflow lite on risc-v. *Third Workshop on Computer Architecture Research with RISC-V (CARRV)*, 2019.
- [15] Warden P., Why the future of machine learning is tiny. Available on: <https://petewarden.com/2018/06/11/why-the-future-of-machine-learning-is-tiny/>, [06.07.2020].
- [16] Situnayake D., Make deep learning models run fast on embedded hardware. Available on: <https://www.edgeimpulse.com/blog/make-deep-learning-models-run-fast-on-embedded-hardware/>, [06.07.2020].