

```

execve("./bm", [".bm"], 0x7ffee271bfe0 /* 65 vars */) = 0
brk(NULL) = 0x564df85aa000
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
access("/etc/ld.so.preload", R_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/etc/ld.so.cache", O_RDONLY|O_CLOEXEC) = 3
fstat(3, {st_mode=S_IFREG|0644, st_size=130145, ...}) = 0
mmap(NULL, 130145, PROT_READ, MAP_PRIVATE, 3, 0) = 0x7fac5e1ef000
close(3) = 0
access("/etc/ld.so.nohwcap", F_OK) = -1 ENOENT (No such file or directory)
openat(AT_FDCWD, "/lib/x86_64-linux-gnu/libc.so.6", O_RDONLY|O_CLOEXEC) = 3
read(3, "\177ELF\2\1\1\3\0\0\0\0\0\0\0\0\3\0>\0\1\0\0\0\260\34\2\0\0\0\0"..., 832) = 832
fstat(3, {st_mode=S_IFREG|0755, st_size=2030544, ...}) = 0
mmap(NULL, 8192, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_ANONYMOUS, -1, 0)
= 0x7fac5e1ed000
mmap(NULL, 4131552, PROT_READ|PROT_EXEC, MAP_PRIVATE|MAP_DENYWRITE, 3, 0)
= 0x7fac5dbf7000
mprotect(0x7fac5ddd000, 2097152, PROT_NONE) = 0
mmap(0x7fac5dfde000, 24576, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|
MAP_DENYWRITE, 3, 0x1e7000) = 0x7fac5dfde000
mmap(0x7fac5dfe4000, 15072, PROT_READ|PROT_WRITE, MAP_PRIVATE|MAP_FIXED|
MAP_ANONYMOUS, -1, 0) = 0x7fac5dfe4000
close(3) = 0
arch_prctl(ARCH_SET_FS, 0x7fac5e1ee4c0) = 0
mprotect(0x7fac5dfde000, 16384, PROT_READ) = 0
mprotect(0x564df6e6b000, 4096, PROT_READ) = 0
mprotect(0x7fac5e20f000, 4096, PROT_READ) = 0
munmap(0x7fac5e1ef000, 130145) = 0
pipe([3, 4]) = 0
pipe([5, 6]) = 0
clone(child_stack=NULL, flags=CLONE_CHILD_CLEARTID|CLONE_CHILD_SETTID|
SIGCHLD, child_tidptr=0x7fac5e1ee790) = 10578
read(2, kol kolokol
"k", 1) = 1
write(4, "k", 1) = 1
read(2, "o", 1) = 1
write(4, "o", 1) = 1
read(2, "l", 1) = 1
write(4, "l", 1) = 1
read(2, " ", 1) = 1
write(4, " ", 1) = 1
read(2, "k", 1) = 1
write(4, "k", 1) = 1
read(2, "o", 1) = 1
write(4, "o", 1) = 1
read(2, "l", 1) = 1
write(4, "l", 1) = 1
read(2, "o", 1) = 1
write(4, "o", 1) = 1
read(2, "k", 1) = 1
write(4, "k", 1) = 1
read(2, "o", 1) = 1
write(4, "o", 1) = 1

```

```

read(2, "l", 1)           = 1
write(4, "l", 1)          = 1
read(2, "\n", 1)          = 1
write(4, "\n", 1)         = 1
read(2, "", 1)            = 0
write(6, "\f\0\0\0", 4)   = 4
read(2, kolok
"k", 1)                   = 1
write(4, "k", 1)          = 1
read(2, "o", 1)           = 1
write(4, "o", 1)          = 1
read(2, "l", 1)           = 1
write(4, "l", 1)          = 1
read(2, "o", 1)           = 1
write(4, "o", 1)          = 1
read(2, "k", 1)           = 1
write(4, "k", 1)          = 1
read(2, "\n", 1)          = 1
write(4, "\n", 1)         = 1
read(2, "", 1)            = 0
write(6, "\6\0\0\0", 4)   = 4
wait4(-1, NULL, 0, NULL)  = 10578
--- SIGCHLD {si_signo=SIGCHLD, si_code=CLD_EXITED, si_pid=10578, si_uid=29999,
si_status=0, si_utime=0, si_stime=0} ---
read(5, "\4\0\0\0", 4)    = 4
fstat(1, {st_mode=S_IFCHR|0620, st_rdev=makedev(136, 0), ...}) = 0
brk(NULL)                 = 0x564df85aa000
brk(0x564df85cb000)       = 0x564df85cb000
write(1, "4\n", 24
)                          = 2
exit_group(0)             = ?
+++ exited with 0 +++

```