





TITLE: MACHINE LEARNING ADAPTIVE BASIS SETS
FOR EFFICIENT LARGE SCALE DENSITY
FUNCTIONAL THEORY SIMULATION

AUTHORS: OLE SCHUT AND JOOST
VANDEVONDELE

JOURNAL: ACS PUBLICATIONS: JOURNAL OF
CHEMICAL THEORY AND COMPUTATION

Subtitle: Revolutionizing DFT with Dynamic Basis Set Adaptation

By: Mark Plowright




THE BASIS SET CHALLENGE IN DFT

- **Density Functional Theory (DFT):** A computational method for electronic structure calculations in computational chemistry and physics.
 - **Basis Sets:** Mathematical functions (e.g., Gaussian type orbitals) approximating atomic orbitals to describe electronic wavefunctions.
 - **The Problem:** Potential inaccuracy due to static nature.
 - **Static Nature:** Conventional basis sets are pre-defined and don't adapt to changing local chemical environments.
 - **Computational Cost:** Accuracy often requires larger, computationally expensive basis sets.
 - **Inefficiency:** Static nature compromises accuracy in dynamic systems, forcing larger basis sets and introducing inefficiencies.
 - **Example:** 6-31G(d,p) basis set for a carbon atom is the *exact same* whether that carbon is in methane (CH_4), formaldehyde (CH_2O), or carbon dioxide (CO_2)
-

ADAPTIVE BASIS SETS:

- **Concept:** Dynamically generated, atom-centered functions that adjust to the unique local chemical environment of each atom.
- **Key Advantage:** Achieves high accuracy with significantly smaller basis sets, leading to substantial computational cost reduction.
- **Mechanism: Polarized Atomic Orbitals (PAOs)**
 - PAOs are atom-centered functions, dimensioned like a minimal basis set, derived from a larger "secondary basis".
 - They are "distorted atomic orbitals" variationally optimized to minimize Self-Consistent Field (SCF) energy in their molecular environment.
 - Flexibility comes from their ability to distort (expand/contract) and admix higher angular momentum functions, mimicking polarization functions dynamically.



DFT AND THE BASIS SET TRADE-OFF.

- Think of a chemist using a computer to "see" a molecule. This process is called Density Functional Theory (DFT). The computer needs a set of tools to draw the electron cloud that surrounds the atoms. This set of tools is called a "**basis set**."

The Police Sketch Artist

- **The Goal:** A police sketch artist needs to draw a suspect's face (this is like the scientist trying to model the molecule).
- **The "Basis Set":** The artist has a book of pre-drawn features: 10 noses, 20 eye shapes, 15 mouths, etc.

Now, the artist has two choices, and both are bad:

- **Use a Small, Simple Basis Set:** This is like a book with only 3 nose shapes and 4 eye shapes.
 - **Result:** The artist can create a sketch **very quickly**.
 - **Problem:** The sketch will be cartoonish and **inaccurate**. It won't look much like the real suspect.
- **Use a Large, Complex Basis Set:** This is like a massive library with 10,000 different noses and 20,000 eye shapes.
 - **Result:** The artist can create a photorealistic, **highly accurate** sketch.
 - **Problem:** It will take time and effort to find the perfect features.

BASIS SETS (THE LIBRARY) FROM IN THIS LAB

- When you use a program like Gaussian, you choose a named basis set, like:
- **STO-3G:** This is a **minimal basis set**. It's the small, cartoonish library of features. It's very fast but not very accurate because the mathematical functions (the "bricks") are very simple and rigid.
- **6-31G(d,p) or cc-pVTZ:** These are much larger basis sets. They are the "big library." They contain many more functions for each atom:
 - **Split-Valence (6-31G):** They use multiple functions to describe the important outer electrons, giving more flexibility.
 - **Polarization Functions (the 'd,p' part):** These are functions with more complex shapes (like d- and p-orbitals) that are added to let the electron cloud get pushed and pulled into non-spherical shapes, which is crucial for describing chemical bonds.

PROCESS OF ADAPTIVE BASIS SET

- **Start with a larger "primary" basis set:** This is like having the big library of features available in the background.
- **Look at the local environment:** The program analyzes the electric field around a single atom caused by its neighbors. A carbon atom double-bonded to an oxygen experiences a very different field than one bonded to four hydrogens.
- **Create a custom function:** The program then combines functions from the primary basis set to create a new, smaller set of optimized functions (the PAOs). This optimization process mathematically "distorts" the basis functions—stretching or shrinking them, and mixing in those complex polarization shapes—so they are a perfect fit for that specific atom's environment.

THE SOLUTION: ADAPTIVE BASIS SETS."

Swapping the Library for Adaptable Clay

- Instead of a book, the artist now has a small set of "adaptable clay" features one clay nose, a pair of clay eyes, etc.
- When a witness describes the suspect's nose as "sharp and pointy," the artist takes the clay nose and **molds it** to be sharp and pointy. It *adapts* to the description.
- **The Benefit:** The artist can now create a highly accurate, custom-fit drawing using only a small, manageable set of tools. They get the accuracy of the giant library but with much less effort.
- This is what the paper's **Polarized Atomic Orbitals (PAOs)** are. They are "moldable" mathematical functions that can change their shape to perfectly describe the electrons on a specific atom in its unique chemical environment.

Instead of using a huge, static library of functions, the adaptive method builds a small, custom-fit basis set for *each atom* in its *specific environment*.

CARBON IN DIFFERENT CHEMICAL ENVIRONMENTS.

- These functions are **static**. The 6-31G(d,p) basis set for a carbon atom is the exact same whether that carbon is in methane (CH₄), formaldehyde (CH₂O), or carbon dioxide (CO₂). To make sure it can handle all these situations reasonably well, the "library" has to be huge, containing many functions that might not be needed for a specific case. This is what makes it slow.
- So, the ML model looks at the carbon atom in formaldehyde and, based on its training, instantly predicts the best custom-fit basis functions for it without ever having to do the expensive optimization calculation. Instead of a one size fits all

CARBON IN DIFFERENT ENVIRONMENT: WHAT REGULAR BASIS SETS DO NOT DISTINGUISH

Feature	Carbon in Methane (CH ₄)	Carbon in Formaldehyde (CH ₂ O)
Neighbors	Bonded to 4 identical Hydrogen atoms.	Bonded to 2 Hydrogen atoms and 1 Oxygen atom.
Bonding	Four identical, single C-H bonds.	Two single C-H bonds and one C=O double bond .
Geometry	Symmetrical tetrahedron. The pull from all 4 hydrogens is equal in all directions.	Flat (trigonal planar). The molecule is asymmetrical.
Polarity	Nonpolar. The C-H bonds have very low polarity. The electron cloud around the carbon is a fairly uniform, symmetrical puffball.	Highly Polar. Oxygen is extremely electronegative. It aggressively pulls electron density away from the carbon atom.
Electron Cloud	Symmetrical, fluffy, and evenly distributed.	Distorted and lopsided. The electrons are heavily shifted toward the oxygen. There's also a dense region of electrons above and below the molecule, forming the second part of the double bond (the pi-bond).

	Regular Basis Set (e.g., 6-31G(d,p))	Adaptive Basis Set (PAO)
On Methane	Uses the same library of functions as for any other carbon. Wastes time considering complex polarization functions that aren't needed.	Sees the symmetry, generates simple, non-polarized functions. Result: High speed.
On Formaldehyde	Pulls generic polarization functions from its library to approximate the distortion caused by the oxygen. It's a "one-size-fits-all" distortion.	Creates custom-shaped polarization functions that point directly at the oxygen and model the pi-bond perfectly. Result: High accuracy.

FINAL SYNOPSIS STEPS



RESULTS FROM THE PAPER

THE MACHINE LEARNING METHODOLOGY

- **Problem Reformulation:** Basis set adaptation is framed as a supervised machine learning task: predicting optimal parameters for adaptive basis functions.
- **Target Prediction:** Specifically, the model predicts parameters for Polarized Atomic Orbitals (PAOs).
- For Gaussian type orbitals, this means scaling the variance of radial Gaussian functions for contraction/expansion.
- **Workflow Integration:** ML prediction occurs *prior* to SCF calculations, acting as an efficient preprocessing step with negligible overhead.
- **Input Features (Descriptors):**
 - Based solely on "local geometrical information".
 - Encoded in a "rotationally invariant parameterization" for generalizability and physical consistency.
 - Achieved using a "potential anchored on neighboring atoms" to construct a "rotation matrix".
 - These descriptors capture radial distances and angular distributions of neighboring atoms.
- **Machine Learning Algorithm:** Kernel Ridge Regression (KRR).
- A "shallow learning" algorithm chosen for its balance of predictive power, efficiency, and interpretability.
- **Output:** Optimal scaling factors for the variance of radial Gaussian functions, defining the adapted basis set for DFT calculation.

TRAINING DATA GENERATION & VALIDATION

Training Data Curation:

- Optimal scaling factors for C, H, O, N, F. *Carbon, Hydrogen, Oxygen, Nitrogen, and Fluorine because they are the most common atoms in biology and medicine.*
- Derived from the smallest 2500 organic molecules in the QM9 database. *QM9 is a giant, public library of information about small molecules.*

Optimal Factor Generation:

- Rigorously obtained through *variational minimization of the Hartree-Fock (HF) energy* for each molecule.
- Ensures physically consistent and high-quality labels for ML training.

Robustness & Transferability:

- Variational nature of QM calculations provides inherent robustness, allowing satisfactory results with relatively small datasets.
- KRR prediction errors decay rapidly, achieving $<1\%$ error for ~ 2000 molecules.
- High transferability demonstrated on larger "out-of-domain" molecules, showing strong generalization.

KEY COMPONENTS OF THE ML METHODOLOGY (TABLE)

Component	Description
Problem Framed As	Prediction of optimal Polarized Atomic Orbital (PAO) parameters
Input Features	Local geometrical information (rotationally invariant descriptors derived from a potential anchored on neighboring atoms)
Machine Learning Model	Kernel Ridge Regression (KRR)
Output	Optimal scaling factors for radial Gaussian functions (defining PAO parameters)
Training Data Source	Smallest 2500 organic molecules from the QM9 database
Training Data Generation Method	Variational minimization of Hartree-Fock (HF) energy
Workflow Integration	Preprocessing step, prior to SCF calculations

IMPACT & ADVANTAGES: ACCURACY AND EFFICIENCY

- **Improved Accuracy with Smaller Basis Sets:**
 - Achieves significantly more accurate simulations with smaller, manageable basis sets.
 - Improved energetics in up to 99% of cases vs. default Pople basis sets.
 - Atomization energy errors substantially lowered (e.g., ~ 31 - 107 kcal/mol reduction for various Pople sets vs. 6-311G(2df,2pd)).
- **Significant Reduction in Computational Costs:**
 - Factor of 200 reduction in computational cost in best cases.
 - Four orders of magnitude decrease in floating-point operations (flops).
 - ML prediction step introduces "negligible computational overhead".
 - Enables previously intractable large-scale molecular dynamics simulations (e.g., liquid water).

IMPACT & ADVANTAGES: AUTOMATION AND INTEGRATION

- **Elimination of Manual Parameter Optimization:**
- ML predicts optimal PAO parameters, removing tedious and expert-intensive manual tuning.
- Streamlines research, reduces human error, and enhances reproducibility.
- **Compatibility and Integration:**
- Designed for seamless integration into existing DFT software frameworks.
- Facilitates widespread adoption without major software overhauls.
- **Demonstrated Effectiveness:**
- Proven in molecular dynamics simulations of liquid water, yielding high-accuracy results comparable to conventional methods but with superior efficiency.
- Enables calculation of nuclear gradients at substantially lower costs, crucial for MD and geometry optimizations.

QUANTIFIED PERFORMANCE IMPROVEMENTS

Performance Metric	Observed Improvement/Value	Context/Comparison
Energetic Accuracy	Improved energetics in up to 99% of cases	Compared to default Pople basis sets
Atomization Energy Error Reduction	STO-3G: ~31 kcal/mol; 3-21G: ~107 kcal/mol; 6-31G: ~11 kcal/mol; 6-31G*: ~11 kcal/mol	Compared to a larger basis set (6-311G(2df,2pd))
Computational Cost Reduction	Factor of 200	In best-case scenarios vs. conventional methods
FLOPs Reduction	4 orders of magnitude	In best-case scenarios vs. conventional methods
ML Overhead	Negligible	Added to DFT calculation time
Training Data Size for <1% Error	~2000 molecules	For Kernel Ridge Regression prediction

CONCLUSION AND FUTURE DIRECTIONS

Pivotal Advancement: Addresses limitations of static basis sets, offering enhanced accuracy, dramatic efficiency, and automation.



Expanded Scope: Enables high-fidelity QM calculations previously too demanding, pushing boundaries of molecular modeling.



Broader Trend: Exemplifies the growing integration of machine learning into fundamental computational chemistry.



Future Avenues:

Applying similar ML adaptation to other basis functions (Slater-type, wavelets) or DFT aspects (functional development, pseudopotentials).

Rigorously exploring transferability to extremely diverse chemical spaces (large biomolecules, interfaces, extended materials).

QUESTIONS?
THANKS FOR ATTENDING

OKC IN 7

