#### **Introduction to the Command Line**

Mark Gross

Slides available →

https://github.com/MarkusG/UCI-Slides



#### **About Me**

- Mathematics student at Saddleback College
- Software Developer at Roland DGA
- Programming since 2016
- Using Linux since 2018

### **Purpose of this Presentation**

- Showcase the power of the command line
- Give you an introductory knowledge of how to use it

## Why Use the Command Line?


#### It's powerful

• "Graphical user interfaces make easy tasks easy, while command line interfaces make difficult tasks possible." (TLCL xvii)


#### It's everywhere

### **Some Quick Terminology**

- Terminal displays text and receives keystrokes from the user
- Shell interprets and runs commands
- Operating system handles the computer's resources
  - Responsible for spawning new programs



# From the Shell's Perspective



### **Shells Across Operating Systems**

#### Windows

- Command Prompt/Windows Terminal
- PowerShell
- Windows Subsystem for Linux → bash

#### Linux and OSX

bash, zsh, fish, and countless others

# **Anatomy of a Shell Command**

```
[jdoe@linux ~]$ ls -la --color=always some_directory
```

- **Prompt** Tells you who and where you are
  - Current directory
- Command The application to run
- Short/long options One-time application settings
- Argument(s) Tells the application what to operate on

#### **Getting Help**

- man "manual" pages for commands (and more!)
- whatis short, one-line help information

## **Working with the File System**

- 1s "list" files/directories in the current directory
- cd "change directory"
- mkdir "make directory"
- mv "move" a file/directory
- rm "remove" delete
- ln "link" shortcuts

Let's try it!

### Kicking Things up a Notch with Expansions

#### The shell can evaluate/expand expressions

- \* "wildcard" expansion matches files in the current directory
- {a..b} range expansion {0..3} expands to 0 1 2 3
- {a,b,c} set expansion expands to a b c
- \$((expr)) arithmetic expansion \$((1 + 1)) expands to 2
  - Not too useful outside of scripts

#### Let's try it!

#### Input/Output

- cat "concatenate" files
- echo "echo" the argument back to you
- grep "it's a long story" search for a pattern in a file
  - Regular expressions coming up in the next presentation!
- wc "word count"
- head view the first few lines of a file
- tail view the last few lines of a file

Let's try it!

#### Redirection

#### The Unix Philosophy

- Each program should do one thing
- The output of one program can be the input to another

#### How do we do it?

- cmd1 | cmd2 "pipes" output of cmd1 to the input of cmd2
- cmd > somefile.txt writes the output of cmd to somefile.txt
- cmd < somefile.txt runs cmd, taking input from somefile.txt
- cmd1 | cmd2 | cmd3 | cmd4 | cmd5 ad infinitum

## **Scripting**

- The shell is a program like any other, so it can take input like any other!
- This allows us to write a sequence of shell commands and then tell the shell to execute them
- The shebang
  - Describes what program to run, taking the rest of the file as input

```
/bin/someprogram is equivalent to echo <stuff> | someprogram
<stuff>
```

#### **Scripting - Variables**

- We can save the output of commands with variables
- Variables are accessed using \$ or \${}

```
my_name="Mark"
greeting="Hello, ${my_name}!"
ls_output="$(ls)"
```

### **Scripting - Control Flow**

- if runs based on whether or not a condition is true
- case works like a series of if statements
- for a "for each" loop; runs once for everything in a given set
- while runs while a certain condition is true

### **Scripting - test**

- if works based on exit codes
- We need a command to output exit codes based on what we want to compare!

```
test expression
or
[[ expression ]]
```

#### **Further Reading**

- The Linux Command Line William Shotts
  - https://www.linuxcommand.org/tlcl.php
- https://explainshell.com