

## Discussion 5:

### Machine Learning Overview & SVM




Markus Hohle

University California, Berkeley

**Machine Learning Algorithms**


MSSE 277B, 3 Units



## Outline

### **General Overview**

### **Support Vector Machine (Supervised Learning)**



## Outline

### General Overview

Support Vector Machine  
(Supervised Learning)



	supervised	unsupervised
regression	linear regression ✓ ANNs (soon)	
classification	logistic regression ✓ Naïve Bayes ✓ K-nearest <b>SVM (today)</b> ANNs (soon)	GMM ✓ K-means ✓ Leiden, DBSCAN HMM Trees ✓





## supervised

### Workflow

1) creating the model:

```
my_model = library.method(argument1 = 'arg1', ... )
```

2) training the model

```
out = my_model.fit(xtrain, ytrain)
```

3) evaluation

```
ypred = out.predict(xeval)  
accur = (ypred == yeval).sum()/len(yeval)
```


4) prediction (actual application)

```
ypred = out.predict(xnew)
```

### How to split the data?

- 80% training (60% actual training 20% evaluation)
- 20% test

evaluation while training!





### supervised

#### Workflow

1) creating the model:

```
my_model = library.method(argument1 = 'arg1', ... )
```

2) training the model

```
out = my_model.fit(xtrain, ytrain)
```

3) evaluation

```
ypred = out.predict(xeval)  
accur = (ypred == yeval).sum()/len(yeval)
```


4) prediction (actual application)

```
ypred = out.predict(xnew)
```

#### How to split the data?

- 80% training (60% actual training 20% evaluation)
- 20% test

prediction after training/evaluation completed





## Workflow

- 1) setting up the model
- ~~2) fitting the model:  $X$  are the **features** (sepal lengths/widths and petal lengths/widths),  
 $Y$  are the **classes** (setosa, versicolor, virginica)~~
- 3) evaluating the model
- 4) applying the model to a new data set

### **unsupervised** learning:

- we don't know the classes
- sometimes we even don't know the **number  $k$  of classes**


unsupervised





resources for the next lectures to come:

## Tutorials and Books



**Dr Fridolin**  
@DrFridolin · 227 subscribers · 37 videos  
Dr Fridolin shows you how to program AI step by step, line by line without using external li...more  
[github.com/DrBigMau](https://github.com/DrBigMau)  
Customize channel Manage videos

Home Videos Playlists Posts

**For You**

**RNN 2 Building a RNN Cell**  
725 views · 11 months ago  
43:37

**RNN 1 Intro**  
615 views · 11 months ago  
10:48

**ANN 1 Single Neuron**  
272 views · 11 months ago  
33:05

building ANNs, RNNs, LSTMs, CNNs **from scratch**  
(only numpy and matplotlib)





## Tutorials and Books

examples and **application** (CNN/RNN/LSTM and more):



**Jason Brownlee**  
Machine Learning Mastery

all about **transformers, LLM/NLP** and way more



### Andrej Karpathy

@AndrejKarpathy · 451K subscribers · 14 videos

FAQ ...more

[karpathy.ai](https://karpathy.ai) and 2 more links

Subscribe




### Misra Turp

@misraturp · 38.2K subscribers · 163 videos

Here is where we learn! This is a space to take it slow

[misraturp.com/roadmap](https://misraturp.com/roadmap) and 3 more links

Subscribe



## Outline

General Overview

**Support Vector Machine**  
(Supervised Learning)




SVM = **S**upport **V**ector **M**achine

- idea:
- 1) finds best **linear** classifier for separating **two** classes by **maximizing margin** using **support vectors**
  - 2) assign new data points to these categories
  - 3) **supervised** learning
  - 4) uses the “kernel trick”

○ support vectors (data points at the edge)

best separator



- 1) What if linear separation is not possible?
- 2) Is there a multiclass SVM?






1) What if linear separation is not possible?

2) Is there a multiclass SVM?

idea: mapping data to higher dimensional feature space



a) data space in N-D

b) a function  $\phi$  maps the data into a M-D ( $M > N$ ) feature space

c) find hyperplane separator in feature space

d) map back into data space (separator not linear)





1) What if linear separation is not possible?

2) Is there a multiclass SVM?

**problems:**

- computationally intensive
- $\phi$  usually unknown


...and dimensionality!!



## 1) What if linear separation is not possible?

2) Is there a multiclass SVM?

What is the fraction of volume  $f(V)$  covered by a certain fraction of length  $f(L) = r/R$  for different dimensions  $D$ ?



answer:  $f(V) \sim f(L)^D$


$$f(V) = C(D)f(L)^D$$

$C(D)$ : constant that only depends on  $D$

$$= C(D) \left(\frac{r}{R}\right)^D$$

$$\left(\frac{r}{R}\right) \sim \sqrt[D]{f(V)}$$



fraction of length that we need to explore in order to find a particular fraction of datapoints (uniformly distributed in  $V$ )



## 1) What if linear separation is not possible?

2) Is there a multiclass SVM?

N - D space




hypersphere:

$C(D)$ : constant that only depends on  $D$

$$V_D(r) = C(D) r^D$$

fraction of volume between  $r$  and  $r - dr$

$$\frac{V_D(r) - V_D(r - dr)}{V_D(r)} = 1 - \frac{(r - dr)^D}{r^D}$$





Most of the volume of a hypersphere is located on its surface!



1) What if linear separation is not possible?

2) Is there a multiclass SVM?



- for **large  $D$**  (= number of dimensions), one has to explore a **larger fraction  $\frac{r}{R}$  of the data space** in order to get the **same fraction of data points**
- many algorithms get **less efficient** for large  $D$
- for  $D \rightarrow \infty$ , the entire volume is located on the surface of the hyperspace




- 1) What if linear separation is not possible?
- 2) Is there a multiclass SVM?

- for **large D** (= number of dimensions), one has to explore a **larger fraction  $\frac{r}{R}$  of the data space** in order to get the **same fraction of data points**
- many algorithms get **less efficient** for large D
- for  $D \rightarrow \infty$ , the entire volume is located on the surface of the hyperspace

Makes many machine learning algorithms less efficient!

“Curse of Dimensionality”

Dimensionality reduction is important!





## 1) What if linear separation is not possible?


2) Is there a multiclass SVM?

### problems:

- computationally intensive
- $\phi$  usually unknown

### idea:

- entire mathematical framework not needed
- for separation: need distances  $d$  in data space and feature space



$$d^2(x, y) = \langle x - y, x - y \rangle$$

$$d_{\phi}^2(\phi(x), \phi(y)) = \langle \phi(x) - \phi(y), \phi(x) - \phi(y) \rangle$$

$$= \langle \phi(x), \phi(x) \rangle - 2\langle \phi(x), \phi(y) \rangle + \langle \phi(y), \phi(y) \rangle \quad \text{kernel } K(x, y) := \langle \phi(x), \phi(y) \rangle$$

$$d_{\phi}^2(\phi(x), \phi(y)) = K(x, x) - 2K(x, y) + K(y, y)$$

### kernel trick:

- we don't know  $K$  either: **we guess it!**



1) What if linear separation is not possible?

2) Is there a multiclass SVM?

$$d^2(\phi(x), \phi(y)) = K(x, x) - 2K(x, y) + K(y, y)$$



example: linear kernel

$$\phi: x \mapsto x$$

$$\phi(x) = x$$

$$d_{\phi}^2(x, y) = \langle x, x \rangle - 2\langle x, y \rangle + \langle y, y \rangle = x^2 - 2xy + y^2 = (x - y)^2$$

$$d_{\phi}^2(x, y) = |x - y|$$







# 1) What if linear separation is not possible?

2) Is there a multiclass SVM?

example: : RBF (radial basis function)  $\phi: x \mapsto \zeta$   $\phi(x) = \exp(-\frac{\|x\|^2}{2\sigma^2})$

$$K(x, y) = \exp\left(-\frac{\|x - y\|^2}{2\sigma^2}\right) \quad d_{\phi}^2(\phi(x), \phi(y)) = 2\left[1 - \exp\left(-\frac{\|x - y\|^2}{2\sigma^2}\right)\right]$$







1) What if linear separation is not possible?

2) Is there a multiclass SVM?

kernels available in sklearn:

- linear:

$$K(x, y) = \|x - y\|$$

- Gaussian aka RBF (radial basis function):

$$K(x, y) = \exp\left(-\frac{\|x - y\|^2}{2\sigma^2}\right)$$

in sklearn we can adjust  $\gamma := \frac{1}{2\sigma^2}$

- polynomial:

$$K(x, y) = \sum_{n=1}^N \|x - y\|^n$$

in sklearn we can adjust  $N$


- sigmoidal:

$$K(x, y) = \frac{e^{\|x-y\|}}{1 + e^{\|x-y\|}}$$

- 1) What if linear separation is not possible?
- 2) Is there a multiclass SVM?

→ one vs rest / one vs one

green vs the rest  
→ storing probabilities




1) What if linear separation is not possible?

2) Is there a multiclass SVM?

→ one vs rest / one vs one

green vs the rest  
→ storing probabilities



orange vs the rest  
→ storing probabilities








1) What if linear separation is not possible?

2) Is there a multiclass SVM?

→ one vs rest / one vs one



green vs the rest  
→ storing probabilities



blue vs the rest  
→ storing probabilities

orange vs the rest  
→ storing probabilities




1) What if linear separation is not possible?

2) Is there a multiclass SVM?

→ one vs rest / one vs one

green vs the rest  
→ storing probabilities



blue vs the rest  
→ storing probabilities

orange vs the rest  
→ storing probabilities






1) What if linear separation is not possible?

2) Is there a multiclass SVM?

→ one vs rest / one vs one

green vs the rest  
→ storing probabilities



three probabilities for each data point  
→ assign class to most probable value

k class classification with two-  
class discriminant functions is  
ambiguous!





```
from sklearn import svm
```

see [Walk\\_Through\\_SVM.ipynb](#)

1) setting up the model & 2) fitting the model

running analysis with different kernel

```
outlinear = svm.SVC(kernel = 'linear', C = 1, decision_function_shape = 'ovr')  
linear     = outlinear.fit(X2D, Y)
```

One Versus Rest

L2 regularization parameter for error tolerance when calculating the classifier

```
outrbf     = svm.SVC(kernel = 'rbf', gamma = 1, C = 1, \  
rbf         = outrbf.fit(X2D, Y)                        decision_function_shape = 'ovr')
```

$$\gamma := \frac{1}{2\sigma^2}$$

```
outpoly    = svm.SVC(kernel = 'poly', degree = 3, C = 1, \  
poly        = outpoly.fit(X2D, Y)                        decision_function_shape = 'ovr')
```

refers to  $N$  in  $\sum_{n=1}^N \|x - y\|^n$



```
outsig     = svm.SVC(kernel = 'sigmoid', C = 1, decision_function_shape = 'ovr')  
sig        = outsig.fit(X2D, Y)
```



```
from sklearn import svm
```



see [Walk\\_Through\\_SVM.ipynb](#)

$$K(x, y) = \|x - y\|$$



$$K(x, y) = \exp\left(-\frac{\|x - y\|^2}{2\sigma^2}\right)$$

$$K(x, y) = \sum_{n=1}^N \|x - y\|^n$$



$$K(x, y) = \frac{e^{\|x - y\|}}{1 + e^{\|x - y\|}}$$







```
from sklearn import svm
```

see `Walk_Through_SVM.ipynb`


$$K(x, y) = \exp\left(-\frac{1}{2\sigma^2} \|x - y\|^2\right)$$




$$\gamma := \frac{1}{2\sigma^2} = 1$$



$$\gamma := \frac{1}{2\sigma^2} = 5$$



$$\gamma := \frac{1}{2\sigma^2} = 50$$




$$\gamma := \frac{1}{2\sigma^2} = 0.1$$




```
from sklearn import svm
```

see [Walk\\_Through\\_SVM.ipynb](#)


$$K(x, y) = \sum_{n=1}^N \|x - y\|^n$$




$N = 3$



$N = 1$



$N = 5$



$N = 0$




```
from sklearn import svm
```


see [Walk\\_Through\\_SVM.ipynb](#)

$$K(x, y) = \exp\left(-\frac{1}{2\sigma^2} \|x - y\|^2\right)$$


C is a [L2 regularization parameter](#)




$C = 1$



$C = 0.1$



$C = 10$



$C = 20$





full **4D** data set



3) evaluating the model

see [Walk\\_Through\\_SVM.ipynb](#)

linear  
accuracy: 99.3%



Gaussian ( $\gamma = 1$ )  
accuracy: 97.3%









full **4D** data set

3) evaluating the model


see [Walk\\_Through\\_SVM.ipynb](#)

polynomial ( $n = 3$ )  
accuracy: 97.3%



4) applying the model to a new data set

```
ypred = outpoly.predict([[6, 3.5],[6.3, 4.5]])
```





Thank you very much for your attention!

