Lecture 06:

Optimization

Markus Hohle

University California, Berkeley

Machine Learning Algorithms

MSSE 277B, 3 Units

Course Map

Lecture 1: Course Overview and Introduction to Machine Learning

Lecture 2: Bayesian Methods in Machine Learning

Lecture 3: Dimensionality Reduction: Principal Component Analysis

Lecture 4: Linear and Non-linear Regression and Classification

Lecture 5: Unsupervised Learning: K-Means, GMM, Trees

Lecture 6: Adaptive Learning and Gradient Descent Optimization Algorithms

classic ML tools & algorithms

Lecture 7: Introduction to Artificial Neural Networks - The Perceptron

Lecture 8: Introduction to Artificial Neural Networks - Building Multiple Dense Layers

Lecture 9: Convolutional Neural Networks (CNNs) - Part I

Lecture 10: CNNs - Part II

Lecture 11: Recurrent Neural Networks (RNNs) and Long Short-Term Memory (LSTMs)

Lecture 12: Combining LSTMs and CNNs

Lecture 13: Running Models on GPUs and Parallel Processing

Lecture 14: Project Presentations

Lecture 15: Transformer

Lecture 16: GNN

ANNs/AI/Deep Learning



Outline

- **The Problem**
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- **Simulated Annealing**



Outline

- **The Problem**
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- **Simulated Annealing**

Optimization:

The Problem

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

regression, e. g. curve fitting



minimize: $$\chi^2_{red} = \frac{1}{N - p - 1} \sum_{i=1}^{N} \frac{(\hat{y}(model)_i - y_i)^2}{\sigma_i^2}$$

classification





maximize: accuracy

minimize: cross entropy $$S = -\sum_i p(true)_i \cdot \ln p(model)_i$$

Optimization:

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

Often, the extreme of the objective function is subject to **constrains**

cross entropy $$S = -\sum_i p(true)_i \cdot \ln p(model)_i$$ constrain: $$\sum_i p_i = 1$$

→ Lagrangian Multipliers and variational calculus

→ mathematically: *Free Energy like term = Energy like term – Entropy term*

examples:
- **E**vidence **L**ower **Bo**und
- Lasso method (linear regression)
- actual energy → Boltzmann distribution

etc

Optimization:

The Problem

Any algorithm needs a “goal” aka **objective function** that has to be ***optimized*** (finding an **extreme**)

These functions are very complicated, **not analytical (= no mathematical equation)** at all

<u>two most common approaches:</u>

- gradient descent
- simulated annealing





Outline

- The Problem
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- Simulated Annealing

Optimization:

main application: **ANN!**

ChatGPT

Get Plus ×

How likely is the "Terminator Scenario"?

The "Terminator Scenario" — meaning a future where AI becomes self-aware, turns hostile, and deliberately tries to exterminate humanity like in The Terminator — is considered **extremely unlikely** by mainstream AI researchers.

Optimization:

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)
→ extreme of an objective function

gradient descent

temperature profile in space and time



T: temperature

$$\frac{dT}{dt} = \frac{\partial T}{\partial x}\frac{dx}{dt} + \frac{\partial T}{\partial y}\frac{dy}{dt} + \frac{\partial T}{\partial z}\frac{dz}{dt} + \frac{\partial T}{\partial t} = \begin{pmatrix} \frac{\partial T}{\partial x} \\ \frac{\partial T}{\partial y} \\ \frac{\partial T}{\partial z} \end{pmatrix} \circ \begin{pmatrix} \frac{dx}{dt} \\ \frac{dy}{dt} \\ \frac{dz}{dt} \end{pmatrix} + \frac{\partial T}{\partial t}$$

$$= grad(T) \circ \vec{v}$$

If *T* doesn't change with time!

Optimization:

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)
→ extreme of an objective function

gradient descent

concentration profile in space and time

E. Coli



c: concentration

$$\frac{dc}{dt} = \frac{\partial c}{\partial x}\frac{dx}{dt} + \frac{\partial c}{\partial y}\frac{dy}{dt} + \frac{\partial c}{\partial z}\frac{dz}{dt} + \frac{\partial c}{\partial t}$$

$$= \begin{pmatrix} \frac{\partial c}{\partial x} \\ \frac{\partial c}{\partial y} \\ \frac{\partial c}{\partial z} \end{pmatrix} \circ \begin{pmatrix} \frac{dx}{dt} \\ \frac{dy}{dt} \\ \frac{dz}{dt} \end{pmatrix} + \frac{\partial c}{\partial t}$$

$$= grad(c) \circ \vec{v}$$

If *c* doesn't change with time!

Optimization:

Any algorithm needs a “goal” aka **objective function** that has to be ***optimized*** (finding an **extreme**)

gradient descent



finding ***a*** and ***b*** of a van-der-Waals gas

if critical points are not accessible
→ fitting curve, finding ***a*** and ***b***

Optimization:

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

gradient descent

$$\chi^2_{red} = \frac{1}{N - p - 1} \sum_{i=1}^{N} \frac{(\hat{y}(model)_i - y_i)^2}{\sigma_i^2}$$

$$p = \frac{RT}{V_m - b} - \frac{a}{V_m^2}$$



χ^2_{red}



finding ***a*** and ***b*** of

$\log(\chi^2_{red})$





Outline

- The Problem
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- **Simulated Annealing**

Optimization: Gradient Descent

Vanilla

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$





$$x(t=2) = x(t=1) - \varepsilon \left.\frac{dy}{dx}\right|_{x(t=1)}$$

$\varepsilon > 0$

Optimization: Gradient Descent

Vanilla

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$





$$x(t=3) = x(t=2) - \varepsilon \left.\frac{dy}{dx}\right|_{x(t=2)}$$

$\varepsilon > 0$

Optimization: Gradient Descent

Vanilla

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$





$$x(t=4) = x(t=3) - \varepsilon \left.\frac{dy}{dx}\right|_{x(t=3)}$$

$\varepsilon > 0$

Optimization: Gradient Descent

Vanilla

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0 + \Delta x) - y(x_0 - \Delta x)}{2\Delta x}$$





$$x(t = 4) = x(t = 3) - \varepsilon \left.\frac{dy}{dx}\right|_{x(t=3)}$$

$\varepsilon > 0$

Optimization: Gradient Descent

Vanilla

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$





$$x(t=2) = x(t=1) - \varepsilon \left.\frac{dy}{dx}\right|_{x(t=1)}$$

$\varepsilon > 0$

Optimization:

Gradient Descent

Vanilla

$$\left.\frac{\partial y}{\partial x_1}\right|_{x_1^*;\, x_2^*} \approx \frac{y(x_1^* + \Delta x_1,\ x_2^*) - y(x_1^* - \Delta x_1,\ x_2^*)}{2\Delta x_1}$$

$$\left.\frac{\partial y}{\partial x_2}\right|_{x_1^*;\, x_2^*} \approx \frac{y(x_1^*,\ x_2^* + \Delta x_2) - y(x_1^*,\ x_2^* - \Delta x_2)}{2\Delta x_2}$$





Optimization:

Gradient Descent

Vanilla

$$\left.\frac{\partial y}{\partial x_1}\right|_{x_1^*;\, x_2^*;\ldots;\, x_N^*} \approx \frac{y(x_1^* + \Delta x_1,\ x_2^*, \ldots, x_N^*) - y(x_1^* - \Delta x_1,\ x_2^*, \ldots, x_N^*)}{2\Delta x_1}$$

$$\left.\frac{\partial y}{\partial x_2}\right|_{x_1^*;\, x_2^*;\ldots;\, x_N^*} \approx \frac{y(x_1^*, x_2^* + \Delta x_2, \ldots, x_N^*) - y(x_1^*, x_2^* - \Delta x_2, \ldots, x_N^*)}{2\Delta x_2}$$

$$\vdots$$

$$\left.\frac{\partial y}{\partial x_i}\right|_{x_1^*;\, x_2^*;\ldots;\, x_N^*} \approx \frac{y(\ldots, x_i^* + \Delta x_i, \ldots, x_N^*) - y(\ldots, x_i^* - \Delta x_i, \ldots, x_N^*)}{2\Delta x_i}$$

$$\vdots$$

$$\left.\frac{\partial y}{\partial x_N}\right|_{x_1^*;\, x_2^*;\ldots;\, x_N^*} \approx \frac{y(x_1^*, x_2^*, \ldots, x_N^* + \Delta x_N) - y(x_1^*, x_2^*, \ldots, x_N^* - \Delta x_N)}{2\Delta x_N}$$

$$\begin{pmatrix} \left.\frac{\partial y}{\partial x_1}\right|_{x_1^*;\, x_2^*;\ldots;\, x_N^*)} \\ \ldots \\ \left.\frac{\partial y}{\partial x_i}\right|_{x_1^*;\, x_2^*;\ldots;\, x_N^*} \\ \ldots \\ \left.\frac{\partial y}{\partial x_N}\right|_{x_1^*;\, x_2^*;\ldots;\, x_N^*} \end{pmatrix} = grad(y)_x$$

gradient of y wrt x



Outline

- The Problem
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- Simulated Annealing

Optimization:

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$

Learning Rate Schedule

$$x(t+1) = x(t) - \boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

$\boldsymbol{\varepsilon} > 0$ called *learning rate*

$$\Delta x = -\boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

defines how large the leap Δx is



$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$

$$x(t+1) = x(t) - \boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

Learning Rate Schedule

$\boldsymbol{\varepsilon} > 0$ called *learning rate*

$$\Delta x = -\boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

defines how large the leap Δx is



$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$

Learning Rate Schedule

$$x(t+1) = x(t) - \boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

$\boldsymbol{\varepsilon} > 0$ called *learning rate*

$$\Delta x = -\boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

defines how large the leap Δx is



… and so on…

→ smaller $\boldsymbol{\varepsilon}$?

Optimization:

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$

$$x(t+1) = x(t) - \boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

Learning Rate Schedule

$\boldsymbol{\varepsilon} > 0$ called *learning rate*



$$\Delta x = -\boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

defines how large the leap Δx is

… and so on…

→ smaller $\boldsymbol{\varepsilon}$?

Takes too long!

Optimization:

Learning Rate Schedule

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$

$$x(t+1) = x(t) - \boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

$\boldsymbol{\varepsilon} > 0$ called *learning rate*

<u>learning rate as function of t:</u>

$$\boldsymbol{\varepsilon}(t) = \frac{\boldsymbol{\varepsilon}_0}{1+\kappa\, t}$$

decay rate κ

$$\Delta x = -\boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

defines how large the leap Δx is

Optimization:

Learning Rate Schedule

$$\left.\frac{dy}{dx}\right|_{x_0} \approx \frac{y(x_0+\Delta x) - y(x_0-\Delta x)}{2\Delta x}$$

$$x(t+1) = x(t) - \boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

$\boldsymbol{\varepsilon} > 0$ called *learning rate*

$$\Delta x = -\boldsymbol{\varepsilon}\left.\frac{dy}{dx}\right|_{x(t)}$$

defines how large the leap Δx is

<u>learning rate as function of t:</u>

$$\boldsymbol{\varepsilon}(t) = \frac{\boldsymbol{\varepsilon}_0}{1+\kappa\, t}$$

decay rate κ

can also be a stepwise function (learning rate schedule)

Learning Rate Schedule

<u>learning rate as function of t:</u>

$$\varepsilon(t) = \frac{\varepsilon_0}{1 + \kappa\, t}$$ decay rate κ

$$\Delta x = -\,\varepsilon \left.\frac{dy}{dx}\right|_{x(t)}$$ defines how large the leap Δx is

can also be a stepwise function (learning rate schedule)



better:
adaptive gradient, aka **AdaGrad**

$$r_{t+1} = r_t + grad(y)_x \oplus grad(y)_x$$

$\oplus$: outer product
δ: small, >0

$$\varepsilon \rightarrow \frac{\varepsilon}{\sqrt{r_{t+1}} + \delta}$$



Outline

- The Problem
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- Simulated Annealing

Optimization: Gradient Descent







Momentum

even with AdaGrad and learning rate schedule
→ would get stuck in local minimum

need to roll over → **momentum**

Momentum



taking the **average** of ***N*** previous gradients

$$\langle grad(y)_{x(t)} \rangle = \frac{1}{N}[grad(y)_{x(t-1)} + grad(y)_{x(t-2)} + \ldots + grad(y)_{x(t-N)}]$$

but we want more recent gradients to contribute more than older gradients

→ **weighted average** with weighting factor $\boldsymbol{\mu_k}$

$$\langle grad(y)_{x(t)} \rangle = \sum_{k=t-N}^{t-1} \mu_k \cdot grad(y)_{x(k)}$$

Finding a clever way to adjust $\boldsymbol{\mu_k}$ during every iteration t



Momentum

weighted average with weighting factor $\boldsymbol{\mu_k}$

Finding a clever way to adjust $\boldsymbol{\mu_k}$ during every iteration t

$$\langle grad(y)_{x(0)} \rangle = grad(y)_{x(0)} \qquad \mu_0 = (0,1)$$

$$\langle \boldsymbol{grad(y)_{x(1)}} \rangle = grad(y)_{x(1)} + \mu_0 \cdot grad(y)_{x(0)}$$



Momentum

weighted average with weighting factor $\boldsymbol{\mu_k}$

Finding a clever way to adjust $\boldsymbol{\mu_k}$ during every iteration t

$$\langle grad(y)_{x(0)} \rangle = grad(y)_{x(0)} \qquad \mu_0 = (0,1)$$

$$\langle \boldsymbol{grad(y)_{x(1)}} \rangle = grad(y)_{x(1)} + \mu_0 \cdot grad(y)_{x(0)}$$

$$\langle \boldsymbol{grad(y)_{x(2)}} \rangle = grad(y)_{x(2)} + \boxed{\mu_0}\,[grad(y)_{x(1)} + \boxed{\mu_0}\,grad(y)_{x(0)}]$$

$$\boldsymbol{\mu_{k=2}} = \mu_0\,\mu_0 = \mu_0^2$$

$$\langle \boldsymbol{grad(y)_{x(3)}} \rangle = grad(y)_{x(3)} + \boxed{\mu_0}\left[grad(y)_{x(2)} + \boxed{\mu_0}\left[grad(y)_{x(1)} + \boxed{\mu_0} \cdot grad(y)_{x(0)}\right]\right]$$

… and so on…

Optimization:

Momentum

weighted average with weighting factor $\boldsymbol{\mu_k}$

$\mu_0 = (0,1)$ called "momentum'



$$\langle \boldsymbol{grad(y)_{x(3)}} \rangle = grad(y)_{x(3)} +$$

$$\mu_0 \left[grad(y)_{x(2)} + \mu_0 \left[grad(y)_{x(1)} + \mu_0 \cdot grad(y)_{x(0)} \right] \right]$$ … and so on…

```
class Optimizer:

    def __init__(self, learning_rate = 0.1, decay = 0, momentum = 0):
      self.learning_rate          = learning_rate
      self.decay                  = decay
      self.current_learning_rate  = learning_rate
      self.iterations             = 0
      self.momentum               = momentum
```



Outline

- The Problem
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- Simulated Annealing

Optimization:

L1 and L2

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

Often, the extreme of the objective function is subject to **constrains**

sometimes we have some **prior knowledge** about the **independent variables**

<u>recall: linear regression</u>

finding best β by

$$\min_{\beta} \left\{ \frac{1}{N} \| Y - X\beta \|^2 \right\}$$

now:
constrain: **encourages sparsity of $\boldsymbol{\beta}$**

$$\min_{\beta} \left\{ \frac{1}{N} \| Y - X\beta \|^2 + \boldsymbol{\lambda} \| \boldsymbol{\beta} \|^1 \right\}$$

λ *Lagrangian Multiplier*

called **L1 regularization**, or LASSO

Optimization:

L1 and L2

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

Often, the extreme of the objective function is subject to **constrains**

sometimes we have some **prior knowledge** about the **independent variables**

L1 regularization



We often have even hard constrains based on the laws of physics!

Optimization:

L1 and L2

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

Often, the extreme of the objective function is subject to **constrains**

sometimes we have some **prior knowledge** about the **independent variables**

<u>recall: linear regression</u>

finding best β by

$$\min_{\beta} \left\{ \frac{1}{N} \| Y - X\beta \|^2 \right\}$$

now:

$$\hat{\beta} = (X^T X + \boldsymbol{\lambda I})^{-1} X^T Y \longrightarrow \min_{\beta} \left\{ \frac{1}{N} \| Y - X\beta \|^2 + \boldsymbol{\lambda} \| \boldsymbol{\beta} \|^2 \right\}$$

λ *Lagrangian Multiplier*

called **L2 regularization**, or RIDGE penalizes large β

L1 and L2 regularization

L1 and L2



$$x(t=2) = x(t=1) - \varepsilon \left.\frac{d[y + \lambda_1 \|x\|^1 + \lambda_2 \|x\|^2]}{dx}\right|_{x(t=1)}$$

$$x(t=2) = x(t=1) - \varepsilon \left.\frac{dy}{dx}\right|_{x(t=1)} - \varepsilon \left.\frac{\lambda_1 d\|x\|^1}{dx}\right|_{x(t=1)} - \varepsilon \left.\frac{\lambda_2 d\|x\|^2}{dx}\right|_{x(t=1)}$$

- gradient descent does not stop if values for x are too large and prefers sparsity
- note: the derivative of $\|x\|^1$ returns the sign (i. e. direction)
- usually $\lambda \ll \|x\|^n$
- will be important for ANNs later



Outline

- The Problem
- **Gradient Descent**
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- Simulated Annealing

Optimization:

More Fine Tuning

Vanilla Gradient Descent → **S**tochastic **G**radient **D**escent

↓

Learning Rate Schedule, L1, L2

↓

momentum

↓

$\varepsilon \rightarrow \frac{\varepsilon}{\sqrt{r_{t+1}}+\delta}$ adaptive gradient, aka **AdaGrad**

↓

Multiplying a decay factor to the sum of gradient squared (similar to momentum), aka **R**oot **M**ean **S**quare **Prop**agation **RMSProp**

different scaling for all different directions

all combined:
Adaptive **M**oment Estimation
aka **Adam**

Optimization:

Lili Jiang

TowardsDataScience

More Fine Tuning



gradient descent (cyan),
momentum (magenta),
AdaGrad (white),
RMSProp (green),
Adam (blue)

Optimization:

Lili Jiang

TowardsDataScience

More Fine Tuning



gradient descent (cyan),
momentum (magenta),
AdaGrad (white),
RMSProp (green),
Adam (blue)



Outline

- The Problem
- Gradient Descent
  - Vanilla
  - Learning Rate Schedule
  - Momentum
  - L1 and L2
  - More Finetuning
- **Simulated Annealing**

Optimization:

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

simulated annealing



If $\Delta E(x,y)$ is **negative**:
→ **always move**
(a ball always rolls down the hill)

If $\Delta E(x,y)$ is **positive**:
→ calculate the **probability to move**
→ leaves some chance to escape local minimum

T: temperature

Boltzmann factor

$$p_{move} \sim \exp\left[-\frac{\Delta E(x,y)}{T}\right]$$

Optimization: Simulated Annealing

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

simulated annealing



If $\Delta E(x,y)$ is **negative**:
→ **always move**
(a ball always rolls down the hill)

If $\Delta E(x,y)$ is **positive**:
→ calculate the **probability to move**
→ leaves some chance to escape local minimum

T: temperature

Boltzmann factor

$$p_{move} \sim \exp\left[-\frac{\Delta E(x,y)}{T}\right]$$

slowly reducing T → making larger jumps ($\Delta E(x,y)$) less likely over time

Optimization:

Any algorithm needs a "goal" aka **objective function** that has to be ***optimized*** (finding an **extreme**)

simulated annealing

Metropolis (Chem 273):

1) suggest a random move Δx and Δy

2) calculate $\Delta E(x, y)$ based on Δx and Δy

3) move or not:

a) move if $\Delta E(x, y) < 0$

b) if $\Delta E(x, y) > 0$

- draw a **random number** $\boldsymbol{\rho}$ from a **uniform distribution** in the interval $(\mathbf{0}, \mathbf{1})$
- move if $\rho < \exp\left[-\frac{\Delta E(x,y)}{T}\right]$

4) reduce T and repeat

Thank you very much for your attention!