Package 'RFlux'

March 14, 2022

Type Package	
Title Eddy Co	variance Flux Data Processing
Version 3.2.0	
Date 2022-02-	07
	nico Vitale [aut, cre], pale [com, ctb]
Maintainer D	omenico Vitale <domvit@unitus.it></domvit@unitus.it>
lease high tural field tered trad ment as v	n R graphical user interface for processing eddy covariance raw data and re- n quality fluxes of the main GHGs exchanged by ecosystems and agricul- ls. Fluxes are estimated through a call to the open source EddyPro software (regis- lemark, LI-COR, Biosciences, 2020). 'RFlux' provides tools for the metadata manage- well as for the implementation of the robust data cleaning procedure described by Vi- (2020) <doi:10.5194 bg-17-1367-2020="">.</doi:10.5194>
License GPL(>=2)
xts, string robfilter,	utils, bit64, data.table, imputeTS, robustbase, zoo, gr, stlplus, egcm, alphaOutlier, timeDate, car, future, future.apply, lubridate, MASS, gtools, test, forecast
Depends R (>=	= 3.5.0)
Suggests knitr	rmarkdown, markdown
VignetteBuilde	er knitr
NeedsCompila	tion no
R topics d	ocumented:
cleanl closed conve despil ecmd ecwon eddyp get_m inst_p	-package 2 Flux 3 l_path_rawdata 8 rt_rawdata 9 ting 11 _table 12 kset 14 ro_run 15 d 17 rob_test 20 21
maint	

2 RFlux-package

RFlux	к-package	Eda	ly C	ova	ria	nce	F_{i}	lux	D	ata	ı P	ro	ce.	ssi	ng								
Index																							27
	tlag_detection																				•		25
	qcStat robf_despiking																						22
	mode																						22

Description

An R graphical user interface for processing eddy covariance raw data and release high quality fluxes of the main GHGs exchanged by ecosystems and agricultural fields. Fluxes are estimated through a call to the open source EddyPro software (registered trademark, LI-COR, Biosciences, 2020). 'RFlux' provides tools for the metadata management as well as for the implementation of the robust data cleaning procedure described by Vitale et al (2020) <doi:10.5194/bg-17-1367-2020>.

Details

RFlux package ingests eddy covariance rawdata sampled by either open- or closed-path system and implement the processing pipeline adopted by the ICOS-ETC (Integrated Carbon Observation System European Research Infrastructure - Ecosystem Thematic Center, http://www.icos-etc.eu/icos/). All metadata information have to be reported in the *filename_ecmd.csv* table. Such information are then processed by the get_md function.

The processing of rawdata aims at

i estimating fluxes and other micrometeorolgical parameters.

ii performing data quality control.

Flux estimation involves the following options/methods:

- Planar fit for tilt correction (Wilczak et al, 2001).
- Maximum cross-covariance method for time lag determination (see Rebmann et al, 2012).
- Block average (see Moncrieff et al, 2004).
- WPL correction, only for open path systems (Webb et al, 1980).
- In-situ spectral corrections (Fratini et al, 2012).

The open source EddyPro software (registered trademark, LI-COR Biosciences, 2019) is used to this aim employing also the estimation of micrometeorological parameters useful in subsequent analyses. It is required the EddyPro software is installed on your system (for download see www.licor.com/EddyPro).

Quality control involves the data cleaning procedure described in Vitale et al (2020). Its implementation involves a three-step procedure

- **Step 1:** Estimation of the QC test statistics via the qcStat function.
- **Step 2:** Generating the workset via the ecworkset function.
- **Step 3:** Application of data cleaning procedure (including despiking) via the cleanFlux function.

Acknowledgements. RFlux has been developed in the context of the ICOS Ecosystem Thematic Centre. DV and DP thank the ENVRIPLUS H2020 European project (Grant Agreement 654182) and the ENVRIFAIR H2020 European project (Grant Agreement 824068) for the support.

Author(s)

Domenico Vitale [aut, cre], Dario Papale [com, ctb] Maintainer: Domenico Vitale <domvit@unitus.it>

References

Fratini, G., Mauder, M. (2014). Towards a consistent eddy-covariance processing: an intercomparison of EddyPro and TK3. Atmospheric Measurement Techniques, 7(7), 2273-2281, doi: https://doi.org/10.5194/amt-7-2273-2014.

Fratini, G., Ibrom, A., Arriga, N., Burba, G., Papale, D. (2012). Relative humidity effects on water vapour fluxes measured with closed-path eddy-covariance systems with short sampling lines. Agricultural and forest meteorology, 165, pp 53-63, doi: https://doi.org/10.1016/j.agrformet. 2012.05.018.

LI-COR Biosciences: EddyPro 7.0.4: Help and User's Guide, LI-COR Biosciences, Lincoln, Nebraska USA, www.licor.com/EddyPro, 2019.

Moncrieff, J., Clement, R., Finnigan, J., Meyers, T. (2004). Averaging, detrending, and filtering of eddy covariance time series. In Handbook of micrometeorology, pp. 7-31, Springer, Dordrecht, doi: https://doi.org/10.1007/1-4020-2265-4_2.

Rebmann, C., Kolle, O., Heinesch, B., Queck, R., Ibrom, A., Aubinet, M. (2012). Data acquisition and flux calculations. In Eddy covariance, pp. 59-83, Springer, Dordrecht.

Vitale, D. Fratini, G. Bilancia, M. Nicolini, G. Sabbatini, S. Papale, D. (2019). A robust data cleaning procedure for eddy covariance flux measurements, Biogeosciences, 17, 1367–1391, doi: https://doi.org/10.5194/bg-17-1367-2020, 2020.

Webb, E.K., Pearman, G.I., Leuning, R. (1980). Correction of flux measurements for density effects due to heat and water vapour transfer. Quarterly Journal of the Royal Meteorological Society, 106(447), pp 85-100, doi: https://doi.org/10.1002/qj.49710644707.

Wilczak, J.M., Oncley, S.P., Stage, S.A. (2001). Sonic anemometer tilt correction algorithms. Boundary-Layer Meteorology, 99(1), pp 127-150, doi: https://doi.org/10.1023/A:1018966204465.

cleanFlux

Cleaning eddy covariane flux measurements

Description

This is the main function of the RFlux library. It performs the data cleaning procedure described by Vitale et al (2019).

Usage

Arguments

path_workset path where the workset file generated from function ecworkset is stored.

path_ecmd path where the eddy covariance metadata file (*CC-xxx*_ecmd.csv) is stored.

path_output path where the output file will be stored. Default is NULL.

FileName file name for the output file. Deafult is NULL.

plotQC Logical. Should the details of data cleaning procedure be saved. If TRUE two

.jpeg files (Details and Synthesis) for each flux variables will be stored in the

path specified by path_output. Default is FALSE.

storage Logical. Should the Net Ecosystem Exchange flux take into account the CO2

storage term. Default is FALSE.

Details

Comparing statistics estimated by qcStat with two threshold values, each test returns one of 3 possible statements:

SevEr: if the test provides strong evidence about the presence of a specific source of systematic error.

ModEr: if the test provides only weak evidence about the presence of a specific source of systematic error.

NoEr: if the test does not provide evidence about the presence of a specific source of systematic error.

The data cleaning is based on a two-step procedure. In the first stage, fluxes that inherited at least one SevEr statement are rejected, while fluxes that inherited no SevEr statements and any number of ModEr statements are retained. In the second stage, flux data that inherited no SevEr statement are subject to an outlier detection procedure and only flux data that are both detected as outlier and inherited at least a ModEr statement are conclusively rejected. This implies that data points that inherited any number of ModEr statements but were not detected to be outliers, as well as outliers which showed no evidence of systematic errors, are retained in the dataset and can be used for any analysis or modeling purposes.

Value

Returns a dataframe containing:

TIMESTAMP_START

ISO timestamp start of averaging period (format: yyyymmddHHMM).

TIMESTAMP_END ISO timestamp end of averaging period (format: yyyymmddHHMM).

TAU_UNCLEANED Momentum flux (uncleaned).

TAU Momentum flux (cleaned).

TAU_DATA_FLAG Flag for TAU (0: observed flux for which any quality control (QC) tests provided

negligible evidences of error; 1: outlying flux rejected because at least one of the QC tests provided a moderate evidence of error; 2: flux removed because at

least one of the QC test provided a severe evidence of error).

H_UNCLEANED Sensible heat turbulent flux (no storage correction, uncleaned).

H Sensible heat turbulent flux (no storage correction, cleaned).

H_DATA_FLAG Flag for H (0: observed flux for which any quality control (QC) tests provided

negligible evidences of error; 1: outlying flux rejected because at least one of the QC tests provided a moderate evidence of error; 2: flux removed because at

least one of the QC test provided a severe evidence of error).

LE_UNCLEANED Latent heat turbulent flux (no storage correction, uncleaned).

LE Latent heat turbulent flux (no storage correction, cleaned).

LE_DATA_FLAG	Flag for LE (0: observed flux for which any quality control (QC) tests provided negligible evidences of error; 1: outlying flux rejected because at least one of the QC tests provided a moderate evidence of error; 2: flux removed because at least one of the QC test provided a severe evidence of error).
FC	Carbon Dioxide (CO2) turbulent flux (no storage correction).
SC	Carbon Dioxide (CO2) storage flux.
NEE_UNCLEANED	Net Ecosystem Exchange (uncleaned).
NEE	Net Ecosystem Exchange (cleaned).
NEE_DATA_FLAG	Flag for NEE (i.e., 0: observed flux for which any quality control (QC) tests provided negligible evidences of error; 1: outlying flux rejected because at least one of the QC tests provided a moderate evidence of error; 2: flux removed because at least one of the QC test provided a severe evidence of error).
X_OUTLYING_FLA	
	Flag for the X flux variable denoting outliers (0: no outlying flux; 1: outlying flux).
X_OOR_FLAG	Flag for the X flux variable denoting values out of the physically plausible range (0: within range; 2: out of range).
X_FMR_STAT	Fraction of Missing Records in raw, high-frequency, data used for the X flux variable estimation.
X_FMR_FLAG	Flag for the FMR test for the X flux variable (0: negligible evidences of error, IF X_FMR<5; 1: moderate evidences of error, 1 IF $5 \le X_FMR \le 15$; 2: severe evidences of error, 2 IF X_FMR>15).
X_LGD_STAT	Longest Gap Duration in raw, high-frequency, data used for the X flux variable estimation.
X_LGD_FLAG	Flag for the LGD test for X flux variable (0: negligible evidences of error, IF $X_LGD < 90$; 1: moderate evidences of error, IF $90 \le X_LGD \le 180$; 2: severe evidences of error, IF $X_LGD > 180$).
SA_DIAG_FLAG	Flag for Sonic Anemometer (SA) instrumental diagnostics (0: negligible evidences of error; 2: severe evidences of error).
GA_DIAG_FLAG	Flag for gas analyzer (GA) instrumental diagnostics (0: negligible evidences of error; 2: severe evidences of error).
WD	Wind direction.
WSECT_FLAG	Footprint quality flag indicating periods when wind was blowing from directions known to significantly affect the turbulent flow (0: negligible evidences of error; 2: severe evidences of error).
X_LSR_STAT	Statistic of the Low Signal Resolution test for the X flux varaible.
X_LSR_FLAG	Flag for the LSR test for the X flux variable (0: negligible evidences of error, IF $X_LSR_STAT>0.995$; 1: moderate evidences of error, IF $0.99 \le X_LSR_STAT \le 0.995$; 2: severe evidences of error, IF $X_LSR_STAT<0.99$).
X_HF5_STAT	Statistic of the homogeneity test applied on the X variable (percentage of data exceeding $\mu+/-5\sigma$).
X_HF5_FLAG	Flag for the homogeneity test applied on the X variable (0: negligible evidences of error, IF X_HF5_STAT<2; 1: moderate evidences of error, IF 2≤X_HF5_STAT≤4; 2: severe evidences of error, IF X_HF5_STAT>4).
X_HF10_STAT	Statistic of the homogeneity test applied on the X variable (percentage of data exceeding $\mu+/-10\sigma$).

X_HF10_FLAG	Flag for the homogeneity test applied on the X variable (0: negligible evidences of error, IF X_HF10_STAT<0.5; 1: moderate evidences of error, IF 0.5\(\section X\)_HF10_STAT\(\section 1\); 2: severe evidences of error, IF X_HF10_STAT\(\section 1\)).
X_HD5_STAT	Statistic of the homogeneity test applied on differenced X variable (percentage of data exceeding $\mu + / - 5\sigma$).
X_HD5_FLAG	Flag for the homogeneity test applied on differenced X variable (0: negligible evidences of error, IF X_HD5_STAT<2; 1: moderate evidences of error, IF 2\leq X_HD5_STAT\leq 4; 2: severe evidences of error, IF X_HD5_STAT\leq 4).
X_HD10_STAT	Statistic of the homogeneity test applied on differenced X variable (percentage of data exceeding $\mu + / -10\sigma$).
X_HD10_FLAG	Flag for the homogeneity test applied on differenced X variable (0: negligible evidences of error, IF $X_{D10}STAT<0.5$; 1: moderate evidences of error, IF $0.5\le X_{D10}STAT\le 1$; 2: severe evidences of error, IF $X_{D10}STAT>1$).
X_AL1_STAT	Autocorrelation at lag 1 for the X variable.
X_AL1_FLAG	Flag for the autocorrelation at lag 1 for the X variable (0: negligible evidences of error, IF $X_{AL1_STAT}>0.75$; 1: moderate evidences of error, IF $0.5; 2: severe evidences of error, IF X_{AL1_STAT}\le0.5).$
X_DDI_STAT	Maximum number of binned data points for the X variable (number of classes (bins) calculated by Freedman-Diaconis rule based on the inte-quartile range proportional to the sample size).
X_DDI_FLAG	Flag for the X_DDI_STAT (0: negligible evidences of error, IF X_DDI_STAT <hz*60*2.5; 1:="" <math="" error,="" evidences="" if="" moderate="" of="">hz*60*2.5 \le X_DDI_STAT < hz*60*5; 2: severe evidences of error, IF X_DDI_STAT $\ge hz*60*5$, where hz denoting the acquisition frequency).</hz*60*2.5;>
X_DIP_STAT	P-value of the Hartigans' Dip Test for Unimodality.
X_DDI_FLAG	Flag for the X_DIP_STAT (0: negligible evidences of error, IF X_DIP_STAT>0.1; 1: moderate evidences of error, IF $0.05 \le X_DDI_STAT<0.1$; 2: severe evidences of error, IF X_DIP_STAT ≥ 0.05).
X_KID_STAT	Kurtosis Index of Differenced X variable.
X_KID_FLAG	Flag for the X_KID_STAT (0: negligible evidences of error, IF X_KID_STAT<30; 1: moderate evidences of error, IF 30≤X_KID_STAT≤50; 2: severe evidences of error, IF X_KID_STAT>50).
ITC_STAT	Statistic of the Integral Turbulence Characteristics test (Foken and Wichura, 1996).
ITC_FLAG	Flag for the ITC test (0: negligible evidences of error, IF ITC_STAT<30; 1: moderate evidences of error, IF 30≤ITC_STAT≤50; 2: severe evidences of error, IF ITC_STAT>50).
X_SCF_STAT	Spectral correction factor for the X variable.
X_M98_STAT	Statistic of the nonstationarity ratio test by Mahrt (1998) for the X flux variable.
X_M98_FLAG	Flag of the X_M98_STAT (0: negligible evidences of error, IF x_M_98_STAT<2; 1: moderate evidences of error, IF $2 \le X_M98_STAT \le 3$; 2: severe evidences of error, IF X_M98_STAT>3).
CO2	Carbon Dioxide (CO2) in mole fraction of wet air.
CO2_SIGMA	Standard deviation of carbon dioxide in mole fraction of wet air.
H20	Water (H2O) vapor mole fraction.
H2O_SIGMA	Standard deviation of water vapor mole fraction.

T_SONIC Sonic temperature.

T_SONIC_SIGMA Standard deviation of sonic temperature.

WS Wind speed.

USTAR Friction velocity.

W_SIGMA Standard deviation of vertical velocity fluctuations.

U_SIGMA Standard deviation of lateral velocity fluctuations (towards main-wind direction

after coordinates rotation).

V_SIGMA Standard deviation of lateral velocity fluctuations (cross main-wind direction

after coordinates rotation).

ZL Monin-Obukhov stability parameter.

MO_LENGTH Monin-Obukhov length.

AT Air temperature.

AP Air pressure.

RHO Air density.

CP Air heat capacity.

CANOPY_HEIGHT Canopy height.

SA_HEIGHT Sonic anemometer height.

SA_NORTH_OFFSET

Sonic anemometer north offset.

INVALID_WIND_SECTOR_c1

Center of the first invalid wind sector, if any.

INVALID_WIND_SECTOR_w1

Width of the first invalid wind sector, if any.

 ${\tt INVALID_WIND_SECTOR_c2}$

Center of the second invalid wind sector, if any.

 ${\tt INVALID_WIND_SECTOR_w2}$

Width of the second invalid wind sector, if any.

INVALID_WIND_SECTOR_c3

Center of the third invalid wind sector, if any.

INVALID_WIND_SECTOR_w3

Width of the third invalid wind sector, if any.

Author(s)

Domenico Vitale

References

Vitale, D. Fratini, G. Bilancia, M. Nicolini, G. Sabbatini, S. Papale, D. A robust data cleaning procedure for eddy covariance flux measurements, Biogeosciences, 17, 1367–1391, doi: https://doi.org/10.5194/bg-17-1367-2020, 2020.

8 closed_path_rawdata

Examples

closed_path_rawdata

Raw, high-frequency, data for closed path systems

Description

An example of raw, high-frequency, eddy covariance data for a closed path systems.

Usage

```
data("closed_path_rawdata")
```

Format

A data frame with 36000 observations of

- U Horizontal wind component along the Gill HS-50 sonic anemometer x axis (m/s).
- V Horizontal wind component along the Gill HS-50 sonic anemometer y axis (m/s).
- W Vertical wind component along the Gill HS-50 sonic anemometer z axis (m/s).
- T_SONIC Temperature measured by the Gill HS-50 sonic anemometer (kelvin).
- C02 Carbon dioxide atmospheric concentrations (mixing ratio) measured by the LI-7200 gas analyzer (ppm).
- H20 Water vapor atmospheric concentrations (mixing ratio) measured by the LI-7200 gas analyzer (ppt).
- SA_DIAG Diagnostic flag output by the Gill HS-50 sonic anemometer (dimensionless).
- GA_DIAG Diagnostic flag output by the LI-7200 gas analyzer (dimensionless).
- T_CELL Average cell temperature of the LI-7200 gas analyzer (celsius).
- T_CELL_IN Temperature at the inlet of the LI-7200 gas analyzer cell (celsius).
- T_CELL_OUT Temperature at the outlet of the LI-7200 gas analyzer cell (celsius).
- PRESS_CELL Cell pressure of the LI-7200 gas analyzer (Kpa).

Source

Data are from the Integrated Carbon Observation System (ICOS) European Research Infrastructure and accessible through the ICOS Carbon Portal http://www.icos-cp.eu.

convert_rawdata 9

Examples

```
data(closed_path_rawdata)
str(closed_path_rawdata)
```

convert_rawdata

Raw Data File Conversion

Description

Converting a generic ASCII raw data file in a format suitable for RFlux package

Usage

```
convert_rawdata(
file_path_in,
file_path_out,
info_U=list(NULL,NULL,1,0),
info_V=list(NULL,NULL,1,0),
info_W=list(NULL,NULL,1,0),
info_T_SONIC=list(NULL,NULL,1,0),
info_CO2=list(NULL, NULL, 1, 0),
info_H2O=list(NULL,NULL,1,0),
info_T_CELL=list(NULL,NULL,1,0),
info_T_CELL_IN=list(NULL,NULL,1,0),
info_T_CELL_OUT=list(NULL, NULL, 1, 0),
info_PRESS_CELL=list(NULL,NULL,1,0),
info_SA_DIAG=NULL,
info_GA_DIAG=NULL,
na.strings,
nrow.header,
sep,
dec,
timestamp_loc=c(NULL, NULL),
timestamp_format,
siteID="Cc-Xxx",
labels=NULL)
```

Arguments

file_path_in	path where raw data file is stored.
file_path_out	path where converted raw data file will be stored.
info_U	a list of 4 elements denoting the column position (integer) of the horizontal U wind component, its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion should be applied).
info_V	a list of 4 elements denoting the column position (integer) of the horizontal V wind component, its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion should be applied).
info_W	a list of 4 elements denoting the column position (integer) of the vertical W wind component, its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion should be applied).

10 convert_rawdata

info_T_SONIC a list of 4 elements denoting the column position (integer) of the sonic temperature, its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion should be applied).

a list of 4 elements denoting the column position (integer) of CO2 concentration, its units (character string, see details), the multiplier and the offset (1 and 0,

respectively, in case no linear conversion should be applied).

a list of 4 elements denoting the column position (integer) of the H2O concen-

tration, its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion should be applied)

and 0, respectively, in case no linear conversion should be applied).

info_T_CELL a list of 4 elements denoting the column position (integer) of cell temperature

(only for EC closed path systems), its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion

should be applied).

info_T_CELL_IN a list of 4 elements denoting the column position (integer) of in-cell temperature

(only for EC closed path systems), its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion

should be applied).

info_T_CELL_OUT

a list of 4 elements denoting the column position (integer) of out-cell temperature (only for EC closed path systems), its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion

should be applied).

info_PRESS_CELL

a list of 4 elements denoting the column position (integer) of cell pressure (only for EC closed path systems), its units (character string, see details), the multiplier and the offset (1 and 0, respectively, in case no linear conversion should be

applied).

info_SA_DIAG integer. Column position of the sonic anemometer diagnostics.

info_GA_DIAG integer. Column position of the gas analyzer diagnostics.

na.strings a character string denoting missing values in the raw data file.

nrow.header the number of header rows in the raw data file.

sep the field separator character of the raw data file. See read.table for specifica-

tions.

dec the character used in the raw data file for decimal points.

timestamp_loc a vector of 2 negative integers denoting the location of the timestamp in the raw

data file name starting from the right (eg. -21, -2).

timestamp_format

a character string denoting the format of the timestamp included in the raw data file name. It must be specified according to specifications of the strptime func-

tion.)

siteID a 6-character string denoting the Site ID (eg. CC-Xxx).

labels (optional) a character string denoting further information. Default is NULL.

Details

Possible units specification in the info_XX field are one among: mm s-1, cm s-1, m s-1 for U, V, W wind components; K, C for sonic temperature (T_SONIC) and cell temperatures (T_CELL, T_CELL_IN, T_CELL_OUT); ppt, ppm, ppb, umol m-3, mmol m-3, ug m-3, mg m-3, g m-3 for

despiking 11

CO2, H2O concentration variables; Pa, hPa, KPa for cell pressure (PRESS_CELL). The multiplier and the offset values in info_XX field aim at converting data expressed in Volt in their physical units. They must be set equals to 1 and 0, respectively, in case no (linear) conversion is required.

Value

A .csv file stored in the file_path_out containing the following variables: U (m s-1), V (m s-1), W (m s-1), T_SONIC (K), CO2 (mmol m-3 in case of molar density, umol/mol (ppm) in case of molar fraction/mixing ratio), H2O (mmol m-3 in case of molar density, mmol/mol (ppt) in case of molar fraction/mixing ratio), SA_DIAG (dimensionless), GA_DIAG (dimensionless), T_CELL (C), T_CELL_IN (C), T_CELL_OUT (C), PRESS_CELL (KPa). Missing values are denoted by "-9999".

Author(s)

Domenico Vitale

Examples

```
##Single raw data file conversion (TO DO)
##Block of raw data file conversion in parallel mode (TO DO)
```

Despiking algorithms

Description

despiking

A suite of despiking algorithms for micro-meteorological variables

Usage

```
despiking(x, mfreq, variant, wsignal, wscale, wby = 1, zth = 5, alpha = 0.01)
```

Arguments

X	a vector of the observed time-series values.
mfreq	the main frequency of the observed time series (24 or 48 for hourly and half-hourly time series, respectively; 10 or 20 for raw EC data acquired at 10Hz or 20Hz, respectively).
variant	"v1" mainly designed for (half-)hourly EC fluxes (missing values are allowed); "v2" mainly designed for (half-)hourly meteo time series (a low percentage of missing values is allowed); "v3" mainly designed for high-frequency EC raw data.
wsignal	the window width used to estimate the underlying signal (only for met and raw variants).
wscale	the window width used to estimate the local scale paramater (only for met and raw variants).
wby	calculate the scale parameter at every by-th point rather than every point (default=1). Large values of wby reduce the computational time, but can introduce bias in the scale parameter estimation.
zth	the threshold value of the z-sigma rule ((only for met and raw variants).
alpha	the significance level used in the outlier detection rule (only for flx variant).

12 ecmd_table

Value

A list containing the following components:

ts_cleaned A vector of the despiked time-series.

spike_loc Integer. Location of the detected spikes.

Author(s)

Domenico Vitale

References

Fried, R. Schettlinger, K. Matthias Borowski, M. robfilter: Robust Time Series Filters. R package version 4.1.1. https://CRAN.R-project.org/package=robfilter, 2018.

Hafen, R. stlplus: Enhanced Seasonal Decomposition of Time Series by Loess. R package version 0.5.1. https://CRAN.R-project.org/package=stlplus, 2016.

Vitale, D. Fratini, G. Bilancia, M. Nicolini, G. Sabbatini, S. Papale, D. A robust data cleaning procedure for eddy covariance flux measurements, Biogeosciences, 17, 1367–1391, doi: https://doi.org/10.5194/bg-17-1367-2020, 2020.

Vitale, D. A perfomance evaluation of despiking algorithms for eddy covariance data. Scientific Reports, 11, 11628, doi: https://doi.org/10.1038/s41598-021-91002-y, 2021.

ecmd_table

Eddy covariance metadata table

Description

A collection of metadata useful for the proper settings of eddy covariance data processing options.

Usage

```
data("ecmd_table")
```

Format

A data frame with the following variables:

DATE_OF_VARIATION_DB Optional. ISO timestamp of the variation in central database. Required format: *yyyymmddHHMM*.

DATE_OF_VARIATION_EF ISO timestamp of effective date of variation. Required format: yyyym-mdd or yyyymmddHHMM.

SITEID Character string indicative of the EC Site's ID (CC-Xxx).

LATITUDE Latitude in decimal degree

LONGITUDE Longitude in decimal degree

ALTITUDE Altitude in meters

CANOPY_HEIGHT Canopy height in meters

SA_MANUFACTURER Sonic anemometer manufacturer (see EddyPro manual.)

SA_MODEL Sonic anemometer model (see EddyPro manual.)

ecmd_table 13

- SA_SW_VERSION Sonic anemometer software version.
- SA_WIND_DATA_FORMAT Format of the wind components (see EddyPro manual.)
- SA_NORTH_ALIGNEMENT Sonic anemometer north alignment (see EddyPro manual.)
- SA_HEIGHT Sonic anemometer height (see EddyPro manual.)
- SA_NORTH_OFFSET Sonic anemometer north offset (see EddyPro manual.)
- SA_NORTH_MAGDEC Sonic anemometer magnetic declination (see EddyPro manual.)
- SA_INVALID_WIND_SECTOR_c1 Center of the first invalid wind sector.
- SA_INVALID_WIND_SECTOR_w1 Width of the first invalid wind sector.
- SA_INVALID_WIND_SECTOR_c2 Center of the second invalid wind sector.
- SA_INVALID_WIND_SECTOR_w2 Width of the second invalid wind sector.
- SA_INVALID_WIND_SECTOR_c3 Center of the third invalid wind sector.
- SA_INVALID_WIND_SECTOR_w3 Width of the third invalid wind sector.
- GA_PATH Specify the eddy covariance path system: closed or open.
- GA_MANUFACTURER Gas analyzer manufacturer (see EddyPro manual).
- GA_MODEL Gas analyzer model (see EddyPro manual).
- GA_SW_VERSION Gas analyzer software version (see EddyPro manual).
- GA_NORTHWARD_SEPARATION The distance between the center of the sample volume (or the inlet of the intake tube) of the current gas analyzer and the sonic anemometer, as measured horizontally along the north-south axis (see EddyPro manual).)
- GA_EASTWARD_SEPARATION The distance between the center of the sample volume (or the inlet of the intake tube) of the current gas analyzer and the sonic anemometer, as measured horizontallu along the east-west axis (see EddyPro manual).)
- GA_VERTICAL_SEPARATION The distance between the center of the sample volume (or the inlet of the intake tube) of the current gas analyzer and the sonic anemometer, as measured vertically (see EddyPro manual).
- GA_TUBE_DIAMETER The inside diameter of the intake tube in centimeters. Mandatory for closed path system.
- GA_FLOWRATE The flow rate in the intake tube. Mandatory for closed path system.
- $\ensuremath{\mathsf{GA_TUBE_LENGTH}}$ The length of the intake tube in centimeters.
- FILE_DURATION File lenght duration in minutes
- ACQUISITION_FREQUENCY Number of sample records per second.
- FILE_FORMAT ASCII (fixed)
- FILE_EXTENSION csv (fixed)
- LN 99 (fixed)
- FN 1 (fixed)
- EXTERNAL_TIMESTAMP END (fixed)
- EOL crlf (fixed)
- SEPARATOR comma (fixed)
- MISSING_DATA_STRING -9999 (fixed)
- NROW_HEADER 1 (fixed)
- UVW_UNITS Units of wind speed components (see EddyPro manual).
- T_SONIC_UNITS Units of sonic temperature (see EddyPro manual).

14 ecworkset

T_CELL_UNITS Units of closed path gas analyzer cell temperature (see EddyPro manual).

P_CELL_UNITS Units of closed path gas analyzer cell pressure (see EddyPro manual).

C02_measure_type Carbon dioxide concentration measurement type (e.g. mixing_ratio, see Ed-dyPro manual).

CO2_UNITS Units of carbon dioxide concentration (e.g. ppm, see EddyPro manual).

H20_measure_type Water vapor concentration measurement type (e.g. mixing_ratio, see EddyPro manual).

H20_UNITS Units of water vapor concentration (e.g. ppt, see EddyPro manual).

SA_DIAG Units of the sonic anemometer diagnostics (dimensionless, fixed)

GA_DIAG Units of the gas analyzer diagnostics (dimensionless (fixed).

Source

Metadata elaborated by ICOS-ETC team (Integrated Carbon Observation System (ICOS-ETC) European Research Infrastructure - Ecosystem Thematic Center, http://www.icos-etc.eu/icos/).

References

LI-COR Biosciences: EddyPro 7.0.4: Help and User's Guide, LI-COR Biosciences, Lincoln, Nebraska USA, www.licor.com/EddyPro, 2019.

Examples

```
data(ecmd_table)
str(ecmd_table)
```

ecworkset

Merge time series and returns the workset dataframe

Description

Merge time series with common indexes (times) and returns the *workset* data frame to be used as input for the data cleaning procedure via cleanFlux function.

Usage

```
ecworkset(path_EPout, path_EPqc, path_EPmd, path_QCstat, path_output=NULL, FileName=NULL)
```

Arguments

path_EPout	path where the fulloutput file generated by EddyPro software is stored.
path_EPqc	path where the qcdetails file generated by EddyPro software is stored.
path_EPmd	path where the metadata file generated by EddyPro software is stored.
path_QCstat	path where the QC statistics file generated by qcStat is stored.
path_output	path where the results will be stored. Default is NULL.
FileName	a character string naming a file for writing. Default is NULL.

eddypro_run 15

Details

Returns a dataframe ordered by common indexes (times) containing a set of variables selected from the fulloutput, metadata, qcdetails files generated by EddyPro via eddypro_run and the statistics of the quality control routines (Vitale et al, 2019) generated by qcStat.

Value

A dataframe object to be used as input of the cleanFlux. For the meaning of variables and units see the EddyPro manual and the qcStat function description.

Author(s)

Domenico Vitale, Dario Papale

References

LI-COR Biosciences: EddyPro 7.0.4: Help and User's Guide, LI-COR Biosciences, Lincoln, Nebraska USA, www.licor.com/EddyPro, 2019.

Vitale, D. Fratini, G. Bilancia, M. Nicolini, G. Sabbatini, S. Papale, D. A robust data cleaning procedure for eddy covariance flux measurements, Biogeosciences, 17, 1367–1391, doi: https://doi.org/10.5194/bg-17-1367-2020, 2020.

Examples

eddypro_run

Fluxes estimation

Description

Estimates flux values and other micrometeorological parameters through a call to LI-COR EddyPro software.

Usage

```
eddypro_run(siteID, path_eddypro_bin, path_eddypro_projfiles, showLOG = TRUE)
```

16 eddypro_run

Arguments

```
siteID Character string indicative of the site's ID (i.e. CC-Xxx)

path_eddypro_bin

path where eddypro_rp and eddypro_fcc executables (i.e. the bin folder) are stored.

path_eddypro_projfiles

path where the EddyPro project files (i.e. the filename.eddypro file) is stored.

showLOG logical. If TRUE (default), the EddyPro Output Console Page is shown on R console.
```

Value

A set of .csv files (e.g. fulloutput, qcdetails and metadata) generated by EddyPro software will be stored in the path specified by get_md.

Warning

It is required LI-COR EddyPro software is currently installed on your system (see www.licor.com/EddyPro).

Author(s)

Domenico Vitale, Dario Papale

References

LI-COR Biosciences: EddyPro 7.0.4: Help and User's Guide, LI-COR Biosciences, Lincoln, Nebraska USA, www.licor.com/EddyPro, 2019.

Examples

```
## Not run:
workdir <- getwd()</pre>
siteID <- "DE-HoH"
PATH_ECMD <- system.file("extdata", "DE-HoH_ecmd.csv", package = "RFlux")
PATH_RAWDATA <- system.file("extdata", package = "RFlux")
PATH_OUTPUT <- paste0(workdir, "/eddypro/processing")</pre>
PATH_SA_FILE <- system.file("extdata", "spectral_assessment.txt", package = "RFlux")
PATH_PF_FILE <- system.file("extdata", "planar_fit.txt", package = "RFlux")
MD <- get_md(path_ecmd=PATH_ECMD,</pre>
             path_rawdata=PATH_RAWDATA,
             path_output=PATH_OUTPUT,
             online=TRUE,
             path_sa_file=PATH_SA_FILE,
             path_pf_file=PATH_PF_FILE,
             tlag_meth=2,
             despike_meth="VM97".
             detrend_meth="BA",
             tilt_correction_meth="PF")
PATH_EDDYPRO_BIN <- "/Applications/eddypro.app/Contents/MacOS/bin" ## put your path!
PATH_EDDYPRO_PROJ <- PATH_OUTPUT
eddypro_run(siteID="DE-HoH",
```

get_md 17

```
path_eddypro_bin=PATH_EDDYPRO_BIN,
    path_eddypro_projfiles=PATH_EDDYPRO_PROJ,
    showLOG=TRUE)
## End(Not run)
```

get_md

Metadata file management

Description

Returns the input files required by EddyPro software (LI-COR registered trademark; Fratini and Mauder, 2014).

Usage

```
get_md(path_ecmd = NULL,
    path_rawdata = NULL,
    path_output = NULL,
    online,
    path_sa_file = NULL,
    path_pf_file = NULL,
    path_biomet_file=NULL,
    roughness_length=NULL,
    displacement_height=NULL,
    tlag_meth,
    despike_meth=c("None", "VM97", "M13"),
    detrend_meth=c("BA", "LD"),
    tilt_correction_meth=c("DR", "PF"))
```

Arguments

path_ecmd path where the CC-Xxx_ecmd.csv file containing metadata information is stored. path_rawdata path where eddy covariance rawdata files are stored. path where the results of eddypro_run will be stored (it will be created, if any). path_output logical. Indicating whether the parameters of the planar fit method and the online spectral correction factors are taken from results of previous processing (online=TRUE) or estimated by using the current set of EC rawdata (online=FALSE). path where the spectral assessment file generated by EddyPro software is stored. path_sa_file path_pf_file path where the planar fit file generated by EddyPro software is stored. path_biomet_file path where the file containing the biometeorological variables is stored (the file

path where the file containing the biometeorological variables is stored (the file format must follow the EddyPro instructions).

roughness_length

a numeric value indicating the surface roughness. If NULL (default) it is estimated based on the canopy height.

displacement_height

a numeric value indicating the zero plane displacement length. If NULL (default) it is estimated based on the canopy height.

18 get_md

tlag_meth time lag detection method: 0 None; 1 Constant time lag, 2 Maximum covariance

with default; 3 Maximum covariance; 4 Automatic optimization.

despike_meth despiking method: "None", not apply; "VM97", algorithm by Vickers and Mahrt

(1997); "M13", algorithm by Mauder et al (2013).

detrend_meth trend removal method: "BA" Block Average; "LD" Linear Detrending (Rannik

and Vesala, 2001).

tilt_correction_meth

axis rotation method for tilt correction: "DR" Double Rotation; "PF" Planar Fit

(Wilczak et al, 2001).

Details

This function builds the input files required by EddyPro software to process eddy covariance rawdata files.

Value

Returns the following files

CC-Xxx.eddypro

CC-Xxx.metadata

CC-Xxx_dynamic_metadata.txt

where CC-Xxx denoting the site's ID.

Warning

If online=FALSE, the number of rawdata needs to be large enough to allow robust estimates of the planar fit parameters (Wilczak et al 2001) and of the spectral correction factors (Fratini et al, 2012). In case of few rawdata, the double rotation method for sonic anemometer tilt correction and the analytical method by Moncrieff et al (1997) for spectral correction will be performed.

Note

Rawdata must be provided as .csv file with the following name: *CC-Xxx????yyyymmddHHMM????.csv*, where *CC-Xxx* is the site's ID, *yyyymmddHHMM* is the ISO timestamp, and ?s denoting free characters. For example: DE-HoH_EC_201901010030_v01.csv.

Author(s)

Domenico Vitale, Dario Papale

References

Fratini, G., Mauder, M. (2014). Towards a consistent eddy-covariance processing: an intercomparison of EddyPro and TK3. Atmospheric Measurement Techniques, 7(7), 2273-2281, doi: https://doi.org/10.5194/amt-7-2273-2014.

Fratini, G., Ibrom, A., Arriga, N., Burba, G., Papale, D. (2012). Relative humidity effects on water vapour fluxes measured with closed-path eddy-covariance systems with short sampling lines. Agricultural and forest meteorology, 165, pp 53-63, doi: https://doi.org/10.1016/j.agrformet. 2012.05.018.

get_md 19

LI-COR Biosciences: EddyPro 7.0.4: Help and User's Guide, LI-COR Biosciences, Lincoln, Nebraska USA, www.licor.com/EddyPro, 2019.

Mauder, M., Cuntz, M., Drue, C., Graf, A., Rebmann, C., Schmid, H. P., ..., Steinbrecher, R. (2013). A strategy for quality and uncertainty assessment of long-term eddy-covariance measurements. Agricultural and Forest Meteorology, 169, 122-135, doi: https://doi.org/10.1016/j.agrformet.2012.09.006.

Moncrieff, J. B., Massheder, J. M., De Bruin, H., Elbers, J., Friborg, T., Heusinkveld, B., ..., Verhoef, A. (1997). A system to measure surface fluxes of momentum, sensible heat, water vapour and carbon dioxide. Journal of Hydrology, 188, 589-611, doi: https://doi.org/10.1016/S0022-1694(96)03194-0.

Rannik, U., Vesala, T. (1999). Autoregressive filtering versus linear detrending in estimation of fluxes by the eddy covariance method. Boundary-Layer Meteorology, 91(2), 259-280, doi: https://doi.org/10.1023/A:1001840416858.

Vickers, D., Mahrt, L. (1997). Quality control and flux sampling problems for tower and aircraft data. Journal of atmospheric and oceanic technology, 14(3), 512-526, doi: https://doi.org/10.1175/1520-0426(1997)014<0512:QCAFSP>2.0.C0;2.

Wilczak, J.M., Oncley, S.P., Stage, S.A. (2001). Sonic anemometer tilt correction algorithms. Boundary-Layer Meteorology, 99(1), 127-150, doi: https://doi.org/10.1023/A:1018966204465.

See Also

closed_path_rawdata

Examples

```
## Not run:
workdir <- getwd()</pre>
siteID <- "DE-HoH"
PATH_ECMD <- system.file("extdata", "DE-HoH_ecmd.csv", package = "RFlux")
PATH_RAWDATA <- system.file("extdata", package = "RFlux")
PATH_OUTPUT <- paste0(workdir, "/eddypro/processing")
PATH_SA_FILE <- system.file("extdata", "spectral_assessment.txt", package = "RFlux")
PATH_PF_FILE <- system.file("extdata", "planar_fit.txt", package = "RFlux")
MD <- get_md(path_ecmd=PATH_ECMD,</pre>
               path_rawdata=PATH_RAWDATA,
               path_output=PATH_OUTPUT,
               online=TRUE,
               path sa file=PATH SA FILE.
               path_pf_file=PATH_PF_FILE,
               path_biomet_file=NULL,
               roughness_length=NULL,
               displacement_height=NULL,
               tlag_meth=2,
               despike_meth="VM97",
               detrend_meth="BA",
               tilt_correction_meth="PF")
## End(Not run)
```

inst_prob_test

tems	inst_prob_test	Detection of instrumental malfunctions, errors in eddy covariance systems
------	----------------	---

Description

A set of tests aims at detecting instrumental malfunctions, errors in eddy covariance systems.

Usage

Arguments

,	
x	raw high frequency eddy covariance time series.
detrend	logical. If TRUE a linear trend is removed from data (see details).
hz	integer. The data acquisition frequency (ie 10 or 20 HZ).
plot	logical. If TRUE a graphical representation of the results is provided. Default FALSE.
var_name	character. One of "U", "V", "W", "T_SONIC", "CO2", "H2O" variable name can be specified to enrich the graphcial output when plot=TRUE.
cex.test	A numerical value giving the amount by which plotting test results. Default set to 1 .

Details

The detrend option should be set in agreement with the processing options adopted for fluxes estimation. In case fluxes are estimated after mean removal (i.e. block average), then detrend should be set to FALSE. In case fluxes are estimated after linear trend removal then detrend should be set to TRUE.

Value

Skew	Skewness.
Kurt	Kurtosis index on original data.
KID0	Kurtosis index on difference data.
KID	Kurtosis index on difference data excluding low resolution problems.
HFx	Homogeneity test statistic based on fluctuation.
HDx	Homogeneity test statistic based on difference data.
AL1	Autocorrelation function estimate at lag 1.
DDI	Data Distribution Integrity test statistic. Maximum number of data points in a bin of the histogram with bins defined according to Freedman-Diaconis rule.
DIP	P-value of the Hartigans' Dip test for unimodality.

mahrt 21

Author(s)

Domenico Vitale

References

Vitale, D. Fratini, G. Bilancia, M. Nicolini, G. Sabbatini, S. Papale, D. A robust data cleaning procedure for eddy covariance flux measurements, Biogeosciences, 17, 1367–1391, doi: https://doi.org/10.5194/bg-17-1367-2020, 2020.

Freedman, D. and Diaconis, P. On the histogram as a density estimator: L2 theory. Zeitschrift fur Wahrscheinlichkeitstheorie und verwandte Gebiete, 57, 453–476, doi: https://doi.org/10.1007/BF01025868, 1981.

Hartigan, P.M. Computation of the Dip Statistic to Test for Unimodality. Applied Statistics (JRSS C) 34, 320–325. Corresponding Fortran code of AS 217 available from Statlib, http://lib.stat.cmu.edu/apstat/217, 1985.

Hartigan, J.A. and Hartigan, P.M. The Dip Test of Unimodality. Annals of Statistics, 13, 70–84, 1985.

Examples

```
data(closed_path_rawdata)
inst_prob_test(closed_path_rawdata$W, detrend=FALSE, h=20, plot=TRUE, var_name="W")
```

mahrt

Stationary test for eddy covariance fluxes

Description

Performs the non-stationary ratio test described by Mahrt (1998)

Usage

mahrt(x)

Arguments

Х

two-column dataframe containing raw high-frequency time series of vertical wind component (i.e. W) and scalar atmospheric variable (e.g. CO2).

Value

Returns the non-stationary ratio test statistic.

Author(s)

Domenico Vitale

References

Mahrt L (1998) Flux sampling errors for aircraft and towers, J. Atmos. Ocean. Tech., 15, 416-429, https://doi.org/10.1175/1520-0426(1998)015<0416:fsefaa>2.0.co; 2.

22 qcStat

Examples

```
PATH_RAWDATA <- system.file("extdata", "DE-HoH_EC_201907301200_v01.csv", package = "RFlux") data(closed_path_rawdata) mahrt(data.frame("W"=closed_path_rawdata$W,"C02"=closed_path_rawdata$C02))
```

mode

Mode estimation

Description

Calculate the modal value

Usage

mode(x)

Arguments

Х

a vactor of data.

Value

Returns the mode.

Author(s)

Domenico Vitale

qcStat

Quality control tests for eddy covariance fluxes

Description

Returns the test statistics of the quality control routines described by Vitale et al (2019).

Usage

```
\verb|qcStat(path_rawdata, ext_tstamp=c("START", "END"), path_output=NULL, FileName=NULL)| \\
```

Arguments

path_rawdata path where raw high-frequency eddy covariance data are stored.

ext_tstamp Character string specifying whether the timestamp in the file name is indicative

of the beginning ("START") or the end ("END") of time series involved.

path_output path where the results will be stored. Default is NULL.

FileName a character string naming a file for writing. Default is NULL.

qcStat 23

Value

A do	to troma	COnto	ning
\wedge ua	ta manic	COntai	mmz.
	ta frame		

TSTAMP	ISO timestamp start of averaging period (format: yyyymmddHHMM).
SADiag	Diagnostic for the sonic anemometer.
FMR_X	Fraction of Missing Records in raw, high-frequency, data used for X flux variable estimation.
LGD_X	Longest Gap Duration in raw, high-frequency, data used for X flux variable estimation.
Skew_X	Skewness of X variable.
Kurt_X	Kurtosis of X variable.
KID0_X	Kurtosis Index of Differenced X variable without esclusion of zero values.
KID_X	Kurtosis Index of Differenced X variable excluding zeros, ie the effect of possible low resolution problems.
HF5_X	Statistic of the homogeneity test applied on X variable fluctuations (percentage of data exceeding $+/-5\sigma$).
HF10_X	Statistic of the homogeneity test applied on X variable fluctuations (percentage of data exceeding $+/-10\sigma$).
HD5_X	Statistic of the homogeneity test applied on differenced X variable (percentage of data exceeding $+/-5\sigma$).
HD10_X	Statistic of the homogeneity test applied on differenced X variable (percentage of data exceeding $+/-10\sigma$).
AL1_X	Autocorrelation at lag 1.
DDI_X	Maximum number of binned data points (number of bins proportional to the sample size).
DIP_X	P-value of the Hartigans' Dip Test for Unimodality.
COV_XY	Covariance between X and Y variables.
N0_X	Number of repeated consecutive values affecting X flux variable.
LSR_X	Statistic of the Low Signal Resolution test for X flux variable.
M98_X	Statistic of the non-stationary ratio test by Mahrt (1988) for X flux variable.

Note

The output of qcStat constitues one of input files required by the ecworkset function.

Author(s)

Domenico Vitale

References

Mahrt L (1998) Flux sampling errors for aircraft and towers, J. Atmos. Ocean. Tech., 15, 416-429, https://doi.org/10.1175/1520-0426(1998)015<0416:fsefaa>2.0.co; 2.

Vitale, D. Fratini, G. Bilancia, M. Nicolini, G. Sabbatini, S. Papale, D. A robust data cleaning procedure for eddy covariance flux measurements, Biogeosciences, 17, 1367–1391, doi: https://doi.org/10.5194/bg-17-1367-2020, 2020.

24 robf_despiking

Examples

PATH_RAWDATA <- system.file("extdata", "DE-HoH_EC_201907301200_v01.csv", package = "RFlux") QC_STAT <- qcStat(path_rawdata=PATH_RAWDATA, ext_tstamp="END", path_output=NULL, FileName=NULL) QC_STAT

robf_despiking

Despiking eddy covariance raw data

Description

A parallel implementation of robust functionals for despiking high-frequency eddy covariance raw data

Usage

```
robf_despiking(x, mfreq, file_length)
```

Arguments

x a vector of the observed time-series values.

mfreq the main frequency of the observed time series (24 or 48 for hourly and half-

hourly time series, respectively; 10 or 20 for raw EC data acquired at 10Hz or

20Hz, respectively).

file_length the raw data file length in minutes (e.g. 30, 60 minutes).

Value

A list containing the following components:

despiked_ts A vector of the despiked time-series.
spike_loc Integer. Location of the detected spikes.

Author(s)

Domenico Vitale

References

Fried, R. Schettlinger, K. Matthias Borowski, M. robfilter: Robust Time Series Filters. R package version 4.1.1. https://CRAN.R-project.org/package=robfilter, 2018.

Vitale, D. A perfomance evaluation of despiking algorithms for eddy covariance data. Scientific Reports, 11, 11628, doi: https://doi.org/10.1038/s41598-021-91002-y, 2021.

tlag_detection 25

ag detection	ig detection
--------------	--------------

Description

Optimal time-lag detection by means of the pre-whitening procedure.

Usage

Arguments

x first component series (e.g. CO2 concentrations).y second component series (e.g. vertical wind speed).

mfreq acquisition frequency.

x.model an ARIMA model; if provided, it is used to prewhiten both series. Otherwise,

an AR model is fitted to the x-series and used to pre-whiten both series.

AIC Logical. If an AR model is used for prewhitening, the AR order is chosen by

minimizing the Akaike Information Criteria (AIC=TRUE), otherwise the AR model is chosen as 10*log10(N) where N is the number of observations. Default

is FALSE.

LAG.MAX maximum lag at which to calculate the ccf. Default is 10 seconds. show.plot Logical. If TRUE, the CCFs will be displayed (default FALSE).

Value

A list containing the following components:

ccf Output from the ccf function on the prewhitened data.

ar The AR model fit to the x-series, or x.model if it is provided.

opt_tlag Optimal time lag detected (timestep).

tlag_pw Time lag of the main peak of the cross-correlation function after pre-whitening.

tlag_lmax Local maxima of the cross-covariance function closest to tlag_pw.
tlag_lmin Local minima of the cross-covariance function closest to tlag_pw.

corr_est Estimated correlation at .

cv1pct Critical (abs) value of the ccf at 0.01 level. cv5pct Critical (abs) value of the ccf at 0.05 level.

Author(s)

Domenico Vitale

References

Vitale et al. (in prep) Optimal Time Lag Detection for Eddy Covariance Data Acquisition Systems

26 tlag_detection

See Also

See also prewhiten function in the TSA R package.

Examples

```
## Not run:
library(RFlux)
library(forecast)
library(xts)
data("closed_path_rawdata")
rawdata <- closed_path_rawdata</pre>
N <- nrow(rawdata)
\label{timestamp_orig} $$ \leftarrow strptime("0000.00", format="%H%M.%OS", tz="GMT") + seq(1, N, 1); $$
data.xts <- xts(rawdata, order.by=timestamp_orig);</pre>
## Detecting time lag betweem H2O and vertical wind speed (W) by using an AR model (default)
tlag\_h2o\_out <- tlag\_detection(x=rawdata\$H2O, y=rawdata\$W, mfreq=20,
                               show.plot=TRUE)
tlag_h2o_out$opt_tlag
tlag_h2o_out$corr_est
## Detecting time lag between CO2 and Sonic Temperature by using an ARIMA model
mod <- auto.arima(rawdata$CO2, stationary=FALSE)</pre>
tlag_co2_out <- tlag_detection(x=rawdata$CO2, y=rawdata$T_SONIC, mfreq=20,</pre>
                               show.plot=TRUE, x.model=mod)
tlag_co2_out$opt_tlag
tlag_co2_out$corr_est
## Time series alignment
tlag_co2 <- tlag_co2_out$opt_tlag</pre>
tlag_h2o <- tlag_h2o_out$opt_tlag</pre>
timestamp_co2 <- strptime("0000.00", format="%H%M.%OS", tz="GMT") +</pre>
                 seq(-tlag_co2+1, N - tlag_co2, 1);
timestamp_h2o <- strptime("0000.00", format="%H%M.%OS", tz="GMT") +
                 seq(-tlag_h2o+1, N - tlag_h2o, 1);
co2s <- xts(rawdata$CO2, order.by=timestamp_co2);</pre>
h2os <- xts(rawdata$H2O, order.by=timestamp_h2o);</pre>
rawdata_aligned <- na.omit(data.frame(merge(data.xts[,c(1:4)],</pre>
                  co2s, h2os, data.xts[,c(7:12)], tzone="GMT")));
"T_CELL", "T_CELL_IN", "T_CELL_OUT", "PRESS_CELL")
## End(Not run)
```

Index

*Topic datagen	mode, 22
cleanFlux, 3	
ecworkset, 14	qcStat, 2, 4, 14, 15, 22, 23
qcStat, 22	road table 10
*Topic datasets	read.table, 10
<pre>closed_path_rawdata, 8</pre>	RFlux (RFlux-package), 2
convert_rawdata,9	RFlux-package, 2 robf_despiking, 24
ecmd_table, 12	robi_despiking, 24
*Topic file	strptime, 10
get_md, 17	5 C. p 5 2 5, 2 S
*Topic htest	tlag_detection, 25
tlag_detection, 25	-
*Topic interface	
eddypro_run, 15	
*Topic methods	
despiking, 11	
robf_despiking, 24	
tlag_detection, 25	
*Topic optimize	
robf_despiking, 24	
*Topic package	
RFlux-package, 2	
*Topic robust	
despiking, 11	
robf_despiking, 24	
*Topic univar	
inst_prob_test, 20	
mahrt, 21	
mode, 22	
cleanFlux, 2, 3, 14, 15	
closed_path_rawdata, 8, 19	
convert_rawdata, 9	
55 5 5 <u></u> aa. 5a, y	
despiking, 11	
ecmd_table, 12	
ecworkset, 2, 14, 23	
eddypro_run, <i>15</i> , <i>15</i> , <i>17</i>	
got md 2 16 17	
$get_md, 2, 16, 17$	
<pre>inst_prob_test, 20</pre>	
mahrt, 21	