

Assignment Logical Formulas

Object Orientation

Spring 2025

The Visitor Pattern

1 Learning Goals

In this assignment we ask you to design and implement a representation for logical formulas in Java. After having completed this assignment, you should be able to:

- Implement a suitable representation of logical formulas, where
 - An interface is defined that serves as a base for all concrete nodes in your syntax tree.
 - Each logical connective is implemented as a record implementing this base interface.
- Introduce new operations using the visitor pattern.
- Utilize UML class and sequence diagrams to design an object oriented program. UML class diagrams were covered in lecture 2.

2 Warming Up With Generics

This is a warm-up exercise. It will not be graded.

In the start project you find a record `Pair` and a test case `PairTest`. The second test case fails with a type cast error. `Pair` stores its components as `Objects`, so whenever you get a component from a pair, you have to type cast it in order to use it. This can lead to run time errors if done inconsistently.

By using generics, you can turn these kind of run time errors into compile time errors. Your task: Make the `Pair` record generic `Pair<F, S>`. When you do everything correctly, the second test case will give two compile errors: “Cannot cast from Boolean to String” and “Cannot cast from String to Boolean”.

3 Logical Formulas

This assignment is about representing and manipulating formulas of propositional logic.

A *logical formula* consists of the constants *true* and *false*, atomic propositions, logical operators \wedge (and), \vee (or), \Rightarrow (implies) and \neg (not). Atomic propositions are like variables in programming languages. Atomic propositions can be any string, but we

usually use single capital letters like A, B, P, Q. The abstract syntax of logical formulas is given by the following grammar.

$$F ::= \text{true} \mid \text{false} \mid \text{Atomic} \mid F_1 \wedge F_2 \mid F_1 \vee F_2 \mid F_1 \Rightarrow F_2 \mid \neg F$$

Examples for logical formulas are $A \Rightarrow B$, $\neg A \vee B$, $A \Rightarrow (A \vee B) \wedge (C \Rightarrow \neg D)$. In these examples A, B, C, D are atomic propositions.

Formulas are represented in Java by trees, where the nodes correspond to the syntactic elements. Such trees are called *abstract syntax trees*. The leaves in such a tree correspond to constants or atomic propositions and internal nodes represent the operators. This means that some internal nodes have 2 children and others 1 child.

The representation of formulas using syntax trees is similar to the numerical expressions in assignment 5. There is one interface for all the different nodes, and records that implement this interface for each concrete type of node. There are three major differences compared to assignment 5.

1. In the numerical expressions, operations were added to the base interface as abstract methods, and implemented in each subclass. In this assignment, the base interface is left unchanged. All operations are implemented as visitors.
2. A single record is used to represent all binary formulas. It uses the *strategy design pattern* to realize their different behaviors.
3. Classes are replaced by records

The visitor pattern has two ingredients. First the visitor interface, in this assignment called `FormulaVisitor`, and second an abstract method `accept` in the formula base interface.

The base interface for logical formulas looks as follows. All of the concrete nodes must implement this interface.

```
public interface Formula {  
    void accept( FormulaVisitor visitor ) ;  
}
```

The `FormulaVisitor` interface has one `visit` method for each concrete node. Note: The visit methods are overloaded, that's why they can all have the same name. It would also have been possible to give these methods different names, like `visitNot`, `visitBinOp`, and so on.

```
public interface FormulaVisitor {  
    void visit( Not form );  
    void visit( BinaryOperator form );  
    // and so on  
}
```

All of the concrete nodes in the syntax tree are records that implement `Formula`. Here is an example for a record of the *not* operator.

```
public record Not(Formula operand) implements Formula {  
    public void accept( FormulaVisitor v ) {  
        v.visit( this );  
    }  
}
```

This definition should be self explanatory. The accept method is boilerplate code that always looks like this.

All binary formulas (i.e., formulas in which binary operations are used) must be represented by a single record `BinaryFormula`, which, in addition to the two `Formula` operands, has an operator `BinOp` as a field. This can be seen as an example of the use of the strategy pattern. `BinOp` should be an enum that implements `BinaryOperator<Boolean>` from the Java standard library. Every `BinOp` should have a string representation, a precedence, and an evaluation function.

4 Operations on Logical Formulas

You should implement two visitors for logical formulas: a pretty-printer and an evaluator.

The pretty-printer should print a given formula to standard output, omitting parentheses when it is safe. For this, every operator should have a precedence. The precedence of the operators are, from high to low: \neg , \wedge , \vee , \Rightarrow . This means that \neg binds stronger than \wedge , and so on. To determine if parentheses are needed, you have to compare the precedence of an operator with that of its parent. The details are left for you to figure out. Hint: pass the precedence of the current operator as an extra argument to the (indirect recursive) calls to accept. For operators with the same precedence, you should always print parenthesis to be safe.

The evaluator needs an environment for atomic propositions, just as the evaluator for numerical expression needs for variables. Where variables were assigned integers, atomic propositions are assigned booleans. This means that the evaluator needs a `Map<String, Boolean>` to evaluate formulas. For example, in the environment $[P \mapsto \text{false}]$, the formula $\neg P$ should evaluate to **true**.

The visit methods of the evaluator have a return value, while the ones of the pretty-printer need an additional argument. This means that the type signature can not be just `public void visit(Not f)`. To introduce the flexibility you need, you should make `FormulaVisitor` generic.

`Void` is a class from the Java standard library that represents the `void` keyword, which stands for the empty type. `Void` methods should always `return null`.

Here are some lines of code to give you inspiration. You should figure out the rest for yourself.

```
public interface FormulaVisitor<Result, AdditionalArg> {
    Result visit(Not form, AdditionalArg a);
}

public interface Formula {
    public <R,A> R accept(FormulaVisitor<R,A> visitor, A a);
}

public class PrintVisitor
    implements FormulaVisitor<Void, Integer>
{
    private StringBuilder result;
    public String getResult() { return result.toString(); }
}

public class EvaluateVisitor
```




Figure 1: Template for the sequence diagram you have to draw.

```
implements FormulaVisitor<Boolean, Void> { }
```

5 Your Tasks

In this assignment you have to draw two UML diagrams in steps 1 and 7. You have to hand in these diagrams. Either draw them on paper and submit a **photo as jpeg**, or use a UML tool and **export as pdf**. No other format will be accepted.

If you already have a UML drawing program you like, feel free to use it. Just make sure it can **export to pdf**. If you do not know which tool to use, we suggest Visual Paradigm. You can use it for free if you sign up with your email address. <https://online.visual-paradigm.com/subscribe.jsp>

1. Before you begin with your implementation, draw one UML class diagram of all the classes you need.
2. Implement the nodes for the syntax tree as described above. You need an interface and four concrete records for the different nodes in the syntax tree. These records should be called Atom, Constant, BinaryFormula, and Not. Hint: there can only be exactly two instances of Constant.
3. For every concrete node, add a corresponding visit method to FormulaVisitor.
4. Create a class PrintVisitor that implements FormulaVisitor and transforms a formula to a string.
5. Create a class EvaluateVisitor that implements FormulaVisitor and evaluates formulas in a given environment.
6. The project template comes with test cases. Make sure that all test cases pass.
7. Draw a sequence diagram for printing the formula $\neg P$, given in the following code. Only include calls to accept and visit. Use the diagram in Figure 1 as a starting point.

```
Atom f2 = new Atom("P");
Not f1 = new Not(f2);
PrintVisitor v = new PrintVisitor();
f1.accept(v);
```

6 Submit Your Project

To submit your project, follow these steps. You have to submit three files: The java project, the class diagram, and the sequence diagram.

1. Submit the diagrams either as **jpeg or pdf**. No other format is accepted.
2. Create a zip file containing your code.
3. **Submit this zip file on Brightspace**. Do not submit individual Java files. Do not submit any other archive format. The root of your zip should contain exactly one folder, containing your code. Only one person in your group has to submit it. Submit your project before the deadline, which can be found on Brightspace.