# Machine-Level Programming IV: Data

CSE 238/2038/2138: Systems Programming

**Instructor:**

Fatma CORUT ERGİN

*Slides adapted from Bryant & O'Hallaron's slides*

# Today


- **Arrays**
  - One-dimensional
  - Multi-dimensional (nested)
  - Multi-level
- **Structures**
  - Allocation
  - Access
  - Alignment
- **Floating Point**

# Array Allocation

- **Basic Principle**

  *T* **`A[`***L***`];`**

  - Array of data type *T* and length *L*
  - Contiguously allocated region of *L* * **`sizeof`**`(`*T*`)` bytes in memory




# Array Access

- **Basic Principle**

  *T* **A[***L***];**

  - Array of data type *T* and length *L*
  - Identifier **A** can be used as a pointer to array element 0: Type *T**





| Reference | Type | Value |
|---|---|---|
| `val[4]` | `int` | `51` |
| `val` | `int *` | *x* |
| `val+1` | `int *` | *x+4* |
| `&val[2]` | `int *` | *x+8* |
| `val[5]` | `int` | `??` |
| `*(val+1)` | `int` | `7` |
| `val + i` | `int *` | *x+4*`i` |

# Array Example


```
#define LEN 4
typedef int int_arr_4[LEN];

int_arr_4 cse2038 = { 2, 0, 3, 8 };
int_arr_4 cse1000 = { 1, 0, 0, 0 };
int_arr_4 cse2025 = { 2, 0, 2, 5 };
```


`int_arr_4 cse2038;`




`int_arr_4 cse1000;`





`int_arr_4 cse2025;`




- **Declaration "`int_arr_4 cse2038`" equivalent to "`int cse2038[4]`"**
- **Assume example arrays were allocated in successive 16 byte blocks**
  - Not guaranteed to happen in general

# Array Accessing Example

```
int_arr_4 cse2038;
```




```
int get_digit(int_arr_4 z, int digit)
{
  return z[digit];
}
```

```
  # %rdi = z
  # %rsi = digit
movl (%rdi,%rsi,4), %eax  # z[digit]
```

- Register **%rdi** contains starting address of array
- Register **%rsi** contains array index
- Desired digit at **%rdi + 4*%rsi**
- Use memory reference **(%rdi,%rsi,4)**

# Array Loop Example

```
void a_incr(int_arr_4 z) {
  size_t i;
  for (i = 0; i < LEN; i++)
    z[i]++;
}
```

```
  # %rdi = z
  movl    $0, %eax            #   i = 0
  jmp     .L3                 #   goto middle
.L4:                          # loop:
  addl    $1, (%rdi,%rax,4)   #   z[i]++
  addq    $1, %rax            #   i++
.L3:                          # middle
  cmpq    $3, %rax            #   i:3
  jbe     .L4                 #   if <=, goto loop
  rep; ret
```


# Understanding Pointers & Arrays #1


| Decl | *An* | | | **An* | | |
|---|---|---|---|---|---|---|
| | Cmp | Bad | Size | Cmp | Bad | Size |
| `int A1[3]` | | | | | | |
| `int *A2` | | | | | | |

- Cmp: Compiles (Y/N)
- Bad: Possible bad pointer reference (Y/N)
- Size: Value returned by `sizeof`

# Understanding Pointers & Arrays #1

| Decl | *An* | | | **An* | | |
|---|---|---|---|---|---|---|
| | Cmp | Bad | Size | Cmp | Bad | Size |
| `int A1[3]` | Y | N | 12 | Y | N | 4 |
| `int *A2` | Y | N | 8 | Y | Y | 4 |




- **Cmp: Compiles (Y/N)**
- **Bad: Possible bad pointer reference (Y/N)**
- **Size: Value returned by `sizeof`**


# Understanding Pointers & Arrays #2

| Decl | *An* | | | **An* | | | ***An* | | |
|---|---|---|---|---|---|---|---|---|---|
| | Cmp | Bad | Size | Cmp | Bad | Size | Cmp | Bad | Size |
| `int A1[3]` | | | | | | | | | |
| `int *A2[3]` | | | | | | | | | |
| `int (*A3)[3]` | | | | | | | | | |
| `int (*A4[3])` | | | | | | | | | |

- Cmp: Compiles (Y/N)
- Bad: Possible bad pointer reference (Y/N)
- Size: Value returned by `sizeof`


# Understanding Pointers & Arrays #2

| Decl | *An* | | | **An* | | | ***An* | | |
|---|---|---|---|---|---|---|---|---|---|
| | Cmp | Bad | Size | Cmp | Bad | Size | Cmp | Bad | Size |
| `int A1[3]` | Y | N | 12 | Y | N | 4 | N | – | – |
| `int *A2[3]` | Y | N | 24 | Y | N | 8 | Y | Y | 4 |
| `int (*A3)[3]` | Y | N | 8 | Y | Y | 12 | Y | Y | 4 |
| `int (*A4[3])` | Y | N | 24 | Y | N | 8 | Y | Y | 4 |




# Multidimensional (Nested) Arrays

- **Declaration**
  - *T* **A**[*R*][*C*];
  - 2D array of data type *T*
  - *R* rows, *C* columns
  - Type *T* element requires *K* bytes
- **Array Size**
  - *R* * *C* * *K* bytes
- **Arrangement**
  - Row-Major Ordering





`int A[R][C];`



# Nested Array Example

```
#define PCOUNT 4
int_arr_4 pgh[PCOUNT] =
  {{2, 0, 3, 8},
   {1, 0, 0, 0},
   {2, 0, 2, 5},
   {1, 0, 4, 2}};
```





- **"`int_arr_4 pgh[4]`" equivalent to "`int pgh[4][4]`"**
  - Variable **`pgh`**: array of 4 elements, allocated contiguously
  - Each element is an array of 4 **`int`**'s, allocated contiguously
- **"Row-Major" ordering of all elements in memory**


# Nested Array Row Access

- **Row Vectors**
  - **`A[i]`** is array of *C* elements
  - Each element of type *T* requires *K* bytes
  - Starting address **`A`** + *i* * (*C* * *K*)

```
int A[R][C];
```



# Nested Array Row Access Code




```
int *get_pgh_zip(int index)
{
  return pgh[index];
}
```

```
# %rdi = index
 leaq (%rdi,%rdi,3),%rax # 4 * index
 leaq pgh(,%rax,4),%rax  # pgh + (16 * index)
```


- **Row Vector**
  - **`pgh[index]`** is array of 4 **`int`**'s
  - Starting address **`pgh+16*index`**
- **Machine Code**
  - Computes and returns address
  - Compute as **`pgh + 4*(index+3*index)`**

# Nested Array Element Access


- **Array Elements**
  - `A[i][j]` is element of type *T*, which requires *K* bytes
  - Address `A + i * (C * K) + j * K`

`= A + (i * C + j) * K`

`int A[R][C];`



# Nested Array Element Access Code




```
int get_pgh_digit (int index, int dig)
{
  return pgh[index][dig];
}
```

```
leaq   (%rdi,%rdi,3), %rax    # 4*index
addl   %rax, %rsi             # 4*index+dig
movl   pgh(,%rsi,4), %eax     # M[pgh + 4*(4*index+dig)]
```


- **Array Elements**
  - `pgh[index][dig]` is `int`
  - Address: `pgh + 16*index + 4*dig`
    - = `pgh + 4*(4*index + dig)`

# Multi-Level Array Example

```
int_arr_4 cse2038 = { 2, 0, 3, 8 };
int_arr_4 cse1000 = { 1, 0, 0, 0 };
int_arr_4 cse2025 = { 2, 0, 2, 5 };
```


```
#define CCOUNT 3
int *course[CCOUNT] =
        {cse2038, cse1000, cse2025};
```

- **Variable `course` denotes array of 3 elements**
- **Each element is a pointer**
  - 8 bytes
- **Each pointer points to array of `int`'s**



# Element Access in Multi-Level Array

```
int get_course_digit
  (size_t index, size_t digit)
{
  return course[index][digit];
}
```




```
  salq    $2, %rsi              # 4*digit
  addq    course(,%rdi,8), %rsi # p = course[index] + 4*digit
  movl    (%rsi), %eax          # return *p
  ret
```

- **Computation**
  - Element access **`Mem[Mem[course+8*index]+4*digit]`**
  - Must do two memory reads
    - First get pointer to row array
    - Then access element within array


# Array Element Accesses


**Nested array**

```
int get_pgh_digit
   (size_t index, size_t digit)
{
  return pgh[index][digit];
}
```

**Multi-level array**

```
int get_course_digit
   (size_t index, size_t digit)
{
  return course [index][digit];
}
```




Accesses looks similar in C, but address computations very different:

**`Mem[pgh+16*index+4*digit]`** **`Mem[Mem[course+8*index]+4*digit]`**

# N X N Matrix Code

- **Fixed dimensions**
  - Know value of N at compile time

- **Variable dimensions, explicit indexing**
  - Traditional way to implement dynamic arrays

- **Variable dimensions, implicit indexing**
  - Now supported by gcc

```
#define N 16
typedef int fix_matrix[N][N];
/* Get element a[i][j] */
int fix_ele(fix_matrix a,
            size_t i, size_t j)
{
  return a[i][j];
}
```

```
#define IDX(n, i, j) ((i)*(n)+(j))
/* Get element a[i][j] */
int vec_ele(size_t n, int *a,
            size_t i, size_t j)
{
  return a[IDX(n,i,j)];
}
```

```
/* Get element a[i][j] */
int var_ele(size_t n, int a[n][n],
            size_t i, size_t j) {
  return a[i][j];
}
```

# 16 X 16 Matrix Access

- **Array Elements**
  - `int a[16][16]`
  - Address `a + i * (C * K) + j * K`
  - C = 16, K = 4

```
/* Get element a[i][j] */
int fix_ele(fix_matrix a, size_t i, size_t j) {
  return a[i][j];
}
```

```
  # a in %rdi, i in %rsi, j in %rdx
  salq    $6, %rsi              # 64*i
  addq    %rsi, %rdi            # a + 64*i
  movl    (%rdi,%rdx,4), %eax   # M[a + 64*i + 4*j]
  ret
```

# n X n Matrix Access

- **Array Elements**
  - `size_t n;`
  - `int a[n][n];`
  - Address `A + i * (C * K) + j * K`
  - C = n, K = 4
  - Must perform integer multiplication

```
/* Get element a[i][j] */
int var_ele(size_t n, int a[n][n], size_t i, size_t j)
{
  return a[i][j];
}
```

```
  # n in %rdi, a in %rsi, i in %rdx, j in %rcx
  imulq   %rdx, %rdi             # n*i
  leaq    (%rsi,%rdi,4), %rax    # a + 4*n*i
  movl    (%rax,%rcx,4), %eax    # M[a + 4*n*i + 4*j]
  ret
```

# Example: Array Access

```
#include <stdio.h>
#define ZLEN 5
#define PCOUNT 4
typedef int zip_dig[ZLEN];

int main(int argc, char** argv) {
zip_dig pgh[PCOUNT] =
    {{1, 5, 2, 0, 6},
     {1, 5, 2, 1, 3 },
     {1, 5, 2, 1, 7 },
     {1, 5, 2, 2, 1 }};
    int *linear_zip = (int *) pgh;
    int *zip2 = (int *) pgh[2];
    int result =
        pgh[0][0] +
        linear_zip[7] +
        *(linear_zip + 8) +
        zip2[1];
    printf("result: %d\n", result);
    return 0;
}
```

```
linux> ./array
result: 9
```

# Example: Array Access

```
#include <stdio.h>
#define ZLEN 5
#define PCOUNT 4
typedef int zip_dig[ZLEN];

int main(int argc, char** argv) {
zip_dig pgh[PCOUNT] =
    {{1, 5, 2, 0, 6},
     {1, 5, 2, 1, 3 },
     {1, 5, 2, 1, 7 },
     {1, 5, 2, 2, 1 }};
    int *linear_zip = (int *) pgh;
    int *zip2 = (int *) pgh[2];
    int result =
        pgh[0][0] +
        linear_zip[7] +
        *(linear_zip + 8) +
        zip2[1];
    printf("result: %d\n", result);
    return 0;
}
```


```
linux> ./array
result: 9
```

# Understanding Pointers & Arrays #3


| Decl | *An* | | | **An* | | | ***An* | | |
|---|---|---|---|---|---|---|---|---|---|
| | Cmp | Bad | Size | Cmp | Bad | Size | Cmp | Bad | Size |
| `int A1[3][5]` | | | | | | | | | |
| `int *A2[3][5]` | | | | | | | | | |
| `int (*A3)[3][5]` | | | | | | | | | |
| `int *(A4[3][5])` | | | | | | | | | |
| `int (*A5[3])[5]` | | | | | | | | | |


- **Cmp: Compiles (Y/N)**
- **Bad: Possible bad pointer reference (Y/N)**
- **Size: Value returned by `sizeof`**


| Decl | ****An* | | |
|---|---|---|---|
| | Cmp | Bad | Size |
| `int A1[3][5]` | | | |
| `int *A2[3][5]` | | | |
| `int (*A3)[3][5]` | | | |
| `int *(A4[3][5])` | | | |
| `int (*A5[3])[5]` | | | |





| Declaration |
| --- |
| `int A1[3][5]` |
| `int *A2[3][5]` |
| `int (*A3)[3][5]` |
| `int *(A4[3][5])` |
| `int (*A5[3])[5]` |



# Understanding Pointers & Arrays #3

| Decl | *An* | | | **An* | | | ***An* | | |
|---|---|---|---|---|---|---|---|---|---|
| | Cmp | Bad | Size | Cmp | Bad | Size | Cmp | Bad | Size |
| `int A1[3][5]` | Y | N | 60 | Y | N | 20 | Y | N | 4 |
| `int *A2[3][5]` | Y | N | 120 | Y | N | 40 | Y | N | 8 |
| `int (*A3)[3][5]` | Y | N | 8 | Y | Y | 60 | Y | Y | 20 |
| `int *(A4[3][5])` | Y | N | 120 | Y | N | 40 | Y | N | 8 |
| `int (*A5[3])[5]` | Y | N | 24 | Y | N | 8 | Y | Y | 20 |

- **Cmp: Compiles (Y/N)**
- **Bad: Possible bad pointer reference (Y/N)**
- **Size: Value returned by `sizeof`**


| Decl | ****An* | | |
|---|---|---|---|
| | Cmp | Bad | Size |
| `int A1[3][5]` | N | – | – |
| `int *A2[3][5]` | Y | Y | 4 |
| `int (*A3)[3][5]` | Y | Y | 4 |
| `int *(A4[3][5])` | Y | Y | 4 |
| `int (*A5[3])[5]` | Y | Y | 4 |

# Today

- **Arrays**
  - One-dimensional
  - Multi-dimensional (nested)
  - Multi-level
- **Structures**
  - Allocation
  - Access
  - Alignment
- **Floating Point**

# Structure Representation


```
struct rec {
    int a[4];
    size_t i;
    struct rec *next;
};
```




- Structure represented as block of memory
  - Big enough to hold all of the fields
- Fields ordered according to declaration
  - Even if another ordering could yield a more compact representation
- Compiler determines overall size + positions of fields
  - Machine-level program has no understanding of the structures in the source code

# Generating Pointer to Structure Member

```
struct rec {
    int a[4];
    size_t i;
    struct rec *next;
};
```




- **Generating Pointer to Array Element**
  - Offset of each structure member determined at compile time
  - Compute as **`r + 4*idx`**

```
int *get_ap
  (struct rec *r, size_t idx){
    return &r->a[idx];
}
```


```
  # r in %rdi, idx in %rsi
  leaq  (%rdi,%rsi,4), %rax
  ret
```

# Following Linked List

- C Code

```
struct rec {
    int a[4];
    int i;
    struct rec *next;
};
```

```
void set_val
  (struct rec *r, int val)
{
  while (r) {
    int idx = r->i;
    r->a[idx] = val;
    r = r->next;
  }
}
```





| Register | Value |
|---|---|
| %rdi | r |
| %rsi | val |

```
.L11:                                  # loop:
  movq    16(%rdi), %rax               #   i = M[r+16]
  movl    %esi, (%rdi,%rax,4)          #   M[r+4*i] = val
  movslq  24(%rdi), %rdi               #   r = M[r+24]
  testq   %rdi, %rdi                   #   Test r
  jne     .L11                         #   if !=0 goto loop
```


# Structures & Alignment

- **Unaligned Data**




```
struct S1 {
  char c;
  int i[2];
  double v;
} *p;
```

- **Aligned Data**
  - Primitive data type requires K bytes
  - Address must be multiple of K



# Alignment Principles

- **Aligned Data**
  - Primitive data type requires K bytes
  - Address must be multiple of K
  - Required on some machines; advised on x86-64
- **Motivation for Aligning Data**
  - Memory accessed by (aligned) chunks of 4 or 8 bytes (system dependent)
    - Inefficient to load or store datum that spans quad word boundaries
    - Virtual memory trickier when datum spans 2 pages
- **Compiler**
  - Inserts gaps in structure to ensure correct alignment of fields


# Specific Cases of Alignment (x86-64)

- **1 byte: `char`, …**
  - no restrictions on address
- **2 bytes: `short`, …**
  - lowest 1 bit of address must be $0_2$
- **4 bytes: `int`, `float`, …**
  - lowest 2 bits of address must be $00_2$
- **8 bytes: `double`, `long`, `char *`, …**
  - lowest 3 bits of address must be $000_2$

# Satisfying Alignment with Structures

- **Within structure:**
  - Must satisfy each element's alignment requirement
- **Overall structure placement**
  - Each structure has alignment requirement K
    - K = Largest alignment of any element
  - Initial address & structure length must be multiples of K
- **Example:**
  - K = 8, due to **`double`** element


```
struct S1 {
  char c;
  int i[2];
  double v;
} *p;
```



# Meeting Overall Alignment Requirement

- For largest alignment requirement K
- Overall structure must be multiple of K


```
struct S2 {
  double v;
  int i[2];
  char c;
} *p;
```



# Arrays of Structures

- Overall structure length multiple of K
- Satisfy alignment requirement for every element


```
struct S2 {
  double v;
  int i[2];
  char c;
}a[10];
```



# Accessing Array Elements

```
struct S3 {
  short i;
  float v;
  short j;
} a[10];
```

- **Compute array offset 12*idx**
  - `sizeof(S3)`, including alignment spacers
- **Element `j` is at offset 8 within structure**
- **Assembler gives offset `a+8`**
  - Resolved during linking





```
short get_j(int idx)
{
  return a[idx].j;
}
```

```
# %rdi = idx
leaq (%rdi,%rdi,2),%rax # 3*idx
movl a+8(,%rax,4),%eax
```

# Saving Space


- Put large data types first

```
struct S4 {
  char c;
  int i;
  char d;
} *p;
```



```
struct S5 {
  int i;
  char c;
  char d;
} *p;
```

- Effect (K=4)




# Today

- **Arrays**
  - One-dimensional
  - Multi-dimensional (nested)
  - Multi-level
- **Structures**
  - Allocation
  - Access
  - Alignment
- **Floating Point**


# Programming with SSE3

## XMM Registers


- 16 total, each 16 bytes
- 16 single-byte integers



- 8 16-bit integers



- 4 32-bit integers




- 4 single-precision floats




- 2 double-precision floats



- 1 single-precision float




- 1 double-precision float



# Scalar & SIMD Operations


- Scalar Operations: Single Precision

`addss %xmm0,%xmm1`





- SIMD Operations: Single Precision

`addps %xmm0,%xmm1`




- Scalar Operations: Double Precision

`addsd %xmm0,%xmm1`



# FP Basics

- Arguments passed in `%xmm0`, `%xmm1`, ...
- Result returned in `%xmm0`
- All XMM registers caller-saved

```
float fadd(float x, float y)
{
    return x + y;
}
```

```
double dadd(double x, double y)
{
    return x + y;
}
```

```
  # x in %xmm0, y in %xmm1
  addss   %xmm1, %xmm0
  ret
```

```
 # x in %xmm0, y in %xmm1
  addsd   %xmm1, %xmm0
  ret
```

# FP Memory Referencing

- Integer (and pointer) arguments passed in regular registers
- FP values passed in XMM registers
- Different `mov` instructions to move between XMM registers, and between memory and XMM registers

```
double dincr(double *p, double v)
{
    double x = *p;
    *p = x + v;
    return x;
}
```

```
  # p in %rdi, v in %xmm0
  movapd   %xmm0, %xmm1    # Copy v
  movsd    (%rdi), %xmm0   # x = *p
  addsd    %xmm0, %xmm1    # t = x + v
  movsd    %xmm1, (%rdi)   # *p = t
  ret
```

# Other Aspects of FP Code

- ***Lots* of instructions**
  - Different operations, different formats, ...
- **Floating-point comparisons**
  - Instructions **`ucomiss`** and **`ucomisd`**
  - Set condition codes CF, ZF, and PF
- **Using constant values**
  - Set XMM0 register to 0 with instruction **`xorpd %xmm0, %xmm0`**
  - Others loaded from memory

# Summary

- **Arrays**
  - Elements packed into contiguous region of memory
  - Use index arithmetic to locate individual elements
- **Structures**
  - Elements packed into single region of memory
  - Access using offsets determined by compiler
  - Possible require internal and external padding to ensure alignment
- **Combinations**
  - Can nest structure and array code arbitrarily
- **Floating Point**
  - Data held and operated on in XMM registers