# Example: SQL > Select

**** Write SQL statements for the following questions using the relational database below. ****

***Flight*** *(**FlightID**: varchar(8),* ***AirlineCompany****: nvarchar(50),* ***FlightDate****: date,* ***FlightTime****: time,* ***DelayInMinutes****: int,* ***DurationInMinutes****: int,* ***FromAirport****: varchar(25),* ***ToAirport****: varchar(25))*

*Sample data → TK5905; THY; 31.12.2015; 13:45; 135; 105; Erzurum; Istanbul Ataturk*

***Passenger*** *(**PassengerID**: bigint,* ***FirstName****: nvarchar(50),* ***LastName****: nvarchar(50),* ***Age****: int,* ***Points****: decimal(9,2))*

*Sample data → 123456789012; Mustafa; Ağaoğlu; 41; 15.34*

***FlightPassenger*** *(**FlightID**: varchar(8),* ***PassengerID****: bigint,* ***SeatNo****: int,* ***SeatPosition****: char(1),* ***Payment****: decimal(9,2))*

*Sample data → TK5905; 123456789012; 3; A; 109.98*

**1)** Retrieve ID, first and last name of passengers.

**2)** Retrieve first & last name, flight date & time and seat number for passengers.

**3)** How many flights are there totally?

**4)** Retrieve airline company and its total flights.

**5)** Retrieve ID, first and last name of passengers with the number of flights. Discard the passengers who have less than 5 flights.

**6)** Retrieve passenger ID, last name, departure (*FromAirport*) and arrival (*ToAirport*) airports for the passengers whose ages are greater than 40. Arrivals will be in Istanbul, *i.e. ToAirport* will contain "Istanbul". Eliminate redundant rows. Order your list by last name and then departure.

**7)** Retrieve departure (*FromAirport*) and arrival (*ToAirport*) airports, and the number of flights for the flights of the passengers if the payment of that flight is at least two times of passenger's average payment.