Chapter 6 Methods



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Methods

Methods can be used to define reusable code and organize and simplify coding.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Opening Problem

Find the sum of integers from 1 to 10, from 20 to 30, and from 35 to 45, respectively.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem

```
int sum = 0;
for (int i = 1; i <= 10; i++)
  sum += i;
System.out.println("Sum from 1 to 10 is " + sum);

sum = 0;
for (int i = 20; i <= 30; i++)
  sum += i;
System.out.println("Sum from 20 to 30 is " + sum);

sum = 0;
for (int i = 35; i <= 45; i++)
  sum += i;
System.out.println("Sum from 35 to 45 is " + sum);
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem

```
int sum = 0;
for (int i = 1; i <= 10; i++)
  sum += i;
System.out.println("Sum from 1 to 10 is " + sum);

sum = 0;
for (int i = 20; i <= 30; i++)
  sum += i;
System.out.println("Sum from 20 to 30 is " + sum);

sum = 0;
for (int i = 35; i <= 45; i++)
  sum += i;
System.out.println("Sum from 35 to 45 is " + sum);
```




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Solution

```
public static int sum(int i1, int i2) {
  int sum = 0;
  for (int i = i1; i <= i2; i++)
    sum += i;
  return sum;
}
```

MethodDemo

```
public static void main(String[] args) {
  System.out.println("Sum from 1 to 10 is " + sum(1, 10));
  System.out.println("Sum from 20 to 30 is " + sum(20, 30));
  System.out.println("Sum from 35 to 45 is " + sum(35, 45));
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Objectives

- To define methods
- To invoke methods
- To pass arguments by value
- To use method overloading and understand ambiguous overloading
- To determine the scope of variables



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Defining Methods

- A *method* is a collection of statements that are grouped together to perform an operation.
- A *method* definition consists of its method name, parameters, return value type, and body.
- The syntax for defining a method is as follows:

```
modifier returnValueType methodName(list of parameters) {
  // Method body;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Defining Methods

This method defines to find the larger between two integers.

Define a method

```
public static int max(int num1, int num2) {

  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```

Invoke a method

```
int z = max(x, y);
```


actual parameters (arguments)



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Method Header


Method header specifies the *modifiers*, *return value type*, *method name*, and *parameters* of the method. Parameters are optional.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Method Signature


Method signature is the combination of the method name and the parameter list.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Formal Parameters


The variables defined in the method header are known as *formal parameters*.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Actual Parameters


When a method is invoked, you pass a value to the parameter. This value is referred to as *actual parameter or argument*.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Return Value Type

A method may return a value. The returnValueType is the data type of the value the method returns. If the method does not return a value, the returnValueType is the keyword void. For example, the returnValueType in the main method is void.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Method Body

- The method body contains a collection of statements that implement the method.
- In order for a value-returning method to return a result, a return statement using the keyword **return** is *required*.
- The method terminates when a return statement is executed.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Calling Methods

Testing the `max` method

This program demonstrates calling a method max to return the largest of the `int` values


TestMax



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Calling Methods, cont.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

i is now 5

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;


  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation




```
public static void main(Strin     args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;


  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation




```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

invoke max(i, j)
Pass the value of i to num1
Pass the value of j to num2

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

declare variable result

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

(num1 > num2) is true since num1 is 5 and num2 is 2

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

result is now 5

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

return result, which is 5

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
pu    tatic int max(int num1, int num2) {
    esult;

  i   num1 > num2)
    esult = num1;
  e se
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

return max(i, j) and assign the return value to k

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Method Invocation

Execute the print statement

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

CAUTION

A return statement is required for a value-returning method. The method shown below in (a) is logically correct, but it has a compilation error because the Java compiler thinks it possible that this method does not return any value.

```
public static int sign(int n) {
  if (n > 0)
    return 1;
  else if (n == 0)
    return 0;
  else if (n < 0)
    return -1;
}
```

(a)

Should be

```
public static int sign(int n) {
  if (n > 0)
    return 1;
  else if (n == 0)
    return 0;
  else
    return -1;
}
```

(b)

Mantıken if bloklarından herhangi birine girmek zorunda olsa da kodlama mantığı olarak bir else koyulması şart

To fix this problem, delete *if (n < 0)* in (a), so that the compiler will see a return statement to be reached regardless of how the if statement is evaluated.

Copyright © 2022 Pearson Education Ltd. All rights reserved.


Reuse Methods from Other Classes

NOTE: One of the benefits of methods is for reuse. The max method can be invoked from any class besides TestMax. If you create a new class Test, you can invoke the max method using ClassName.methodName (e.g., TestMax.max).



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Call Stacks



(a) The `main` method is invoked.

(b) The `max` method is invoked.

(c) The `max` method is being executed.

(d) The `max` method is finished and the return value is sent to `k`.

(e) The `main` method is finished.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

i is declared and initialized


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

j is declared and initialized


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

Declare k


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

Invoke max(i, j)


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

pass the values of i and j to num1 and num2


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The max method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);


  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```

Declare result



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

(num1 > num2) is true


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The max method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);


  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2)
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```

Assign num1 to result



The max method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

Return result and assign it to k


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Call Stack

Execute print statement


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

void Method Example

This type of method does not return a value. The method performs some actions.

TestVoidMethod

TestReturnGradeMethod



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Passing Parameters

```
public static void nPrintln(String message, int n) {
  for (int i = 0; i < n; i++)
    System.out.println(message);
}
```

Suppose you invoke the method using

nPrintln("Welcome to Java", 5);

What is the output?

Suppose you invoke the method using

nPrintln("Computer Science", 15);

What is the output?

Can you invoke the method using

nPrintln(15, "Computer Science");



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Pass by Value

- When you invoke a method with an argument, the value of the argument is passed to the parameter.
  This is referred to as *pass-by-value*.
  The variable is not affected, regardless of the changes made to the parameter inside the method
- This program demonstrates passing values to the methods.

Increment



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Pass by Value

Testing Pass by value


This program demonstrates passing values to the methods.

TestPassByValue



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Pass by Value, cont.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Modularizing Code

Methods can be used to reduce redundant coding and enable code reuse. Methods can also be used to modularize code and improve the quality of the program.

GreatestCommonDivisorMethod

PrimeNumberMethod



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Case Study: Converting Hexadecimals to Decimals

Write a method that converts a hexadecimal number into a decimal number.

ABCD =>

A*16^3 + B*16^2 + C*16^1+ D*16^0

= ((A*16 + B)*16 + C)*16+D

= ((10*16 + 11)*16 + 12)*16+13 = ?

Hex2Dec



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Overloading Methods

Overloading methods enables you to define the methods with the same name as long as their signatures are different.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Overloading Methods

Overloading the `max` Method

```
public static double max(int num1, int num2) {
  if (num1 > num2)
    return num1;
  else
    return num2;
}

public static double max(double num1, double num2) {
  if (num1 > num2)
    return num1;
  else
    return num2;
}
```

TestMethodOverloading



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Ambiguous Invocation

Sometimes there may be two or more possible matches for an invocation of a method, but the compiler cannot determine the most specific match. This is referred to as *ambiguous invocation*. Ambiguous invocation is a compile error.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Ambiguous Invocation

```
public class AmbiguousOverloading {
  public static void main(String[] args) {
    System.out.println(max(1, 2));
  }

  public static double max(int num1, double num2) {
    if (num1 > num2)
      return num1;
    else
      return num2;
  }

  public static double max(double num1, int num2) {
    if (num1 > num2)
      return num1;
    else
      return num2;
  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Scope of Local Variables

A local variable: a variable defined inside a method.

Scope: the part of the program where the variable can be referenced.

The scope of a local variable starts from its declaration and continues to the end of the block that contains the variable. A local variable must be declared before it can be used.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Scope of Local Variables, cont.


You can declare a local variable with the same name multiple times in different non-nesting blocks in a method, but you cannot declare a local variable twice in nested blocks.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Scope of Local Variables, cont.

A variable declared in the initial action part of a for loop header has its scope in the entire loop. But a variable declared inside a for loop body has its scope limited in the loop body from its declaration and to the end of the block that contains the variable.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Scope of Local Variables, cont.

It is fine to declare i in two non-nesting blocks

```
public static void method1() {
  int x = 1;
  int y = 1;

  for (int i = 1; i < 10; i++) {
    x += i;
  }

  for (int i = 1; i < 10; i++) {
    y += i;
  }
}
```

It is wrong to declare i in two nesting blocks

```
public static void method2() {
  int i = 1;
  int sum = 0;

  for (int i = 1; i < 10; i++) {
    sum += i;
  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Scope of Local Variables, cont.

```
// Fine with no errors
public static void correctMethod() {
  int x = 1;
  int y = 1;
  // i is declared
  for (int i = 1; i < 10; i++) {
    x += i;
  }
  // i is declared again
  for (int i = 1; i < 10; i++) {
    y += i;
  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Scope of Local Variables, cont.

```
// With errors
public static void incorrectMethod() {
  int x = 1;
  int y = 1;
  for (int i = 1; i < 10; i++) {
    int x = 0;
    x += i;
  }
}
```




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Case Study: Generating Random Characters

Computer programs process numerical data and characters. You have seen many examples that involve numerical data. It is also important to understand characters and how to process them.

As introduced in Section 4.3, each character has a unique Unicode between 0 and FFFF in hexadecimal (65535 in decimal). To generate a random character is to generate a random integer between 0 and 65535 using the following expression: (note that since 0 <= Math.random() < 1.0, you have to add 1 to 65535.)

```
(int)(Math.random() * (65535 + 1))
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.


Case Study: Generating Random Characters, cont.

Now let us consider how to generate a random lowercase letter. The Unicode for lowercase letters are consecutive integers starting from the Unicode for 'a', then for 'b', 'c', ..., and 'z'. The Unicode for 'a' is

```
(int)'a'
```

So, a random integer between (int)'a' and (int)'z' is

```
(int)((int)'a' + Math.random() * ((int)'z' - (int)'a' + 1)
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.


Case Study: Generating Random Characters, cont.

Now let us consider how to generate a random lowercase letter. The Unicode for lowercase letters are consecutive integers starting from the Unicode for 'a', then for 'b', 'c', ..., and 'z'. The Unicode for 'a' is

```
(int)'a'
```

So, a random integer between (int)'a' and (int)'z' is

```
(int)((int)'a' + Math.random() * ((int)'z' - (int)'a' + 1)
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Case Study: Generating Random Characters, cont.

As discussed in Chapter 2, all numeric operators can be applied to the char operands. The char operand is cast into a number if the other operand is a number or a character. So, the preceding expression can be simplified as follows:

```
'a' + Math.random() * ('z' - 'a' + 1)
```

So a random lowercase letter is

```
(char)('a' + Math.random() * ('z' - 'a' + 1))
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Case Study: Generating Random Characters, cont.

To generalize the foregoing discussion, a random character between any two characters ch1 and ch2 with ch1 < ch2 can be generated as follows:

```
(char)(ch1 + Math.random() * (ch2 – ch1 + 1))
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The RandomCharacter Class

```
// RandomCharacter.java: Generate random characters
public class RandomCharacter {
  /** Generate a random character between ch1 and ch2 */
  public static char getRandomCharacter(char ch1, char ch2) {
    return (char)(ch1 + Math.random() * (ch2 - ch1 + 1));
  }

  /** Generate a random lowercase letter */
  public static char getRandomLowerCaseLetter() {
    return getRandomCharacter('a', 'z');
  }

  /** Generate a random uppercase letter */
  public static char getRandomUpperCaseLetter() {
    return getRandomCharacter('A', 'Z');
  }

  /** Generate a random digit character */
  public static char getRandomDigitCharacter() {
    return getRandomCharacter('0', '9');
  }

  /** Generate a random character */
  public static char getRandomCharacter() {
    return getRandomCharacter('\u0000', '\uFFFF');
  }
}
```

RandomCharacter


TestRandomCharacter



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Method Abstraction

You can think of the method body as a black box that contains the detailed implementation for the method.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Benefits of Methods

- Write a method once and reuse it anywhere.
- Information hiding. Hide the implementation from the user.
- Reduce complexity.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Stepwise Refinement (Optional)


The concept of method abstraction can be applied to the process of developing programs. When writing a large program, you can use the "divide and conquer" strategy, also known as *stepwise refinement*, to decompose it into subproblems. The subproblems can be further decomposed into smaller, more manageable problems.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

PrintCalender Case Study


Let us use the PrintCalendar example to demonstrate the stepwise refinement approach.



PrintCalendar


Copyright © 2022 Pearson Education Ltd. All rights reserved.

Design Diagram




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Design Diagram




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Design Diagram




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Design Diagram




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Design Diagram




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Design Diagram



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Design Diagram



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Implementation: Top-Down

Top-down approach is to implement one method in the structure chart at a time from the top to the bottom. Stubs can be used for the methods waiting to be implemented. A stub is a simple but incomplete version of a method. The use of stubs enables you to test invoking the method from a caller. Implement the main method first and then use a stub for the printMonth method. For example, let printMonth display the year and the month in the stub. Thus, your program may begin like this:

A Skeleton for printCalendar



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Implementation: Bottom-Up

Bottom-up approach is to implement one method in the structure chart at a time from the bottom to the top. For each method implemented, write a test program to test it. Both top-down and bottom-up methods are fine. Both approaches implement the methods incrementally and help to isolate programming errors and makes debugging easy. Sometimes, they can be used together.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Benefits of Stepwise Refinement

Simpler Program

Reusing Methods

Easier Developing, Debugging, and Testing

Better Facilitating Teamwork



Copyright © 2022 Pearson Education Ltd. All rights reserved.