① A modeler is building a model for the call center of Student Affairs Development in the validation phase, output results of the simulation model will be compared with the observed system behaviour which has a mean number of 73 calls per day 6 independent replications of the model were run and the following results are obtained as the average number of calls.


$S.E = \frac{s}{\sqrt{n}}$

Replication r	1	2	3	4	5	6
Sample mean for replication r	73	66	63	60	64	70

a) Develop and conduct a statistical test to evaluate whether model output is consistent with system behaviour for the significance levels $\alpha = 0.05$ and $\alpha = 0.01$.

$H_0 \Rightarrow$ mean = 73

$H_1 \Rightarrow$ mean ≠ 73



$\bar{y} \pm t_{\alpha/2, n-1} \frac{s}{\sqrt{n}}$

$\bar{x}$ sample mean $\mu = \frac{73+66+63+60+64+70}{6} = 66$

variance $s^2 = \frac{49+0^2+9+36+4+16}{5} = 22,8 \Rightarrow s = 4,77$ (standard deviation)

$|t_0| = \left|\frac{\bar{y}_2 - \mu_0}{s/\sqrt{n}}\right| = \left|\frac{66-73}{4,77/\sqrt{6}}\right| = \frac{6}{1,95} = 3,08$

$\bar{y} \pm t_{\alpha/2, n-1} \frac{s}{\sqrt{n}}$

For $\alpha = 0.10$ (in one tail, 0,05) $= 2,015$ → rejected

$\alpha = 0,05$ (0,025) $= 2,571$

$\alpha = 0,01$ (0,005) $= 4,032$ → not rejected.

$3,08 > 2,015$

$2,571$

$\bar{y} \pm t_{\alpha, n-1} \frac{s}{\sqrt{n}}$ confidence

$|t_0| = \left|\frac{\bar{y}_2 - \mu_0}{s/\sqrt{n}}\right|$

$66 \pm 2,015 \cdot 1,95$

$3,93$ $3,6$

$(62,08, 69,92)$ confidence interval

$62,08 <= \mu <= 69,92$

b) What is the power of this test if the 5 calls is viewed as critical (at most 5 calls) for the significance level $\alpha = 0.05$?

$\delta = \frac{|E(Y) - \mu|}{S} = \frac{5}{4,77} = 1,05$ $\quad \beta = 0,75$ $\quad (1 - 0,75) = 0,25$

c) What sample size is needed to have a power of 0.9 or (critical) for the significance level $\alpha = 0.05$?

$\beta = (1 - 0,9) = 0,1$ (12-13)

$P = n \cdot \frac{e^{-a} \cdot a^x}{x!}$

Scanned by CamScanner

(2) Assume that the model defined in Problem 1 has been validated. Now, the modelor is testing a system performance for new system designs. For a new design, the simulation analyst made R=10 replication. Sample mean of number of calls (succesfully replied) for each replication is given in the table below

Replication r	1	2	3	4	5	6	7	8	9	10
Sample mean for replication r	88	86	80	75	65	75	69	81	77	79

a) Estimate the long run avarage number of calls and find the error of estimate by 95% and 99% confidence intervals (find the confidence intervals)

$\alpha = 0,05$ $\alpha = 0,01$

$\alpha = 0.05$
$\alpha = 0.01$
$\bar{y} = 77,5$
$\sigma = 7,03$

$\bar{y} \pm t_{0,025}\, s/\sqrt{n} = 77,5 \pm 2,262 \times 7,03/\sqrt{10} = 77,5 \pm 5,03$

$\bar{y} \pm t_{0,005}\, s/\sqrt{n} = 77,5 \pm 3,250 \times 7,03/\sqrt{10} = 77,5 \pm 7,23$

$\frac{\alpha}{2} \rightarrow$ Dr tal $\alpha = 0,05$, $\alpha = 0,01$

$77,5 \pm 2,262 \cdot \frac{7,03}{\sqrt{10}} = 77,5 \pm 5,03 \rightarrow (72,47 - 82,53)$

$77,5 \pm 3,25$ ( )

Scanned by CamScanner

(3) Assume that you have developed the model of a software development company with two system designs. In the first system design there are two developers working in a team and in the second system design there are three developers working in a team. When the two systems are simulated for 8 replications, the sample means for the time to complete a work (in terms of hours) is given below. In each system design, same random numbers are used for the same events.

Find out whether the second system is better than the first one (in terms of time to complete a work) for the confidence levels 98% and 99%?

$\alpha = 0,02$

$\alpha = 0,01$

Rep. #	System 1	System 2	difference
1	205	209	-4
2	210	215	-5
3	208	202	6
4	199	203	-4
5	207	193	14
6	211	201	10
7	206	201	5
8	205	199	6
mean →	208,375	202,875	3,5
s^2 →	13,696	43,554	50,286

No evidence that one system is better than another.

Standard error: $\frac{s}{\sqrt{n}} = \frac{\sqrt{50,286}}{\sqrt{8}} = 2,507$

$\alpha = 0,02$

$\alpha = 0,01$

$\bar{y} \pm t \cdot \frac{s}{\sqrt{n}}$ (7,516)

$3,5 \pm (2,998)(2,507) = (-4,11) \rightarrow x \cdot (2,11)$

$3,5 \pm (3,499)(2,507) = (-5,112 \cdot x$ (8,7)

$(-5,-2)$

dahilve

eğer 0'sa, kontrolünü 2.

tamamı 0'ın solundaysa.

İkinci sistem daha iyi

tamamı 0'ın sağındaysa

birinci sistem daha iyi

Scanned by CamScanner

Do not Reject | correct decision | "Type$_a$" Error |

(4) A simulation will be conducted for a car washing facility where various car models will be included in the simulation. The facility manager says that service time is related with the .. of the car. (It means that in the simulation, car size and service time might not be generated separately from different distribution). Therefore, data were collected for the next 10 cars.

Car size (length in meters)	4.65	4.36	4.78	4.88	4.80	4.42	4.88	4.9	4.35	4.07	4,609
Washing Time (minutes)	6.1	5.3	7.3	8.2	7.4	5.8	8.4	9.1	5.1	4.6	6,721

Compute the sample correlation between the car size and the washing time and find out if the long time is dependent to car size?

$$\hat{cov} = [314,028 - (10)(4.609)(6,721)] / (10-1)$$

$$(314,028 - 309,77) / 9 = 0,47$$

Covariance.

$$\sum_{j=1}^{10} x_j x_{2j} = 314,028$$

$$\rho = \frac{cov}{\sigma_1 \cdot \sigma_2} = \frac{0,47}{(0,29)(1,56)} = 1,04$$

correlation. bağ güçlü

bağ ↓

$0,1$

$corr = \frac{\hat{cov}}{\sigma_1 \cdot \sigma_2}$

1) -1 . yakınsa bağ zayıftır.

0 yakınsa bağ zayıftır.

0 'sa. bağ yoktur.

$$\rho = \frac{\hat{cov}}{\sigma_1 \cdot \sigma_2} = 0$$

Scanned by CamScanner

→ The power may also be expressed as 1 minus the probability of a Type II. or β. $\beta = P(\text{Type II error}) = P(\text{failing to reject } H_0 / H_1 \text{ is true})$

$f = \frac{|E(Y_2) - \mu_0|}{\sigma}$ For $\mu_0 = 4.3$ minutes, by 1 minute; $\alpha = 0,05$

$\frac{1}{1,66} = 0,60$ $\beta = (\hat{f}) = \beta(0,6) = 0,75$ for $n = 6$

→ Verification: Building the model correctly (correctly implemented with good input and structure) "Did we build the model right"?

Validation: Building the correct model (an accurate representation of the real system) "Did we built the right model"

Model Building:

- Observing the real system and the interactions
- Construction of conceptual model
- Implementation of an operation model

Ex

Random var.
- Poisson arrivals → rate = 45/hour → $X_{11}, X_{12} \dots$
- Service time → $N(D_2, 0,2^2)$ → $X_{21}, X_{22} \dots$



Teller's utilization → $Y_1 = \rho$

Avg. delay → Y_2

Max. line length → Y_3

$\alpha = 0,05$
$n = 6$

Decision variables
- One teller → $D_1 = 1$
- Mean service time → $D_2 = 1,1$ min
- One line → $D_3 = 1$

Avg. delay = 4.3

Hypothesis test: $H_0: E(Y_2) = 4,3$ min
$H_1: E(Y_2) = 4,3$ min

$\bar{Y}_2 = \frac{1}{n} \sum_{i=1}^{n} Y_{2i} = 2,51$ min

$S = 0,82$ $t_{0,025,5} = 2,571$

$t_0 = \frac{\bar{Y}_2 - \mu_0}{S/\sqrt{n}} = \left| \frac{2,51 - 4,3}{0,82/\sqrt{6}} \right| = 5,34$

$5,34 > 2,571$ so H_0 is rejected

Rep	Y4	Y5	Y2 = Avg. Delay
1	51	1.07	2.79
2	40	1.12	1.12
3	49.5	1.06	2.24
4	50.5	1.10	3.45
5	53	1.09	3.13
6	49	1.07	2.38

Simple mean →

Scanned by CamScanner

	when H_0 is true	when H_1 is true
Do not Reject H_0	Correct decision $P = 1-\alpha$	Type II error $P = \beta$
Reject H_0	Type I error $P = \alpha$	correct decision $P = 1-\beta$

Ex: Suppose that the overall avg. of the avg. cycle time on 120 rep. of a mnv. sim. is 5,80 hours, std. dev. is 1.60 hours. Since $t_{0.025,119} = 1,98$ a 95% confidence interval for the long-run expected daily avg. cycle time is

$$5.80 \pm 1.98(1.60)\sqrt{1+\frac{1}{20}} = 5.80 \pm 3.18$$

Ex: Estimate the agent's utilization over the first 2 hours of the workday.

$R_0 = 4$, $S_0^2 = 0.00518$

$\varepsilon = 0.04$

$$\left(\frac{z_{0.025}\, S_0}{\varepsilon}\right)^2 = \frac{1.96^2 * 0.00518}{0.04^2} = 12.14$$

R	13	14	15
$t_{0.025,R-1}$	2.18	2.16	2.14
$(t_{\alpha/2,R-1} S_0/\varepsilon)^2$	15.39	15.1	14.83
$t_{\alpha/2,R-1}\frac{S}{\sqrt{R}}$	0.04353	0.04156	0.03992
ε			

$R = 15$ is the smallest integer

$R - R_0 = 11$

Ex Suppose $R = 1000$ reps, to estimate the $p = 0.8$ quantile with a 95% confidence interval

output	rank
180.92	779
→ 188.96	780
190.55	781
208.58	799
212.03	800 ←
216.99	801
250.32	819
256.79	820
256.99	821

$1000 \cdot (0.8) = 800^{th}$ smallest value.

$$P_L = 0.8 - 1.96\sqrt{\frac{.8(1-.8)}{1000-1}} = 0.78$$

$$P_U = 0.8 + 1.96\sqrt{\frac{.8(1-.8)}{1000-1}} = 0.82$$

The point estimate with 95% C.I is $[188.96, 256.79)$

Scanned by CamScanner