Chapter 6 Methods



Methods

Methods can be used to define reusable code and organize and simplify coding.



Opening Problem

Find the sum of integers from 1 to 10, from 20 to 30, and from 35 to 45, respectively.




Problem

```
int sum = 0;
for (int i = 1; i <= 10; i++)
  sum += i;
System.out.println("Sum from 1 to 10 is " + sum);

sum = 0;
for (int i = 20; i <= 30; i++)
  sum += i;
System.out.println("Sum from 20 to 30 is " + sum);

sum = 0;
for (int i = 35; i <= 45; i++)
  sum += i;
System.out.println("Sum from 35 to 45 is " + sum);
```




Problem

```
int sum = 0;
for (int i = 1; i <= 10; i++)
  sum += i;
System.out.println("Sum from 1 to 10 is " + sum);

sum = 0;
for (int i = 20; i <= 30; i++)
  sum += i;
System.out.println("Sum from 20 to 30 is " + sum);


sum = 0;
for (int i = 35; i <= 45; i++)
  sum += i;
System.out.println("Sum from 35 to 45 is " + sum);
```



Solution

```
public static int sum(int i1, int i2) {
  int sum = 0;
  for (int i = i1; i <= i2; i++)
    sum += i;
  return sum;
}
```

```
public static void main(String[] args) {
  System.out.println("Sum from 1 to 10 is " + sum(1, 10));
  System.out.println("Sum from 20 to 30 is " + sum(20, 30));
  System.out.println("Sum from 35 to 45 is " + sum(35, 45));
}
```



Objectives

- To define methods
- To invoke methods
- To pass arguments by value
- To use method overloading and understand ambiguous overloading
- To determine the scope of variables



Defining Methods

- A *method* is a collection of statements that are grouped together to perform an operation.
- A *method* definition consists of its method name, parameters, return value type, and body.
- The syntax for defining a method is as follows:

```
modifier returnValueType methodName(list of parameters) {
  // Method body;
}
```



Defining Methods

This method defines to find the larger between two integers.

Define a method

```
public static int max(int num1, int num2) {

  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```

Invoke a method


```
int z = max(x, y);
```

actual parameters (arguments)




Method Header

Method header specifies the *modifiers*, *return value type*, *method name*, and *parameters* of the method. Parameters are optional.




Method Signature

Method signature is the combination of the method name and the parameter list.




Formal Parameters

The variables defined in the method header are known as *formal parameters*.



Actual Parameters


When a method is invoked, you pass a value to the parameter. This value is referred to as *actual parameter or argument*.




Return Value Type

- A method may return a value.
- The returnValueType is the data type of the value the method returns.
- If the method does not return a value, the returnValueType is the keyword void.
- For example, the returnValueType in the main method is void.

Define a method



Invoke a method



Method Body

- The method body contains a collection of statements that implement the method.
- In order for a value-returning method to return a result, a return statement using the keyword **return** is *required.*
- The method terminates when a return statement is executed.



Calling Methods


Testing the `max` method

This program demonstrates calling a method max to return the largest of the `int` values



animation

Calling Methods, cont.



animation

Trace Method Invocation

i is now 5

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



animation

Trace Method Invocation

j is now 2

```
public static void main(Strin    args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;


  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



animation

Trace Method Invocation



Trace Method Invocation

invoke max(i, j)
Pass the value of i to num1
Pass the value of j to num2

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Trace Method Invocation

declare variable result

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



Trace Method Invocation

(num1 > num2) is true since num1 is 5 and num2 is 2

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



animation

Trace Method Invocation

result is now 5

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



animation

Trace Method Invocation

return result, which is 5

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
pu      tatic int max(int num1, int num2) {
        esult;

    num1 > num2)
    esult = num1;
   se
    result = num2;

  return result;
}
```



animation

Trace Method Invocation

return max(i, j) and assign the return value to k

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



animation

Trace Method Invocation

Execute the print statement

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
   "The maximum between " + i +
   " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



CAUTION

A return statement is required for a value-returning method. The method shown below in (a) is logically correct, but it has a compilation error because the Java compiler thinks it possible that this method does not return any value.

```
public static int sign(int n) {
  if (n > 0)
    return 1;
  else if (n == 0)
    return 0;
  else if (n < 0)
    return -1;
}
```

(a)

Should be

```
public static int sign(int n) {
  if (n > 0)
    return 1;
  else if (n == 0)
    return 0;
  else
    return -1;
}
```

(b)


To fix this problem, delete *if (n < 0)* in (a), so that the compiler will see a return statement to be reached regardless of how the if statement is evaluated.

Reuse Methods from Other Classes

NOTE: One of the benefits of methods is for reuse. The max method can be invoked from any class besides TestMax. If you create a new class Test, you can invoke the max method using ClassName.methodName (e.g., TestMax.max).



Call Stacks



(a) The `main` method is invoked.

(b) The `max` method is invoked.

(c) The `max` method is being executed.

(d) The `max` method is finished and the return value is sent to `k`.

(e) The `main` method is finished.

animation

Trace Call Stack

i is declared and initialized


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

animation

Trace Call Stack

j is declared and initialized


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

animation

Trace Call Stack

Declare k


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

animation

Trace Call Stack

Invoke max(i, j)


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



The main method is invoked.

animation

Trace Call Stack

pass the values of i and j to num1 and num2


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



animation

Trace Call Stack

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);


  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```

Declare result



animation

Trace Call Stack

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);


  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```

(num1 > num2) is true



The max method is invoked.

animation

Trace Call Stack

```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);


  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2)
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```

Assign num1 to result



The max method is invoked.

animation

Trace Call Stack

Return result and assign it to k


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;

  return result;
}
```



animation

Trace Call Stack

Execute print statement


```
public static void main(String[] args) {
  int i = 5;
  int j = 2;
  int k = max(i, j);

  System.out.println(
    "The maximum between " + i +
    " and " + j + " is " + k);
}
```

```
public static int max(int num1, int num2) {
  int result;

  if (num1 > num2)
    result = num1;
  else
    result = num2;


  return result;
}
```



The main method is invoked.

void Method Example

This type of method does not return a value. The method performs some actions.



Passing Parameters

```
public static void nPrintln(String message, int n) {
  for (int i = 0; i < n; i++)
    System.out.println(message);
}
```

Suppose you invoke the method using

nPrintln("Welcome to Java", 5);

What is the output?

The **nPrintln(" Welcome to Java ",5)** statement passes the actual string parameter **Welcome to Java** to the parameter **message**, passes **5** to **n**, and prints

Welcome to Java
Welcome to Java
Welcome to Java
Welcome to Java
Welcome to Java



Passing Parameters

```
public static void nPrintln(String message, int n) {
  for (int i = 0; i < n; i++)
    System.out.println(message);
}
```

Can you invoke the method using

nPrintln(15, “Computer Science”);

The **nPrintln(15, "Computer Science")** statement would be wrong. The data type of **15** does not match the data type for the first parameter, **message**, nor does the second argument, **Computer Science**, match the second parameter, **n**.



Pass by Value

- When you invoke a method with an argument, the value of the argument is passed to the parameter.
  This is referred to as *pass-by-value*.
  The variable is not affected, regardless of the changes made to the parameter inside the method
- This program demonstrates passing values to the methods.



Increment

Run

Pass by Value

Testing Pass by value


This program demonstrates passing values to the methods.



TestPassByValue


Run

Pass by Value, cont.



Modularizing Code

Methods can be used to reduce redundant coding and enable code reuse. Methods can also be used to modularize code and improve the quality of the program.



Case Study: Converting Hexadecimals to Decimals

Write a method that converts a hexadecimal number into a decimal number.

ABCD =>

A*16^3 + B*16^2 + C*16^1+ D*16^0

= ((A*16 + B)*16 + C)*16+D

= ((10*16 + 11)*16 + 12)*16+13 = ?



Hex2Dec

Run

Overloading Methods

Overloading methods enables you to define the methods with the same name as long as their signatures are different.



Overloading Methods

Overloading the `max` Method

```
public static double max(int num1, int num2) {
  if (num1 > num2)
    return num1;
  else
    return num2;
}

public static double max(double num1, double num2) {
  if (num1 > num2)
    return num1;
  else
    return num2;
}
```



TestMethodOverloading

Run

Ambiguous Invocation

- Sometimes there may be two or more possible matches for an invocation of a method, but the compiler cannot determine the most specific match.

- This is referred to as *ambiguous invocation*.

- Ambiguous invocation is a compile error.



Ambiguous Invocation

```
public class AmbiguousOverloading {
  public static void main(String[] args) {
    System.out.println(max(1, 2));
  }

  public static double max(int num1, double num2) {
    if (num1 > num2)
      return num1;
    else
      return num2;
  }

  public static double max(double num1, int num2) {
    if (num1 > num2)
      return num1;
    else
      return num2;
  }
}
```



Scope of Local Variables

- *The scope of a variable is the part of the program where the variable can be referenced.*

- A variable defined inside a method is referred to as a *local variable.*

- The scope of a local variable starts from its declaration and continues to the end of the block that contains the variable. A local variable must be declared before it can be used.




Scope of Local Variables, cont.

You can declare a local variable with the same name multiple times in different non-nesting blocks in a method, but you cannot declare a local variable twice in nested blocks.



Scope of Local Variables, cont.

A variable declared in the initial action part of a for loop header has its scope in the entire loop. But a variable declared inside a for loop body has its scope limited in the loop body from its declaration and to the end of the block that contains the variable.



Scope of Local Variables, cont.

It is fine to declare i in two non-nesting blocks

```
public static void method1() {
  int x = 1;
  int y = 1;


  for (int i = 1; i < 10; i++) {
    x += i;
  }

  for (int i = 1; i < 10; i++) {
    y += i;
  }
}
```

It is wrong to declare i in two nesting blocks

```
public static void method2() {
  int i = 1;
  int sum = 0;

  for (int i = 1; i < 10; i++) {
    sum += i;
  }
}
```



Scope of Local Variables, cont.

```
// Fine with no errors
public static void correctMethod() {
  int x = 1;
  int y = 1;
  // i is declared
  for (int i = 1; i < 10; i++) {
    x += i;
  }
  // i is declared again
  for (int i = 1; i < 10; i++) {
    y += i;
  }
}
```



Scope of Local Variables, cont.

```
// With errors
public static void incorrectMethod() {
  int x = 1;
  int y = 1;
  for (int i = 1; i < 10; i++) {
    int x = 0;
    x += i;
  }
}
```



Case Study: Generating Random Characters

Computer programs process numerical data and characters. You have seen many examples that involve numerical data. It is also important to understand characters and how to process them.

As introduced in Section 2.9, each character has a unique Unicode between 0 and FFFF in hexadecimal (65535 in decimal). To generate a random character is to generate a random integer between 0 and 65535 using the following expression: (note that since 0 <= Math.random() < 1.0, you have to add 1 to 65535.)

```
(int)(Math.random() * (65535 + 1))
```




Case Study: Generating Random Characters, cont.

Now let us consider how to generate a random lowercase letter. The Unicode for lowercase letters are consecutive integers starting from the Unicode for 'a', then for 'b', 'c', ..., and 'z'. The Unicode for 'a' is

```
(int)'a'
```

So, a random integer between (int)'a' and (int)'z' is

```
(int)((int)'a' + Math.random() * ((int)'z' - (int)'a' + 1)
```



Case Study: Generating Random Characters, cont.

As discussed in Chapter 2., all numeric operators can be applied to the char operands. The char operand is cast into a number if the other operand is a number or a character. So, the preceding expression can be simplified as follows:

```
'a' + Math.random() * ('z' - 'a' + 1)
```

So a random lowercase letter is

```
(char)('a' + Math.random() * ('z' - 'a' + 1))
```



Case Study: Generating Random Characters, cont.

To generalize the foregoing discussion, a random character between any two characters ch1 and ch2 with ch1 < ch2 can be generated as follows:

```
(char)(ch1 + Math.random() * (ch2 – ch1 + 1))
```



The RandomCharacter Class

```
// RandomCharacter.java: Generate random characters
public class RandomCharacter {
  /** Generate a random character between ch1 and ch2 */
  public static char getRandomCharacter(char ch1, char ch2) {
    return (char)(ch1 + Math.random() * (ch2 - ch1 + 1));
  }

  /** Generate a random lowercase letter */
  public static char getRandomLowerCaseLetter() {
    return getRandomCharacter('a', 'z');
  }

  /** Generate a random uppercase letter */
  public static char getRandomUpperCaseLetter() {
    return getRandomCharacter('A', 'Z');
  }

  /** Generate a random digit character */
  public static char getRandomDigitCharacter() {
    return getRandomCharacter('0', '9');
  }

  /** Generate a random character */
  public static char getRandomCharacter() {
    return getRandomCharacter('\u0000', '\uFFFF');
  }
}
```








Method Abstraction

You can think of the method body as a black box that contains the detailed implementation for the method.



Benefits of Methods

- Write a method once and reuse it anywhere.
- Information hiding. Hide the implementation from the user.
- Reduce complexity.



Stepwise Refinement


The concept of method abstraction can be applied to the process of developing programs. When writing a large program, you can use the "divide and conquer" strategy, also known as *stepwise refinement*, to decompose it into subproblems. The subproblems can be further decomposed into smaller, more manageable problems.




PrintCalender Case Study

Let us use the PrintCalendar example to demonstrate the stepwise refinement approach.


Suppose you write a program that displays the calendar for a given month of the year. The program prompts the user to enter the year and the month, then displays the entire calendar for the month.




Design Diagram




Design Diagram




Design Diagram




Design Diagram




Design Diagram



Design Diagram



Design Diagram



Implementation: Top-Down

Top-down approach is to implement one method in the structure chart at a time from the top to the bottom. Stubs can be used for the methods waiting to be implemented. A stub is a simple but incomplete version of a method. The use of stubs enables you to test invoking the method from a caller. Implement the main method first and then use a stub for the printMonth method. For example, let printMonth display the year and the month in the stub. Thus, your program may begin like this:

A Skeleton for printCalendar


Implementation: Bottom-Up

Bottom-up approach is to implement one method in the structure chart at a time from the bottom to the top. For each method implemented, write a test program to test it. Both top-down and bottom-up methods are fine. Both approaches implement the methods incrementally and help to isolate programming errors and makes debugging easy. Sometimes, they can be used together.



PrintCalender Case Study

Let us use the PrintCalendar example to demonstrate the stepwise refinement approach.



PrintCalendar

Run

Benefits of Stepwise Refinement

Simpler Program

Reusing Methods

Easier Developing, Debugging, and Testing

Better Facilitating Teamwork

