Chapter 10 Thinking in Objects


Motivations

You see the advantages of object-oriented programming from the preceding chapter.

This chapter will demonstrate how to solve problems using the object-oriented paradigm.

Class Abstraction and Encapsulation

- Class abstraction means to separate class implementation from the use of the class.
- The creator of the class provides a description of the class and let the user know how the class can be used.
- The user of the class does not need to know how the class is implemented.
- The detail of implementation is encapsulated and hidden from the user.



Designing the Loan Class

Loan	
-annualInterestRate: double	The annual interest rate of the loan (default: 2.5).
-numberOfYears: int	The number of years for the loan (default: 1)
-loanAmount: double	The loan amount (default: 1000).
-loanDate: Date	The date this loan was created.
+Loan()	Constructs a default Loan object.
+Loan(annualInterestRate: double, numberOfYears: int, loanAmount: double)	Constructs a loan with specified interest rate, years, and loan amount.
+getAnnualInterestRate(): double	Returns the annual interest rate of this loan.
+getNumberOfYears(): int	Returns the number of the years of this loan.
+getLoanAmount(): double	Returns the amount of this loan.
+getLoanDate(): Date	Returns the date of the creation of this loan.
+setAnnualInterestRate(annualInterestRate: double): void	Sets a new annual interest rate to this loan.
+setNumberOfYears(numberOfYears: int): void	Sets a new number of years to this loan.
+setLoanAmount(loanAmount: double): void	Sets a new amount to this loan.
+getMonthlyPayment(): double	Returns the monthly payment of this loan.
+getTotalPayment(): double	Returns the total payment of this loan.

Loan TestLoanClass Run

Object-Oriented Thinking

- Chapters 1-8 introduced fundamental programming techniques for problem solving using loops, methods, and arrays.
- The studies of these techniques lay a solid foundation for object-oriented programming.
- Classes provide more flexibility and modularity for building reusable software.
- This section improves the solution for a problem introduced in Chapter 3 using the object-oriented approach.
- From the improvements, you will gain the insight on the differences between the procedural programming and object-oriented programming and see the benefits of developing reusable code using objects and classes.

The BMI Class

The get methods for these data fields are provided in the class, but omitted in the UML diagram for brevity.

BMI	
-name: String	The name of the person.
-age: int	The age of the person.
-weight: double	The weight of the person in pounds.
-height: double	The height of the person in inches.
+BMI(name: String, age: int, weight: double, height: double)	Creates a BMI object with the specified name, age, weight, and height.
+BMI(name: String, weight: double, height: double)	Creates a BMI object with the specified name, weight, height, and a default age 20.
+getBMI(): double	Returns the BMI
+getStatus(): String	Returns the BMI status (e.g., normal, overweight, etc.)


BMI UseBMIClass Run

Class Relationships

- To design classes, you need to explore the relationships among classes.
- The common relationships among classes are
  - association
  - aggregation
  - composition
  - inheritance (Chapter 11)

Association

- *Association* is a general binary relationship that describes an activity between two classes.
- This UML diagram shows that a student may take any number of courses, a faculty member may teach at most three courses, a course may have from five to sixty students, and a course is taught by only one faculty member.



Association (cont.)

```
public class Student {
  private Course[]
    courseList;

  public void addCourse(
    Course s) { ... }
}
```

```
public class Course {
  private Student[]
    classList;
  private Faculty faculty;


  public void addStudent(
    Student s) { ... }

  public void setFaculty(
    Faculty faculty) { ... }
}
```

```
public class Faculty {
  private Course[]
    courseList;

  public void addCourse(
    Course c) { ... }
}
```

The association relations are implemented using data fields and methods in classes.



Aggregation and Composition


- *Aggregation* is a special form of association that represents an ownership relationship between two objects.
- Aggregation models *has-a* relationships.
- The owner object is called an *aggregating object* and its class an *aggregating class*.
- The subject object is called an *aggregated object* and its class an *aggregated class*.

Composition

- Composition is actually a special case of the aggregation relationship.
- If an object is exclusively owned by an aggregating object, the relationship between the object and its aggregating object is referred to as a *composition.*

Composition

For example, "a student has a name" is a composition relationship between the **Student** class and the **Name** class, whereas "a student has an address" is an aggregation relationship between the **Student** class and the **Address** class, since an address can be shared by several students



Class Representation

An aggregation relationship is usually represented as a data field in the aggregating class. For example, the relationship can be represented as follows:

```
public class Name {
  ...
}
```

Aggregated class

```
public class Student {
  private Name name;
  private Address address;

  ...
}
```

Aggregating class

```
public class Address {
  ...
}
```


Aggregated class

Aggregation or Composition

Since aggregation and composition relationships are represented using classes in similar ways, many texts don't differentiate them and call both compositions.

Aggregation Between Same Class


Aggregation may exist between objects of the same class. For example, a person may have a supervisor.




```
public class Person {
  // The type for the data is the class itself
  private Person supervisor;
  ...
}
```


Aggregation Between Same Class

What happens if a person has several supervisors?




```
public class Person {
  ...
  private Person[] supervisors;
}
```

Example: The Course Class

Course	
-courseName: String	The name of the course.
-students: String[]	An array to store the students for the course.
-numberOfStudents: int	The number of students (default: 0).
+Course(courseName: String)	Creates a course with the specified name.
+getCourseName(): String	Returns the course name.
+addStudent(student: String): void	Adds a new student to the course.
+dropStudent(student: String): void	Drops a student from the course.
+getStudents(): String[]	Returns the students in the course.
+getNumberOfStudents(): int	Returns the number of students in the course.



Wrapper Classes

A primitive type value is not an object, but it can be wrapped in an object using a wrapper class in the Java API.

- Boolean
- Character
- Short
- Byte
- Integer
- Long
- Float
- Double

Wrapper Classes

- Boolean
- Character
- Short
- Byte
- Integer
- Long
- Float
- Double

NOTE:
(1) The wrapper classes do not have no-arg constructors.
(2) The instances of all wrapper classes are immutable, i.e., their internal values cannot be changed once the objects are created.

The `Integer` and `Double` Classes

java.lang.Integer
-value: int
+MAX_VALUE: int
+MIN_VALUE: int
+Integer(value: int)
+Integer(s: String)
+byteValue(): byte
+shortValue(): short
+intValue(): int
+longVlaue(): long
+floatValue(): float
+doubleValue():double
+compareTo(o: Integer): int
+toString(): String
+valueOf(s: String): Integer
+valueOf(s: String, radix: int): Integer
+parseInt(s: String): int
+parseInt(s: String, radix: int): int

java.lang.Double
-value: double
+MAX_VALUE: double
+MIN_VALUE: double
+Double(value: double)
+Double(s: String)
+byteValue(): byte
+shortValue(): short
+intValue(): int
+longVlaue(): long
+floatValue(): float
+doubleValue():double
+compareTo(o: Double): int
+toString(): String
+valueOf(s: String): Double
+valueOf(s: String, radix: int): Double
+parseDouble(s: String): double
+parseDouble(s: String, radix: int): double

The `Integer` Class and the `Double` Class

- Constructors
- Class Constants `MAX_VALUE`, `MIN_VALUE`
- Conversion Methods

Numeric Wrapper Class Constructors

You can construct a wrapper object either from a primitive data type value or from a string representing the numeric value. The constructors for Integer and Double are:

public Integer(int value)

public Integer(String s)

public Double(double value)

public Double(String s)

For example:

```
new Integer(5)
new Integer("5")

new Double(5.0)
new Double("5.0")
```


Numeric Wrapper Class Constants

- Each numerical wrapper class has the constants MAX_VALUE and MIN_VALUE.
- MAX_VALUE represents the maximum value of the corresponding primitive data type.
- For Byte, Short, Integer, and Long, MIN_VALUE represents the minimum byte, short, int, and long values.
- For Float and Double, MIN_VALUE represents the minimum *positive* float and double values.
- The following statements display the maximum integer (2,147,483,647), the minimum positive float (1.4E-45), and the maximum double floating-point number (1.79769313486231570e+308d).

```
System.out.println("The maximum integer is " + Integer.MAX_VALUE);
System.out.println("The minimum positive float is " +
  Float.MIN_VALUE);
System.out.println(
  "The maximum double-precision floating-point number is " +
  Double.MAX_VALUE);
```


The Static valueOf Methods

The numeric wrapper classes have a useful class method, valueOf(String s). This method creates a new object initialized to the value represented by the specified string.

For example:

```
Double doubleObject = Double.valueOf("12.4");
Integer integerObject = Integer.valueOf("12");
```

The Methods for Parsing Strings into Numbers

- You have used the *parseInt* method in the Integer class to parse a numeric string into an int value and the *parseDouble* method in the Double class to parse a numeric string into a double value.
- Each numeric wrapper class has two overloaded parsing methods to parse a numeric string into an appropriate numeric value.

For example,

```
Integer.parseInt("11", 2) returns 3;
Integer.parseInt("12", 8) returns 10;
Integer.parseInt("13", 10) returns 13;
Integer.parseInt("1A", 16) returns 26;
```



BigInteger and BigDecimal

- If you need to compute with very large integers or high precision floating-point values, you can use the BigInteger and BigDecimal classes in the java.math package.
- Both are *immutable*.



BigInteger and BigDecimal

```
BigInteger a = new BigInteger("92233720368547758O7");
BigInteger b = new BigInteger("2");
BigInteger c = a.multiply(b); // 9223372036854775807 * 2
System.out.println(c);  // 18446744073709551614

BigDecimal a = new BigDecimal(1.0);
BigDecimal b = new BigDecimal(3);
BigDecimal c = a.divide(b, 20, BigDecimal.ROUND_UP);
System.out.println(c); //  0.33333333333333333334
```



The `String` Class

- Constructing a String:
  - `String message = "Welcome to Java ";`
  - `String message = new String("Welcome to Java");`
  - `String s = new String();`
- Obtaining String length and Retrieving Individual Characters in a string
- String Concatenation (concat)
- Substrings (substring(index), substring(start, end))
- Comparisons (equals, compareTo)
- String Conversions
- Finding a Character or a Substring in a String
- Conversions between Strings and Arrays
- Converting Characters and Numeric Values to Strings



Constructing Strings

```
String newString = new String(stringLiteral);
String message = new String("Welcome to Java");
```

Since strings are used frequently, Java provides a shorthand initializer for creating a string:

```
String message = "Welcome to Java";

char[] charArray = {'G', 'o', 'o', 'd', ' ', 'D', 'a', 'y'};
String message = new String(charArray);
```



Strings Are Immutable

A String object is immutable; its contents cannot be changed. Does the following code change the contents of the string?


```
String s = "Java";
s = "HTML";
```



animation

Trace Code


```
String s = "Java";
s = "HTML";
```




animation

Trace Code

```
String s = "Java";
s = "HTML";
```





Interned Strings

Since strings are immutable and are frequently used, to improve efficiency and save memory, the JVM uses a unique instance for string literals with the same character sequence. Such an instance is called *interned*. For example, the following statements:




Examples

```
String s1 = "Welcome to Java";

String s2 = new String("Welcome to Java");

String s3 = "Welcome to Java";

System.out.println("s1 == s2 is " + (s1 == s2));
System.out.println("s1 == s3 is " + (s1 == s3));
```



display

s1 == s2 is false

s1 == s3 is true

A new object is created if you use the new operator.


If you use the string initializer, no new object is created if the interned object is already created.



animation

Trace Code


```
String s1 = "Welcome to Java";
String s2 = new String("Welcome to Java");
String s3 = "Welcome to Java";
```





Trace Code


```
String s1 = "Welcome to Java";
String s2 = new String("Welcome to Java");
String s3 = "Welcome to Java";
```





Trace Code

```
String s1 = "Welcome to Java";
String s2 = new String("Welcome to Java");
String s3 = "Welcome to Java";
```





Replacing and Splitting Strings

java.lang.String	
+replace(oldChar: char, newChar: char): String	Returns a new string that replaces all matching character in this string with the new character.
+replaceFirst(oldString: String, newString: String): String	Returns a new string that replaces the first matching substring in this string with the new substring.
+replaceAll(oldString: String, newString: String): String	Returns a new string that replace all matching substrings in this string with the new substring.
+split(delimiter: String): String[]	Returns an array of strings consisting of the substrings split by the delimiter.



Examples

"Welcome".replace('e', 'A') returns a new string, WAlcomA.

"Welcome".replaceFirst("e", "AB") returns a new string, WABlcome.

"Welcome".replace("e", "AB") returns a new string, WABlcomAB.

"Welcome".replace("el", "AB") returns a new string, WABcome.



Splitting a String

```
String[] tokens = "Java#HTML#Perl".split("#");
for (int i = 0; i < tokens.length; i++)
  System.out.print(tokens[i] + " ");
```

displays

Java HTML Perl



`StringBuilder` and `StringBuffer`

- The `StringBuilder`/`StringBuffer` class is an alternative to the `String` class.
- In general, a StringBuilder/StringBuffer can be used wherever a string is used.
- StringBuilder/StringBuffer is more flexible than String.
- You can add, insert, or append new contents into a string buffer, whereas the value of a String object is fixed once the string is created.



`StringBuilder` Constructors

java.lang.StringBuilder	
+StringBuilder()	Constructs an empty string builder with capacity 16.
+StringBuilder(capacity: int)	Constructs a string builder with the specified capacity.
+StringBuilder(s: String)	Constructs a string builder with the specified string.



Modifying Strings in the Builder

java.lang.StringBuilder	
+append(data: char[]): StringBuilder	Appends a char array into this string builder.
+append(data: char[], offset: int, len: int): StringBuilder	Appends a subarray in data into this string builder.
+append(v: *aPrimitiveType*): StringBuilder	Appends a primitive type value as a string to this builder.
+append(s: String): StringBuilder	Appends a string to this string builder.
+delete(startIndex: int, endIndex: int): StringBuilder	Deletes characters from startIndex to endIndex.
+deleteCharAt(index: int): StringBuilder	Deletes a character at the specified index.
+insert(index: int, data: char[], offset: int, len: int): StringBuilder	Inserts a subarray of the data in the array to the builder at the specified index.
+insert(offset: int, data: char[]): StringBuilder	Inserts data into this builder at the position offset.
+insert(offset: int, b: *aPrimitiveType*): StringBuilder	Inserts a value converted to a string into this builder.
+insert(offset: int, s: String): StringBuilder	Inserts a string into this builder at the position offset.
+replace(startIndex: int, endIndex: int, s: String): StringBuilder	Replaces the characters in this builder from startIndex to endIndex with the specified string.
+reverse(): StringBuilder	Reverses the characters in the builder.
+setCharAt(index: int, ch: char): void	Sets a new character at the specified index in this builder.



Examples

```
StringBuilder stringBuilder = new StringBuilder();
stringBuilder.append("Welcome");
stringBuilder.append(' ');
stringBuilder.append("to");
stringBuilder.append(' ');
stringBuilder.append("Java");

stringBuilder.insert(11, "HTML and "); // Welcome to HTML and Java.
stringBuilder.delete(8, 11) // changes the builder to Welcome Java.
stringBuilder.deleteCharAt(8) // changes the builder to Welcome o Java.
stringBuilder.reverse() // changes the builder to avaJ ot emocleW.
stringBuilder.replace(11, 15, "HTML") //changes the builder to Welcome to HTML.
stringBuilder.setCharAt(0, 'w') // sets the builder to welcome to Java.
```



The toString, capacity, length, setLength, and charAt Methods

java.lang.StringBuilder	
+toString(): String	Returns a string object from the string builder.
+capacity(): int	Returns the capacity of this string builder.
+charAt(index: int): char	Returns the character at the specified index.
+length(): int	Returns the number of characters in this builder.
+setLength(newLength: int): void	Sets a new length in this builder.
+substring(startIndex: int): String	Returns a substring starting at startIndex.
+substring(startIndex: int, endIndex: int): String	Returns a substring from startIndex to endIndex-1.
+trimToSize(): void	Reduces the storage size used for the string builder.

