Chapter 7 Single-Dimensional Arrays



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Opening Problem

Read one hundred numbers, compute their average, and find out how many numbers are above the average.

- Your program first reads the numbers and computes their average, then compares each number with the average to determine whether it is above the average.
- In order to accomplish this task, the numbers must all be stored in variables.
- You have to declare **100** variables and repeatedly write almost identical code 100 times.
- Writing a program this way would be impractical.




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Opening Problem (cont.)

- How do you solve this problem?

- Java provides a data structure, the *array*, which stores a fixed-size sequential collection of elements of the same type.

- In this example, you can store all 100 numbers into an array and access them through a single array variable.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Objectives


- To declare array reference variables and create arrays
- To access array elements using indexes
- To declare, create, and initialize an array using an array initializer
- To program common array operations (displaying arrays, summing all elements, finding the minimum and maximum elements, random shuffling, and shifting elements)
- To simplify programming using the foreach loops
- To copy contents from one array to another
- To develop and invoke methods with array arguments and return values
- To define a method with a variable-length argument list
- To search elements using the linear or binary search algorithm.
- To sort an array using the selection sort approach
- To use the methods in the **java.util.Arrays** class



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Introducing Arrays

Array is a data structure that represents a collection of the same types of data.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Declaring Array Variables

- `datatype[] arrayRefVar;`

  Example:

  `double[] myList;`

- `datatype arrayRefVar[];` // This style is allowed, but not preferred

  Example:

  `double myList[];`



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Creating Arrays

```
arrayRefVar = new datatype[arraySize];
```

Example:

```
myList = new double[10];
```

`myList[0]` references the first element in the array.

`myList[9]` references the last element in the array.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Declaring and Creating in One Step

- `datatype[] arrayRefVar = new datatype[arraySize];`

```
double[] myList = new double[10];
```

- `datatype arrayRefVar[] = new datatype[arraySize];`

```
double myList[] = new double[10];
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The Length of an Array

Once an array is created, its size is fixed. It cannot be changed. You can find its size using

```
arrayRefVar.length
```

For example,

myList.length returns 10



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Default Values

When an array is created, its elements are assigned the default value of

0 for the numeric primitive data types,

'\u0000' for char types, and

false for boolean types.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Indexed Variables

The array elements are accessed through the index. The array indices are *0-based*, i.e., it starts from 0 to arrayRefVar.length-1.

In the example, myList holds ten double values and the indices are from 0 to 9.

Each element in the array is represented using the following syntax, known as an *indexed variable*:

```
arrayRefVar[index];
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Using Indexed Variables

To assign values to the elements, use the syntax:

```
arrayRefVar[index] = value;
```

Example:

```
myList[5] = 20.5;
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Using Indexed Variables (cont.)

After an array is created, an indexed variable can be used in the same way as a regular variable.

For example, the following code adds the value in myList[0] and myList[1] to myList[2].

```
myList[2] = myList[0] + myList[1];
```

Example:

```
for (int i = 0; i < myList.length; i++)
{
    myList[i] = i;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Array Initializers

- Declaring, creating, initializing in one step:

```
double[] myList = {1.9, 2.9, 3.4, 3.5};
```

This shorthand syntax must be in one statement.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Declaring, creating, initializing Using the Shorthand Notation

```
double[] myList = {1.9, 2.9, 3.4, 3.5};
```

This shorthand notation is equivalent to the following statements:

```
double[] myList = new double[4];

myList[0] = 1.9;

myList[1] = 2.9;

myList[2] = 3.4;

myList[3] = 3.5;
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

CAUTION

Using the shorthand notation, you have to declare, create, and initialize the array all in one statement. Splitting it would cause a syntax error. For example, the following is wrong:

```
double[] myList;

myList = {1.9, 2.9, 3.4, 3.5};
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.


animation

Trace Program with Arrays

Declare array variable values, create an array, and assign its reference to values

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the array is created



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

i becomes 1

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the array is created

0	0
1	0
2	0
3	0
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

i (=1) is less than 5

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the array is created

0	0
1	0
2	0
3	0
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.


animation

Trace Program with Arrays

After this line is executed, value[1] is 1

```
public class Test {
  public static void main(Strin      gs) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the first iteration



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

After i++, i becomes 2

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the first iteration

0	0
1	1
2	0
3	0
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

```
public class Test {
  public static void main(String[]
      args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] +
      values[4];
  }
}
```

i (= 2) is less than 5

After the first iteration

0	0
1	1
2	0
3	0
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.


animation

Trace Program with Arrays

After this line is executed, values[2] is 3 (2 + 1)

```
public class Test {
  public static void main(Strin      gs) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the second iteration





Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

After this, i becomes 3.

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the second iteration

0	0
1	1
2	3
3	0
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

i (=3) is still less than 5.

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the second iteration

0	0
1	1
2	3
3	0
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.


animation

Trace Program with Arrays

After this line, values[3] becomes 6 (3 + 3)

```
public class Test {
  public static void main(String[] args
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the third iteration





Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

After this, i becomes 4

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

i (=4) is still less than 5

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the third iteration

0	0
1	1
2	3
3	6
4	0



Copyright © 2022 Pearson Education Ltd. All rights reserved.


animation

Trace Program with Arrays

After this, values[4] becomes 10 (4 + 6)

```
public class Test {
  public static void main(Stri      args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the fourth iteration



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

After i++, i becomes 5

```
public class Test {
  public static void main(String[] arg
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the fourth iteration

0	0
1	1
2	3
3	6
4	10



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

i (=5) < 5 is false. Exit the loop

```
public class Test {
  public static void main(String[] args) {
    int[] values = new int[5];
    for (int i = 1; i < 5; i++) {
      values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

After the fourth iteration

0	0
1	1
2	3
3	6
4	10




Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace Program with Arrays

After this line, values[0] is 11 (1 + 10)

```
public class Test {
  public static void m      ring[] args) {
    int[] values = ne      [5];
    for (int i = 1; i      ; i++) {
      values[i] = i      values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Errors

```
public class Test {
  public static void main(String[] args)
  {
    int[] values = new int[5];
    for (int i = 1; i < 6; i++) {
       values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[4];
  }
}
```

3

Runtime Error: ArrayIndexOutOfBoundsException: 5



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Errors (cont.)

```
public class Test {
  public static void main(String[] args)
  {
    int[] values = new int[5];
    for (int i = 1; i < 6; i++) {
       values[i] = i + values[i-1];
    }
    values[0] = values[1] + values[5];
  }
}
```

3

Runtime Error: ArrayIndexOutOfBoundsException: 5



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Processing Arrays

See the examples in the text.

1. (Initializing arrays with input values)
2. (Initializing arrays with random values)
3. (Printing arrays)
4. (Summing all elements)
5. (Finding the largest element)
6. (Finding the smallest index of the largest element)
7. (*Random shuffling*)
8. (*Shifting elements*)



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Initializing arrays with input values

```
double[] myList = new double[5];

Scanner input = new Scanner(System.in);
System.out.print("Enter " + myList.length + "
    values: ");

for (int i = 0; i < myList.length; i++)
  myList[i] = input.nextDouble();
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Initializing arrays with random values

```
for (int i = 0; i < myList.length; i++) {
  myList[i] = Math.random() * 100;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Printing arrays

```
for (int i = 0; i < myList.length; i++){
  System.out.print(myList[i] + " ");
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Summing all elements

```
double total = 0;
for (int i = 0; i < myList.length; i++){
  total += myList[i];
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Finding the largest element

```
double max = myList[0];
for (int i = 1; i < myList.length; i++){
  if (myList[i] > max)
    max = myList[i];
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Finding the smallest index of the largest element

// Suppose the array **myList** is {**1**, **5**, **3**, **4**, **5**, **5**}.

```
double max = myList[0];
int indexOfMax = 0;

for (int i = 1; i < myList.length; i++){
    if (myList[i] > max) {
      max = myList[i];
      indexOfMax = i;
    }
}
```




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Random shuffling

In many applications, you need to randomly reorder the elements in an array. This is called *shuffling*.

```
for (int i = myList.length - 1; i > 0; i--) {
  // Generate an index j randomly with 0 <= j <= i
  int j = (int)(Math.random()
    * (i + 1));

  // Swap myList[i] with myList[j]
  double temp = myList[i];
  myList[i] = myList[j];
  myList[j] = temp;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.


Shifting Elements

Sometimes you need to shift the elements left or right.

```
double temp = myList[0]; // Retain the first element

// Shift elements left
for (int i = 1; i < myList.length; i++) {
  myList[i - 1] = myList[i];
}

// Move the first element to fill in the last position
myList[myList.length - 1] = temp;
```





Copyright © 2022 Pearson Education Ltd. All rights reserved.

Enhanced for Loop (for-each loop)

JDK 1.5 introduced a new for loop that enables you to traverse the complete array sequentially without using an index variable. For example, the following code displays all elements in the array myList:

```
for (double value: myList)
  System.out.println(value);
```

In general, the syntax is

```
for (elementType value: arrayRefVar) {
  // Process the value
}
```

You still have to use an index variable if you wish to traverse the array in a different order or change the elements in the array.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Example 1

```
int x = 30;
int[] numbers = new int[x];
x = 60;
System.out.println("x is " + x);
System.out.println("The size of numbers
is " + numbers.length);
```

Output:

```
x is 60
The size of numbers is 30
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Analyze Numbers

Read one hundred numbers, compute their average, and find out how many numbers are above the average.

AnalyzeNumbers



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem: Deck of Cards

The problem is to write a program that picks four cards randomly from a deck of 52 cards. All the cards can be represented using an array named deck, filled with initial values 0 to 51, as follows:


```
int[] deck = new int[52];
// Initialize cards
for (int i = 0; i < deck.length; i++)
  deck[i] = i;
```

DeckOfCards




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem: Deck of Cards, cont.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem: Deck of Cards, cont.



DeckOfCards


Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem: Deck of Cards

This problem builds a foundation for future more interesting and realistic applications:

https://liveexample.pearsoncmg.com/dsanimation/24Point.html

See Exercise 20.15.





Copyright © 2022 Pearson Education Ltd. All rights reserved.

Copying Arrays

Often, in a program, you need to duplicate an array or a part of an array. In such cases you could attempt to use the assignment statement (=), as follows:

list2 = list1;





Copyright © 2022 Pearson Education Ltd. All rights reserved.

Copying Arrays

There are three ways to copy arrays:

- Use a loop to copy individual elements one by one.

- Use the static **arraycopy** method in the **System** class.

- Use the **clone** method to copy arrays; this will be introduced in Chapter 13, Abstract Classes and Interfaces.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Copying Arrays

Using a loop:

```
int[] sourceArray = {2, 3, 1, 5, 10};
int[] targetArray = new
  int[sourceArray.length];

for (int i = 0; i < sourceArrays.length; i++)
   targetArray[i] = sourceArray[i];
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The `arraycopy` Utility

```
arraycopy(sourceArray, src_pos,
  targetArray, tar_pos, length);
```

Example:

```
System.arraycopy(sourceArray, 0,
  targetArray, 0, sourceArray.length);
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Passing Arrays to Methods

```
public static void printArray(int[] array) {
  for (int i = 0; i < array.length; i++) {
    System.out.print(array[i] + " ");
  }
}
```

Invoke the method

```
int[] list = {3, 1, 2, 6, 4, 2};
printArray(list);
```

Invoke the method

```
printArray(new int[]{3, 1, 2, 6, 4, 2});
```

Anonymous array



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Anonymous Array

The statement

```
printArray(new int[]{3, 1, 2, 6, 4, 2});
```

creates an array using the following syntax:

```
new dataType[]{literal0, literal1, ..., literalk};
```

There is no explicit reference variable for the array. Such array is called an *anonymous array*.




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Pass By Value

Java uses *pass by value* to pass arguments to a method. There are important differences between passing a value of variables of primitive data types and passing arrays.

- **For a parameter of a primitive type value**, the actual value is passed. Changing the value of the local parameter inside the method does not affect the value of the variable outside the method.

- **For a parameter of an array type**, the value of the parameter contains a reference to an array; this reference is passed to the method. Any changes to the array that occur inside the method body will affect the original array that was passed as the argument.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Simple Example

```
public class Test {
  public static void main(String[] args) {
    int x = 1; // x represents an int value
    int[] y = new int[10]; // y represents an array of int values

    m(x, y); // Invoke m with arguments x and y


    System.out.println("x is " + x);
    System.out.println("y[0] is " + y[0]);
  }

  public static void m(int number, int[] numbers) {
    number = 1001; // Assign a new value to number
    numbers[0] = 5555; // Assign a new value to numbers[0]
  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.


Call Stack



When invoking m(x, y), the values of x and y are passed to number and numbers. Since y contains the reference value to the array, numbers now contains the same reference value to the same array.

Copyright © 2022 Pearson Education Ltd. All rights reserved.


Call Stack



When invoking m(x, y), the values of x and y are passed to number and numbers. Since y contains the reference value to the array, numbers now contains the same reference value to the same array.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

Heap



The JVM stores the array in an area of memory, called *heap*, which is used for dynamic memory allocation where blocks of memory are allocated and freed in an arbitrary order.

Copyright © 2022 Pearson Education Ltd. All rights reserved.

Passing Arrays as Arguments


- Objective: Demonstrate differences of passing primitive data type variables and array variables.

TestPassArray



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Example, cont.



Invoke swap(int n1, int n2). The primitive type values in a[0] and a[1] are passed to the swap method.

The arrays are stored in a heap.

Invoke swapFirstTwoInArray(int[] array). The reference value in a is passed to the swapFirstTwoInArray method.


Copyright © 2022 Pearson Education Ltd. All rights reserved.

Returning an Array from a Method

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```




```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

Declare result and create array

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

i = 0 and j = 5

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

i (= 0) is less than 6

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i = 0 and j = 5
Assign list[0] to result[5]



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

After this, i becomes 1 and j becomes 4

list	1	2	3	4	5	6

result	0	0	0	0	0	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i (=1) is less than 6

list	1	2	3	4	5	6

result	0	0	0	0	0	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i = 1 and j = 4
Assign list[1] to result[4]



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

After this, i becomes 2 and j becomes 3

list	1	2	3	4	5	6

result	0	0	0	0	2	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i (=2) is still less than 6

list	1	2	3	4	5	6

result	0	0	0	0	2	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i = 2 and j = 3
Assign list[i] to result[j]



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

After this, i becomes 3 and j becomes 2



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i (=3) is still less than 6

list	1	2	3	4	5	6

result	0	0	0	3	2	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i = 3 and j = 2
Assign list[i] to result[j]



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

After this, i becomes 4 and j becomes 1

list	1	2	3	4	5	6

result	0	0	4	3	2	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i (=4) is still less than 6

list	1	2	3	4	5	6

result	0	0	4	3	2	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i = 4 and j = 1
Assign list[i] to result[j]



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

After this, i becomes 5 and j becomes 0





Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i (=5) is still less than 6





Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i = 5 and j = 0
Assign list[i] to result[j]



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

After this, i becomes 6 and j becomes -1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.

```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```

i (=6) < 6 is false. So exit the loop.

list	1	2	3	4	5	6

result	6	5	4	3	2	1



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Trace the reverse Method, cont.


```
int[] list1 = {1, 2, 3, 4, 5, 6};
int[] list2 = reverse(list1);
```

```
public static int[] reverse(int[] list) {
  int[] result = new int[list.length];

  for (int i = 0, j = result.length - 1;
       i < list.length; i++, j--) {
    result[j] = list[i];
  }

  return result;
}
```


Return result




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem: Counting Occurrence of Each Letter

- Generate 100 lowercase letters randomly and assign to an array of characters.
- Count the occurrence of each letter in the array.



(a) Executing `createArray` in line 5



(b) After exiting `createArray` in line 5

CountLettersInArray

Copyright © 2022 Pearson Education Ltd. All rights reserved.

Variable-Length Arguments

You can pass a variable number of arguments of the same type to a method.

VarArgsDemo




Copyright © 2022 Pearson Education Ltd. All rights reserved.

Searching Arrays

Searching is the process of looking for a specific element in an array; for example, discovering whether a certain score is included in a list of scores. Searching is a common task in computer programming. There are many algorithms and data structures devoted to searching. In this section, two commonly used approaches are discussed, *linear search* and *binary search*.

```
public class LinearSearch {
  /** The method for finding a key in the list */
  public static int linearSearch(int[] list, int key) {
    for (int i = 0; i < list.length; i++)
      if (key == list[i])
        return i;
    return -1;
  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Linear Search


The linear search approach compares the key element, key, *sequentially* with each element in the array list. The method continues to do so until the key matches an element in the list or the list is exhausted without a match being found. If a match is made, the linear search returns the index of the element in the array that matches the key. If no match is found, the search returns -1.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Linear Search Animation



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Linear Search Animation

https://liveexample.pearsoncmg.com/dsanimation/LinearSearcheBook.html



Copyright © 2022 Pearson Education Ltd. All rights reserved.

From Idea to Solution

```
/** The method for finding a key in the list */
public static int linearSearch(int[] list, int key) {
  for (int i = 0; i < list.length; i++)
    if (key == list[i])
      return i;
  return -1;
}
```

Trace the method

```
int[] list = {1, 4, 4, 2, 5, -3, 6, 2};
int i = linearSearch(list, 4);  // returns 1
int j = linearSearch(list, -4); // returns -1
int k = linearSearch(list, -3); // returns 5
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Binary Search

For binary search to work, the elements in the array must already be ordered. Without loss of generality, assume that the array is in ascending order.

e.g., 2 4 7 10 11 45 50 59 60 66 69 70 79

The binary search first compares the key with the element in the middle of the array.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Binary Search, cont.

Consider the following three cases:


- If the key is less than the middle element, you only need to search the key in the first half of the array.
- If the key is equal to the middle element, the search ends with a match.
- If the key is greater than the middle element, you only need to search the key in the second half of the array.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Binary Search



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Binary Search Animation


https://liveexample.pearsoncmg.com/dsanimation/BinarySearcheBook.html






Copyright © 2022 Pearson Education Ltd. All rights reserved.

Binary Search, cont.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Binary Search, cont.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Binary Search, cont.

The binarySearch method returns the index of the element in the list that matches the search key if it is contained in the list. Otherwise, it returns

-insertion point - 1.

The insertion point is the point at which the key would be inserted into the list.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

From Idea to Soluton

```
/** Use binary search to find the key in the list */
public static int binarySearch(int[] list, int key) {
  int low = 0;
  int high = list.length - 1;

  while (high >= low) {
    int mid = (low + high) / 2;
    if (key < list[mid])
      high = mid - 1;
    else if (key == list[mid])
      return mid;
    else
      low = mid + 1;
  }

  return -1 - low;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Sorting Arrays


Sorting, like searching, is also a common task in computer programming. Many different algorithms have been developed for sorting. This section introduces a simple, intuitive sorting algorithms: *selection sort*.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Selection Sort

Selection sort finds the smallest number in the list and places it first. It then finds the smallest number remaining and places it second, and so on until the list contains only a single number.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

animation

Selection Sort Animation

https://liveexample.pearsoncmg.com/dsanimation/SelectionSortNew.html





Copyright © 2022 Pearson Education Ltd. All rights reserved.

From Idea to Solution

```
for (int i = 0; i < list.length; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i+1..listSize-1]
}
```

```
list[0] list[1] list[2] list[3] ...          list[10]

list[0] list[1] list[2] list[3] ...          list[10]

list[0] list[1] list[2] list[3] ...          list[10]

list[0] list[1] list[2] list[3] ...          list[10]

list[0] list[1] list[2] list[3] ...          list[10]

                                ...

list[0] list[1] list[2] list[3] ...          list[10]
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

```
for (int i = 0; i < listSize; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i..listSize-1]
}
```

Expand

```
double currentMin = list[i];

for (int j = i+1; j < list.length; j++) {
  if (currentMin > list[j]) {
    currentMin = list[j];

  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

```
for (int i = 0; i < listSize; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i..listSize-1]
}
```

Expand

```
double currentMin = list[i];
int currentMinIndex = i;
for (int j = i; j < list.length; j++) {
  if (currentMin > list[j]) {
    currentMin = list[j];
    currentMinIndex = j;
  }
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

```
for (int i = 0; i < listSize; i++) {
  select the smallest element in list[i..listSize-1];
  swap the smallest with list[i], if necessary;
  // list[i] is in its correct position.
  // The next iteration apply on list[i..listSize-1]
}
```

Expand

```
if (currentMinIndex != i) {
  list[currentMinIndex] = list[i];
  list[i] = currentMin;
}
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Wrap it in a Method

```
/** The method for sorting the numbers */
public static void selectionSort(double[] list) {
  for (int i = 0; i < list.length; i++) {
    // Find the minimum in the list[i..list.length-1]
    double currentMin = list[i];
    int currentMinIndex = i;
    for (int j = i + 1; j < list.length; j++) {
      if (currentMin > list[j]) {
        currentMin = list[j];
        currentMinIndex = j;
      }
    }

    // Swap list[i] with list[currentMinIndex] if necessary;
    if (currentMinIndex != i) {
      list[currentMinIndex] = list[i];
      list[i] = currentMin;
    }
  }
}
```

Invoke it

selectionSort(yourList);



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The **Arrays** Class

The **java.util.Arrays** class contains useful methods for common array operations such as sorting and searching.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The **Arrays** Class (cont.)

Arrays.toString(list) method can be used to return a string representation for the list.

```
int[] list = {2, 4, 7, 10};
System.out.println(Arrays.toString(list));
```

displays **[2, 4, 7, 10]**.

- Arrays.equals(list1, list2) checks whether two arrays are strictly equal

```
int[] list1 = {2, 4, 7, 10};
int[] list2 = {2, 4, 7, 10};
int[] list3 = {4, 2, 7, 10};
System.out.println(java.util.Arrays.equals(list1,
list2)); // true
System.out.println(java.util.Arrays.equals(list2,
list3)); // false
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The Arrays.binarySearch Method

Since binary search is frequently used in programming, Java provides several overloaded binarySearch methods for searching a key in an array of int, double, char, short, long, and float in the java.util.Arrays class. For example, the following code searches the keys in an array of numbers and an array of characters.

```
int[] list = {2, 4, 7, 10, 11, 45, 50, 59, 60, 66, 69, 70, 79};
System.out.println("Index is " +
  java.util.Arrays.binarySearch(list, 11));
```

Return is 4

```
char[] chars = {'a', 'c', 'g', 'x', 'y', 'z'};
System.out.println("Index is " +
  java.util.Arrays.binarySearch(chars, 't'));
```

Return is –4 (insertion point is 3, so return is -3-1)

For the binarySearch method to work, the array must be pre-sorted in increasing order.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The Arrays.sort Method

Since sorting is frequently used in programming, Java provides several overloaded sort methods for sorting an array of int, double, char, short, long, and float in the java.util.Arrays class. For example, the following code sorts an array of numbers and an array of characters.

```
double[] numbers = {6.0, 4.4, 1.9, 2.9, 3.4, 3.5};
java.util.Arrays.sort(numbers);

char[] chars = {'a', 'A', '4', 'F', 'D', 'P'};
java.util.Arrays.sort(chars);
```

Java 8 now provides Arrays.parallelSort(list) that utilizes the multicore for fast sorting.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

The Arrays.toString(list) Method

The Arrays.toString(list) method can be used to return a string representation for the list.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Pass Arguments to Invoke the Main Method



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Main Method Is Just a Regular Method

You can call a regular method by passing actual parameters. Can you pass arguments to main? Of course, yes. For example, the main method in class B is invoked by a method in A, as shown below:

```
public class A {
  public static void main(String[] args) {
    String[] strings = {"New York",
      "Boston", "Atlanta"};
    B.main(strings);
  }
}
```

```
class B {
  public static void main(String[] args) {
    for (int i = 0; i < args.length; i++)
      System.out.println(args[i]);
  }
}
```


Copyright © 2022 Pearson Education Ltd. All rights reserved.

Command-Line Parameters

```
class TestMain {
  public static void main(String[] args) {
  ...
  }
}
```

```
java TestMain arg0 arg1 arg2 ... argn
```



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Processing Command-Line Parameters

In the main method, get the arguments from `args[0], args[1], ..., args[n]`, which corresponds to `arg0, arg1, ..., argn` in the command line.



Copyright © 2022 Pearson Education Ltd. All rights reserved.

Problem: Calculator

- Objective: Write a program that will perform binary operations on integers. The program receives three parameters: an operator and two integers.

Calculator

java Calculator 2 + 3

java Calculator 2 - 3

java Calculator 2 / 3

java Calculator 2 . 3



Copyright © 2022 Pearson Education Ltd. All rights reserved.