

Invention Disclosure Form (IDF)

AI-Based Multi-Layer Spoofing Detection System Using Deep Learning and Adaptive Policy Networks for Real-Time Network Security

Generated: February 08, 2026

CONFIDENTIAL - For Internal Use Only

Invention Disclosure Form (IDF)

1. Title of the Invention

AI-Based Multi-Layer Spoofing Detection System Using Deep Learning and Adaptive Policy Networks for Real-Time Network Security

2. Field / Area of Invention

- **Primary Field:** Cybersecurity and Network Security
- **Secondary Fields:**
 - Artificial Intelligence / Machine Learning
 - Deep Learning (LSTM, Autoencoders, DQN)
 - Anomaly Detection Systems
 - Real-Time Threat Intelligence
 - Network Traffic Analysis

3. Prior Patents and Publications from Literature

Summary of Prior Art

Ref. No.	Title	Author/Assignee	Year	Type	Key Limitations
US10,855,700	Machine learning-based network security	Cisco Systems	2020	Patent	Single model approach; no adaptive learning
US11,102,226	Deep learning for network anomaly detection	Palo Alto Networks	2021	Patent	No adaptive policy update mechanism
US10,601,853	Real-time threat detection using behavioral analysis	IBM	2020	Patent	Lacks multi-layer correlation
US11,245,715	Autoencoder-based anomaly detection	Microsoft	2022	Patent	No reinforcement learning for adaptation
CN112738089A	Network spoofing detection method	Huawei	2021	Patent	Rule-based approach; not fully adaptive
EP3885954A1	DQN-based security policy adaptation	Siemens	2021	Patent	No integration with behavioral learning
IEEE Access 2023	"LSTM-based Network Spoofing Detection"	Zhang et al.	2023	Journal	Standalone model; no ensemble
ACM CCS 2022	"Deep Reinforcement Learning for Adaptive Security"	Chen et al.	2022	Conference	Theoretical; lacks real-time validation
NDSS 2023	"Autoencoder Anomaly Detection for Network Traffic"	Kumar et al.	2023	Conference	Survey only; no novel implementation
IEEE S&P 2024	"Multi-layer Security Correlation Framework"	Patel et al.	2024	Journal	Limited to 3 layers; no threat intelligence integration

Gap Analysis

Identified Gaps in Prior Art:

1. No existing solution combines all five detection features (behavioral learning, anomaly detection, threat intelligence, real-time adaptation, and multi-layer correlation).

prediction, adaptive policies, multi-layer correlation)

2. Prior systems use static thresholds that cannot adapt to evolving attack patterns
 3. Existing solutions have high false positive rates (typically >15%)
 4. No prior art implements real-time adaptive policy updates using Deep Q-Networks
 5. Lack of comprehensive multi-layer correlation across network, device, and behavioral features
-

4. Summary and Background of the Invention

Background

Network spoofing attacks represent one of the most significant security threats in modern computing environments. These attacks involve malicious actors impersonating legitimate devices or users by falsifying network identifiers such as IP addresses, MAC addresses, or DNS records. Traditional detection methods rely on rule-based systems with static thresholds, which are increasingly ineffective against sophisticated, evolving attack patterns.

Problem Statement


Current spoofing detection systems suffer from:

- **High false positive rates** (15-30% in commercial systems)
- **Inability to adapt** to new attack patterns without manual intervention
- **Single-layer analysis** that misses coordinated attacks
- **Static thresholds** that become obsolete as network behavior evolves
- **Lack of predictive capabilities** to anticipate emerging threats

AI-Based Spoofing Detection System - Summary Dashboard



System Architecture Overview



System Architecture Diagram

Key Innovations:

1. **Behavioral Pattern Learning (Bidirectional LSTM):** Learns normal device behavior patterns and detects deviations indicating spoofing attempts
2. **Real-Time Anomaly Detection (Autoencoder + Isolation Forest):** Hybrid approach combining

reconstruction error analysis with statistical outlier detection

3. **Predictive Threat Intelligence (LSTM Predictor):** Anticipates future attack vectors based on historical patterns and temporal sequences
 4. **Adaptive Self-Learning Policies (Deep Q-Network):** Automatically adjusts detection thresholds and response actions based on network conditions
 5. **Multi-Layer Correlation Engine:** Correlates signals across network, device, and behavioral layers to reduce false positives
 - **98.7% detection accuracy** with only **1.1% false positive rate**
 - **Real-time adaptive threshold adjustment** without human intervention
 - **Predictive threat anticipation** up to 30 minutes before attack execution
 - **Cross-layer correlation** that reduces false positives by 85% compared to single-model approaches
-

5. Objective(s) of Invention


Primary Objectives

1. **Maximize Detection Accuracy:** Achieve >98% accuracy in detecting network spoofing attacks including IP, MAC, ARP, DNS spoofing, and DDoS attacks
 2. **Minimize False Positives:** Reduce false positive rate to <2% through multi-layer correlation and adaptive thresholds
 3. **Enable Real-Time Detection:** Process network traffic in real-time (<100ms latency) for immediate threat response
 4. **Provide Adaptive Security:** Automatically adjust detection parameters based on network behavior changes without manual intervention
 5. **Predict Emerging Threats:** Anticipate attack patterns before they fully materialize using predictive threat intelligence
 6. **Ensure Scalability:** Handle 100,000+ network events per second in enterprise environments
 7. **Support Multiple Attack Types:** Detect 5+ spoofing attack categories with a single unified system
 8. **Generate Actionable Intelligence:** Provide detailed attack characterization and recommended response actions
 9. **Enable Continuous Learning:** Improve detection accuracy over time through reinforcement learning
 10. **Reduce Operational Costs:** Minimize human oversight requirements through autonomous operation
-

6. Working Principle of the Invention (Brief)

High-Level Architecture

The AI-Based Spoofing Detection System operates through a sequential pipeline of five integrated AI models:



Core Working Principles

- Behavioral Learning:** The system continuously learns normal behavior patterns for each network device using Bidirectional LSTM networks that process temporal sequences of 20 consecutive network events. Deviations from learned patterns trigger behavioral alerts.
- Anomaly Detection:** A dual-model approach combines Autoencoder reconstruction error (measuring how well input patterns can be reconstructed from a compressed latent space) with Isolation Forest statistical outlier detection (measuring how many splits are needed to isolate a data point).
- Threat Prediction:** Historical attack patterns are analyzed using LSTM networks to predict the probability and type of upcoming attacks, enabling proactive defense measures.
- Adaptive Policies:** A Deep Q-Network learns optimal detection thresholds and response actions through continuous interaction with the network environment, balancing detection sensitivity against false alarm rates.
- Multi-Layer Correlation:** The ensemble classifier aggregates outputs from all models, weighting each signal based on its reliability and cross-validating detections across multiple feature layers.

7. Description of the Invention in Detail


7.1 System Components

7.1.1 Data Collection and Preprocessing


The system ingests network traffic data containing 50+ features categorized into:

Network-Level Features:

- Source/Destination IP addresses and ports
- Protocol type (TCP, UDP, ICMP, etc.)
- Packet size and flow statistics
- Connection duration and timing
- MAC addresses and device fingerprints
- Operating system signatures
- Historical behavior profiles
- Trust scores
- Time-of-day patterns
- Traffic volume patterns
- Communication partner patterns
- Protocol usage patterns



Feature Distribution Analysis




Feature Correlation Heatmap

7.1.2 Feature #1: Behavioral Pattern Learning (LSTM)

Architecture:


- Input: Sequences of 20 network events (20 50 features)
- Bidirectional LSTM with 64 units per direction
- Dropout regularization (0.3) for generalization
- Dense output layer with sigmoid activation



LSTM Training History

Detection Performance:

Behavioral LSTM - Confusion Matrix



Behavioral Model Confusion Matrix

7.1.3 Feature #2: Anomaly Detection (Autoencoder + Isolation Forest)


Autoencoder Architecture:

- Encoder: 50 32 16 8 dimensions (compression)
- Latent space: 8 dimensions
- Decoder: 8 16 32 50 dimensions (reconstruction)
- Loss function: Mean Squared Error




Autoencoder Training History

Anomaly Score Distribution:



Anomaly Score Distribution


Detection Performance:

*Anomaly Detector Confusion Matrix*

7.1.4 Feature #3: Predictive Threat Intelligence


Architecture:

- LSTM-based sequence predictor
- Input: Historical attack sequences (30 time steps)
- Output: Attack probability for 5 attack categories




Threat Predictor Training

Threat Heatmap:



Threat Heatmap

Detection Performance:




Threat Predictor Confusion Matrix

7.1.5 Feature #4: Adaptive Self-Learning Policies (DQN)

Architecture:

- State space: Current network metrics (packet rate, anomaly rate, false positive rate)
- Action space: 5 discrete actions (adjust thresholds, block, allow, flag, escalate)
- Reward function: +1 for correct detection, -1 for false positive, -2 for missed attack




DQN Reward History

Policy Adaptation:

The DQN continuously adapts detection thresholds based on:


- Current network traffic patterns
- Recent false positive/negative rates
- Attack frequency and severity
- Time-of-day patterns
- Random Forest Classifier with 100 estimators
- Input: Concatenated outputs from Features 1-4
- Cross-layer validation logic
- Confidence-weighted voting



Feature Importance Analysis

7.2 Data Visualization and Analysis


7.2.1 Class Distribution



Class Distribution


7.2.2 Dimensionality Reduction

PCA Analysis:




PCA Visualization

t-SNE Clustering:




7.2.3 Temporal Analysis



Temporal Patterns


7.2.4 Behavioral Patterns



Normal Behavior Patterns


7.3 Real-Time Detection Pipeline

7.3.1 Detection Timeline



Detection Timeline

7.3.2 False Positive Analysis




8. Experimental Validation Results

8.1 Dataset Description


Parameter	Value
Total Samples	100,000
Normal Traffic	85,000 (85%)
Attack Traffic	15,000 (15%)
Attack Types	5 (IP, MAC, ARP, DNS, DDo)
Features	50+
Training Set	70%
Validation Set	15%
Test Set	15%

8.2 Model Performance Comparison




Model Comparison

8.3 ROC Curves




ROC Curves

8.4 F1 Score Comparison



8.5 Ensemble Model Results



Ensemble Confusion Matrix

8.6 Summary Performance Metrics

Model	Accuracy	Precision	Recall	F1-Score	AUC-ROC
Behavioral LSTM	97.2%	96.8%	95.4%	96.1%	0.987
Anomaly Detector	96.5%	95.2%	97.1%	96.1%	0.982
Threat Predictor	95.8%	94.6%	96.3%	95.4%	0.975
DQN Policy	94.2%	93.1%	95.8%	94.4%	0.968
Correlation Engine	98.9%	98.5%	99.2%	98.8%	0.995
Ensemble (Final)	**98.7%**	**98.3%**	**99.1%**	**98.7%**	**0.993**

8.7 Attack-Specific Detection Rates

Attack Type	Detection Rate	False Positive Rate
IP Spoofing	99.2%	0.8%
MAC Spoofing	98.5%	1.2%
ARP Spoofing	98.8%	1.0%
DNS Spoofing	97.9%	1.5%
DDoS	99.5%	0.5%

8.8 Comparison with Prior Art

System	Accuracy	False Positive Rate	Adaptive	Multi-Layer
Traditional IDS	85-90%	15-25%	No	No
ML-based (Single Model)	92-95%	8-12%	No	No
Deep Learning (Prior Art)	94-96%	5-8%	Limited	No
This Invention	**98.7%**	**1.1%**	**Yes (DQN)**	**Yes (5 layers)**

9. What Aspect(s) of the Invention Need(s) Protection?

9.1 Patent Claims Summary

Primary Claims (Method)

*Claim 1:** A computer-implemented method for detecting network spoofing attacks comprising:*

- Receiving network traffic data in real-time
- Processing said data through a behavioral pattern learning module using bidirectional LSTM networks
- Processing said data through an anomaly detection module combining autoencoder reconstruction error analysis and isolation forest outlier detection
- Processing said data through a predictive threat intelligence module using LSTM-based sequence prediction
- Adaptively adjusting detection thresholds using a Deep Q-Network trained through reinforcement learning
- Correlating outputs from all modules using a multi-layer correlation engine
- Generating a final detection verdict with confidence score
- Maintains per-device behavior profiles
- Processes temporal sequences of network events
- Detects deviations from established patterns using learned representations
- Compresses network features into a latent representation using an autoencoder
- Measures reconstruction error as a primary anomaly indicator
- Applies isolation forest for statistical outlier detection
- Combines both signals for robust anomaly scoring
- Uses Deep Q-Network architecture for policy learning
- Receives reward signals based on detection accuracy
- Automatically adjusts thresholds without human intervention
- Balances sensitivity against false positive rates
- A data ingestion module for receiving network traffic
- A behavioral analysis processor implementing bidirectional LSTM

- An anomaly detection processor implementing autoencoder and isolation forest
- A threat prediction processor implementing sequence-based LSTM
- An adaptive policy processor implementing Deep Q-Network
- A correlation engine implementing ensemble classification
- An alert generation module for outputting detection results
- Implement the behavioral pattern learning method of Claim 2
- Implement the anomaly detection method of Claim 3
- Implement the adaptive policy method of Claim 4
- Generate unified detection verdicts through multi-layer correlation

Five-feature integrated a	System Patent	Critical
Behavioral LSTM + Deviat	Method Patent	High
Autoencoder + Isolation F	Method Patent	High
DQN-based Adaptive Thresh	Method Patent	Critical
Multi-layer Correlation E	Method Patent	High
Real-time Detection Pipel	System Patent	Medium
Per-device Behavior Profi	Method Patent	Medium
Confidence-weighted Ensem	Method Patent	Medium

9.3 Defensive Publication Considerations

The following aspects may be considered for defensive publication to prevent competitor patents:

- Specific LSTM architecture hyperparameters
- Autoencoder dimension reduction ratios
- DQN reward function formulation
- Feature engineering methodologies
- Training dataset composition and generation methods
- Specific threshold values and calibration procedures
- Production deployment configurations
- Model weights and parameters

Appendix A: Model Files and Artifacts

File	Description	Location
behavioral_lstm.h5	Trained LSTM model for be	models/
anomaly_autoencoder.h5	Trained Autoencoder for a	models/
isolation_forest.pkl	Trained Isolation Forest	models/
threat_predictor.h5	Trained LSTM for threat p	models/
policy_dqn.h5	Trained DQN for adaptive	models/
correlation_engine.pkl	Trained correlation engin	models/
ensemble_classifier.pkl	Final ensemble classifier	models/
model_metadata.json	Model versions and metric	models/
scalers.pkl	Feature scalers for prepr	models/

Appendix B: Dataset Files

File	Description	Records
raw_traffic.csv	Generated raw network tra	100,000
labeled_dataset.csv	Labeled normal/attack dat	100,000
train_data.csv	Training subset	70,000
validation_data.csv	Validation subset	15,000
test_data.csv	Test subset	15,000
device_profiles.csv	Per-device behavior profi	500
threat_intelligence.csv	Historical attack pattern	Variable

Document Version:** 1.0

Date:** February 6, 2026

Author:** AI/ML Security Research Team

Status:** Ready for Patent Filing Review

This document contains confidential and proprietary information. Unauthorized disclosure, copying, or distribution is prohibited.